

Introduction

Conditionals

Logical
Operators

Pitfalls

Exercises

Computer Science I

Conditionals

Dr. Chris Bourke

cbourke@cse.unl.edu

Introduction

Conditionals

Logical
Operators

Pitfalls

Exercises

1. Introduction

2. Conditionals

3. Logical Operators

4. Pitfalls

5. Exercises

Introduction

Conditionals
Boolean
Statements
Numeric
Comparisons
Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

Part I: Introduction

Control Flow & Logical Operators

Sequential Control Flow

Introduction


- Conditionals
- Boolean Statements
- Numeric Comparisons
- Complex Logic Statements

Conditionals


- Logical Operators

- Pitfalls

- Exercises



If Statement Flow



Introduction

Conditionals

Boolean
Statements
Numeric
Comparisons
Complex Logic
Statements


Conditionals

Logical
Operators

Pitfalls

Exercises

If-Else Statement Flow



Introduction

Conditionals

Boolean
Statements
Numeric
Comparisons
Complex Logic
Statements


Conditionals

Logical
Operators

Pitfalls

Exercises

If-Else-If Statement Flow



Introduction

Conditionals


Boolean
Statements
Numeric
Comparisons
Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises



Boolean Statements

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons
Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

- A *boolean* condition or expression is a logical expression that evaluates to either *true* or *false*

Boolean Statements

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons
Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

- A *boolean* condition or expression is a logical expression that evaluates to either *true* or *false*
- May involve numerical comparisons $a \geq 0$

Boolean Statements

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons
Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

- A *boolean* condition or expression is a logical expression that evaluates to either *true* or *false*
- May involve numerical comparisons $a \geq 0$
- A condition can be *simple* or *complex*

- A *boolean* condition or expression is a logical expression that evaluates to either *true* or *false*
- May involve numerical comparisons $a \geq 0$
- A condition can be *simple* or *complex*
- May connect one or more expressions using a logical *and* or a logical *or*

Numeric Comparisons

- We need a way to compare the value stored in variables

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons

Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:
 - Are two values equal or not equal?

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:
 - Are two values equal or not equal?
 - Is one value greater than or equal to/lesser than or equal to another?

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:
 - Are two values equal or not equal?
 - Is one value greater than or equal to/lesser than or equal to another?
 - Is one value strictly greater/lesser than another?

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:
 - Are two values equal or not equal?
 - Is one value greater than or equal to/lesser than or equal to another?
 - Is one value strictly greater/lesser than another?
- Standard mathematical notations

$= \neq \geq \leq > <$

Numeric Comparisons

- We need a way to compare the value stored in variables
- Compare the relative value of two variables
- Compare the value stored in one variable with a fixed value (literal)
- Comparisons:
 - Are two values equal or not equal?
 - Is one value greater than or equal to/lesser than or equal to another?
 - Is one value strictly greater/lesser than another?
- Standard mathematical notations

$= \neq \geq \leq > <$

- Code versions:

`== != >= <= > <`

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons

Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

A	B	$A \text{ and } B$
false	false	false
false	true	false
true	false	false
true	true	true

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons

Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

A	B	$A \text{ and } B$
false	false	false
false	true	false
true	false	false
true	true	true

Code version: `&&`

Logical Or

Introduction

Conditionals

Boolean
Statements

Numeric
Comparisons

Complex Logic
Statements

Conditionals

Logical
Operators

Pitfalls

Exercises

A	B	$A \text{ or } B$
false	false	false
false	true	true
true	false	true
true	true	true

<i>A</i>	<i>B</i>	<i>A or B</i>
false	false	false
false	true	true
true	false	true
true	true	true

Code version: `||`

A	$not\ A$
false	true
true	false

Code version: !

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

Part II: Conditionals

If, If-Else, If-Else-If & Numeric Comparisons

If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //conditional body: code inside this code block
3      //will only execute if the <condition> evaluates
4      //to true, otherwise it will not execute at all
5  }
```

- Uses the keyword `if`

If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //conditional body: code inside this code block
3      //will only execute if the <condition> evaluates
4      //to true, otherwise it will not execute at all
5  }
```

- Uses the keyword `if`
- The condition is enclosed in parentheses

If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //conditional body: code inside this code block
3      //will only execute if the <condition> evaluates
4      //to true, otherwise it will not execute at all
5  }
```

- Uses the keyword `if`
- The condition is enclosed in parentheses
- The code block begins and ends with curly brackets

If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //conditional body: code inside this code block
3      //will only execute if the <condition> evaluates
4      //to true, otherwise it will not execute at all
5  }
```

- Uses the keyword `if`
- The condition is enclosed in parentheses
- The code block begins and ends with curly brackets
- Behavior

If-Else Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //code block A
3  } else {
4      //code block B
5  }
```

- Uses the keyword `else`

If-Else Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition>) {
2      //code block A
3  } else {
4      //code block B
5  }
```

- Uses the keyword `else`
- Behavior: if `<condition>` evaluates to true code block `A` is executed

If-Else Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```
1  if(<condition>) {  
2    //code block A  
3  } else {  
4    //code block B  
5  }
```

- Uses the keyword `else`
- Behavior: if `<condition>` evaluates to true code block `A` is executed
- If `<condition>` evaluates to false, code block `B` is executed

If-Else Statement

```
1  if(<condition>) {  
2    //code block A  
3  } else {  
4    //code block B  
5  }
```

- Uses the keyword `else`
- Behavior: if `<condition>` evaluates to true code block `A` is executed
- If `<condition>` evaluates to false, code block `B` is executed
- The two code blocks are *mutually exclusive*

If-Else Statement

```

1  if(<condition>) {
2      //code block A
3  } else {
4      //code block B
5  }

```

- Uses the keyword `else`
- Behavior: if `<condition>` evaluates to true code block `A` is executed
- If `<condition>` evaluates to false, code block `B` is executed
- The two code blocks are *mutually exclusive*
- A generalization of the `if` statement

If-Else-If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition1>) {
2      //code block A
3  } else if(<condition2>) {
4      //code block B
5  } else {
6      //code block C
7  }
```

- Multiple conditions: may define as many as you want

If-Else-If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition1>) {
2      //code block A
3  } else if(<condition2>) {
4      //code block B
5  } else {
6      //code block C
7  }
```

- Multiple conditions: may define as many as you want
- The *first* condition that evaluates to true is the one (and only one) that is executed

If-Else-If Statement

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  if(<condition1>) {
2      //code block A
3  } else if(<condition2>) {
4      //code block B
5  } else {
6      //code block C
7  }
```

- Multiple conditions: may define as many as you want
- The *first* condition that evaluates to true is the one (and only one) that is executed
- Each code block is *mutually exclusive*

If-Else-If Statement

```

1  if(<condition1>) {
2      //code block A
3  } else if(<condition2>) {
4      //code block B
5  } else {
6      //code block C
7  }

```

- Multiple conditions: may define as many as you want
- The *first* condition that evaluates to true is the one (and only one) that is executed
- Each code block is *mutually exclusive*
- The most specific conditions come *first*, more general *last*

- Multiple conditions: may define as many as you want
- The *first* condition that evaluates to true is the one (and only one) that is executed
- Each code block is *mutually exclusive*
- The most specific conditions come *first*, more general *last*
- You may omit the final `else` block if there is no “final case” to consider

Numerical Comparisons

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

- Comparison operators:

`<`, `>`, `<=`, `>=`

- Equality operator: `==`

Numerical Comparisons

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

- Comparison operators:

`<`, `>`, `<=`, `>=`

- Equality operator: `==`

- Inequality operators `!=`

Numerical Comparisons

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

- Comparison operators:

`<`, `>`, `<=`, `>=`

- Equality operator: `==`

- Inequality operators `!=`

- May be used in combinations of *literals* (hardcoded numerical values), variables or expressions

Numerical Comparisons

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  int a, b, c;
2
3  //comparing a variable to a literal
4  if(a == 0) {
5      printf("a is zero!\n");
6  }
7
8  //comparing two variable values:
9  if(a == b) {
10     printf("the two values are equal\n");
11 }
12
13 //you can, but shouldn't do the following
14 if(10 == a) {
15     //...
16 }
17
18 if(b * b - 4 * a * c < 0) {
19     printf("looks bad...\n");
20 }
21
22 //you can but shouldn't:
23 if(10 < 20) {
24     printf("duh, that's always true\n");
25 }
    
```

Conditional Examples

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```

1  int huskerScore;
2  int opponentScore;
3
4  //a simple if statement:
5  if(huskerScore > opponentScore) {
6      printf("Huskers Win!\n");
7  }
8
9  //an if-else statement:
10 if(huskerScore > opponentScore) {
11     printf("Huskers Win!\n");
12 } else {
13     printf("Huskers do not win.\n");
14 }
15
16 //an if-else-if statement:
17 if(huskerScore > opponentScore) {
18     printf("Huskers Win!\n");
19 } else if(huskerScore < opponentScore) {
20     printf("Huskers Lose!\n");
21 } else {
22     printf("Tie, let's go to overtime!\n");
23 }
```


Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```
1  if(huskerScore > opponentScore) {  
2      printf("Huskers Win!\n");  
3  } else if(huskersScore < opponentScore) {  
4      printf("Huskers Lose!\n");  
5  } else {  
6      printf("Tie, let's go to overtime!\n");  
7  }
```

- Use of spaces

```

1  if(huskerScore > opponentScore) {
2      printf("Huskers Win!\n");
3  } else if(huskersScore < opponentScore) {
4      printf("Huskers Lose!\n");
5  } else {
6      printf("Tie, let's go to overtime!\n");
7  }

```

- Use of spaces
- Opening curly brackets on the same line as keywords

Introduction

Conditionals

Numerical
Comparisons

Examples

Logical
Operators

Pitfalls

Exercises

```
1  if(huskerScore > opponentScore) {  
2      printf("Huskers Win!\n");  
3  } else if(huskersScore < opponentScore) {  
4      printf("Huskers Lose!\n");  
5  } else {  
6      printf("Tie, let's go to overtime!\n");  
7  }
```

- Use of spaces
- Opening curly brackets on the same line as keywords
- Closing curly brackets on the same indentation level

```

1  if(huskerScore > opponentScore) {
2      printf("Huskers Win!\n");
3  } else if(huskersScore < opponentScore) {
4      printf("Huskers Lose!\n");
5  } else {
6      printf("Tie, let's go to overtime!\n");
7  }

```

- Use of spaces
- Opening curly brackets on the same line as keywords
- Closing curly brackets on the same indentation level
- All blocks are indented at the same level

```

1  if(huskerScore > opponentScore) {
2      printf("Huskers Win!\n");
3  } else if(huskersScore < opponentScore) {
4      printf("Huskers Lose!\n");
5  } else {
6      printf("Tie, let's go to overtime!\n");
7  }

```

- Use of spaces
- Opening curly brackets on the same line as keywords
- Closing curly brackets on the same indentation level
- All blocks are indented at the same level
- Consistency is the most important thing

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And

Logical Or

Examples

Pitfalls

Exercises

Part III: Logical Operators

Negation, Logical And, Logical Or

Negation Operator

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- Any logical statement can be negated using `!`

Negation Operator

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- Any logical statement can be negated using `!`
- Negation of `(a == b)` can be `!(a == b)`

Negation Operator

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- Any logical statement can be negated using `!`
- Negation of `(a == b)` can be `!(a == b)`
- Negation of `(a <= b)` can be `!(a <= b)`

Negation Operator

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- Any logical statement can be negated using `!`
- Negation of `(a == b)` can be `!(a == b)`
- Negation of `(a <= b)` can be `!(a <= b)`
- Better to use: `(a != b)` and `(a > b)`

Negation Operator

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- Any logical statement can be negated using `!`
- Negation of `(a == b)` can be `!(a == b)`
- Negation of `(a <= b)` can be `!(a <= b)`
- Better to use: `(a != b)` and `(a > b)`
- Usually a negation is used on a “flag” variable: a variable that simply holds a truth value (true or false)

Flag Variables

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- C has no “boolean variables”

Flag Variables

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value

Flag Variables

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value
- `0` is false

Flag Variables

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value
- `0` is false
- Any non-zero value is true

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value
- `0` is false
- Any non-zero value is true
- `3, 3.5, 3.14, -10` are all true

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value
- `0` is false
- Any non-zero value is true
- `3, 3.5, 3.14, -10` are all true
- Convention: use `1` as true

- C has no “boolean variables”
- Any numerical value can be treated as a boolean value
- `0` is false
- Any non-zero value is true
- `3, 3.5, 3.14, -10` are all true
- Convention: use `1` as true
- Best practice: only use `int` variables as booleans

Flag Variables

Example

Introduction

Conditionals

Logical
Operators

Negation

Flag Variables

Logical And
Logical Or
Examples

Pitfalls

Exercises

```

1  //flag variable to indicate if someone is a
2  //student (true) or not (false)
3  int isStudent;
4
5  //set the variable to true:
6  isStudent = 1;
7
8  //they are not a student:
9  isStudent = 0;
10
11 if(isStudent) {
12     printf("You get a student discount!\n");
13 }
14
15 //using a negation
16 if(!isStudent) {
17     printf("You pay full price!\n");
18 }
    
```

- Logical And operator: `&&`

Introduction

Conditionals

Logical
Operators

Negation
Flag Variables

Logical And

Logical Or
Examples

Pitfalls

Exercises

Logical And

- Logical And operator: `&&`
- Evaluates to true only if *both* operands evaluate to true

Introduction

Conditionals

Logical
Operators

Negation
Flag Variables

Logical And

Logical Or
Examples

Pitfalls

Exercises

- Logical And operator: `&&`
- Evaluates to true only if *both* operands evaluate to true

```
1  if(subTotal >= 50.0 && isPreferredMember) {  
2      discount = .20;  
3      shipping = 0;  
4  } else if(subTotal >= 50.0 && !isPreferredMember) {  
5      discount = 0.0;  
6      shipping = 0;  
7  } else {  
8      discount = 0.0;  
9      shipping = 10.50;  
10 }
```

Introduction

Conditionals

Logical
Operators

Negation
Flag Variables
Logical And

Logical Or

Examples

Pitfalls

Exercises

- Logical Or operator: `||`

Introduction

Conditionals

Logical

Operators

Negation

Flag Variables

Logical And

Logical Or

Examples

Pitfalls

Exercises

- Logical Or operator: `||`
- Evaluates to true only if *at least one* of its operands evaluate to true

- Logical Or operator: `||`
- Evaluates to true only if *at least one* of its operands evaluate to true

```
1  if(isStudent || isPreferredMember) {
2      discount = .20;
3  }
```

```
1  if(a > 10 && a < 20) {  
2    //...  
3  }  
4  
5  if(a == b && a < 10) {  
6    //...  
7  }  
8  
9  if(a > 10 || a < 20) {  
10   //...  
11  }  
12  
13  if(a == b || a < 10) {  
14   //...  
15  }
```

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Part IV: Pitfalls

Common Errors & Misconceptions

Pitfall

Incorrect Complex Logic

Consider the following code:

```
1  if(0 <= a <= 10) {  
2      printf("Value is within range!\n");  
3  }
```

- The above code will compile, will execute, but will not work for certain values

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Consider the following code:

```
1  if(0 <= a <= 10) {  
2      printf("Value is within range!\n");  
3  }
```

- The above code will compile, will execute, but will not work for certain values
- What happens when `a = 20` ?

Consider the following code:

```
1  if(0 <= a <= 10) {  
2      printf("Value is within range!\n");  
3  }
```

- The above code will compile, will execute, but will not work for certain values
- What happens when `a = 20` ?
- First comparison: `0 <= 20`

Pitfall

Incorrect Complex Logic

Consider the following code:

```
1  if(0 <= a <= 10) {
2      printf("Value is within range!\n");
3  }
```

- The above code will compile, will execute, but will not work for certain values
- What happens when `a = 20` ?
- First comparison: `0 <= 20`
- Evaluates to true (`1`)

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Consider the following code:

```
1  if(0 <= a <= 10) {  
2      printf("Value is within range!\n");  
3  }
```

- The above code will compile, will execute, but will not work for certain values
- What happens when `a = 20` ?
- First comparison: `0 <= 20`
- Evaluates to true (`1`)
- Second comparison: `1 <= 10` (true)

Pitfall

Incorrect Complex Logic

Consider the following code:

```
1  if(0 <= a <= 10) {
2      printf("Value is within range!\n");
3  }
```

- The above code will compile, will execute, but will not work for certain values
- What happens when `a = 20` ?
- First comparison: `0 <= 20`
- Evaluates to true (`1`)
- Second comparison: `1 <= 10` (true)
- Incorrect result

Pitfall

Incorrect Complex Logic

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
ComparisonsPrecedence
Rules

Short Circuiting

Exercises

Solution: break up your conditions using a `&&`

```
1  if(0 <= a && a <= 10) {  
2      printf("Value is within range!\n");  
3  }
```

Pitfall

Confusing Comparisons & Assignments

Consider the following code:

```
1  int a = 5;  
2  
3  if(a = 10) {  
4      printf("a is ten\n");  
5  }
```

- The above code will compile, run, but will give incorrect results

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Pitfall

Confusing Comparisons & Assignments

Consider the following code:

```
1  int a = 5;
2
3  if(a = 10) {
4      printf("a is ten\n");
5  }
```

- The above code will compile, run, but will give incorrect results
- `a = 10` results in an assignment of the value 10 to the variable `a`

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Pitfall

Confusing Comparisons & Assignments

Consider the following code:

```
1  int a = 5;
2
3  if(a = 10) {
4      printf("a is ten\n");
5  }
```

- The above code will compile, run, but will give incorrect results
- `a = 10` results in an assignment of the value 10 to the variable `a`
- A value of 10 evaluates to true

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Pitfall

Confusing Comparisons & Assignments

Consider the following code:

```
1  int a = 5;
2
3  if(a = 10) {
4      printf("a is ten\n");
5  }
```

- The above code will compile, run, but will give incorrect results
- `a = 10` results in an assignment of the value 10 to the variable `a`
- A value of 10 evaluates to true
- The `if` body gets executed regardless of the original value of `a`

Pitfall

Improper Semicolons

Consider the following code:

```
1  int a = 5;
2
3  if(a == 10); {
4      printf("a is ten!\n");
5  }
```

- Semicolon (in general) only go after *executable* statements

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Pitfall

Improper Semicolons

Consider the following code:

```
1  int a = 5;
2
3  if(a == 10); {
4      printf("a is ten!\n");
5  }
```

- Semicolon (in general) only go after *executable* statements
- Above code will compile, will run, but will not give the correct results

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Pitfall

Improper Semicolons

Consider the following code:

```
1  int a = 5;
2
3  if(a == 10); {
4      printf("a is ten!\n");
5  }
```

- Semicolon (in general) only go after *executable* statements
- Above code will compile, will run, but will not give the correct results
- Conditional statement is *bound* to an empty statement

Non-Numerical Comparisons

- You can compare single `char` values with character literals:

```
1 char initial = 'C';  
2  
3 if(initial == 'c' || initial == 'C') {  
4     //...  
5 }
```

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
ComparisonsPrecedence
Rules

Short Circuiting

Exercises

Non-Numerical Comparisons

- You can compare single `char` values with character literals:

```
1 char initial = 'C';  
2  
3 if(initial == 'c' || initial == 'C') {  
4     //...  
5 }
```

- You *cannot* use equality and inequality operators on strings (sequences of characters)

```
1 if(name == "Chris") {  
2     printf("Greetings, Professor.\n");  
3 }
```

Non-Numerical Comparisons

- You can compare single `char` values with character literals:

```
1 char initial = 'C';  
2  
3 if(initial == 'c' || initial == 'C') {  
4     //...  
5 }
```

- You *cannot* use equality and inequality operators on strings (sequences of characters)

```
1 if(name == "Chris") {  
2     printf("Greetings, Professor.\n");  
3 }
```

- The above will *never* give correct results

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

- The logical *and* `&&` is evaluated before the logical *or* `||`

- The logical *and* `&&` is evaluated before the logical *or* `||`
- The following are *not* equivalent:

```
a && (b || c)
```

```
a && b || c
```

- The logical *and* `&&` is evaluated before the logical *or* `||`

- The following are *not* equivalent:

```
a && (b || c)
```

```
a && b || c
```

- Use parentheses when necessary

- The logical *and* `&&` is evaluated before the logical *or* `||`
- The following are *not* equivalent:

```
a && (b || c)
```

```
a && b || c
```

- Use parentheses when necessary
- Best practice: use them even when not necessary to express *intent*

Introduction

Conditionals

Logical
Operators

Pitfalls
Non-Numerical
Comparisons
Precedence
Rules

Short Circuiting

Exercises

Consider a logical and: `a && b`

- If `a` evaluates to false, it does not matter what `b` evaluates to

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

Consider a logical and: `a && b`

- If `a` evaluates to false, it does not matter what `b` evaluates to
- Since `a` is false, the entire expression is false

Consider a logical and: `a && b`

- If `a` evaluates to false, it does not matter what `b` evaluates to
- Since `a` is false, the entire expression is false
- Consequently: `b` is not evaluated/executed

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
ComparisonsPrecedence
Rules

Short Circuiting

Exercises

Consider a logical and: `a || b`

- If `a` evaluates to true, it does not matter what `b` evaluates to

Consider a logical and: `a || b`

- If `a` evaluates to true, it does not matter what `b` evaluates to
- Since `a` is true, the entire expression is true

Consider a logical and: `a || b`

- If `a` evaluates to true, it does not matter what `b` evaluates to
- Since `a` is true, the entire expression is true
- Consequently: `b` is not evaluated/executed

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

- Short circuiting is common to the vast majority of programming language

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
Comparisons

Precedence
Rules

Short Circuiting

Exercises

- Short circuiting is common to the vast majority of programming language
- Historic reasons

Introduction

Conditionals

Logical
Operators

Pitfalls

Non-Numerical
ComparisonsPrecedence
Rules

Short Circuiting

Exercises

- Short circuiting is common to the vast majority of programming language
- Historic reasons
- Common *idiom* in many programming languages:

```
1  if(a != NULL && a[0] == 10) {  
2      //...  
3  }
```

Introduction

Conditionals

Logical
Operators

Pitfalls

Exercises

Part V: Exercises

Introduction

Conditionals

Logical
Operators

Pitfalls

Exercises

Write a code snippet that determines the maximum of three integer values.

Write a program that reads a decibel level from the user and gives them a description of the sound level based on the following categories.

- 0 - 60 Quiet
- 61 - 70 Conversational
- 71 - 90 Loud
- 91 - 110 Very Loud
- 111 - 129 Dangerous
- 130 - 194 Very Dangerous

Exercise




Figure: Examples of Equilateral, Isosceles, and Scalene triangles

3 sides are a valid triangle only if the sum of the length of any two sides is strictly greater than the length of the third side.

Write a program to determine if 3 inputs form a valid triangle and if so, what type.