# RTL8196C-GR

# IEEE 802.11n AP/ROUTER NETWORK PROCESSOR WITH EEE

## PRELIMINARY DATASHEET
### (CONFIDENTIAL: Development Partners Only)

**Rev. 0.7**
**30 November 2009**
**Track ID: JATR-2265-11**

## COPYRIGHT

## DISCLAIMER

Realtek provides this document "as is", without warranty of any kind. Realtek may make improvements and/or changes in this document or in the product described in this document at any time. This document could include technical inaccuracies or typographical errors.

## TRADEMARKS

Realtek is a trademark of Realtek Semiconductor Corporation. Other names mentioned in this document are trademarks/registered trademarks of their respective owners.

## USING THIS DOCUMENT

This document provides detailed user guidelines to achieve the best performance when implementing the RTL8196C.

Though every effort has been made to ensure that this document is current and accurate, more information may have become available subsequent to the production of this guide.

## REVISION HISTORY

| Revision | Release Date | Summary |
|----------|--------------|---------|
| 0.7 | 2009/11/30 | Preliminary release. |

# Table of Contents

# List of Tables

# List of Figures

# 1.  General Description

The RTL8196C is an integrated System-on-a-Chip (SoC) Application Specific Integrated Circuit (ASIC) that implements a basic L2 5-port Ethernet switch and a high performance CPU. The embedded RISC CPU is an RLX4181, and the clock rate can be up to 400MHz. To improve computational performance, a 16-Kbyte I-Cache, 8-Kbyte D-Cache, 16-K I-MEM, and 8-Kbyte D-MEM are provided. A standard 5-signal P1149.1 compliant EJTAG test interface is supported for CPU testing and software development.

The RTL8196C provides five ports (from port 0 to port 4), integrated with five MAC and five physical layer transceivers for 10Base-T and 100Base-TX. Each port of the RTL8196C may be configured as a LAN or WAN port.

The RTL8196C supports flexible IEEE 802.3x full-duplex flow control and optional half-duplex backpressure control. For full-duplex, standard IEEE 803.3x flow control will enable pause ability only when both sides of UTP have auto-negotiation ability and have enabled pause ability. The RTL8196C also provides optional forced mode IEEE 802.3x full-duplex flow control. Based on optimized packet memory management, the RTL8196C is capable of Head-Of-Line blocking prevention.

L2 Switch Features: The RTL8196C contains a 1024-entry address look-up table with a 10-bit 4-way XOR hashing algorithm for address searching and learning. Auto aging of each entry is provided and the aging time is 300~450 seconds.

The RTL8196C supports IEEE 802.3az Draft 2.0, also known as Energy Efficient Ethernet (EEE). IEEE 802.3az operates with the IEEE 802.3 Media Access Control (MAC) Sublayer to support operation in Low Power Idle mode. When the Ethernet network is in low link utilization, EEE allows systems on both sides of the link to save power. Green Ethernet power saving provides: link-on and dynamic detection of cable length, and dynamic adjustment of power required for the detected cable length. This feature provides high performance with minimum power consumption. The RTL8196C also implements link-down power saving on a per-port basis, greatly cutting power consumption when the network cable is disconnected.

For peripheral interfaces, one 16550-compatible UART is supported, and a 16-byte FIFO buffer is provided. A USB 2.0 host controller is embedded in the RTL8196C to provide EHCI and OHCI 1.1 compliant host functionality. A USB PHY is also embedded in the RTL8196C.

An MDI/MDIX auto-crossover function is supported. For accessing high-speed devices, the RTL8196C provides a PCI Express bridge to access a PCI Express interface.

The RTL8196C requires only a single 25MHz crystal or 40MHz clock input for the system PLL. The RTL8196C also has two hardware timers and one watchdog timer to provide accurate timing and watchdog functionality. For extension and flexibility, the RTL8196C has up to 17 GPIO pins.

The RTL8196C is provided in a PQFP 128-pin package. It requires only a 3.3V and 1.0V external power supply.

# 2. Features

- SOC
  - Embedded RISC CPU, RLX4181 with 16K I-Cache, 8K D-Cache, 16K I-MEM, 8K D-MEM
  - Supports MIPS-1 ISA, MIPS16 ISA
  - Clock rate up to 400MHz
  - Provides a standard 5-signal P1149.1 EJTAG test port
  - Supports RLX4181 CPU suspend mode

- L2 Capabilities
  - Five Ethernet MAC integrated switch with five 10M/100Mbps physical layers and transceivers for IEEE 802.3 10Base-T and 100Base-TX
  - Non-blocking wire-speed reception and transmission and non-head-of-line-blocking/forwarding
  - Internal 512Kbit SRAM for packet buffering
  - Internal 1024 entry 4-way hash L2 look-up table
  - Supports source and destination MAC address filtering
  - Supports IEEE 802.1x port-based and MAC-based Network Access Control
  - Complies with IEEE 802.3/802.3u/802.1q/802.1d
  - Flexible full-duplex 802.3x flow control and optional half-duplex backpressure flow control
  - MAC learning supports Shared VLAN Learning (SVL) and Independent VLAN Learning (IVL) modes

- CPU Interface (NIC)
  - Supports BSD mbuf-like packet structure with adjustable cluster size (128-byte to 2Kbyte) to provide optimum memory utilization
  - Provides the 'To-CPU reason' in the packet header to facilitate packet processing
  - The NIC DMA supports multiple-descriptor-ring architecture for QoS applications (supports 6 RX descriptor rings and 2 TX descriptor rings)

- Peripheral Interfaces
  - Supports one PCI Express Host with integrated PHY
  - Supports one 16550 UART
  - Supports up to 17 GPIO pins
  - Supports one-port USB 2.0 host interface
  - Embedded USB PHY

- Memory Interfaces
  - Flash (NOR Type)
    - Supports two Flash banks that can be configured as 8/16-bit bus, 256k/512k/1M/2M/4M/8M bytes
    - System supports up to 16Mbyte Flash memory space
    - Boot up from NOR Flash is supported
  - Flash (SPI Type)
    - Supports 4 channels for SPI Flash application
    - Boot up from SPI Flash is supported
    - System supports up to 32Mbyte Flash memory space

- ◆ SDRAM
  - ▪ Supports two SDRAM banks that can be configured as 2M/4M/8M/16M/32M/64Mbyte
  - ▪ 16-bit SDRAM data bus is supported. System totally supports up to 128Mbyte SDRAM memory space

- ■ Supports Green Ethernet
  - ◆ Cable length power saving
  - ◆ Power down power saving

- ◆ Supports IEEE 802.3az Draft 2.0 Energy Efficient Ethernet (EEE) for 100Base-TX in full duplex operation, and 10Base-T in full/half duplex mode

- ■ Other Add-on-Value Features
  - ◆ Supports Link down power saving in Ethernet PHY
  - ◆ Supports two hardware timers and one watchdog timer
  - ◆ Per-port configurable auto-crossover function
  - ◆ Single 25MHz crystal or 40MHz clock input
  - ◆ PQFP 128-pin package

# 3. Block Diagram



**Figure 1.    Block Diagram**

# 4. Pin Assignments

## 4.1. Pin Assignments



**Figure 2.    Pin Assignments**

## 4.2. Package Identification

Green package is indicated by a 'G' in the location marked 'T' in Figure 2.

# 5. Pin Descriptions

In this section the following abbreviations are used:

| | |
|---|---|
| I: Input | AI: Analog Input |
| O: Output | AO: Analog Output |
| IO: Bi-Directional Input/Output | AI/O: Analog Bi-Directional Input/Output |
| P: Digital Power | AP: Analog Power |
| G: Digital Ground | AG: Analog Ground |
| T/S: Tri-State Bi-Directional Input/Output | S/T/S: Sustained Tri-State |
| $I_{PD}$: Input Pin With Pull-Down Resistor | $O_{OD}$: Output With Open Drain |
| $I_{PU}$: Input Pin With Pull-Up Resistor; (Typical Value = 75K Ohm) | $O_{3S}$: Output With Tri-State |

**Table 1.    Pin Descriptions**

| Pin Name | Pin No. | Type | Description |
|---|---|---|---|
| **Clock & Reset** | | | |
| 25M_XI | 127 | I | 25MHz Crystal Clock Input |
| 25M_XO | 126 | O | 25MHz Crystal Clock Output |
| 40M_CLK | 125 | I | 40MHz Clock Input $V_{peak\text{-}to\text{-}peak}$ 1.4 Voltage |
| 40M_SEL | 124 | I | System Clock Source Select. 0: 25MHz 1: 40MHz |
| RESET# | 108 | I | The System Reset Active Low |
| **10M/100Mbps Physical Layer** | | | |
| TXOP[4:0] TXON[4:0] | 28, 26, 18, 16, 7 29, 25, 19, 15, 8 | AO | 10/100M Ethernet Physical Layer Transmit Pair. For differential data transmission |
| RXIP[4:0] RXIN[4:0] | 30, 24, 20, 13, 9 31, 23, 21, 12, 8 | AI | 10/100M Ethernet Physical Layer Receive Pair. For differential data reception |
| **Memory Bus** | | | |
| MD[15:0] | 94, 93, 92, 91, 90, 89, 88, 87, 74, 75, 77, 78, 79, 80, 81, 82 | I/O | Data for SDRAM and NOR Type Flash |
| MA[21:0] | 48, 47, 46, 45, 43, 85, 72, 63, 65, 57, 56, 62, 55, 53, 52, 51, 50, 49, 58, 59, 60, 61 | O | Address for SDRAM and NOR Type Flash. Shared pins: MA[13]: SDRAM BS0          MA[14]: SDRAM BS1 MA[15]: SDRAM LDQM      MA[16]: SDRAM UDQM MA[17]: SPI Flash SDIO3      MA[18]: SPI Flash SDIO2 MA[19]: SPI Flash SDIO1      MA[20]: SPI Flash SDIO0 MA[21]: SPI Flash SCK |

| Pin Name | Pin No. | Type | Description |
|---|---|---|---|
| **SDRAM Control** | | | |
| MCLK | 84 | O | SDRAM Clock |
| MCLKE | 40 | O | SDRAM Clock Enable |
| MCS0# | 66 | O | SDRAM Bank 0 Chip Select |
| MCS1# | 67 | O | SDRAM Bank 1 Chip Select |
| BS[1:0] | 63, 65 | O | SDRAM Chip Bank Select [1:0]<br>Shared with A[14:13] |
| RAS# | 69 | O | Raw Address Strobe for SDRAM |
| CAS# | 70 | O | Column Address Strobe for SDRAM |
| WE# | 71 | O | Write Enable for SDRAM |
| LDQM | 72 | O | Lower Data Mask Output to SDRAM<br>Corresponds to D[7:0]<br>Pin shared with A[15] |
| UDQM | 85 | O | Upper Data Mask Output to SDRAM<br>Corresponds to D[15:8]<br>Pin shared with A[16] |
| **NOR Type Flash Control** | | | |
| NF_CS0# | 41 | O | ROM Bank 0 Chip Select for NOR Type Flash Memory |
| NF_CS1# | 40 | O | ROM Bank 0 Chip Select for NOR Type Flash Memory |
| OE# | 69 | O | Output Enable (OE#) for NOR Type Flash.<br>Pin shared with SDRAM RAS# |
| WE# | 71 | O | Write Enable for NOR Type Flash.<br>Pin shared with SDRAM WE# |
| **SPI Serial Flash Control** | | | |
| SF_CS0# | 41 | O | SPI Serial Flash Chip Select 0<br>Pin shared with NOF_CS0# |
| SF_CS1# | 40 | O | SPI Serial Flash Chip Select 1<br>Pin shared with NOF_CS1# |
| SF_SDIO[3:0] | 43, 45, 46, 47 | I/O | SPI Serial Flash Serial Data Input/Output |
| SF_SCK | 48 | O | SPI Serial Flash Serial Clock Output<br>The SF_SDI will be driven on the falling edge<br>The SF_SDO will be latched on the rising edge |
| **UART** | | | |
| UART_TX | 37 | O | UART Data Transmit Serial Output |
| UART_RX | 36 | $I_{PD}$ | UART Data Receive Serial Input |
| **JTAG** | | | |
| JTAG_TCK | 100 | $I_{PU}$ | JTAG Test Clock |
| JTAG_TMS | 97 | $I_{PU}$ | JTAG Test Mode Select |
| JTAG_TDO | 98 | O | JTAG Test Data Output |
| JTAG_TDI | 99 | $I_{PU}$ | JTAG Test Data In |
| JTAG_TRST# | 96 | $I_{PU}$ | JTAG Test Reset |
| **LED** | | | |
| LED_PORT[4:0] | 107, 105, 104, 102, 101 | O | Link/Activity Status of 5 Ethernet Ports |
| **GPIO** | | | |
| GPIOA[7:0] | 36, 98, 99, 97, 96, 100, 40, 67 | I/O | GPIO Port A |

| Pin Name | Pin No. | Type | Description |
|---|---|---|---|
| GPIOB[7:0] | 108, 107, 105, 104, 102, 101, 4, 37 | I/O | GPIO Port B |
| GPIOC0 | 109 | O | GPIO Port C |
| **PCI Express Interface** | | | |
| HSON<br>HSOP | 115<br>116 | AO | Transmitter Differential Pair |
| HSIN<br>HSIP | 121<br>122 | AI | Receiver Differential Pair |
| REFCLKN<br>REFCLKP | 118<br>119 | AO | Reference Clock Differential Pair |
| PCIE_RST# | 4 | O | PCI Express Reset Active Low |
| **USB2.0** | | | |
| USB_DP | 113 | AI/O | USB Device Data Plus Pin |
| USB_DN | 112 | AI/O | USB Device Data Minus Pin |
| **Test** | | | |
| TESETMODE | 38 | $I_{PD}$ | For Chip Internal Test<br>1: Test Mode<br>0: Normal Mode |
| **Reference Voltage** | | | |
| IBREF | 33 | AI | Reference Voltage for Ethernet PHY<br>2.5K 1% pull down |
| R12K | 1 | AI | Reference Voltage for System<br>12K 1% pull down |
| **Power & GND** | | | |
| VDD33 | 3, 44, 54, 64, 76, 86, 95, 106 | P | Digital I/O Power Supply 3.3V |
| AVDD33 | 11, 22, 32 | AP | Ethernet Analog Power Supply 3.3V |
| VDD10 | 5, 39, 73, 103 | P | Digital Core Power Supply 1.0V |
| AVDD10 | 6, 17, 27 | AP | Ethernet Analog Power Supply 1.0V |
| AVDD33_X25M | 123 | AP | 25M Crystal Power 3.3V |
| AVDD33_BG | 128 | AP | System Bandgap Power Supply 3.3V |
| AVDD10_PCIE | 117 | AP | PCI Express Analog Power Supply 1.0V |
| AVDD10_PHYPLL | 34 | AP | Ethernet PHY PLL Power 1.0V |
| AVDD33_USB_PCIE | 114 | AP | USB2.0 and PCI Express Analog Power 3.3V |
| AVDD10_USB | 110 | AP | USB2.0 Analog Power 1.0V |
| GND | 14, 42, 68, 83, 111 | G | System GND |
| AGND_SYSPLL | 2 | AG | System PLL GND |
| AGND_PCIE | 120 | AG | PCI Express GND |

# 5.1. RTL8196C Configuration Upon Power On Strapping

All mode configuration pins are internal pull low. The 1.0V digital core power input pin voltage is up to 0.7V on system power-on. The strap data will be latched after a delay of 300ms.

**Table 2.    RTL8196C Configuration Upon Power On Strapping**

| H/W Pin Name | Configuration Name | Pin No | Description |
|---|---|---|---|
| MA11, MA10, MA9 | ck_cpu_freq_sel[2:0] | 56, 62, 55 | CPU Clock Configuration<br>000: 250MHz<br>001: 270MHz<br>010: 290MHz<br>011: 310MHz<br>100: 330MHz<br>101: 350MHz<br>110: 370MHz<br>111: 390MHz |
| MA8, MA7, MA6 | ck_freq_sel[2:0] | 53, 52, 51 | SDRAM Clock Rate Configuration<br>000: 65.625MHz<br>001: 78.125MHz<br>010: 125MHz<br>011: 150MHz<br>100: 156.25MHz<br>101: 168.75MHz<br>110: 193.75MHz<br>111: Reserved |
| MA5 | Sync_lx_oc | 50 | Selection for Internal Bus Test Mode<br>This is a hardware strapping pin.<br>0: Normal mode<br>1: Test mode |
| MA2 | EnOLTautoTestMode | 59 | Enable Operational Level Test (OLT) Auto Test Mode<br>0: Normal mode<br>1: Test mode |
| MA1 | BOOTSEL | 60 | Boot Device Select for Flash Booting<br>0: Boot from NOR-type Flash (default)<br>1: Boot from Serial Flash (SPI) |
| MA3 | Clklx_from_clkm | 58 | Internal Local Bus Source<br>0: 200MHz<br>1: From memory clock |
| MA4 | ENABLE_EXT_RSTN | 49 | External Reset<br>0: Disable chip RESET function; Pin 108 can be used as a GPIO or DBG pin<br>1: Enable chip RESET function |
| MA12 | ck_cpu_div_sel | 57 | PLL Clock for CPU<br>0: CPU PLL clock is not divided by 2<br>1: CPU PLL clock is divided by 2 |
| MA13 | en_router_mode | 65 | Router or AP Mode Select<br>0: AP mode (Turns-off Ethernet Switch and Port 0 to Port 3 PHY circuit for power-saving)<br>1: Router mode (All Ethernet Ports are working) |
| MA14 | swap_dbg_halfword | 63 | Internal Debug Mode Select |

## 5.2. Shared I/O Pin Mapping

Table 3.    Shared I/O Pin Mapping

| Pin No. | GPIO | EJTAG | LED | UART | Reset | Memory |
|---|---|---|---|---|---|---|
| 67 | GPIOA[0] | - | - | - | - | MCS1# |
| 40 | GPIOA[1] | - | - | - | - | NF_CS1# SF_CS1# MCLKE |
| 100 | GPIOA[2] | JTAG_TCK | - | - | - | - |
| 96 | GPIOA[3] | JTAG_TRST# | - | - | - | - |
| 97 | GPIOA[4] | JTAG_TMS | - | - | - | - |
| 99 | GPIOA[5] | JTAG_TDI | - | - | - | - |
| 98 | GPIOA[6] | JTAG_TDO | - | - | - | - |
| 36 | GPIOA[7] | - | - | UART_RX | - | - |
| 37 | GPIOB[0] | - | - | UART_TX | - | - |
| 4 | GPIOB[1] | - | - | - | PCIE_RST# | - |
| 101 | GPIOB[2] | - | LED_PORT0 | - | - | - |
| 102 | GPIOB[3] | - | LED_PORT1 | - | - | - |
| 104 | GPIOB[4] | - | LED_PORT2 | - | - | - |
| 105 | GPIOB[5] | - | LED_PORT3 | - | - | - |
| 107 | GPIOB[6] | - | LED_PORT4 | - | - | - |
| 108 | GPIOB[7] | - | - | - | RESET# | - |
| 109 | GPIOC[0] | - | - | - | - | - |

# 6.   Memory Controller

The RTL8196C integrates a memory control module to access external SDRAM and Flash memory.

The interface is designed for PC133 or PC166-compliant SDRAM, and supports auto-refresh mode, which requires a 4096 refresh cycle within 64ms, and the SDRAM size and timing is configurable in registers.

The RTL8196C also supports one flash memory chip (NF_CS0#). The interface supports 8/16-bit NOR-type flash memory. When NOR type is used, the system will boot from KSEG1 at virtual address 0xBFC0_0000 (physical address: 0x1FC0_0000). The flash size is configurable from 1M to 8M bytes for each chip. If the flash size is set to 4M or 8M bytes, 0xBFC0_0000 still maps the first 4M bytes of flash, and there will be a new memory mapping from 0xBD00_0000 (0xBD00_0000 maps to chip 0 byte 0).

## 6.1.   SDRAM Control Interface

PC100~PC166-compliant SDRAM is supported. The SDRAM controller supports Auto Refresh mode, which requires a 4096-cycle refresh each 64ms. The RTL8196C provides a maximum of 512Mbit address space (8Mx16x4Banks) and the SDRAM size is configurable.

### 6.1.1.   Features

- Interface (Bus Width): 16-bit

- Targeted SDR Frequency: Up to 166MHz

- Supported SDR SDRAM Chip Specification:
    - Bank Counts: 2, 4
    - Row Counts: 2K (A0~A10), 4K (A0~A11), 8K (A0~A12)
    - Column Counts: 256 (A0~A7), 512 (A0~A8), 1K (A0~A9), 2K (A0~A9, A11)

## 6.2.   NOR Flash Type Memory

### 6.2.1.   Features

- Interface (Bus Width): 8-bit/16-bit

- Supports NOR Flash Chip Specification:
    - 8-bit: 256Kbyte, 512Kbyte, 1Mbyte, 2Mbyte, 4Mbyte
    - 16-bit: 512Kbyte, 1Mbyte, 2Mbyte, 4Mbyte, 8Mbyte

## 6.2.2. Bank Address Mapping

The flash controller supports boot sector flash memory and the system always boots from bank0. The boot bank (bank 0) is mapped to KSEG1 with the start physical address of 0x1E00.0000 (virtual address: 0xBD00.0000). Bank0 is also mapped to the start physical address of 0x1FC0.0000.

The system always boots up from bank 0. For software, it is suggested that the program jumps to the space [0x1E00.0000~0x1EFF.FFFF] for a larger continuous space after booting up from 0x1FC0.0000. However, for backward compatibility, the program can choose to stay in the 4MByte space [0x1FC0.0000~0x1FFF.FFFF].



**Figure 3.    One 16-bit, for 1M/2M/4M/8M Bytes Flash Configuration**

## 6.2.3. Flash Command Sequence

Directly write or read the target Flash address following the command sequence specified in the flash memory provider's datasheet. However, programmers must pay attention to the following:

- Use 16-bit (half-word) manipulation. Byte or full word manipulation will cause unpredictable errors

- The Program address is the address defined for the Flash

- The Command address is 0xBFC0.0000 + command address * 2

- Program data/Command data. The data may be placed in either the lower half-word or upper half-word position in a 32-bit full word. It depends on the least significant two bits of the accessed address

## 6.3. *SPI Flash Controller*

The SPI flash controller is a new design and incorporates new features.

### 6.3.1. Features

- Targeted SPI Flash Frequency: Up to 78MHz (when the SDRAM clock is 156MHz)

- In addition to a programmed I/O interface, also supports a memory-mapped I/O interface for read operations

- Supports Read and Fast Read in memory-mapped I/O mode

## 6.4. *Software Register Definition*

### 6.4.1. Memory Control Register (MCR) (0xB800_1000)

This register does not provide byte access.

**Table 4.    Memory Control Register (MCR) (0xB800_1000)**

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31 | DRAMTYPE | Report the Hardware Strapping Initial Value for DRAM Type<br>0: SDR DRAM                              1: Reserved | R | 0B |
| 30 | BOOTSEL | Report the Hardware Strapping Initial Value for Boot Flash Type<br>0: NOR flash                      1: SPI flash | R | 0B |
| 29 | IPREF | Enable Instruction Prefetch Function<br>0: Disable prefetch (also resets buffer status)<br>1: Enable prefetch (4 words) | RW | 0B |
| 28 | DPREF | Enable Data Prefetch Function<br>0: Disable prefetch (also resets buffer status)<br>1: Enable prefetch (4 words) | RW | 0B |
| 27 | IPREF_MODE | Choose Instruction Prefetch Mode<br>0: Old prefetch mechanism          1: New prefetch mechanism | RW | 0B |
| 26 | DPREF_MODE | Choose Data Prefetch Mode<br>0: Old prefetch mechanism          1: New prefetch mechanism | RW | 0B |
| 25 | BOOTSEL2 | Report the Hardware Strapping Initial Value for Boot Source<br>0: Flash Type (NOR or SPI Flash)<br>1: Reserved | R | 0B |
| 24:0 | Reserved | Reserved | R | 0B |

## 6.4.2. DRAM Configuration Register (DCR) (0xB800_1004)

This register does not provide byte access.

**Table 5. DRAM Configuration Register (DCR) (0xB800_1004)**

| Bit | Name | Description | | Mode | Default |
|---|---|---|---|---|---|
| 31:30 | T_CAS | CAS Latency<br>00: Latency=2<br>10: Latency=2.5 | 01: Latency=3<br>11: Reserved | RW | 01B |
| 29:28 | DBUSWID | DRAM Bus Width<br>00: Reserved<br>10: Reserved | 01: 16-bit<br>11: Reserved | RW | 01B |
| 27 | DCHIPSEL | DRAM Chip Select<br>0: Test mode | 1: Normal mode | RW | 1B |
| 26:25 | ROWCNT | Row Counts<br>00: 2K (A0~A10)<br>10: 8K (A0~A12) | 01: 4K (A0~A11)<br>11: 16K (A0~A13) | RW | 00B |
| 24:22 | COLCNT | Column Counts<br>000: 256 (A0~A7)<br>010: 1K (A0~A9)<br>100: 4K (A0~A9, A11, A12)<br>110: Reserved | 001: 512 (A0~A8)<br>011: 2K (A0~A9, A11)<br>101: Reserved<br>111: Reserved | RW | 000B |
| 21 | BSTREF | Bursted 8 Auto-Refresh Commands (Used for DDR)<br>0: Disable | 1: Enable | RW | 0B |
| 20 | ARBIT | Enforce Interface Arbitration to Take Effect<br>0: Reserved | 1: Take effect | RW | 0B |
| 19 | BANKCNT | Bank Counts<br>0: 2 banks (used for SDR) | 1: 4 banks (used for SDR, DDR) | RW | 1B |
| 18 | FAST_RX | If RX path turnaround delay is small enough, the memory controller can return read data with reduced latency within 1DRAM clock cycle (used for DDR).<br>0: Normal path | 1: Fast path | RW | 0B |
| 17 | MR_MODE | Select the Memory Command that the Memory Controller Issues (Used for DDR)<br>0: Mode Register | 1: Extended Mode Register | RW | 0B |
| 16 | DRV_STR | Drive Strength Setting of DRAM Chip (Used for DDR)<br>For this option to be effective, MR_MODE must be first set to 1.<br>0: Normal | 1: Reduced | RW | 0B |
| 15:0 | Reserved | Reserved | | - | - |

## 6.4.3. DRAM Timing Register (DTR) (0xB800_1008)

This register does not provide byte access.

Table 6. DRAM Timing Register (DTR) (0xB800_1008)

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:29 | T_RP | tRP Timing Parameter of DRAM<br>Basic unit = 1* DRAM_CLK<br>000 means 1 unit | RW | 111B |
| 28:26 | T_RCD | tRCD Timing Parameter of DRAM<br>Basic unit = 1* DRAM_CLK<br>000 means 1 unit | RW | 111B |
| 25:21 | T_RAS | Minimum T_RAS Timing Parameter of DRAM<br>Basic unit = 1* DRAM_CLK<br>00000 means 1 unit | RW | 11111B |
| 20:16 | T_RFC | tRFC Timing Parameter of DRAM<br>Refresh row cycle time<br>Basic unit = 1* DRAM_CLK<br>00000 means 1 unit | RW | 11111B |
| 15:12 | T_REFI | tREF Timing Parameter of DRAM<br>Refresh row interval time<br>Basic unit = T_REFI_UNIT<br>0000: 1 unit<br>0001: 2 units<br>…<br>1111: 16 units | RW | 0000B |
| 11:9 | T_REFI_UNIT | Basic Unit of T_REFI<br>000: 32 DRAM_CLK   001: 64 DRAM_CLK<br>010: 128 DRAM_CLK   011: 256 DRAM_CLK<br>100: 512 DRAM_CLK   101: 1024 DRAM_CLK<br>110: 2048 DRAM_CLK   111: 4096 DRAM_CLK | RW | 111B |
| 8:6 | T_WR | tWR Timing Parameter of DRAM<br>Write recovery time<br>Basic unit = 1* DRAM_CLK<br>000 means 1 unit | RW | 111B |
| 5:0 | Reserved | Reserved | - | - |

## 6.4.4.    NOR Flash Configuration Register (NFCR) (0xB800_1100)

This register does not provide byte access.

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:28 | T_CEPL | The Timing Interval for CE# to be Pulled-Low before WE#/OE# is Pulled-Low<br>Basic Unit = 1 * DRAM clock cycle<br>0000 means 1 unit | RW | 1111B |
| 27:23 | T_WEOEPL | The Timing Interval for WE#/OE# to be Pulled-Low<br>Basic Unit = 1 * DRAM clock cycle<br>00000 means 1 unit | RW | 11111B |
| 22:19 | T_RDOZ | The Timing Interval for OE# to be Pulled-High before Read-Data Output High-Z<br>Basic Unit = 1 * DRAM clock cycle<br>0000 means 1 unit | RW | 1111B |
| 18:16 | NFSIZE | NOR Flash Size<br>000: 256Kbyte          001: 512Kbyte<br>010: 1Mbyte          011: 2Mbyte<br>100: 4Mbyte          101: 8Mbyte<br>110: Reserved          111: Reserved | RW | 110B |
| 15 | NBUSW | NOR Flash Bus Width<br>0: 8-bit          1: 16-bit | R | 1B |
| 14:0 | Reserved | Reserved | - | - |

## 6.4.5.    SPI Flash Configuration Register (SFCR) (0xB800_1200)

This register does not provide byte access.

**Table 8.    SPI Flash Configuration Register (SFCR) (0xB800_1200)**

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:29 | SPI_CLK_DIV | SPI Operating Clock Rate Selection<br>The value defines the divisor to generate the SPI clock.<br>SPI Clock = (SDRAM Clock) / (SPI_CLK_DIV)<br>000: DIV = 2          001: DIV = 4<br>010: DIV = 6          011: DIV = 8<br>100: DIV = 10          101: DIV = 12<br>110: DIV = 14          111: DIV = 16 | RW | 111B |
| 28 | RBO | Serial Flash Read Byte Ordering<br>0: The byte order is from low to high<br>1: The byte order is from high to low | RW | 1B |
| 27 | WBO | Serial Flash Write Byte Ordering<br>0: The byte order is from low to high<br>1: The byte order is from high to low | RW | 1B |
| 26-23 | SPI_TCS | SPI Chip Deselect Time<br>Basic unit = 1 * DRAM clock cycle<br>0000 means 1 unit, 0001 means 2 units, etc. | RW | 1111B |
| 22:0 | Reserved | Reserved | - | - |

## 6.4.6. SPI Flash Configuration Register 2 (SFCR2) (0xB800_1204)

This register does not provide byte access.

**Table 9.    SPI Flash Configuration Register 2 (SPCR2) (0xB800_1204)**

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:24 | SFCMD | SPI Flash 8-Bit Command Code of a Read Transaction<br>Example:<br>'Read Data' is 0x03.<br>'Fast Read' is 0x0B. | RW | 0x03H |
| 23:21 | SFSIZE | SPI Flash Size<br>000: 128Kbytes                001: 256Kbytes<br>010: 512Kbytes                011: 1Mbytes<br>100: 2Mbytes                101: 4Mbytes<br>110: 8Mbytes                111: 16Mbytes | RW | 111B |
| 20 | RD_OPT | SPI Flash Sequential Access Optimization<br>0: No optimization<br>1: Optimization for sequential access | RW | 0B |
| 19:18 | CMD_IO | SPI Flash I/O Mode Selection for the Command Phase of a Read Transaction<br>00: Serial I/O (8 cycles)<br>01: Dual I/O (4 cycles)<br>10: Quad I/O (2 cycles)<br>11: Reserved | RW | 00B |
| 17:16 | ADDR_IO | SPI Flash I/O Mode Selection for the Address Phase of a Read Transaction<br>00: Serial I/O (24 cycles)<br>01: Dual I/O (12 cycles)<br>10: Quad I/O (6 cycles)<br>11: Reserved | RW | 00B |
| 15:13 | DUMMY_CYCLES | SPI Flash Inserted Dummy Cycles for the Dummy Cycle Phase of a Read Transaction<br>000: 0 cycles                001: 2 cycles<br>010: 4 cycles                011: 6 cycles<br>100: 8 cycles                101: 10 cycles<br>110: 12 cycles                111: 14 cycles | RW | 000B |
| 12:11 | DATA_IO | SPI Flash I/O Mode Selection for the Data Phase of a Read Transaction (Assume 8*N Cycles)<br>00: Serial I/O (8*N cycles)<br>01: Dual I/O (4*N cycles)<br>10: Quad I/O (2*N cycles)<br>11: Reserved | RW | 00B |
| 10 | HOLD_TILL_SFDR2 | If this bit is '1', it indicates the write operation to this register (SFCR2) will not take effect immediately but will be delayed until another write operation to SFDR2. | RW | 0B |
| 9:0 | Reserved | Reserved | - | - |

## 6.4.7.  SPI Flash Control and Status Register (SFCSR) (0xB800_1208)

This register does not provide byte access.

Table 10.  SPI Flash Control and Status Register (SFCSR) (0xB800_1208)

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31 | SPI_CSB0 | SPI Flash Chip Select 0 (CS0#)<br>0: Active<br>1: Not active | RW | 1B |
| 30 | SPI_CSB1 | SPI Flash Chip Select 1 (CS1#)<br>0: Active<br>1: Not active | RW | 1B |
| 29:28 | LEN | SPI Read/Write Data Length (Unit = byte)<br>00: 1 byte<br>01: 2 byte<br>10: 3 byte<br>11: 4 byte | RW | 11B |
| 27 | SPI_RDY | SPI Flash Operation Busy Indication Flag<br>0: Busy (operation in progress)<br>1: Ready (idle or SPI access command is ready) | R | 1B |
| 26:25 | IO_WIDTH | SPI Flash I/O Mode Selection of a Transaction<br>00: Serial I/O<br>01: Dual I/O<br>10: Quad I/O<br>11: Reserved | RW | 00B |
| 24 | CHIP_SEL | Chip Selection<br>0: CS0#<br>1: CS1# | RW | 0B |
| 23:16 | CMD_BYTE | SPI Flash 8-Bit Command Code of a Transaction<br>This field is only used in Memory-Mapped I/O (MMIO) mode.<br>Example:<br>'Read Data' is 0x03.<br>'Fast Read' is 0x0B. | RW | 0B |
| 15:0 | Reserved | Reserved | - | - |

## 6.4.8.  SPI Flash Data Register (SFDR) (0xB800_120C)

This register does not provide byte access.

**This configuration register is used under PIO (Programmed I/O) access mode.**

Table 11.  SPI Flash Data Register (SFDR) (0xB800_120C)

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:24 | Data3 | Read/Write Data Byte 3 | RW | 0B |
| 23:16 | Data2 | Read/Write Data Byte 2 | RW | 0B |
| 15:8 | Data1 | Read/Write Data Byte 1 | RW | 0B |
| 7:0 | Data0 | Read/Write Data Byte 0 | RW | 0B |

## 6.4.9. SPI Flash Data Register 2 (SFDR2) (0xB800_1210)

This register does not provide byte access.

**This configuration register is used under Memory-Mapped I/O (MMIO) access mode.**

**Table 12.    SPI Flash Data Register 2 (SFDR2) (0xB800_1210)**

| Bit | Name | Description | Mode | Default |
|---|---|---|---|---|
| 31:24 | Data3 | Read/Write Data Byte 3 | RW | 0B |
| 23:16 | Data2 | Read/Write Data Byte 2 | RW | 0B |
| 15:8 | Data1 | Read/Write Data Byte 1 | RW | 0B |
| 7:0 | Data0 | Read/Write Data Byte 0 | RW | 0B |

# 7.    Peripheral and MISC Control

## 7.1.    GPIO Control

The RTL8196C provides four sets of General Purpose Input/Output (GPIO) pins (GPIO A, B, C, D). Each GPIO pin may be configured as an input or output pin. The GPIO DATA register may be used to control GPIO pin signals. The GPIO pins are shared with some peripheral pins, and the type of peripheral can affect the attributes of the shared pins. All GPIO sets can be used to generate interrupts, and an interrupt mask and status register are provided. All the GPIO control registers are defined in the following tables.

### 7.1.1.    GPIO Register Set (0xB800_3500)

Table 13.    GPIO Register Set (0xB800_3500)

| Offset | Size (byte) | Name | Description |
|--------|-------------|------|-------------|
| 0x00 | 4 | PABCD_CNR | Port A, B, C, D Control Register |
| 0x08 | 4 | PABCD_DIR | Port A, B, C, D Direction Register |
| 0x0C | 4 | PABCD_DAT | Port A, B, C, D Data Register |
| 0x10 | 4 | PABCD_ISR | Port A, B, C, D Interrupt Status Register |
| 0x14 | 4 | PAB_IMR | Port A, B Interrupt Mask Register |
| 0x18 | 4 | PCD_IMR | Port C, D Interrupt Mask Register |

### 7.1.2.    GPIO Port A, B, C, D Control Register (PABCD_CNR) (0xB800_3500)

Table 14.    GPIO Port A, B, C, D Control Register (PABCD_CNR) (0xB800_3500)

| Bit | Name | Description | RW | Default |
|-----|------|-------------|----|---------|
| 31:24 | PFC_D[7:0] | Pin Function Configuration of Port D | RW | FFH |
| 23:16 | PFC_C[7:0] | Pin Function Configuration of Port C | RW | FFH |
| 15:8 | PFC_B[7:0] | Pin Function Configuration of Port B | RW | FFH |
| 7:0 | PFC_A[7:0] | Pin Function Configuration of Port A<br>Bit Value:<br>0: Configured as GPIO pin<br>1: Configured as dedicated peripheral pin | RW | FFH |

### 7.1.3.    GPIO Port A, B, C, D Direction Register (PABCD_DIR) (0xB800_3508)

Table 15.    GPIO Port A, B, C, D Direction Register (PABCD_DIR) (0xB800_3508)

| Bit | Name | Description | RW | Default |
|-----|------|-------------|----|---------|
| n.31-n.24 | DRC_D[7:0] | Pin Direction Configuration of Port D<br>0: Configured as input pin          1: Configured as output pin | RW | 00H |
| n.23-n.16 | DRC_C[7:0] | Pin Direction Configuration of Port C<br>0: Configured as input pin          1: Configured as output pin | RW | 00H |
| n.15-n.8 | DRC_B[7:0] | Pin Direction Configuration of Port B<br>0: Configured as input pin          1: Configured as output pin | RW | 00H |
| n.7-n.0 | DRC_A[7:0] | Pin Direction Configuration of Port A<br>0: Configured as input pin          1: Configured as output pin | RW | 00H |

## 7.1.4. Port A, B, C, D Data Register (PABCD_DAT) (0xB800_350C)

**Table 16. Port A, B, C, D Data Register (PABCD_DAT) (0xB800_350C)**

| Bit | Name | Description | | RW | Default |
|---|---|---|---|---|---|
| n.31-n.24 | PD_D[7:0] | Pin Data of Port D<br>0: Data=0 | 1: Data=1 | RW | 00H |
| n.23-n.16 | PD_C[7:0] | Pin Data of Port C<br>0: Data=0 | 1: Data=1 | RW | 00H |
| n.15-n.8 | PD_B[7:0] | Pin Data of Port B<br>0: Data=0 | 1: Data=1 | RW | 00H |
| n.7-n.0 | PD_A[7:0] | Pin Data of Port A<br>0: Data=0 | 1: Data=1 | RW | 00H |

## 7.1.5. Port A, B, C, D Interrupt Status Register (PABCD_ISR) (0xB800_3510)

**Table 17. Port A, B, C, D Interrupt Status Register (PABCD_ISR) (0xB800_3510)**

| Bit | Name | Description | RW | Default |
|---|---|---|---|---|
| n.31-n.24 | IPS_D[7:0] | Interrupt Pending Status of Port D<br>Write '1' to clear the interrupt | RW | 00H |
| n.23-n.16 | IPS_C[7:0] | Interrupt Pending Status of Port C<br>Write '1' to clear the interrupt | RW | 00H |
| n.15-n.8 | IPS_B[7:0] | Interrupt Pending Status of Port B<br>Write '1' to clear the interrupt | RW | 00H |
| n.7-n.0 | IPS_A[7:0] | Interrupt Pending Status of Port A<br>Write '1' to clear the interrupt | RW | 00H |

## 7.1.6. Port A, B Interrupt Mask Register (PAB_IMR) (0xB800_3514)

**Table 18. Port A, B Interrupt Mask Register (PAB_IMR) (0xB800_3514)**

| Bit | Name | Description | RW | Default |
|---|---|---|---|---|
| n.31- n.30 | PB7_IM[1:0] | PortB.7 Interrupt Mode | RW | 00B |
| n.29- n.28 | PB6_IM[1:0] | PortB.6 Interrupt Mode | RW | 00B |
| n.27- n.26 | PB5_IM[1:0] | PortB.5 Interrupt Mode | RW | 00B |
| n.25- n.24 | PB4_IM[1:0] | PortB.4 Interrupt Mode | RW | 00B |
| n.23- n.22 | PB3_IM[1:0] | PortB.3 Interrupt Mode | RW | 00B |
| n.21- n.20 | PB2_IM[1:0] | PortB.2 Interrupt Mode | RW | 00B |
| n.19- n.18 | PB1_IM[1:0] | PortB.1 Interrupt Mode | RW | 00B |
| n.17- n.16 | PB0_IM[1:0] | PortB.0 Interrupt Mode | RW | 00B |
| n.15- n.14 | PA7_IM[1:0] | PortA.7 Interrupt Mode | RW | 00B |
| n.13-n.12 | PA6_IM[1:0] | PortA.6 Interrupt Mode | RW | 00B |
| n.11- n.10 | PA5_IM[1:0] | PortA.5 Interrupt Mode | RW | 00B |
| n.9-n.8 | PA4_IM[1:0] | PortA.4 Interrupt Mode | RW | 00B |
| n.7-n.6 | PA3_IM[1:0] | PortA.3 Interrupt Mode | RW | 00B |
| n.5-n.4 | PA2_IM[1:0] | PortA.2 Interrupt Mode | RW | 00B |

| Bit | Name | Description | RW | Default |
|---|---|---|---|---|
| n.3-n.2 | PA1_IM[1:0] | PortA.1 Interrupt Mode | RW | 00B |
| n.1-n.0 | PA0_IM[1:0] | PortA.0 Interrupt Mode<br>00: Disable interrupt<br>01: Enable falling edge interrupt<br>10: Enable rising edge interrupt<br>11: Enable both falling or rising edge interrupt | RW | 00B |

## 7.1.7. Port C, D Interrupt Mask Register (PCD_IMR) (0xB800_3518)

**Table 19.    Port C, D Interrupt Mask Register (PCD_IMR) (0xB800_3518)**

| Bit | Name | Description | RW | Default |
|---|---|---|---|---|
| n.31- n.30 | PD7_IM[1:0] | PortD.7 Interrupt Mode | RW | 00B |
| n.29- n.28 | PD6_IM[1:0] | PortD.6 Interrupt Mode | RW | 00B |
| n.27- n.26 | PD5_IM[1:0] | PortD.5 Interrupt Mode | RW | 00B |
| n.25- n.24 | PD4_IM[1:0] | PortD.4 Interrupt Mode | RW | 00B |
| n.23- n.22 | PD3_IM[1:0] | PortD.3 Interrupt Mode | RW | 00B |
| n.21- n.20 | PD2_IM[1:0] | PortD.2 Interrupt Mode | RW | 00B |
| n.19- n.18 | PD1_IM[1:0] | PortD.1 Interrupt Mode | RW | 00B |
| n.17- n.16 | PD0_IM[1:0] | PortC.0 Interrupt Mode | RW | 00B |
| n.15- n.14 | PC7_IM[1:0] | PortC.7 Interrupt Mode | RW | 00B |
| n.13-n.12 | PC6_IM[1:0] | PortC.6 Interrupt Mode | RW | 00B |
| n.11- n.10 | PC5_IM[1:0] | PortC.5 Interrupt Mode | RW | 00B |
| n.9-n.8 | PC4_IM[1:0] | PortC.4 Interrupt Mode | RW | 00B |
| n.7-n.6 | PC3_IM[1:0] | PortC.3 Interrupt Mode | RW | 00B |
| n.5-n.4 | PC2_IM[1:0] | PortC.2 Interrupt Mode | RW | 00B |
| n.3-n.2 | PC1_IM[1:0] | PortC.1 Interrupt Mode | RW | 00B |
| n.1-n.0 | PC0_IM[1:0] | PortC.0 Interrupt Mode<br>00: Disable interrupt<br>01: Enable falling edge interrupt<br>10: Enable rising edge interrupt<br>11: Enable both falling or rising edge interrupt | RW | 00B |

# 7.2.  GPIO Shared Pin Mapping List

The RTL8196C GPIO pins are shared with other functions.

**Table 20.    Shared Pin Register (PIN_MUX_SEL) (0xB800_0040)**

| Bit | Bit Name | Description | RW | Default |
|---|---|---|---|---|
| 31:24 | Reserved | Reserved | - | - |
| 23 | reg_iocfg_pcie | Configure PCIE_RST# as PCIE_RST# or GPIO<br>0: PCIE_RST#<br>1: GPIOB1 | RW | 2'b0 |
| 22 | reg_iocfg_uart | Configure UART Pins as UART, DBG, or GPIO Mode<br>0: UART<br>1: GPIOA7 and GPIOB0 | RW | 2'b0 |

| Bit | Bit Name | Description | RW | Default |
|---|---|---|---|---|
| 21:20 | reg_iocfg_jtag | Configure JTAG Pins as JTAG, DBG, or GPIO Mode<br>0x: JTAG<br>10: DBG mode      11: GPIOA[6:2] | RW | 2'b00 |
| 19:18 | reg_iocfg_mem | Configure Flash/DRAM CS1# as Flash/DRAM CS1#, DRAM CKE, DBG, or GPIO Mode<br>00: NF_CS1#/MCS1#    01: DRAM CKE<br>10: DBG mode      11: GPIOA[1:0] | RW | 2'b00 |
| 17:14 | Reserved | Reserved | - | - |
| 13:12 | reg_iocfg_led_p2 | Configure LEDPHASE2 Pin as DBG or GPIO Mode<br>0x: Reserved<br>10: DBG mode      11: GPIOC0 | RW | 2'b00 |
| 11:10 | reg_iocfg_led_p1 | Configure LEDPHASE1 Pin as DBG or GPIO Mode<br>0x: Reserved<br>10: DBG mode      11: GPIOB7 | RW | 2'b00 |
| 9:8 | reg_iocfg_led_p0 | Configure LEDPHASE0 Pin as LED-SW, DBG, or GPIO Mode<br>0x: LED_PORT4<br>10: DBG mode      11: GPIOC6 | RW | 3'b000 |
| 7:6 | reg_iocfg_led_s3 | Configure LEDSIG3 Pin as LED-SW, DBG, or GPIO Mode<br>0x: LED_PORT3<br>10: DBG mode      11: GPIOB5 | RW | 2'b00 |
| 5:4 | reg_iocfg_led_s2 | Configure LEDSIG2 Pin as LED-SW, DBG, or GPIO Mode<br>0x: LED_PORT2<br>10: DBG mode      11: GPIOB4 | RW | 2'b00 |
| 3:2 | reg_iocfg_led_s1 | Configure LEDSIG1 Pin as LED-SW, DBG, or GPIO Mode<br>0x: LED_PORT1<br>10: DBG mode      11: GPIOB3 | RW | 2'b00 |
| 1:0 | reg_iocfg_led_s0 | Configure LEDSIG0 Pin as LED-SW, DBG, or GPIO Mode<br>0x: LED_PORT0<br>10: DBG mode      11: GPIOB2 | RW | 2'b00 |

# 8. Green Ethernet

## 8.1. Cable Length Power Saving

The RTL8196C provides link-on and dynamic detection of cable length, and dynamic adjustment of power required for the detected cable length. This feature provides high performance with minimum power consumption.

## 8.2. Link Down Power Saving

The RTL8196C implements link-down power saving on a per-port basis, greatly cutting power consumption when the network cable is disconnected. A port automatically enters link down power saving mode ten seconds after the cable is disconnected from it. Once a port enters link down power saving mode, it transmits normal link pulses on its TXOP/TXON pins and continues to monitor the RXIP/RXIN pins to detect incoming signals, which might be 100Base-TX MLT-3 idle pattern, 10Base-T link pulses, or Auto-Negotiation's FLP (Fast Link Pulse). After it detects an incoming signal, it wakes up from link down power saving mode and operates in normal mode according to the result of the connection.

## 8.3. Energy Efficient Ethernet (EEE)

The RTL8196C supports IEEE 802.3az Draft 2.0, also known as Energy Efficient Ethernet (EEE) in 100Base-TX in full duplex operation, and 10Base-T in full/half duplex mode. This standard is being developed by the IEEE 802.3az Task Force, and should be finalized by September 2010. It provides a protocol to coordinate transitions to/from a lower power consumption level (Low Power Idle mode) based on link utilization. When no packets are being transmitted, the system goes to Low Power Idle mode to save power. Once packets need to be transmitted, the system returns to normal mode, and does this without changing the link status and without dropping/corrupting frames.

To save power, when the system is in Low Power Idle mode, most of the circuits are disabled, however, the transition time to/from Low Power Idle mode is kept small enough to be transparent to upper layer protocols and applications.

EEE also specifies a negotiation method to enable link partners to determine whether EEE is supported and to select the best set of parameters common to both devices.

- For 100Base-TX PHY: Supports Energy Efficient Ethernet with the optional function of Low Power Idle.

- For 10Base-T, EEE defines a 10Mbps PHY (10Base-Te) with reduced transmit amplitude requirements. 10Base-Te is fully interoperable with 10Base-T PHYs over 100m of class-D (Cat-5) cable.

Refer to http://ieee802.org/3/interims/index.html for more details.

# 9.  DC Specifications

## 9.1.  Operating Conditions

**Table 21.   Operating Conditions**

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|---|---|---|---|---|---|
| VDD33 | Digital I/O Power Supply 3.3V | TBD | TBD | TBD | V |
| AVDD33 | Ethernet Analog Power Supply 3.3V | TBD | TBD | TBD | V |
| VDD10 | Core Power Supply 1.0V | TBD | TBD | TBD | V |
| AVDD10 | Ethernet Analog Power Supply 1.0V | TBD | TBD | TBD | V |
| AVDD33_X25M | 25M Crystal Power 3.3V | TBD | TBD | TBD | V |
| VDD33_BG | System Bandgap Power Supply 3.3V | TBD | TBD | TBD | V |
| AVDD10_PCIE | PCI Express Analog Power 1.0V | TBD | TBD | TBD | V |
| AVDD10_PHYPLL | Ethernet PHY PLL Power 1.0V | TBD | TBD | TBD | V |
| AVDD33_USB_PCIE | USB 2.0 Analog Power 3.3V | TBD | TBD | TBD | V |
| AVDD10_USB | USB 2.0 Analog Power 1.0V | TBD | TBD | TBD | V |

## 9.2.  Power Dissipation

**Table 22.   Power Dissipation**

| Parameter | SYM | Conditions | Min | Typ. | Max | Units |
|---|---|---|---|---|---|---|
| Power Supply Current for VDD33 | $I_{VDD33}$ | All LAN Ports Idle | - | TBD | - | mA |
| | | LAN Full Load Active for Link at 10Base-T | - | TBD | - | |
| | | LAN Full Load Active for Link at 100Base-TX | - | TBD | - | |
| Power Supply Current for VDD10 | $I_{VDD10}$ | All LAN Ports Idle and CPU Suspend | - | TBD | - | mA |
| | | All LAN Ports Idle | - | TBD | - | |
| | | LAN Full Load Active for Link at 10Base-T | - | TBD | - | |
| | | LAN Full Load Active for Link at 100Base-TX | - | TBD | - | |
| 3.3V Ethernet Analog Current for AVDD33 | $I_{AVDD33}$ | All LAN Ports Idle | - | TBD | - | mA |
| | | LAN Full Load Active for Link at 10Base-T | - | TBD | - | |
| | | LAN Full Load Active for Link at 100Base-TX | - | TBD | - | |
| 1.0V Ethernet Analog Current for AVDD10 | $I_{AVDD10}$ | All LAN Ports Idle | - | TBD | - | mA |
| | | LAN Full Load Active for Link at 10Base-T | - | TBD | - | |
| | | LAN Full Load Active for Link at 100Base-TX | - | TBD | - | |
| 3.3V Current for AVDD33_X25M | $I_{AVDDX}$ | 25M Crystal 3.3V Current | - | TBD | - | mA |
| 3.3V Current for AVDD33_BG | $I_{AVDDBG}$ | System Bandgap 3.3V Current | - | TBD | - | mA |
| 1.0V Current for AVDD10_PCIE | $I_{PCIE}$ | PCI Express 1.0V Current | - | TBD | - | mA |
| 1.0V Current for AVDD10_PHYPLL | $I_{PHYPLL}$ | Ethernet PHY PLL Power 1.0V | - | TBD | - | mA |
| 3.3V Current for AVDD33_USB_PCIE | $I_{USB\_AVDD33}$ | USB 2.0 and PCI Express Analog Power 3.3V | - | TBD | | mA |
| 1.0V Current for AVDD10_USB | $I_{LV\_USB\_PCIE}$ | USB 2.0 Analog Power 1.0V | - | TBD | - | mA |

| Parameter | SYM | Conditions | Min | Typ. | Max | Units |
|---|---|---|---|---|---|---|
| Total Power Consumption | PS | All LAN Ports Idle and CPU Suspended | - | TBD | - | Watt |
| | | All LAN Ports Idle | - | TBD | - | |
| | | LAN Full Load Active for Link at 10Base-T | - | TBD | - | |
| | | LAN Full Load Active for Link at 100Base-TX | - | TBD | - | |

*Note: The power consumption is measured at full load of the chip system with the operating condition of: CPU=330MHz, SDRAM=162MHz.*

# 9.3. SDRAM Bus DC Parameters

Table 23.   SDRAM Bus DC Parameters

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|---|---|---|---|---|---|---|---|
| $V_{IH}$ | Input-High Voltage | LVTTL | TBD | - | - | V | 1 |
| $V_{IL}$ | Input-Low Voltage | LVTTL | - | - | TBD | V | 2 |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | - | V | 3 |
| $V_{OL}$ | Output-Low Voltage | - | - | - | TBD | V | 3 |
| $I_{IL}$ | Input-Leakage Current | $V_{IN}$=3.3V or 0 | TBD | ±1 | TBD | μA | - |
| $I_{OZ}$ | Tri-State Output-Leakage Current | - | TBD | ±1 | TBD | μA | - |
| $R_{PU}$ | Input Pull-Up Resistance | - | - | TBD | - | KΩ | 4 |
| $R_{PD}$ | Input Pull-Down Resistance | - | - | TBD | - | KΩ | 4 |

*Note 1: VIH overshot: VIH (MAX)=VDDH + 2V for a pulse width ≤ 3ns, and the pulse width not greater than one third of the cycle rate.*

*Note 2: VIL undershot: VIL (MIN)=-2V for a pulse width ≤ 3ns cannot be exceeded.*

*Note 3: The output current buffer is 16mA for SDRAM clock, address, and data bus.*

*Note 4: These values are typical values checked in the manufacturing process and are not tested.*

# 9.4. Flash Bus DC Parameters

Table 24.   Flash Bus DC Parameters

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|---|---|---|---|---|---|---|---|
| $V_{IH}$ | Input-High Voltage | LVTTL | TBD | - | - | V | 1 |
| $V_{IL}$ | Input-Low Voltage | LVTTL | - | - | TBD | V | 2 |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | - | V | 3 |
| $V_{OL}$ | Output-Low Voltage | - | - | - | TBD | V | 3 |
| $I_{IL}$ | Input-Leakage Current | $V_{IN}$=3.3V or 0 | TBD | ±1 | TBD | μA | - |
| $I_{OZ}$ | Tri-State Output-Leakage Current | - | TBD | ±1 | TBD | μA | - |
| $R_{PU}$ | Input Pull-Up Resistance | - | - | TBD | - | KΩ | 4 |
| $R_{PD}$ | Input Pull-Down Resistance | - | - | TBD | - | KΩ | 4 |

*Note 1: VIH overshot: VIH (MAX)=VDDH + 2V for a pulse width ≤ 3ns.*

*Note 2: VIL undershot: VIL (MIN)= -2V for a pulse width ≤ 3ns.*

*Note 3: The output current buffer is 8mA for the flash address and data bus; and is 8mA for Flash control signals.*

*Note 4: These values are typical values checked in the manufacturing process and are not tested.*

## 9.5.  USB 1.1 DC Parameters

**Table 25.   USB 1.1 DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|--------|-----------|------------|------|------|------|-------|-------|
| $V_{IH}$ | Input-High Voltage | - | TBD | - | - | V | 2 |
| $V_{IL}$ | Input-Low Voltage | - | - | - | TBD | V | 2 |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | - | V | 2 |
| $V_{OL}$ | Output-Low Voltage | - | - | - | TBD | V | 2 |
| $I_{IL}$ | Input-Leakage Current | $V_{IN}$=3.3V or 0 | - | - | - | µA | 1 |

Note 1: These values are typical values checked in the manufacturing process and are not tested.
Note 2: For additional information, see the USB 1.1 Specification.

## 9.6.  USB 2.0 DC Parameters

**Table 26.   USB 2.0 DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|--------|-----------|------------|------|------|------|-------|-------|
| $V_{IH}$ | Input-High Voltage | - | TBD | - | - | mV | 2 |
| $V_{IL}$ | Input-Low Voltage | - | - | - | TBD | mV | 2 |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | TBD | mV | 2 |
| $V_{OL}$ | Output-Low Voltage | - | TBD | - | TBD | mV | 2 |
| $I_{IL}$ | Input-Leakage Current | - | - | - | - | µA | 1 |

Note 1: These values are typical values checked in the manufacturing process and are not tested.
Note 2: For additional information, see the USB 2.0 Specifications.

## 9.7.  UART DC Parameters

**Table 27.   UART DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|--------|-----------|------------|------|------|------|-------|-------|
| $V_{IH}$ | Input-High Voltage | LVTTL | TBD | - | - | V | - |
| $V_{IL}$ | Input-Low Voltage | LVTTL | TBD | - | TBD | V | - |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | TBD | V | 1 |
| $V_{OL}$ | Output-Low Voltage | - | TBD | - | TBD | V | 1 |
| $I_{IL}$ | Input-Leakage Current | $V_{IN}$=3.3V or 0 | TBD | TBD | TBD | µA | 2 |
| $R_{PU}$ | Input Pull-Up Resistance | - | - | TBD | - | KΩ | 2 |
| $R_{PD}$ | Input Pull-Down Resistance | - | - | TBD | - | KΩ | 2 |

Note 1: The output current buffer is 8mA for UART related signals.
Note 2: These values are typical values checked in the manufacturing process and are not tested.

## 9.8.  GPIO DC Parameters

**Table 28.   GPIO DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|--------|-----------|------------|------|------|------|-------|-------|
| $V_{IH}$ | Input-High Voltage | LVTTL | TBD | - | - | V | - |
| $V_{IL}$ | Input-Low Voltage | LVTTL | TBD | - | TBD | V | - |
| $V_{OH}$ | Output-High Voltage | - | TBD | - | TBD | V | 1 |
| $V_{OL}$ | Output-Low Voltage | - | TBD | - | TBD | V | 1 |
| $I_{IL}$ | Input-Leakage Current | - | TBD | TBD | TBD | μA | 2 |
| $R_{PD}$ | Input Pull-Down Resistance | - | - | TBD | - | KΩ | 2 |

*Note 1: The output current buffer is 8mA for GPIO related signals.*
*Note 2: These values are typical values checked in the manufacturing process and are not tested.*

## 9.9.  JTAG DC Parameters

**Table 29.   JTAG DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | Notes |
|--------|-----------|------------|------|------|------|-------|-------|
| $V_{IH}$ | Input-High Voltage | LVTTL | TBD | TBD | TBD | V | - |
| $V_{IL}$ | Input-Low Voltage | LVTTL | TBD | TBD | TBD | V | - |
| $V_{OH}$ | Output-High Voltage | $\lvert I_{OH} \rvert$ =2~16mA | TBD | TBD | TBD | V | 1 |
| $V_{OL}$ | Output-Low Voltage | $\lvert I_{OL} \rvert$ =2~16mA | TBD | TBD | TBD | V | 1 |
| $I_{IL}$ | Input-Leakage Current | - | TBD | TBD | TBD | μA | 2 |
| $R_{PD}$ | Input Pull-Down Resistance | - | TBD | TBD | TBD | KΩ | 2 |

*Note 1: The output current buffer is 8mA for JTAG related signals.*
*Note 2: These values are typical values checked in the manufacturing process and are not tested.*

## 9.10.  LED DC Parameters

**Table 30.   LED DC Parameters**

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units |
|--------|-----------|------------|------|------|------|-------|
| $V_{OHED}$ | Output-High Voltage | - | TBD | TBD | TBD | V |
| $V_{OLLED}$ | Output-Low Voltage | - | TBD | TBD | TBD | V |

*Note: The output current buffer for LED signals is 8mA.*

# 10. AC Specifications

## 10.1. Clock Signal Timing

**Table 31.   Clock Signal Timing**

| Symbol | Parameter | Min. | Typ. | Max. | Units | Notes |
|---|---|---|---|---|---|---|
| $V_{IH}$ | Input-High Voltage | TBD | TBD | TBD | V | - |
| $V_{IL}$ | Input-Low Voltage | TBD | TBD | TBD | V | - |
| $T_{FREQUENCY}$ | Clock Frequency for RTL8196C Crystal or Oscillator | TBD | TBD | TBD | MHz | 1 |
| $\Delta_{FREQUENCY}$ | Clock Tolerance (between 0ºC~50ºC) | TBD | TBD | TBD | ppm | - |
| $C_{SHUNT}$ | Crystal Parameter<br>*Note: Sometimes referred to as the Holder Capacitance.* | TBD | TBD | TBD | pF | 2 |
| $C_1$ | Load Capacitance | TBD | TBD | TBD | pF | 3 |
| $C_2$ | Load Capacitance | TBD | TBD | TBD | pF | 3 |
| $T_{DC}$ | Duty Cycle<br>*Note: This parameter applies when driving the clock input with an oscillator.* | TBD | TBD | TBD | % | - |

*Note 1: This value could be an oscillator input or a series resonant frequency from a crystal. If used as an oscillator input, tie to the crystal input pin and leave the crystal output pin disconnected.*
*Note 2: The 25MHz Crystal CL=16pF is used on the RTL8196C.*
*Note 3: The RTL8196C PLL circuit requires an external 25MHz crystal with shunt capacitors. These shunt capacitors cannot be over 30pF due to chip design requirements.*

**Figure 4.    Typical Connection to a Crystal**

**Figure 5.    Typical Connection to an Oscillator**

## 10.1.1. SDRAM Clock Timing

**Table 32. SDRAM Clock Timing**

| Symbol | Parameter | 130~180MHz | | | Units | Notes |
|---|---|---|---|---|---|---|
| | | Min. (130MHz) | Typ. (160MHz) | Max. (180MHz) | | |
| $T_{PERIOD\_SDRAMCLK}$ | Clock Period for SDRAM Clock | TBD | TBD | TBD | ns | - |
| $T_{CLKHIGH}$ | SDRAM Clock High Time | TBD | TBD | TBD | ns | - |
| $T_{CLKLOW}$ | SDRAM Clock Low Time | TBD | TBD | TBD | ns | - |
| $T_{RISE/FALL}$ | Rising and Falling Time Requirements for SDRAM Clock | TBD | TBD | TBD | ns | - |
| $T_{RISE/FALL\_OUTPUT}$ | Propagation Delay for Output Rising and Falling | TBD | TBD | TBD | ns | 1 |

*Note 1: Please contact Realtek for the IBIS model.*



**Figure 6. SDRAM Clock Specifications-1**



**Figure 7. SDRAM Clock Specifications-2**

# 10.2. Bus Signal Timing

## 10.2.1. SDRAM Bus

### 10.2.1.1 SDRAM Input Timing

**Table 33.   SDRAM Input Timing**

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|--------|-----------|------|------|------|-------|
| $T_{SETUP}$ | Input setup prior to rising edge of clock. Inputs included in this timing are D[31:0] (during a read operation) | TBD | TBD | - | ns |
| $T_{HOLD}$ | Input hold time after the rising edge of clock. Inputs included in this timing are D[31:0] (during a read operation) | TBD | TBD | - | ns |

*Note: The RTL8196C integrates some timing controls on the interface. Here the timing parameters listed in the table are extracted in the default situation (without specific controls).*



**Figure 8.     SDRAM Input Timing**

### 10.2.1.2 SDRAM Output Timing

**Table 34.   SDRAM Output Timing**

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|--------|-----------|------|------|------|-------|
| $T_{CLK2OUT}$ | Rising edge of clock-to-signal output. Outputs included in this timing are D[31:0], CS0#, CS1#, RAS#, CAS#, LDQM, UDQM, WE# (during a write operation) | TBD | TBD | TBD | ns |
| $T_{HOLDOUT}$ | Signal output hold time after the rising edge of the clock. Outputs included in this timing are D[31:0] (during a write operation) | TBD | TBD | TBD | ns |

*Note: The RTL8196C integrates some timing controls on the interface. Here the timing parameters listed in the table are extracted in the default situation (without specific controls).*



**Figure 9.     SDRAM Output Timing**

## 10.2.1.3   SDRAM Access Control Timing

**Table 35.   SDRAM Access Control Timing**

| Symbol | Parameter | Units | Notes |
|---|---|---|---|
| $T_{REFRESH}$ | Auto-Refresh Timing<br>Controlled by Reg. 0xB8001008 (DTR) | µs | - |
| $T_{RCD}$ | The Time Interval between RAS# Active and CAS# Active<br>Controlled by Reg. 0xB8001008 (DTR) | ns | - |
| $T_{RP}$ | The Time Interval between Pre-Charge and the Next Active<br>Controlled by Reg. 0xB8001008 (DTR) | ns | - |
| $T_{RAS}$ | The Time Interval between Active and Pre-Charge<br>Controlled by Reg. 0xB8001008 (DTR) | ns | - |
| $T_{RC}$ | The Time Interval between Active and the Next Active<br>Controlled by Reg. 0xB8001008 (DTR) | ns | 1 |
| $T_{RFC}$ | The Time Interval between Auto-Refresh and Active<br>Controlled by Reg. 0xB8001008 (DTR) | ns | - |
| $T_{CAS\_LATENCY}$ | The Data Output Delay after CAS# Active<br>Controlled by Reg. 0xB8001004 (DCR) | ns | - |

*Note 1: TRC = TRAS + TRP*



**Figure 10.   SDRAM Access Control Timing**

## 10.2.2.  Flash Bus

**Table 36.    Flash Access Timing Values**

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|--------|-----------|------|------|------|-------|
| $T_{CS}$ | The Timing Interval between NF_CS0# (or NF_CS1#) and WE# | Controlled by Reg. 0xB8001100 (NFCR) | | | ns |
| $T_{WP}$ | The Timing Interval for WE# to be Pulled Low (RAS# for Read Operation) | Controlled by Reg. 0xB8001100 (NFCR) | | | ns |



**Figure 11.    Flash Access Timing**

## 10.2.3.  Power Sequence

**Table 37.    Power-Up Timing Parameters**

| Symbol | Parameter | Min. | Typ. | Max. | Units |
|--------|-----------|------|------|------|-------|
| t1 | 3.3V Stable to 1.0V | 1 | - | - | ms |

*Note: The 3.3V (I/O) must be powered up before 1.0V (core) and 1.0V (analog) voltage.*



**Figure 12.    Power Up Sequence Timing Diagram**

## 10.2.4. Power Configuration Timing

Power up configuration only relates to internal timing. The external hardware pin reset is irrelevant with regard to power up configuration. The Hardware reset pin is valid when an internal reset ends the active state.



**Figure 13.    Power Up Configuration Timing Diagram**

# 11. Thermal Characteristics

Heat generated by the chip causes a temperature rise of the package. If the temperature of the chip ($T_j$, junction temperature) is beyond the design limits, there will be negative effects on operation and the life of the IC package. Heat dissipation, either through a heat sink or electrical fan, is necessary to provide a reasonable environment ($T_a$, ambient temperature) in a closed case. As power density increases, thermal management becomes more critical. A method to estimate the possible $T_a$ is outlined below.

Thermal parameters are defined as below according to JEDEC standard JESD 51-2, 51-6:

(1) $\theta_{ja}$ (Thermal resistance from junction to ambient), represents resistance to heat flow from the chip to ambient air. This is an index of heat dissipation capability. A lower $\theta_{ja}$ means better thermal performance.

$\theta_{ja} = (T_j - T_a) / P$

Where $T_j$ is the die junction temperature, $T_a$ is the ambient air temperature

P is the power dissipation by device (Watts)

(2) $\theta_{jc}$ (Thermal Resistance Junction-to-Case, °C/W), measures the heat flow resistance between the die surface and the surface of the package (case). This data is relevant for packages used with external heat sinks.

$\theta_{jc} = (T_j - T_c) / P$

Where $T_j$ is the die junction temperature, $T_c$ is the package case temperature

P is the power dissipation by device (Watts)

(3) $\Psi_{jt}$ (Thermal Characterization Parameter: Junction to package top), represents the correlation between the temperature of the chip and the package top.

$\Psi_{jt} = (T_j - T_t) / P$

Where $T_j$ is the die junction temperature, $T_t$ is the top of package temperature

P is the power dissipation by device (Watts)

**Thermal Terminology**

The major thermal dissipation paths can be illustrated as follows:

Tj: The maximum junction temperature

Ta: The ambient or environment temperature

Tc: The maximum compound surface temperature

Tb: The maximum surface temperature of PCB bottom

P: Total input power

PQFP Junction to ambient thermal resistance, θja, defined as:

$$\theta_{JA} = \frac{TJ - TA}{P}$$



**Thermal Dissipation of PQFP Package**

# 11.1. Thermal Operating Range

**Table 38.    Thermal Operating Range**

| Parameter | SYM | Condition | Min | Typical | Max | Units |
|---|---|---|---|---|---|---|
| Junction Operating Temperature | Tj | - | TBD | TBD | TBD | °C |
| Ambient Operating Temperature | Ta | 4-layer FR4 PCB (without head sink) | TBD | TBD | TBD | °C |

*Note: PCB conditions (JEDEC JESD51-7). Dimensions: 7.62mm x 11.43mm. Thickness: 1.6mm.*

# 11.2. RTL8196C Thermal Parameters

**Table 39.    RTL8196C Thermal Parameters**

| Parameter | SYM | Condition | Air Flow 0 m/s | Air Flow 1 m/s | Air Flow 2 m/s | Air Flow 3 m/s | Units |
|---|---|---|---|---|---|---|---|
| Thermal Resistance: Junction to ambient | θja | 2-layer FR4 PCB | TBD | TBD | TBD | TBD | °C/W |
| Thermal Resistance: Junction to ambient | θja | 4-layer FR4 PCB | TBD | TBD | TBD | TBD | °C/W |
| Thermal Characterization: Junction to package top | Ψjt | 2-layer FR4 PCB | TBD | TBD | TBD | TBD | °C/W |
| Thermal Characterization: Junction to package top | Ψjt | 4-layer FR4 PCB | TBD | TBD | TBD | TBD | °C/W |

*Note: PCB conditions (JEDEC JESD51-7): Dimensions: 7.62mm x 11.43mm; Thickness: 1.6mm.*

# 12. Mechanical Dimensions

## 12.1. Plastic Quad Flat Package 128-Pin 14x20mm Outline



| Symbol | Dimension in mm | | | Dimension in inch | | |
|--------|-----|-----|-----|-----|-----|-----|
| | Min | Nom | Max | Min | Nom | Max |
| A | - | - | 3.40 | - | - | 0.134 |
| $A_1$ | 0.25 | - | - | 0.010 | - | - |
| $A_2$ | 2.50 | 2.70 | 2.90 | 0.100 | 0.106 | 0.114 |
| b | 0.17 | 0.22 | 0.27 | 0.007 | 0.009 | 0.011 |
| D | 23.2BSC | | | 0.913BSC | | |
| $D_1$ | 20.00BSC | | | 0.787BSC | | |
| E | 17.20BSC | | | 0.677BSC | | |
| $E_1$ | 14.00BSC | | | 0.551BSC | | |
| e | 0.50BSC | | | 0.020BSC | | |
| L | 0.73 | 0.88 | 1.03 | 0.029 | 0.035 | 0.041 |
| L1 | 1.60REF | | | 0.063REF | | |

Notes: CONTROLLING DIMENSION: MILLIMETER (mm).

system