

pt-archiver生产归档报错解决方案

1、归档条件存在中文，pt-archiver生成的sql执行时存在乱码

解决办法：

pt-archiver脚本前面几行，增加一行 use encoding "utf8";

```
#!/usr/bin/env perl

# This program is part of Percona Toolkit: http://www.percona.com/software/
# See "COPYRIGHT, LICENSE, AND WARRANTY" at the end of this file for legal
# notices and disclaimers.

use strict;
use warnings FATAL => 'all';
#use utf8;
use encoding "utf8";

# This tool is "fat-packed": most of its dependent modules are embedded
# in this file.  Setting %INC to this file for each module makes Perl aware
# of this so it will not try to load the module from @INC.  See the tool's
```

2、数据有特殊字符时，使用bulk-insert出现乱码报错，pt-archiver无法识别该字符集

报错提示：

DBD::mysql::st execute failed: Invalid utf8 character string: 'â°é£' [for Statement "LOAD DATA LOCAL INFILE ? INTO TABLE `arch\_store`.`t\_event\_log` CHARACTER SET utf8('id`,`store_code`,`be_code`,`task_code`,`event_type`,`event_sub_type`,`event_code`,`event_source`,`change_data`,`reason`,`reason_desc`,`is_active`,`version`,`created_date`,`created_user`,`updated_date`,`updated_user`)" with ParamValues: 0=/tmp/IC2stmy5Umpt-archiver] at /usr/bin/pt-archiver line 6876.

解决办法：

写死字符集，CHARACTER SET utf8mb4

```
if ( $dst ) {
    $ins_stmt = $snibbler->generate_ins_stmt(
        ins_tbl => $dst->{info},
        sel_cols => \@sel_cols,
    );
    PTDEBUG && _d("inst stmt: ", Dumper($ins_stmt));
    @ins_slice = @{$ins_stmt->{slice}};
    if ( $o->get('bulk-insert') ) {
        $ins_sql = "LOAD DATA"
            . ( $o->get('low-priority-insert') ? ' LOW_PRIORITY' : '' )
            . ' LOCAL INFILE ?'
            . ( $o->get('replace') ? ' REPLACE' : '' )
            . ( $o->get('ignore') ? ' IGNORE' : '' )
            . " INTO TABLE $dst->{db.tbl}"
            . ( $o->get_charset ? " CHARACTER SET utf8mb4" : "" )
            . "("
            . join(", ", map { $q->quote($_) } @{$ins_stmt->{cols}} )
            . ")";
    }
    else {
        $ins_sql = ( $o->get('replace') ? ' REPLACE' : ' INSERT' )
            . ( $o->get('low-priority-insert') ? ' LOW_PRIORITY' : '' )
            . ( $o->get('delayed-insert') ? ' DELAYED' : '' )
            . ( $o->get('ignore') ? ' IGNORE' : '' )
            . " INTO $dst->{db.tbl}"
            . join(", ", map { $q->quote($_) } @{$ins_stmt->{cols}} )
            . " VALUES ("
            . join(", ", map { " ? " } @{$ins_stmt->{cols}} ) . " )";
    }
}
```

3、archery配置归档ob数据时提示Character set mismatch

报错提示: pt-archiver --no-version-check --source h=10.126.106.152,u=root@sc_store#sc_store_prd,p=****,P=2883,D=sc_center,
t=sc_abnormal_price_sku_info,A=utf8mb4,i= --where "business_day < NOW() - INTERVAL 90 DAY" --progress 20000 --statistics --charset utf8 --
limit 10000 --txn-size 1000 --sleep 1 --purge --bulk-delete
Character set mismatch: --source DSN uses utf8mb4, table uses . You can disable this check by specifying --no-check-charset.

解决办法:

增加--no-check-charset