

MySQL出现Crash后BUG查找思路

#error日志

```
2025-07-21T17:27:21.874917+08:00 30 [Warning] [MY-010584] [Repl] Slave SQL for channel "": Worker 4 failed executing transaction '3e5d24cc-7ca9-11ef-986c-bc97e17bc4c0:104113039' at master log mysql-bin.002487, end_log_pos 104229604; Could not execute Write_rows event on table delta_base.t_ele_product_ref; Deadlock found when trying to get lock; try restarting transaction, Error_code: 1213; handler error HA_ERR_LOCK_DEADLOCK; the event's master log mysql-bin.002487, end_log_pos 104229604, Error_code: MY-001213
```

09:27:22 UTC - mysqld got signal 11 ;

Most likely, you have hit a bug, but this error can also be caused by malfunctioning hardware.

Thread pointer: 0x7f65d80008c0

Attempting backtrace. You can use the following information to find out

where mysqld died. If you see no messages after this, something went

terribly wrong...

stack_bottom = 7f6bf8553d78 thread_stack 0x46000

/data2/mysql/base/8.0.25/bin/mysqld(my_print_stacktrace(unsigned char const*, unsigned long)+0x2e) [0x2079c3e]

/data2/mysql/base/8.0.25/bin/mysqld(handle_fatal_signal+0x323) [0x10616b3]

/lib64/libpthread.so.0(+0xf5d0) [0x7f6c2fec05d0]

/data2/mysql/base/8.0.25/bin/mysqld(slave_worker_exec_job_group(Slave_worker*, Relay_log_info*)+0x2c5) [0x1cd1fd5]

/data2/mysql/base/8.0.25/bin/mysqld() [0x1cd948b]

/data2/mysql/base/8.0.25/bin/mysqld() [0x25aef7c]

/lib64/libpthread.so.0(+0x7dd5) [0x7f6c2feb8dd5]

/lib64/libc.so.6(clone+0x6d) [0x7f6c2df9eead]

常用方法一:

gdb

示例:

gdb core dump

-b 0x1cd1fd5 #设置断点

常用方法二:

addr2line -e /usr/local/src/mysql/bin/mysqld -C -f 0x1cd1fd5

返回结果

slave_worker_exec_job_group(Slave_worker*, Relay_log_info*)

./obj/sql/././mysql-8.0.25/sql/rpl_rli_pdb.cc:2548

通过以上返回的信息可以去以下地址查找

<https://github.com/mysql/mysql-server>

<https://bugs.mysql.com/>

还有就是查找上下临近版本的note

<https://dev.mysql.com/doc/relnotes/mysql/8.0/en/>