

# DAT159 Refactoring - Oblig 01

By Kristoffer-Andre Kallinen (181192)

Extracting the switch case to its own method `determineAmount()`, but before extracting the method I extracted the `each.getMovie().getPriceCode()` and `each.getDaysRented()` into separate variables.

from

```
switch (each.getMovie().getPriceCode()) {
    case Movie.REGULAR:
        thisAmount += 2;
        if (each.getDaysRented() > 2)
            thisAmount += (each.getDaysRented() - 2) * 1.5;
        break;
    case Movie.NEW_RELEASE:
        thisAmount += each.getDaysRented() * 3;
        break;
    case Movie.CHILDRENS:
        thisAmount += 1.5;
        if (each.getDaysRented() > 3)
            thisAmount += (each.getDaysRented() - 3) * 1.5;
        break;
}
```

to

```
int priceCode = movie.getPriceCode();
int daysRented = each.getDaysRented();
double thisAmount = determineAmount(priceCode, daysRented);

private double determineAmount(int priceCode, int daysRented) {
    double thisAmount = 0;
    switch (priceCode) {
        case Movie.REGULAR:
            thisAmount += 2;
            if (daysRented > 2)
                thisAmount += (daysRented - 2) * 1.5;
            break;
        case Movie.NEW_RELEASE:
            thisAmount += daysRented * 3;
            break;
        case Movie.CHILDRENS:
            thisAmount += 1.5;
    }
}
```

```

        if (daysRented > 3)
            thisAmount += (daysRented - 3) * 1.5;
        break;
    }
    return thisAmount;
}

```

Then I moved the method over to the Movie class and created three subclasses that was each case in the switchcase

**Children**, **Regular** and **NewRelease**. I made the method abstract in Movie class and then override the method in childclasses. In each class I added the code corresponding to the code inside each case in the switch.

```

Movie movie = each.getMovie();
String title = movie.getTitle();
int priceCode = movie.getPriceCode();
double thisAmount = movie.determineAmount(daysRented);

public abstract class Movie {

    [...]

    abstract double determineAmount(int daysRented);

    class Children extends Movie {

        public Children(String title, int priceCode) {
            super(title, priceCode);
        }

        @Override
        double determineAmount(int daysRented) {
            double thisAmount = 1.5;
            if (daysRented > 3)
                thisAmount += (daysRented - 3) * 1.5;
            return thisAmount;
        }
    }

    class Regular extends Movie {

        public Regular(String title, int priceCode) {
            super(title, priceCode);
        }
    }
}

```

```

    @Override
    double determineAmount(int daysRented) {
        double thisAmount = 2;
        if (daysRented > 2)
            thisAmount += (daysRented - 2) * 1.5;
        return thisAmount;
    }
}

class NewRelease extends Movie {

    public NewRelease(String title, int priceCode) {
        super(title, priceCode);
    }

    @Override
    double determineAmount(int daysRented) {
        return daysRented * 3;
    }
}

```

Extracted the frequent renterpoints lines into its own method called `getFrequentRenterPoints()`.

*from*

```

// add frequent renter points
frequentRenterPoints++;
// add bonus for a two day new release rental
if ((priceCode == Movie.NEW_RELEASE) &&
    daysRented > 1) frequentRenterPoints++;

```

*to*

```

frequentRenterPoints = getFrequentRenterPoints(frequentRenterPoints, priceCode, daysRented);

private int getFrequentRenterPoints(int frequentRenterPoints, int priceCode, int daysRented) {
    // add frequent renter points
    frequentRenterPoints++;
    // add bonus for a two day new release rental
    if ((priceCode == Movie.NEW_RELEASE) &&
        daysRented > 1) frequentRenterPoints++;
}

```

```
    return frequentRenterPoints;
}
```

Extracting the movie variable `each.getMovie()`

```
Movie movie = each.getMovie();
String title = movie.getTitle();
int priceCode = movie.getPriceCode();
frequentRenterPoints += getFrequentRenterPoints(frequentRenterPoints, priceCode, daysRented);
```

Moving the `getFrequentRenterPoints` from `Customer` class to `Movie`. For the special case when its an `Rew Release`,  
Im doing a override of the method and check for the two-days rented bonus.

*Customer.class*

```
frequentRenterPoints += movie.getFrequentRenterPoints(frequentRenterPoints, priceCode, daysRented);
```

*Movie.class*

```
public int getFrequentRenterPoints(int frequentRenterPoints, int priceCode, int daysRented) {
    return ++frequentRenterPoints;
}
```

*NewRelease.class*

```
@Override
public int getFrequentRenterPoints(int frequentRenterPoints, int priceCode, int daysRented) {
    // add frequent renter points
    frequentRenterPoints++;
    // add bonus for a two day new release rental
    if (daysRented > 1) frequentRenterPoints++;
    return frequentRenterPoints;
}
```

Then removing the constant in the top of the class

*Deleting*

```
public static final int CHILDRENS = 2;
public static final int REGULAR = 0;
public static final int NEW_RELEASE = 1;
```

Extracting the footer lines to its own method.

*from*

```
//add footer lines
result += "Amount owed is " + String.valueOf(totalAmount) + "\n";
result += "You earned " + String.valueOf(frequentRenterPoints) +
" frequent renter points";
```

*to*

```
result += getFooterLines(totalAmount, frequentRenterPoints, result);

private String getFooterLines(double totalAmount, int frequentRenterPoints, String result) {
    //add footer lines
    result += "Amount owed is " + String.valueOf(totalAmount) + "\n";
    result += "You earned " + String.valueOf(frequentRenterPoints) +
        " frequent renter points";
    return result;
}
```

Extracting the result string to its own method

*from*

```
result += ("\t" + title + "\t" + String.valueOf(thisAmount) + "\n");
```

*to*

```
result += printFiguresForRental(result, title, thisAmount);

private String printFiguresForRental(String result, String title, double thisAmount) {
    return result + ("\t" + title + "\t" + String.valueOf(thisAmount) + "\n");
}
```

## Final Result

*Customer.java*

```
package net.jeremykendall.refactoring.videostore;
```

```

import java.util.Enumeration;
import java.util.Vector;

public class Customer {
    private String _name;
    private Vector _rentals = new Vector();

    public Customer(String name) {
        _name = name;
    }

    public String statement() {
        double totalAmount = 0;
        int frequentRenterPoints = 0;
        Enumeration rentals = _rentals.elements();
        String result = "Rental Record for " + getName() + "\n";
        while (rentals.hasMoreElements()) {
            Rental each = (Rental) rentals.nextElement();
            int daysRented = each.getDaysRented();
            Movie movie = each.getMovie();

            int priceCode = movie.getPriceCode();
            frequentRenterPoints += movie.getFrequentRenterPoints(frequentRenterPoints, priceCode, daysRented);

            String title = movie.getTitle();
            double thisAmount = movie.determineAmount(daysRented);
            result += printFiguresForRental(result, title, thisAmount);
            totalAmount += thisAmount;
        }
        result += getFooterLines(totalAmount, frequentRenterPoints, result);
        return result;
    }

    private String printFiguresForRental(String result, String title, double thisAmount) {
        return result + ("\t" + title + "\t" + String.valueOf(thisAmount) + "\n");
    }

    private String getFooterLines(double totalAmount, int frequentRenterPoints, String result) {
        return result
            + "Amount owed is " + String.valueOf(totalAmount) + "\n"
            + "You earned " + String.valueOf(frequentRenterPoints)
            + " frequent renter points";
    }

    public void addRental(Rental arg) {

```

```
        _rentals.addElement(arg);
    }

    public String getName() {
        return _name;
    }
}
```

#### Movie.java

```
package net.jeremykendall.refactoring.videostore;

public abstract class Movie {

    private String _title;
    private int _priceCode;

    public Movie(String title, int priceCode) {
        _title = title;
        _priceCode = priceCode;
    }

    public int getPriceCode() {
        return _priceCode;
    }

    public void setPriceCode(int _priceCode) {
        this._priceCode = _priceCode;
    }

    public String getTitle() {
        return _title;
    }

    public abstract double determineAmount(int daysRented);

    public int getFrequentRenterPoints(int frequentRenterPoints, int priceCode, int daysRented) {
        return ++frequentRenterPoints;
    }

    class Children extends Movie {
```

```

    public Children(String title, int priceCode) {
        super(title, priceCode);
    }

    @Override
    public double determineAmount(int daysRented) {
        double thisAmount = 1.5;
        if (daysRented > 3)
            thisAmount += (daysRented - 3) * 1.5;
        return thisAmount;
    }
}

class Regular extends Movie {

    public Regular(String title, int priceCode) {
        super(title, priceCode);
    }

    @Override
    public double determineAmount(int daysRented) {
        double thisAmount = 2;
        if (daysRented > 2)
            thisAmount += (daysRented - 2) * 1.5;
        return thisAmount;
    }
}

class NewRelease extends Movie {

    public NewRelease(String title, int priceCode) {
        super(title, priceCode);
    }

    @Override
    public double determineAmount(int daysRented) {
        return daysRented * 3;
    }

    @Override
    public int getFrequentRenterPoints(int frequentRenterPoints, int priceCode, int daysRented) {
        // add frequent renter points
        frequentRenterPoints++;
        // add bonus for a two day new release rental
        if (daysRented > 1) frequentRenterPoints++;
    }
}

```



```
        return frequentRenterPoints;
    }
}
}
```

### *Rental.java*

```
package net.jeremykendall.refactoring.videostore;

public class Rental {
    private Movie _movie;
    private int _daysRented;

    public Rental(Movie movie, int daysRented) {
        _movie = movie;
        _daysRented = daysRented;
    }

    public Movie getMovie() {
        return _movie;
    }

    public int getDaysRented() {
        return _daysRented;
    }
}
```