

Анализ данных

## Лекция 4

# Трансформация данных в R

Гедранович Ольга Брониславовна,  
старший преподаватель кафедры ИТ, МИУ  
[volha.b.k@gmail.com](mailto:volha.b.k@gmail.com)

11.09.2017

2

### Вопросы лекции


- Фильтрация (filter)
- Сортировка (arrange)
- Выборка (select)
- Модификация (mutate)
- Групповые операции
- Принципы Tidy Data и пакет `tidyr`

11.09.2017 3

## Трансформация данных

Ключевые функции пакета `dplyr` для трансформации данных:

- Pick observations by their values – `filter()`.
- Reorder the rows – `arrange()`.
- Pick variables by their names – `select()`.
- Create new variables with functions of existing variables – `mutate()`.
- Collapse many values down to a single summary – `summarise()`.
- These can all be used in conjunction with `group_by()` which changes the scope of each function from operating on the entire dataset to operating on it group-by-group.




11.09.2017 4

## Трансформация данных

All verbs work similarly:

- The first argument is a data frame.
- The subsequent arguments describe what to do with the data frame, using the variable names (without quotes).
- The result is a new data frame.

Together these properties make it easy to chain together multiple simple steps to achieve a complex result.




11.09.2017 5

## Трансформация данных

```
library(dplyr)
library(nycflights13)

flights
# A tibble: 336,776 × 19
#   year month   day dep_time sched_dep_time dep_delay arr_time sched_arr_time arr_delay
#   <int> <int> <int>   <int>         <int>         <dbl>   <int>         <int>         <dbl>
1  2013     1     1     517             515           2       830             819           11
2  2013     1     1     533             529           4       850             830           20
3  2013     1     1     542             540           2       923             850           33
4  2013     1     1     544             545          -1      1004            1022          -18
5  2013     1     1     554             600          -6       812             837           -25
6  2013     1     1     554             558          -4       740             728           12
7  2013     1     1     555             600          -5       913             854           19
8  2013     1     1     557             600          -3       709             723          -14
9  2013     1     1     557             600          -3       838             846           -8
10 2013     1     1     558             600          -2       753             745            8
# ... with 336,766 more rows, and 10 more variables: carrier <chr>, flight <int>,
#   tailnum <chr>, origin <chr>, dest <chr>, air_time <dbl>, distance <dbl>, hour <dbl>,
#   minute <dbl>, time_hour <dtm>
```




11.09.2017 6

## Фильтрация (filter)

`filter()` allows you to subset observations based on their values

```
> filter(flights, month == 1, day == 1)
# A tibble: 842 × 19
#   year month   day dep_time sched_dep_time dep_delay arr_time sched_arr_time arr_delay
#   <int> <int> <int>   <int>         <int>         <dbl>   <int>         <int>         <dbl>
1  2013     1     1     517             515           2       830             819           11
2  2013     1     1     533             529           4       850             830           20
3  2013     1     1     542             540           2       923             850           33
4  2013     1     1     544             545          -1      1004            1022          -18
5  2013     1     1     554             600          -6       812             837           -25
6  2013     1     1     554             558          -4       740             728           12
7  2013     1     1     555             600          -5       913             854           19
8  2013     1     1     557             600          -3       709             723          -14
9  2013     1     1     557             600          -3       838             846           -8
10 2013     1     1     558             600          -2       753             745            8
# ... with 832 more rows, and 10 more variables: carrier <chr>, flight <int>, tailnum <chr>,
#   origin <chr>, dest <chr>, air_time <dbl>, distance <dbl>, hour <dbl>, minute <dbl>,
#   time_hour <dtm>
```




11.09.2017 7

## Сортировка (arrange)

`arrange()` changes rows' order.

It takes a data frame and a set of column names (or more complicated expressions) to order by.

If you provide more than one column name, each additional column will be used to break ties in the values of preceding columns.



11.09.2017 8


## Сортировка (arrange)

```
arrange(flights, year, month, day)
```

# A tibble: 336,776 x 19

	year	month	day	dep_time	sched_dep_time	dep_delay	arr_time	sched_arr_time	arr_delay
	<int>	<int>	<int>	<int>	<int>	<dbl>	<int>	<int>	<dbl>
1	2013	1	1	517	515	2	830	819	11
2	2013	1	1	533	529	4	850	830	20
3	2013	1	1	542	540	2	923	850	33
4	2013	1	1	544	545	-1	1004	1022	-18
5	2013	1	1	554	600	-6	812	837	-25
6	2013	1	1	554	558	-4	740	728	12
7	2013	1	1	555	600	-5	913	854	19
8	2013	1	1	557	600	-3	709	723	-14
9	2013	1	1	557	600	-3	838	846	-8
10	2013	1	1	558	600	-2	753	745	8

# ... with 336,766 more rows, and 10 more variables: carrier <chr>, flight <int>,  
 # tailnum <chr>, origin <chr>, dest <chr>, air\_time <dbl>, distance <dbl>, hour <dbl>,  
 # minute <dbl>, time\_hour <dtm>




11.09.2017 9

## Выборка (select)

`select()` allows to zoom in on a useful subset basing on the names of the variables.

```
select(flights, year, month, day)
# A tibble: 336,776 × 3
  year month   day
  <int> <int> <int>
1  2013     1     1
2  2013     1     1
3  2013     1     1
4  2013     1     1
5  2013     1     1
6  2013     1     1
7  2013     1     1
8  2013     1     1
9  2013     1     1
10 2013     1     1
# ... with 336,766 more rows
```




11.09.2017 10

There are a number of helper functions you can use within `select()`:

- `starts_with("abc")`: matches names that begin with "abc"
- `ends_with("xyz")`: matches names that end with "xyz"
- `contains("ijk")`: matches names that contain "ijk"
- `matches("(.)\\1")`: selects variables that match a regular expression. This one matches any variables that contain repeated characters
- `num_range("x", 1:3)`: matches x1, x2 and x3.

```
rename(flights, tail_num = tailnum)

select(flights, time_hour, air_time, everything())
```



11.09.2017 11

## Модификация (mutate)

`mutate()` always adds new columns at the end of your dataset.

```
mutate(flights_sml,
  gain = arr_delay - dep_delay,
  speed = distance / air_time * 60
)
```

# A tibble: 336,776 × 9

	year	month	day	dep_delay	arr_delay	distance	air_time	gain	speed
	<int>	<int>	<int>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	2013	1	1	2	11	1400	227	9	370.0441
2	2013	1	1	4	20	1416	227	16	374.2731
3	2013	1	1	2	33	1089	160	31	408.3750
4	2013	1	1	-1	-18	1576	183	-17	516.7213
5	2013	1	1	-6	-25	762	116	-19	394.1379
6	2013	1	1	-4	12	719	150	16	287.6000
7	2013	1	1	-5	19	1065	158	24	404.4304
8	2013	1	1	-3	-14	229	53	-11	259.2453
9	2013	1	1	-3	-8	944	140	-5	404.5714
10	2013	1	1	-2	8	733	138	10	318.6957

# ... with 336,766 more rows

11.09.2017 12

## Групповые операции

`summarise()` collapses a data frame to a single row.

`summarise()` is not terribly useful unless we pair it with `group_by()`. This changes the unit of analysis from the complete dataset to individual groups.

11.09.2017 13

## Групповые операции

```
by_day <- group_by(flights, year, month, day)

summarise(by_day, delay = mean(dep_delay, na.rm = TRUE))
```

Source: local data frame [365 x 4]  
Groups: year, month [?]

	year	month	day	delay
	<int>	<int>	<int>	<dbl>
1	2013	1	1	11.548926
2	2013	1	2	13.858824
3	2013	1	3	10.987832
4	2013	1	4	8.951595
5	2013	1	5	5.732218
6	2013	1	6	7.148014
7	2013	1	7	5.417204
8	2013	1	8	2.553073
9	2013	1	9	2.276477
10	2013	1	10	2.844995

# ... with 355 more rows

11.09.2017 14

## Групповые операции

If you need to remove grouping, and return to operations on ungrouped data, use `ungroup( )`.

```
daily %>%
  ungroup() %>%           # no longer grouped by date
  summarise(flights = n()) # all flights
```


11.09.2017 15

## Принципы Tidy Data и пакет `tidyr`

**Hadley Wickham** is a statistician from New Zealand who is currently Chief Scientist at RStudio.

He is best known for his development of packages for R, that implement logics of data visualisation and data transformation, including `tidyr`, `ggplot2`, `plyr`, `dplyr`, and `reshape2`.

Wickham's data analysis packages for R are collectively known as the '*tidyverse*'.



Decorative footer with orange and grey human icons.

11.09.2017 16

## Принципы Tidy Data и пакет `tidyr`

A dataset is a collection of **values**, usually either numbers (if quantitative) or strings (if qualitative).

Values are organized in two ways. Every value belongs to a **variable** and an **observation**.

A variable contains all values that measure the same underlying attribute across units.

An observation contains all values measured on the same unit across attributes.

Decorative footer with orange and grey human icons.




11.09.2017 17

## Принципы Tidy Data и пакет `tidyr`

A dataset is messy or tidy depending on how rows, columns and tables are matched up with observations, variables and types.

In **tidy data**:

- Each variable forms a column.
- Each observation forms a row.
- Each type of observational unit forms a table.




11.09.2017 18

## Принципы Tidy Data и пакет `tidyr`

The five **most common problems** with messy datasets, along with their remedies:


- Column headers are values, not variable names.
- Multiple variables are stored in one column.
- Variables are stored in both rows and columns.
- Multiple types of observational units are stored in the same table.
- A single observational unit is stored in multiple tables.



11.09.2017 19

## Column headers are values, not variable names


```
pew <- tbl_df(read.csv("pew.csv", stringsAsFactors = FALSE, check.names = FALSE))
pew
#> # A tibble: 18 x 11
#>   religion `<$10k` `<$10-20k` `<$20-30k` `<$30-40k` `<$40-50k`
#>   <chr>    <int>    <int>    <int>    <int>    <int>
#> 1 Agnostic    27      34      60      81      76
#> 2 Atheist     12      27      37      52      35
#> 3 Buddhist    27      21      30      34      33
#> 4 Catholic   418     617     732     670     638
#> 5 Don't know/refused 15      14      15      11      10
#> 6 Evangelical Prot 575     869    1064     982     881
#> 7 Hindu        1        9        7        9      11
#> 8 Historically Black Prot 228     244     236     238     197
#> 9 Jehovah's Witness  20      27      24      24      21
#> 10 Jewish      19      19      25      25      30
#> # ... with 8 more rows, and 5 more variables: `<$50-75k` <int>,
#> #   `<$75-100k` <int>, `<$100-150k` <int>, `<150k` <int>, `Don't
#> #   know/refused` <int>
```



11.09.2017 20

## Column headers are values, not variable names

```
pew %>%
  gather(income, frequency, -religion)
#> # A tibble: 180 x 3
#>   religion income frequency
#>   <chr>    <chr>    <int>
#> 1 Agnostic <$10k      27
#> 2 Atheist  <$10k      12
#> 3 Buddhist <$10k      27
#> 4 Catholic <$10k     418
#> 5 Don't know/refused <$10k      15
#> 6 Evangelical Prot <$10k     575
#> 7 Hindu    <$10k        1
#> 8 Historically Black Prot <$10k    228
#> 9 Jehovah's Witness <$10k     20
#> 10 Jewish  <$10k     19
#> # ... with 170 more rows
```



11.09.2017 21

## Column headers are values, not variable names

```
billboard <- tbl_df(read.csv("billboard.csv", stringsAsFactors = FALSE))
billboard
#> # A tibble: 317 x 81
#>   year  artist track time date.entered wk1
#>   <int>   <chr>   <chr> <chr>   <chr>   <chr>
#> 1  2000      2 Pac Baby Don't Cry (Keep... 4:22 2000-02-26 87
#> 2  2000      2Gether The Hardest Part Of ... 3:15 2000-09-02 91
#> 3  2000      3 Doors Down Kryptonite 3:53 2000-04-08 81
#> 4  2000      3 Doors Down Loser 4:24 2000-10-21 76
#> 5  2000      504 Boyz Wobble Wobble 3:35 2000-04-15 57
#> 6  2000      98^0 Give Me Just One Nig... 3:24 2000-08-19 51
#> 7  2000      A*Teens Dancing Queen 3:44 2000-07-08 97
#> 8  2000      Aaliyah I Don't Wanna 4:15 2000-01-29 84
#> 9  2000      Aaliyah Try Again 4:03 2000-03-18 59
#> 10 2000 Adams, Yolanda Open My Heart 5:30 2000-08-26 76
#> # ... with 307 more rows, and 75 more variables: wk2 <int>, wk3 <int>,
#> # wk4 <int>, wk5 <int>, wk6 <int>, wk7 <int>, wk8 <int>, wk9 <int>,
#> # wk10 <int>, wk11 <int>, wk12 <int>, wk13 <int>, wk14 <int>,
#> # wk15 <int>, wk16 <int>, wk17 <int>, wk18 <int>, wk19 <int>,
#> # wk20 <int>, wk21 <int>, wk22 <int>, wk23 <int>, wk24 <int>,
#> # wk25 <int>, wk26 <int>, wk27 <int>, wk28 <int>, wk29 <int>,
#> # wk30 <int>, wk31 <int>, wk32 <int>, wk33 <int>, wk34 <int>,
#> # wk35 <int>, wk36 <int>, wk37 <int>, wk38 <int>, wk39 <int>,
#> # wk40 <int>, wk41 <int>, wk42 <int>, wk43 <int>, wk44 <int>,
#> # wk45 <int>, wk46 <int>, wk47 <int>, wk48 <int>, wk49 <int>,
#> # wk50 <int>, wk51 <int>, wk52 <int>, wk53 <int>, wk54 <int>,
#> # wk55 <int>, wk56 <int>, wk57 <int>, wk58 <int>, wk59 <int>,
#> # wk60 <int>, wk61 <int>, wk62 <int>, wk63 <int>, wk64 <int>,
#> # wk65 <int>, wk66 <int>, wk67 <int>, wk68 <int>, wk69 <int>,
#> # wk70 <int>, wk71 <int>, wk72 <int>, wk73 <int>, wk74 <int>,
#> # wk75 <int>, wk76 <int>
```


11.09.2017 22

## Column headers are values, not variable names

```
billboard2 <- billboard %>%
  gather(week, rank, wk1:wk76, na.rm = TRUE)
billboard2
#> # A tibble: 5,307 x 7
#>   year  artist track time date.entered week
#>   *   <int>   <chr>   <chr> <chr>   <chr>   <chr>
#> 1  2000      2 Pac Baby Don't Cry (Keep... 4:22 2000-02-26 wk1
#> 2  2000      2Gether The Hardest Part Of ... 3:15 2000-09-02 wk1
#> 3  2000      3 Doors Down Kryptonite 3:53 2000-04-08 wk1
#> 4  2000      3 Doors Down Loser 4:24 2000-10-21 wk1
#> 5  2000      504 Boyz Wobble Wobble 3:35 2000-04-15 wk1
#> 6  2000      98^0 Give Me Just One Nig... 3:24 2000-08-19 wk1
#> 7  2000      A*Teens Dancing Queen 3:44 2000-07-08 wk1
#> 8  2000      Aaliyah I Don't Wanna 4:15 2000-01-29 wk1
#> 9  2000      Aaliyah Try Again 4:03 2000-03-18 wk1
#> 10 2000 Adams, Yolanda Open My Heart 5:30 2000-08-26 wk1
#> # ... with 5,297 more rows, and 1 more variables: rank <int>
```

11.09.2017 23


```
billboard3 <- billboard2 %>%
  mutate(
    week = extract_numeric(week),
    date = as.Date(date.entered) + 7 * (week - 1)) %>%
  select(-date.entered)
#> extract_numeric() is deprecated: please use readr::parse_number() instead
billboard3
#> # A tibble: 5,307 × 7
#>   year   artist          track time week rank
#>   <int>   <chr>          <chr> <chr> <dbl> <int>
#> 1  2000     2 Pac Baby Don't Cry (Keep... 4:22     1    87
#> 2  2000  2Ge+her The Hardest Part Of ... 3:15     1    91
#> 3  2000  3 Doors Down          Kryptonite 3:53     1    81
#> 4  2000  3 Doors Down          Loser 4:24     1    76
#> 5  2000     504 Boyz          Wobble Wobble 3:35     1    57
#> 6  2000     98^0 Give Me Just One Nig... 3:24     1    51
#> 7  2000     A*Teens          Dancing Queen 3:44     1    97
#> 8  2000     Aaliyah          I Don't Wanna 4:15     1    84
#> 9  2000     Aaliyah          Try Again 4:03     1    59
#> 10 2000 Adams, Yolanda          Open My Heart 5:30     1    76
#> # ... with 5,297 more rows, and 1 more variables: date <date>
```



11.09.2017 24

## Column headers are values, not variable names


```
billboard3 %>% arrange(artist, track, week)
#> # A tibble: 5,307 × 7
#>   year artist          track time week rank   date
#>   <int>   <chr>          <chr> <chr> <dbl> <int> <date>
#> 1  2000     2 Pac Baby Don't Cry (Keep... 4:22     1    87 2000-02-26
#> 2  2000     2 Pac Baby Don't Cry (Keep... 4:22     2    82 2000-03-04
#> 3  2000     2 Pac Baby Don't Cry (Keep... 4:22     3    72 2000-03-11
#> 4  2000     2 Pac Baby Don't Cry (Keep... 4:22     4    77 2000-03-18
#> 5  2000     2 Pac Baby Don't Cry (Keep... 4:22     5    87 2000-03-25
#> 6  2000     2 Pac Baby Don't Cry (Keep... 4:22     6    94 2000-04-01
#> 7  2000     2 Pac Baby Don't Cry (Keep... 4:22     7    99 2000-04-08
#> 8  2000  2Ge+her The Hardest Part Of ... 3:15     1    91 2000-09-02
#> 9  2000  2Ge+her The Hardest Part Of ... 3:15     2    87 2000-09-09
#> 10 2000  2Ge+her The Hardest Part Of ... 3:15     3    92 2000-09-16
#> # ... with 5,297 more rows
```



11.09.2017 25

## Multiple variables stored in one column

```
tb <- tbl_df(read.csv("tb.csv", stringsAsFactors = FALSE))
tb
#> # A tibble: 5,769 × 22
#>   iso2 year m04 m514 m014 m1524 m2534 m3544 m4554 m5564 m65 mu
#>   <chr> <int> <int> <int> <int> <int> <int> <int> <int> <int> <int>
#> 1 AD 1989 NA NA NA NA NA NA NA NA NA NA
#> 2 AD 1990 NA NA NA NA NA NA NA NA NA NA
#> 3 AD 1991 NA NA NA NA NA NA NA NA NA NA
#> 4 AD 1992 NA NA NA NA NA NA NA NA NA NA
#> 5 AD 1993 NA NA NA NA NA NA NA NA NA NA
#> 6 AD 1994 NA NA NA NA NA NA NA NA NA NA
#> 7 AD 1996 NA NA 0 0 0 4 1 0 0 NA
#> 8 AD 1997 NA NA 0 0 1 2 2 1 6 NA
#> 9 AD 1998 NA NA 0 0 0 1 0 0 0 NA
#> 10 AD 1999 NA NA 0 0 0 1 1 0 0 NA
#> # ... with 5,759 more rows, and 10 more variables: f04 <int>, f514 <int>,
#> # f014 <int>, f1524 <int>, f2534 <int>, f3544 <int>, f4554 <int>,
#> # f5564 <int>, f65 <int>, fu <int>
```




11.09.2017 26

## Multiple variables stored in one column

```
tb2 <- tb %>%
  gather(demo, n, -iso2, -year, na.rm = TRUE)
tb2
#> # A tibble: 35,750 × 4
#>   iso2 year demo n
#>   <chr> <int> <chr> <int>
#> 1 AD 2005 m04 0
#> 2 AD 2006 m04 0
#> 3 AD 2008 m04 0
#> 4 AE 2006 m04 0
#> 5 AE 2007 m04 0
#> 6 AE 2008 m04 0
#> 7 AG 2007 m04 0
#> 8 AL 2005 m04 0
#> 9 AL 2006 m04 1
#> 10 AL 2007 m04 0
#> # ... with 35,740 more rows
```

```
tb3 <- tb2 %>%
  separate(demo, c("sex", "age"), 1)
tb3
#> # A tibble: 35,750 × 5
#>   iso2 year sex age n
#>   <chr> <int> <chr> <chr> <int>
#> 1 AD 2005 m 04 0
#> 2 AD 2006 m 04 0
#> 3 AD 2008 m 04 0
#> 4 AE 2006 m 04 0
#> 5 AE 2007 m 04 0
#> 6 AE 2008 m 04 0
#> 7 AG 2007 m 04 0
#> 8 AL 2005 m 04 0
#> 9 AL 2006 m 04 1
#> 10 AL 2007 m 04 0
#> # ... with 35,740 more rows
```



11.09.2017 27

## Variables are stored in both rows and columns

```
weather <- tbl_df(read.csv("weather.csv", stringsAsFactors = FALSE))
weather
```

```
#> # A tibble: 22 x 35
```

#>	id	year	month	element	d1	d2	d3	d4	d5	d6	d7
#>	<chr>	<int>	<int>	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
#> 1	MX17004	2010	1	tmax	NA	NA	NA	NA	NA	NA	NA
#> 2	MX17004	2010	1	tmin	NA	NA	NA	NA	NA	NA	NA
#> 3	MX17004	2010	2	tmax	NA	27.3	24.1	NA	NA	NA	NA
#> 4	MX17004	2010	2	tmin	NA	14.4	14.4	NA	NA	NA	NA
#> 5	MX17004	2010	3	tmax	NA	NA	NA	NA	32.1	NA	NA
#> 6	MX17004	2010	3	tmin	NA	NA	NA	NA	14.2	NA	NA
#> 7	MX17004	2010	4	tmax	NA	NA	NA	NA	NA	NA	NA
#> 8	MX17004	2010	4	tmin	NA	NA	NA	NA	NA	NA	NA
#> 9	MX17004	2010	5	tmax	NA	NA	NA	NA	NA	NA	NA
#> 10	MX17004	2010	5	tmin	NA	NA	NA	NA	NA	NA	NA

```
#> # ... with 12 more rows, and 24 more variables: d8 <dbl>, d9 <lgl>,
#> # d10 <dbl>, d11 <dbl>, d12 <lgl>, d13 <dbl>, d14 <dbl>, d15 <dbl>,
#> # d16 <dbl>, d17 <dbl>, d18 <lgl>, d19 <lgl>, d20 <lgl>, d21 <lgl>,
#> # d22 <lgl>, d23 <dbl>, d24 <lgl>, d25 <dbl>, d26 <dbl>, d27 <dbl>,
#> # d28 <dbl>, d29 <dbl>, d30 <dbl>, d31 <dbl>
```

11.09.2017 28

## Variables are stored in both rows and columns

```
weather2 <- weather %>%
  gather(day, value, d1:d31, na.rm = TRUE)
weather2
```

```
#> # A tibble: 66 x 6
```


#>	id	year	month	element	day	value
#>	<chr>	<int>	<int>	<chr>	<chr>	<dbl>
#> 1	MX17004	2010	12	tmax	d1	29.9
#> 2	MX17004	2010	12	tmin	d1	13.8
#> 3	MX17004	2010	2	tmax	d2	27.3
#> 4	MX17004	2010	2	tmin	d2	14.4
#> 5	MX17004	2010	11	tmax	d2	31.3
#> 6	MX17004	2010	11	tmin	d2	16.3
#> 7	MX17004	2010	2	tmax	d3	24.1
#> 8	MX17004	2010	2	tmin	d3	14.4
#> 9	MX17004	2010	7	tmax	d3	28.6
#> 10	MX17004	2010	7	tmin	d3	17.5

```
#> # ... with 56 more rows
```

11.09.2017 29

## Variables are stored in both rows and columns


```
weather3 <- weather2 %>%
  mutate(day = extract_numeric(day)) %>%
  select(id, year, month, day, element, value) %>%
  arrange(id, year, month, day)
#> extract_numeric() is deprecated: please use readr::parse_number() instead
weather3
#> # A tibble: 66 x 6
#>   id year month day element value
#>   <chr> <int> <int> <dbl> <chr> <dbl>
#> 1 MX17004 2010 1 30 tmax 27.8
#> 2 MX17004 2010 1 30 tmin 14.5
#> 3 MX17004 2010 2 2 tmax 27.3
#> 4 MX17004 2010 2 2 tmin 14.4
#> 5 MX17004 2010 2 3 tmax 24.1
#> 6 MX17004 2010 2 3 tmin 14.4
#> 7 MX17004 2010 2 11 tmax 29.7
#> 8 MX17004 2010 2 11 tmin 13.4
#> 9 MX17004 2010 2 23 tmax 29.9
#> 10 MX17004 2010 2 23 tmin 10.7
#> # ... with 56 more rows
```



11.09.2017 30

## Variables are stored in both rows and columns

```
weather3 %>% spread(element, value)
#> # A tibble: 33 x 6
#>   id year month day tmax tmin
#>   * <chr> <int> <int> <dbl> <dbl> <dbl>
#> 1 MX17004 2010 1 30 27.8 14.5
#> 2 MX17004 2010 2 2 27.3 14.4
#> 3 MX17004 2010 2 3 24.1 14.4
#> 4 MX17004 2010 2 11 29.7 13.4
#> 5 MX17004 2010 2 23 29.9 10.7
#> 6 MX17004 2010 3 5 32.1 14.2
#> 7 MX17004 2010 3 10 34.5 16.8
#> 8 MX17004 2010 3 16 31.1 17.6
#> 9 MX17004 2010 4 27 36.3 16.7
#> 10 MX17004 2010 5 27 33.2 18.2
#> # ... with 23 more rows
```



11.09.2017 31

## Multiple types in one table

```
song <- billboard3 %>%
  select(artist, track, year, time) %>%
  unique() %>%
  mutate(song_id = row_number())
song
```

#> # A tibble: 317 × 5

	artist	track	year	time	song_id
	<chr>	<chr>	<int>	<chr>	<int>
#> 1	2 Pac	Baby Don't Cry (Keep...	2000	4:22	1
#> 2	2Gether	The Hardest Part Of ...	2000	3:15	2
#> 3	3 Doors Down	Kryptonite	2000	3:53	3
#> 4	3 Doors Down	Loser	2000	4:24	4
#> 5	504 Boyz	Wobble Wobble	2000	3:35	5
#> 6	98^0	Give Me Just One Nig...	2000	3:24	6
#> 7	A*Teens	Dancing Queen	2000	3:44	7
#> 8	Aaliyah	I Don't Wanna	2000	4:15	8
#> 9	Aaliyah	Try Again	2000	4:03	9
#> 10	Adams, Yolanda	Open My Heart	2000	5:30	10

#> # ... with 307 more rows

11.09.2017 32

## Multiple types in one table

```
rank <- billboard3 %>%
  left_join(song, c("artist", "track", "year", "time")) %>%
  select(song_id, date, week, rank) %>%
  arrange(song_id, date)
rank
```

#> # A tibble: 5,307 × 4

	song_id	date	week	rank
	<int>	<date>	<dbl>	<int>
#> 1	1	2000-02-26	1	87
#> 2	1	2000-03-04	2	82
#> 3	1	2000-03-11	3	72
#> 4	1	2000-03-18	4	77
#> 5	1	2000-03-25	5	87
#> 6	1	2000-04-01	6	94
#> 7	1	2000-04-08	7	99
#> 8	2	2000-09-02	1	91
#> 9	2	2000-09-09	2	87
#> 10	2	2000-09-16	3	92

#> # ... with 5,297 more rows



11.09.2017 33

## One type in multiple tables


It's also common to find data values about a single type of observational unit spread out over multiple tables or files. These tables and files are often split up by another variable, so that each represents a single year, person, or location.

As long as the format for individual records is consistent, this is an easy problem to fix:

- Read the files into a list of tables.
- For each table, add a new column that records the original file name (the file name is often the value of an important variable).
- Combine all tables into a single table.

11.09.2017 34

## One type in multiple tables



The screenshot shows the 'Popular Baby Names' section of the Social Security Online website. It displays a table titled 'Popularity for top 100 names in Alabama for births in 2015'. The table has five columns: Rank, Male name, Number of males, Female name, and Number of females. The data is as of February 12, 2017. Below the table, there is a list of states with radio buttons for selection.

Rank	Male name	Number of males	Female name	Number of females
1	William	411	Ava	297
2	James	322	Emma	285
3	John	317	Olivia	258
4	Mason	294	Harper	213
5	Elijah	276	Elizabeth	196
6	Noah	248	Madison	172
7	Jackson	235	Amelia	147
8	Carter	204	Isabella	147
9	Michael	196	Skyler	147
10	Samuel	194	Anna	143

11.09.2017 35

## One type in multiple tables

hadley / data-baby-names

Watch 11 Star 101 Fork 77

Code Issues 0 Pull requests 1 Projects 0 Wiki Pulse Graphs

Branch: master data-baby-names / by-state / 1-download.r Find file Copy path

hadley Download top baby names by state aa353a7 on Jun 8, 2009

1 contributor

15 lines (11 sloc) 687 Bytes

```

1 library(RCurl)
2 library(plyr)
3
4 save_year <- function(state, year) {
5   url <- "http://www.ssa.gov/cgi-bin/namesbystate.cgi"
6   data <- postForm(url, style = "post", "year" = year, "state" = state)
7   writelines(data, paste("original/", state, "-", year, ".html", sep=""))
8 }
9
10 years <- 1960:2008
11 states <- c("AL", "AK", "AZ", "AR", "CA", "CO", "CT", "DE", "DC", "FL", "GA", "HI", "ID", "IL", "IN", "IA", "KS", "KY", "LA", "ME",
12
13 m_ply(expand.grid(state = states, year = years), save_year,
14       .progress = "text")

```

library(plyr)  
paths <- dir("data", pattern = "\\\*.csv\$", full.names = TRUE)  
names(paths) <- basename(paths)  
ldply(paths, read.csv, stringsAsFactors = FALSE)



11.09.2017 36

## Основная литература

- Grolemund, G. R for Data Science [Electronic resource] / Garrett Grolemund, Hadley Wickham. – 2016. – Mode of access: <http://r4ds.had.co.nz/index.html>. – Date of access: 01.09.2016.
- Wickham, H. Tidy data [Electronic resource] / Hadley Wickham // The Journal of Statistical Software. – Vol. 59. – 2014. – Mode of access: <http://vita.had.co.nz/papers/tidy-data.html>. – Date of access: 01.09.2016.
- Wickham, H. Tidy data [Electronic resource]. – 2017. – Mode of access: <ftp://cran.r-project.org/pub/R/web/packages/tidyr/vignettes/tidy-data.html>. – Date of access: 01.02.2017.
- Ogurtsov, A. Tidy data (Перевод) [Electronic resource]. – 2015. – Mode of access: <http://biostat-r.blogspot.com.by/2016/01/tidy-data.html>. – Date of access: 01.02.2017.

