



D-ATIS 126.7  
TWR 118.1(125.0)  
GND 121.65 APN 122.15  
Delivery 121.9(DCL ABVL)

**ZWWW URUMQI/Diwopu**  
N43° 54.5'E087° 28.5' ELEV 647.9m

## AERODROME CHART

RWY	Direction	Bearing strength(PCN)		BEARINGS ARE MAGNETIC ALTITUDES, DISTANCES, ELEVATIONS AND HEIGHTS IN METERS
07	071°	RWY	87/R/B/W/T	
		TWYs A(west of F),A5,A8(north of B),M	86/F/B/X/T	
		TWYs B1,B2,J(north of K3),K(T&K3),T(BTN L&K),K1(K&J) K2(K&J),N,T(B2&east cargo apron),T(east cargo apron)	83/R/B/X/T	
		TWYs A7,A8(south of B),A9,F(south of B),K(BTN A&B),L(south of B)	80/F/B/W/T	
25	251°	TWYs A2-A4,B(L&F),F(north of B),L(north of B)	79/R/B/W/T	
		TWYs A1,A6	78/F/B/W/T	
		TWYs B(DC1 to stand Nr.170),B3	78/R/B/X/T	
		TWY T(BTN stand Nr.141&B2)	76/R/B/W/T	
		TWYs H,K1(except K&J),K2(except K&J)	74/R/B/W/T	
		TWYs A10,K(BTN B&T),T(BTN K&stand Nr.141)	70/R/B/W/T	
		TWYs A(east of F),B4,J(south of K3),K(south of K3),K3,K4,K5,K6	69/R/B/W/T	
		TWY B(F to DC1)	61/R/B/W/T	
		TWYs T1-T4	52/R/A/W/T	



TAKE-OFF MINIMA(WITH RELIABLE ALTN)(m)					LIGHTS		
ACFT Type		RWY07/25		LVP in force RWY25		RWY07	RWY25
		REDL	NIL(Day only)	REDL RCLL	REDL RCLL		
2 TURB ENG or 3&4 ENG	A	RVR400 VIS800	RVR500 VIS800	RVR200	HUD RVR150	PALS CAT I SFL PAPI REDL RCLL	PALS CAT III SFL PAPI TDZL REDL RCLL
	B						
	C						
	D			RVR250			
Other 1&2 ENG							
Note:							
Changes: Delete SWY of RWY07/25.							