

STANDARD DEPARTURE CHART-INSTRUMENT

D-ATIS 127.45(DEP)
TWR 130.35(118.05)(E)
VAR2° W 118.45(130.35)(W)



ZGSZ SHENZHEN/Baoan
RNAV RWY16

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

Zhuhai APP(R) TM01 120.35(127.95)
TM02 124.25(126.0)
TM03 123.85(126.0)
TM04 124.75(127.95)
TM05 119.025(119.55)

1. RADAR REQUIRED
2. RNAV 1 3. RNP1
4. GNSS or DME/DME/IRU REQUIRED

TL 3600(QNH <980hPa)
3300(QNH ≥980hPa)
TA 2700



- Note:**
- ① Deviation to south of R065° SHK is forbidden for OVG-9X, IDU-9X, MIP-9X, SLS-9X.
 - ② When two RWYs used for independent departure, OVG-9X, SLS-9X, IDU-9X, MIP-9X need ATC clearance.
 - ③ Turning is forbidden until DER.
 - ④ Deviation to southeast is forbidden.

Changes: APP.

