ATIS 126.45 APP 120.85(124.65) TWR 118.0(118.7) ZGKL GUILIN/Liangjiang
RNAV RWY01

VAR1.8° W TL 3600 TA 3000 BEARINGS ARE MAGNETIC ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS 1. RNP1/RNAV1 2. GNSS REQUIRED 3300(QNH ≥1031hPa) DME DISTANCES IN NAUTICAL MILES DISTANCES IN KM 2700(QNH ≤979hPa) 3. RADAR REQUIRED(RNAV1 ONLY) SANJIANG 4200/4800 CAT C.D.E 116.8 SJG 3600 CAT B enroute ALT CAT A CH 115X \odot N25 46.6E109 36.6 ONEMI A NOT TO SCALE KL416 MAX230kt Fix A **KL410** 1400 ONE-8Y(by ATC) 172° 5.0% 077° KL 415 400 -QIFENGLING_¬ **KL519** 417 Y <u>3000</u> MAX230kt∢ <u> 2100</u> or by ATC N25 10.3E110 19.1 MAX230kt for QP-9Y ONE-9Y KL 419 3000 QP-8Y <u>2100</u> MAX230kt KL 418 3000 or by ATC MAX230kt for LBN-8Y(by ATC) ERTANG 213 QP N24 40.2E110 46.6 3900/4500 CAT C.D.E 2700 CAT B enroute ALT CAT A MOTOM LAIBIN 113.7 LBN CH 84X 2450 **√**1700 N23 45.8E109 08.8 ARP ← 268 1900 MSA 46km Changes: Procedure.