

STANDARD ARRIVAL CHART-INSTRUMENT

VAR 7° W

D-ATIS 126.65
AP01 123.85(127.95)
AP02 119.6(127.95)
TWR 118.25(118.85)

ZYTL DALIAN/Zhoushuizi
RNAV RWY10

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

1. RADAR REQUIRED
2. RNAV 1
3. GNSS REQUIRED


TL 3600
TA 3000
3300(QNH ≥ 1031hPa)
2700(QNH ≤ 979hPa)





NOT TO SCALE

CHANGHAI
116.8 CHI
CH 115X
N39 16.0E122 37.0

When aircraft ALT is 3000m or below,
MAX IAS 250kt .



STAR	ROUTING
CHI-07A	CHI-VENOS-TL113-TL111-TL107
CHI-08A	CHI-VENOS-TL113-TL111-TL110-TL106
SANKO-07A	SANKO-RUPID-UDETI-TL111-TL107
SANKO-08A	SANKO-RUPID-UDETI-TL111-TL110-TL106
NIXEP-07A	NIXEP-DOBGA-PATRI-TL111-TL107
NIXEP-08A	NIXEP-DOBGA-PATRI-TL111-TL110-TL106
ANRAT-07A	ANRAT-LOTGO-INTIV-TANIB-PATRI-TL111-TL107
ANRAT-08A	ANRAT-LOTGO-INTIV-TANIB-PATRI-TL111-TL110-TL106



MSA 46km

Changes: Routing.