

**ZSWX AD 2.1 机场地名代码和名称 Aerodrome location indicator and name**

ZSWX-无锡/硕放 WUXI/Shuofang

**ZSWX AD 2.2 机场地理位置和管理资料 Aerodrome geographical and administrative data**

1	机场基准点坐标及其在机场的位置 ARP coordinates and site at AD	N31°29.6' E120°25.7' 1280 m north of THR03
2	方向、距离 Direction and distance from city	130°GEO, 16km from city center
3	标高/参考气温 Elevation / Reference temperature	5.1m/30.6℃(JUL)
4	机场标高位置/大地水准面波幅 AD ELEV PSN / geoid undulation	-/-
5	磁差/年变率 MAG VAR/ Annual change	5°13'W/
6	机场管理部门、地址、电话、传真、AFS、电子邮箱、网址 AD administration, address, telephone, telefax, AFS, E-mail, website	Sunan Shuofang Airport CO. LTD. No.1, Airport Road 7, National High-Tech Development District, Wuxi, Jiangsu province, China Post code:214028 TEL:86-510-85215008 FAX:86-510-85217166 AFS:ZSWXZXZX Website:www.wuxiairport.com
7	允许飞行种类 Types of traffic permitted(IFR / VFR)	IFR/VFR
8	机场性质/飞行区指标 Military or civil airport &Reference code	CIVIL/4E
9	备注 Remarks	Nil

**ZSWX AD 2.3 工作时间 Operational hours**

1	机场当局(机场开放时间) AD Administration (AD operational hours)	H24
2	海关和移民 Customs and immigration	HS or O/R
3	卫生健康部门	HS or O/R

	Health and sanitation	
4	航行情报服务讲解室 AIS Briefing Office	HS or O/R
5	空中交通服务报告室 ATS Reporting Office (ARO)	HS or O/R
6	气象讲解室 MET Briefing Office	HS or O/R
7	空中交通服务 ATS	HS or O/R
8	加油 Fuelling	HS or O/R
9	地勤服务 Handling	HS or O/R
10	保安 Security	HS or O/R
11	除冰 De-icing	HS or O/R
12	备注 Remarks	Nil

### ZSWX AD 2.4 地勤服务和设施 Handling services and facilities

1	货物装卸设施 Cargo-handling facilities	Platform lift, baggage towing vehicle, container tractor, truck, baggage conveyor belt truck, electric fork truck, diesel fork truck, electric pallet truck, elevation platform, transmission machine system, hydraulic fork truck, lateral lifting composition platform.
2	燃油/滑油牌号 Fuel/oil types	Nr.3 jet fuel/ OIL-2197
3	加油设施/能力 Fuelling facilities/capacity	Oil tank(9000m <sup>3</sup> ), refueling truck(20000 litres, 35000 litres, 45000 litres).
4	除冰设施 De-icing facilities	De-icer, de-icing fluid(KHF-1)
5	过站航空器机库 Hangar space for visiting aircraft	Nil
6	过站航空器的维修设施	Working ladder

	Repair facilities for visiting aircraft	
7	备注 Remarks	Ground power unit, ground air supply unit, towing tractor

**ZSWX AD 2.5 旅客设施 Passenger facilities**

1	宾馆 Hotels	In the city
2	餐馆 Restaurants	At AD and in the city
3	交通工具 Transportation	Passenger's coaches, taxis
4	医疗设施 Medical facilities	First-aid and ambulance at AD
5	银行和邮局 Bank and Post Office	In the city
6	旅行社 Tourist Office	In the city
7	备注 Remarks	Nil

**ZSWX AD 2.6 援救与消防服务 Rescue and fire fighting services**

1	机场消防等级 AD category for fire fighting	CAT 8
2	援救设备 Rescue equipment	<p>Fire fighting facilities: rapid intervention vehicle, primary foam tender, dry-chemical tender, heavy foam tender, medium load foam tender, lighting tender, command car, demolition rescue truck, fire tender;</p> <p>Rescue equipments: hydraulic pressure scissor, life-saving air-cushion, toothless cutter, smoke machine, fire fighting axe, fire fighting hanger, fire fighting pickaxe, fire fighting iron collar, iron scissors, portable broadcast device, insulated pliers, medical bag.</p> <p>Armarium: defibrillator, emergency breathing machine, aspirator, emergency ambulance, electric gastric lavage machine, litter carrier, electrocardiograph, portable external defibrillator.</p>
3	搬移受损航空器的能力 Capability for removal of disabled aircraft	Nil

4	备注 Remarks	Nil
---	---------------	-----

**ZSWX AD 2.7 可用季节- 扫雪 Seasonal availability-clearing**

1	可用季节及扫雪设备类型 Types of clearing equipment	All seasons, Snow blower
2	扫雪顺序 Clearance priorities	RWY, TWY, Apron
3	备注 Remarks	Nil

**ZSWX AD 2.8 停机坪、滑行道及校正位置数据 Aprons, taxiways and check locations data**

1	停机坪道面和强度 Apron surface and strength	Surface:	CONC
		Strength:	PCN 92/R/A/W/T: Stands Nr. 25-32 PCN 89/R/A/W/T: Stands Nr. 16-24, 23L, 23R, 24L, 24R PCN 66/R/B/W/T: Stands Nr.14, 15 PCN 65/R/B/W/T: Stands Nr. 1-13, 2A
2	滑行道宽度、道面和强度 Taxiway width, surface and strength	Width:	48m: G(BTN main A& apron) 45m: G(BTN main A& RWY) 42m: E(BTN main A& apron), F 35m: D(BTN main A& apron) 34m: D(BTN main A& RWY), E(BTN main A&RWY) 23m: A(Vertical to RWY), main A, B, C
		Surface:	CONC: G(BTN main A& apron) ASPH: others
		Strength:	PCN 89/R/A/W/T: F, G(BTN main A& apron) PCN 89/R/B/W/T: A (Vertical to RWY) PCN 82/R/B/W/T: D(BTN main A& RWY) PCN 79/R/B/W/T: main A PCN 76/R/B/W/T: B, C, E(BTN main A&RWY), G(BTN main A& RWY) PCN 66/R/B/W/T: E(BTN main A& apron) PCN 65/R/B/W/T: D(BTN main A& apron)
3	高度表校正点的位置及其标高 ACL location and elevation	Nil	

4	VOR/INS 校正点 VOR/INS checkpoints	Nil
5	备注 Remarks	RWY shoulder 10.5m: A(north of main D), E(BTN main A& apron), F, south of G(BTN main A& apron) 7.5m: others

### ZSWX AD 2.9 地面活动引导和管制系统与标识

#### Surface movement guidance and control system and markings

1	航空器机位号码标记牌、滑行道引导线、航空器目视停靠引导系统的使用 Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands	Taxiing guidance signs at all intersections of RWY and TWY and at all holding positions. Taxiing guidance lines at all TWYs and aprons; Aircraft stand identification sign board at apron; Nose-in guidance for aircraft stands.	
2	跑道和滑行道标志及灯光 RWY and TWY marking and LGT	RWY markings	THR, RWY designation, center line, edge line, TDZ, aiming point
		RWY lights	THR, center line, wing bar, edge line, RWY end
		TWY markings	RWY holding position, center line, edge line, curve marking
		TWY lights	Edge line, center line, RWY guard lights( for TWY A (vertical to RWY ), B, D, E, G)
3	停止排灯 Stop bars	Nil	
4	备注 Remarks	Blue apron edge line lights	

### ZSWX AD 2.10 机场障碍物 Aerodrome obstacles

Obstacles within a circle with a radius of 15km centered on the center of ARP						
序号 Serial Nr.	障碍物类型(*代表有灯光) Obstacle type(*Lighted)	磁方位 BRG (MAG)(degree)	距离 DIST(m)	海拔高度 Elevation(m)	影响的飞行程序及起飞航径区 Flight procedure / take-off flight path area affected	备注 Remarks
1	*TWR	002	2634	53.8		
2	MT	006	12500	126	RWY21 intermediate approach	

Obstacles within a circle with a radius of 15km centered on the center of ARP						
序号 Serial Nr.	障碍物类型(*代表 有灯光) Obstacle type(*Lighted)	磁方位 BRG (MAG)(degree)	距离 DIST(m)	海拔高度 Elevation(m)	影响的飞行程序及起飞 航径区 Flight procedure / take - off flight path area affected	备注 Remarks
3	TWR	012	4908	58.2		
4	BLDG	012	5339	53.8		
5	*TWR	014	4612	50.8		
6	BLDG	015	6799	96.2	RWY21 final approach	
7	MT	015	14900	126		
8	*Antenna	028	1613	19.8		
9	*TWR	034	1138	26.6	RWY21 ILS/DME precision approach	
10	*Chimney	045	5114	86.9	RWY21 VOR/DME final approach	
11	*BLDG	047	4915	53.4		
12	Control TWR	050	800	31.4		
13	TWR	061	3864	54.9		
14	TWR	063	4025	63.5		
15	Iron TWR	065	5340	67.6		
16	Iron TWR	084	4499	67.6		
17	TWR	103	1346	51.3		
18	TWR	103	1411	50.8		
19	Pole	104	1850	50.6		
20	Iron TWR	104	4212	60.6		
21	TWR	113	2006	50.9		
22	TWR	114	1830	50.6		
23	Pole	126	2934	55.6		
24	*TWR	135	1855	64.2		
25	TWR	144	3530	51.3		

Obstacles within a circle with a radius of 15km centered on the center of ARP						
序号 Serial Nr.	障碍物类型(*代表 有灯光) Obstacle type(*Lighted)	磁方位 BRG (MAG)(degree)	距离 DIST(m)	海拔高度 Elevation(m)	影响的飞行程序及起飞 航径区 Flight procedure / take - off flight path area affected	备注 Remarks
26	*Chimney	178	5566	185.2	RWY03 VOR/DME final approach	
27	*Antenna	197	993	20.6		
28	*TWR	205	4529	56.8	RWY03 GP INOP, final approach; RWY21 take-off path	
29	BLDG	216	760	18.5		
30	TWR	244	4657	53.6		
31	BLDG	249	4073	65		
32	*BLDG	250	4108	64		
33	Iron TWR	263	4167	52.2		
34	*BLDG	271	4849	88.7		
35	*BLDG	271	4907	88.9		
36	*BLDG	272	4794	88.6		
37	Control TWR	276	325	43.7	RWY03 ILS/DME precision approach	
38	*Chimney	277	5752	125.4	Circling CAT C/D	
39	TWR	343	4662	50.4		
40	BLDG	353	450	22.5		
41	TWR	355	3954	55.2		
42	Pole	357	2963	50.5		
43	*BLDG	357	6455	101.1	Circling CAT B	
44	TWR	358	2444	61.1	RWY21 GP INOP final approach; Circling CAT A	
Others:						

Obstacles between two circles with the radius of 15km and 50km centered on the center of ARP						
序号 Serial Nr.	障碍物类型(*代表 有灯光) Obstacle type(*Lighted)	磁方位 BRG (MAG)(degree)	距离 DIST(m)	海拔高度 Elevation(m)	影响的飞行程序及起飞 航径区 Flight procedure / take - off flight path area affected	备注 Remarks
1	*BLDG	003	37264	334	RWY21 RNAV holding	
2	MT	036	27700	108	RWY21 RNAV initial approach	
3	MT	060	32603	261	RWY21 holding	
4	*BLDG	135	30044	280		
5	*BLDG	150	25395	178		
6	*BLDG	153	25364	200		
7	*BLDG	156	25144	229		
8	MT	165	31400	295		
9	MT	175	15672	274		
10	MT	180	16200	343	RWY03 holding, intermediate approach, RNAV initial approach; RWY21 RNAV departure	
11	MT	187	25800	343		
12	MT	191	44200	294		
13	MT	201	25500	253	RWY03 initial approach	
14	MT	205	43620	307		
15	MT	206	45600	337	RWY03 arrival	
16	MT	261	30900	263		
17	MT	262	20300	231	RWY03 initial approach	
18	*TV TWR	304	19413	431	sector; arrival	
19	*BLDG	310	15574	218		
20	*BLDG	311	16168	260		
21	MT	332	41900	189		



Obstacles between two circles with the radius of 15km and 50km centered on the center of ARP						
序号 Serial Nr.	障碍物类型(*代表 有灯光) Obstacle type(*Lighted)	磁方位 BRG (MAG)(degree)	距离 DIST(m)	海拔高度 Elevation(m)	影响的飞行程序及起飞 航径区 Flight procedure / take - off flight path area affected	备注 Remarks
22	MT	357	43800	263		
Others:						

## ZSWX AD 2.11 提供的气象信息、机场观测与报告

## Meteorological information provided &amp; aerodrome observations and reports

1	相关气象台的名称 Associated MET Office	Wuxi Shuofang Airport MET Office
2	气象服务时间；服务时间以外的责任气象台 Hours of service, MET Office outside hours	H24
3	负责编发 TAF 的气象台；有效时段；发布间隔 Office responsible for TAF preparation, Periods of validity; Interval of issuance	WUXI/Shuofang Airport MET Office 9 HR, 24HR; 3HR, 6HR
4	趋势预报发布间隔 Issuance interval of trend forecast	Trend 1 HR
5	所提供的讲解/咨询服务 Briefing/consultation provided	P, T, FAX, international MET codes
6	飞行文件及其使用语言 Flight documentation, Languages used	Ch, En
7	讲解/咨询服务时可利用的图表和其它信息 Charts and other information available for briefing or consultation	Synoptic charts, significant weather charts, upper W/T charts, satellite and radar material, AWOS Real-time Data
8	提供信息的辅助设备 Supplementary equipment available for providing information	printer, plotting instrument, FAX
9	提供气象情报的空中交通服务单位 ATS units provided with information	Wuxi Shuofang Airport ATC office, Control center

10	观测类型与频率/自动观测设备 Type & frequency of observation/Automatic observation equipment	Hourly plus special observation/Yes
11	气象报告类型及所包含的补充资料 Type of MET Report & supplementary information included	METAR, SPECI, TEND
12	观测系统及位置 Observation System & Site(s)	RVR EQPT A: 110m E of RCL, 352m inward THR21; B: 110m E of RCL, 1620m inward THR21; C: 110m E of RCL, 305m inward THR03. SFC wind sensors RWY03: 120m E of RCL, 335m inward THR RWY03/21: 120m E of RCL, 1600m inward THR21 RWY21: 120m E of RCL, 332m inward THR Ceilometer RWY03: 110m E of RCL, 340m inward THR; RWY21: 110m E of RCL, 342m inward THR.
13	气象观测系统的工作时间 Hours of operation for meteorological observation system	H24
14	气候资料 Climatological information	Climatological tables AVBL
15	其他信息 Additional information	Nil

### ZSWX AD 2.12 跑道物理特征 Runway physical characteristics

跑道号码 Designations RWY NR	真方位和磁方位 TRUE & MAG BRG	跑道长宽 Dimensions of RWY(m)	跑道强度(PCN), 跑道道面/ 停止 道道面 RWY strength (PCN), RWY surface / SWY surface	着陆入口坐标及 高程异常 THR coordinates and geoid undulation	跑道入口标高,精密进近 跑道接地带最高标高 THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
03	020 °GEO 025 °MAG	3200×50	67/R/B/W/T ASPH/-	Nil	THR4.6m

21	200 °GEO 205 °MAG	3200×50	67/R/B/W/T ASPH/-	Nil	THR5.1m
跑道-停止道坡度 Slope of RWY-SWY	停止道长宽 SWY dimensions(m)	净空道长宽 CWY dimensions(m)	升降带长宽 Strip dimensions(m)	无障碍物区 OFZ	跑道端安全区长宽 RWY end safety area dimensions(m)
7	8	9	10	11	12
See AOC	Nil	Nil	3320×300	Nil	140×120
See AOC	Nil	Nil	3320×300	Nil	140×120
Remark: RWY shoulder: 5m on each side; Forced landing area is 3200m×100m, located at east of RWY and surface is soil.					

## ZSWX AD 2.13 公布距离 Declared distances

跑道号码 RWY Designator	可用起飞滑跑距离 TORA(m)	可用起飞距离 TODA(m)	可用加速停止距离 ASDA(m)	可用着陆距离 LDA(m)	备注 Remarks
1	2	3	4	5	6
03	3200	3200	3200	3200	Nil
21	3200	3200	3200	3200	Nil

## ZSWX AD 2.14 进近和跑道灯光 Approach and runway lighting

跑道 代号 RWY Designator	进近灯 类型、 长度、 强度 APCH LGT type LEN INTST	入口灯 颜色、 翼排灯 THR LGT colour WBAR	目视进近坡 度指示系统( 跑道入口最 低眼高), 精 密进近航道 指示器 VASIS (MEHT) PAPI	接地地带 灯长度 TDZ LGT LEN	跑道中心线灯 长度、间隔、 颜色、强度 RWY Center line LGT LEN, spacing, colour, INTST	跑道边灯长 度、间隔、颜 色、强度 RWY edge LGT LEN, spacing, colour, INTST	跑道末端 灯颜色 RWY end LGT colour	停止道灯 长度、颜 色 SWY LGT LEN, colour
1	2	3	4	5	6	7	8	9
03	PALS CAT I* 900m LIH	GREEN Yes	PAPI LEFT/3 ° 21.9m	Nil	3200m** spacing 30m	3200m*** spacing 60m	RED	Nil

跑道 代号 RWY Designator	进近灯 类型、 长度、 强度 APCH LGT type LEN INTST	入口灯 颜色、 翼排灯 THR LGT colour WBAR	目视进近坡 度指示系统( 跑道入口最 低眼高), 精 密进近航道 指示器 VASIS (MEHT) PAPI	接地地带 灯长度 TDZ LGT LEN	跑道中心线灯 长度、间隔、 颜色、强度 RWY Center line LGT LEN, spacing, colour, INTST	跑道边灯长 度、间隔、颜 色、强度 RWY edge LGT LEN, spacing, colour, INTST	跑道末端 灯颜色 RWY end LGT colour	停止道灯 长度、颜 色 SWY LGT LEN, colour
21	PALS CAT I* 720m LIH	GREEN Yes	PAPI LEFT/3 ° 21.9m	Nil	3200m** spacing 30m	3200m*** spacing 60m	RED	Nil
Remarks: *SFL **up to 2300m WHITE VRB LIH, 2300-2900m RED/WHITE VRB LIH, 2900-3200m RED VRB LIH ***up to 2600m WHITE VRB LIH, 2600-3200m YELLOW VRB LIH								

### ZSWX AD 2.15 其他灯光,备份电源 Other lighting, secondary power supply

1	机场灯标/识别灯标位置、特性和工作时间 ABN/IBN location, characteristics and hours of operation	Nil
2	着陆方向标/风向标位置和灯光 LDI/WDI location and LGT	LDI: White landing lights locate on the left of RWY03/21, 280m inward THR03/21. WDI: 03:120m E of RCL, 335m inward THR 03/21:120m E of RCL, 1600m inward THR21 21:120m E of RCL, 332m inward THR
3	滑行道边灯和中线灯 TWY edge and center line lighting	All TWYs
4	备份电源/转换时间 Secondary power supply/switch-over time	Secondary power and diesel supply available/15 sec
5	备注 Remarks	Nil

**ZSWX AD 2.16 直升机着陆区域 Helicopter landing area**

1	TLOF 坐标或 FATO 入口坐标及大地水准面 波幅 Coordinates TLOF or THR of FATO Geoid undulation	Nil
2	TLOF 和/或 FATO 标高 (m/ft) TLOF and/or FATO elevation (m/ft)	Nil
3	TLOF 和 FATO 区域范围、道面、强度和 标志 TLOF and FATO area dimensions,surface, strength, marking	Nil
4	FATO 的真方位和磁方位 True and MAG BRG of FATO	Nil
5	公布距离 Declared distance available	Nil
6	进近灯光和 FATO 灯光 APP and FATO lighting	Nil
7	备注 Remarks	Nil

**ZSWX AD 2.17 空中交通服务空域 ATS airspace**

名称 Designation	水平范围 Lateral limits	垂直范围 Vertical limits	备注 Remarks
Wuxi tower control area	N313522E1201910- N314309E1202458- N312900E1204111- N311636E1203618- N311535E1202212- N313522E1201910	3000m(QNE) and below	Nil
Fuel Dumping Area	N3113E12300- N3130E12400- N3100E12400- N3100E12300- N3113E12300	3000m or above	MAX fuel dumping speed is 500kmH(IAS) (Refer ZSSS/ZSPD Fuel Dumping Area Chart)

名称 Designation	水平范围 Lateral limits	垂直范围 Vertical limits	备注 Remarks
Altimeter setting region and TL/TH		TL by ATC TH (1800)m	Nil

**ZSWX AD 2.18 空中交通服务通信设施 ATS communication facilities**

服务名称 Service Designation	呼号 Call sign	频率 Frequency (MHz)	工作时间 Hours of operation	备注 Remarks
1	2	3	4	5
ATIS		127.65	H24	Nil
TWR	Wuxi Tower	118.0(130.0)	H24	Nil
GND	Wuxi Ground	121.625(130.0)	01:30-12:30 UTC	when GND U/S, contact TWR
EMG	Wuxi Tower	121.5	H24	Nil

**ZSWX AD 2.19 无线电导航和着陆设施 Radio navigation and landing aids**

设施名称和类型 Name and type of aid	识别 ID	频率 Frequency	发射天线位置、坐标 Antenna site coordinates	DME 发射天线标 高 Elevation of DME transmitting antenna	备注 Remarks
1	2	3	4	5	6
Wuxi VOR/DME	VMB	113.9MHz CH86X	N31°44.6' E120°11.5'	38m	
Shuofang VOR/DME	SUF	114.1MHz CH88X	N31°29.9' E120°25.9' 240m E of RCL 1700m inward THR03	11m	
LOM 03	MF	306kHz	205 °MAG/4050m FM THR03		
LMM 03	M	632kHz	205 °MAG/1000m FM THR03		
LOC 03 ILS CAT I	IMF	109.9MHz	025 °MAG/345m FM RWY03 end		
GP 03		333.8MHz	120m E of RCL 295m inward THR03		

设施名称和类型 Name and type of aid	识别 ID	频率 Frequency	发射天线位置、坐标 Antenna site coordinates	DME 发射天线标 高 Elevation of DME transmitting antenna	备注 Remarks
DME 03	IMF	CH36X (109.9MHz)		7m	Co-located with GP 03
LOM 21	RH	306kHz	025 °MAG/4880m FM THR21		
LMM 21	R	632kHz	025 °MAG/1200m FM THR21		
LOC 21 ILS CAT I	IFS	108.9MHz	205 °MAG/265m FM RWY21 end		
GP 21		329.3MHz	120m E of RCL, 312m inward THR21		
DME 21	IFS	CH26X (108.9MHz)	120m E of RCL 312m inward THR21	8m	Co-located with GP 21

**ZSWX AD 2.20 本场飞行规定****ZSWX AD 2.20 Local traffic regulations****1. 机场使用规定****1. Airport operations regulations**

1.1 禁止未安装二次雷达应答机的航空器起降；

1.1 Take off/landing of aircraft without SSR transponder are forbidden;

1.2 最大起飞重量大于 15000kg 或批准的旅客座位数量超过 30 的民用固定翼涡轮发动机飞机，若无 ACASII 装置，不得在本场起降；

1.2 For fixed wing turbine engine aircraft (ACASII be not equipped or MTOW more than 15000 kilogram or approved passenger seat number more than 30 ), departure and landing are forbidden;

1.3 所有技术试飞需事先申请，并得到空中交通管制部门批准后方可进行；

1.3 Each and every technical test flight shall be filed in advance and shall be made only after clearance has been obtained from ATC;

1.4 可使用最大机型：B747-400 及同类机型；

1.4 Maximum aircraft to be available: B747-400 and equivalent;

1.5 除紧急任务外，本场不接收停场过夜的公务飞行；

1.5 Overnight business flight is not acceptable in this airport except emergency.

## 2. 跑道和滑行道的使用

## 2. Use of runways and taxiways

2.1 可以通过指挥中心申请引导车和拖车服务；

2.1 Follow-me vehicle service and towing service are available via Operational Control Center;

2.2 严禁在跑道、滑行道上带刹车滑行；

2.2 Taxiing with braking on RWY and TWY is strictly forbidden;

2.3 禁止航空器在跑道、滑行道上做 180°转弯,如果必须至掉头坪掉头；

2.3 180° turnaround on RWY and TWY is strictly forbidden for all aircraft, all aircraft can only turnaround on RWY turn pads;

2.4 禁止通过 C 滑行道进入跑道；

2.4 Enter into RWY via TWY C is strictly forbidden;

2.5 A 滑 (D 滑以南)、B 滑、C 滑限翼展 62m (不含)以下飞机滑行, B747-SP、B747-100、B747-200、B747-300、A340-200、A340-300、IL96 机型不可使用 A 滑 (D 滑以南)、B 滑、C 滑；A 滑 (D 滑以北) 限翼展 65m (不含) 以下航空器滑行。

2.5 TWY A (south of TWY D), TWY B, TWY C is only available for aircraft with wing span less than 62m. TWY A (south of TWY D), TWY B, TWY C isn't available for B747-SP, B747-100, B747-200, B747-300, A340-200, A340-300, IL96. TWY A (north of TWY D) is only available for aircraft with wing span less than 65m.

## 3. 机坪和机位的使用

## 3. Use of aprons and parking stands

3.1 离场航空器在推出开车前必须联系塔台申请

3.1 Departing aircraft shall contact TWR for



放行许可，经塔台许可后方可推出开车；

departure clearance prior to push-out for engine start-up;

3.2 发动机试车必须获得现场指挥中心许可并在指定的地点进行。严禁在有廊桥的机位试车；

3.2 Engine run-ups shall ask for the clearance from Aircraft Operation Control Center and it shall be carried out at a designated location. Engine run-ups at stands in the vicinity of boarding bridges is strictly forbidden;

3.3 本场航空器采用机位除冰方式。离港航空器需要除冰服务时，机组应事先向指挥中心提出申请；

3.3 The method of deicing at local stands applied for departure aircraft shall apply to Operation control in advance for deicing service;

3.4 机位使用限制/Limits for aircraft parking on the following stands:

停机位/Stands	航空器翼展限制/ Wing span limits for aircraft	航空器机身限制/ Fuselage limits for aircraft
Nr. 23, 24	<65m	
Nr. 2A、4	≤60.3m	≤63.6m
Nr. 9, 13, 14, 19, 20, 24R	<52m	<55m
Nr. 1-3, 5-8, 10-12, 15-18, 21, 22, 23L, 23R, 24L, 25-32	<36m	
Remarks:  1. Aircraft shall enter/exit stands Nr.23, 24 only via TWY G;  2. When aircraft CAT E parking at stand Nr.2A or 4, the limitation of taxiline east of cooresponding parking stand wing span is 36m;  3. Aircraft CAT E shall enter/exit stand Nr.2A or 4 only via TWY D;  4. Departure aircraft CAT E shall push back from stand Nr.2A or 4 to TWY main A.  5. When aircraft CAT E parking at stand Nr.4, stand Nr.5 is forbidden to be used.		

3.5 航空器不能同时使用的机位/ Pair of stands forbidden to use simultaneously:

使用机位/The stand in use	不能同时使用的机位/The stands forbidden to be used
Nr. 2A	Nr. 2 and 3
Nr. 2 or 3	Nr. 2A
Nr. 23	Nr. 23L and 23R
Nr. 23L or 23R	Nr. 23
Nr. 24	Nr. 24L and 24R
Nr. 24L or 24R	Nr. 24

3.6 1-24, 2A, 23L, 23R, 24L, 24R, 25-32 号停机位需自滑进顶推出。

3.6 Aircraft parking on stands Nr.1-24, 2A, 24L, 24R, 25-32 shall taxi in on own power and pushed-back by tow tractor.

4. 进、离场管制规定

4. Air traffic control regulations

4.1 所有经 SASAN 进港落地的航班，必须在过 SASAN 前 30min, 向无锡塔台报告预计过 SASAN 时间；所有经九亭台（JTN）或 EKIMU 进港落地的航班，必须在过 E120 40'经度线前 15min 向无锡塔台报告预计过 E120 40'经度线的时间。所有进港落地的航班实际过 SASAN 或 E120 40'经度线的时间与第一次通报的位置报时间相差 1min 及以上的，必须及时报告无锡塔台更新该信息。所有进港落地的航班向塔台第一次通报完位置报后，如果更改了应答机编码，应该通知无锡塔台；

4.1 All landing aircraft from SASAN shall report TWR Controller the time of passing SASAN thirty minutes before flying across SASAN.All landing aircraft from JTN VOR/DME or EKIMU shall report TWR Controller the time of passing the longitude line of E120 40' fifteen minutes before flying across the longitude line of E120 40' . If the difference between actual time and the first reported time is more than 1 minute (including 1 minute) , pilot shall report TWR controller again. If the transponder code is changed after the first location reporting, pilot shall report TWR controller;

4.2 使用 03 号跑道起飞左转直飞 VMB 台的离场航线、使用 21 号跑道经 VMB 台直接切入五边的进场航线在 E120°20'00" 经线以西,高度应控制在 2100m 或以上。

4.2 When departure aircraft take off and turn LEFT to VMB VOR/DME via RWY03, pilot shall keep 2100m or above at the west of the longitude line of E120°20'00". When landing aircraft to RWY21 via VMB VOR/DME, pilot shall keep 2100m or above at the west of the longitude line of E120°20'00".

## 5. 机场的 II/III 类运行

## 5. CAT II/III operations at AD

无

Nil

## 6. 除冰规则

## 6. Rules for deicing

无

Nil

## 7. 平行跑道同时仪表运行

## 7. Simultaneous operations on parallel runways

无

Nil

## 8. 警告

## 8. Warning

无

Nil

## 9. 直升机飞行限制, 直升机停靠区

## 9. Helicopter operation restrictions and helicopter parking / docking area

无

Nil

## ZSWX AD 2.21 噪音限制规定及减噪程序

## ZSWX AD 2.21 Noise restrictions and Noise abatement procedures

无

Nil

**ZSWX AD 2.22 飞行程序****ZSWX AD 2.22 Flight procedures****1. 总则**

除经无锡塔台特殊许可外，在塔台管制区内的飞行，必须按照仪表飞行规则进行。

**1. General**

Flights within Tower Control Area shall operate under IFR unless special clearance has been obtained from Wuxi Tower Control.

**2. 起落航线**

目视盘旋和起落航线在跑道西侧进行。C、D 类航空器高（450）m，A、B 类航空器高（350）m。

**2. Traffic circuits**

Circling and traffic circuits shall be made to the west of RWY at the height of (450)m for aircraft CAT C/D, and (350)m for aircraft CAT A/B.

**3. 仪表飞行程序**

3.1 严格按照航图中公布的进、离场程序飞行。如果需要，航空器可在空中交通管制部门指定的航路、导航台或定位点上空等待或做机动飞行。

**3. IFR flight procedures**

3.1 On normal conditions, strict adherence is required to the relevant arrival/departure procedures published in the aeronautical charts. Aircraft may, if necessary, hold or maneuver on an airway, over a navigation facility or a fix designated by ATC.

**4. 雷达程序和/或 ADS-B 程序**

无

**4. Radar procedures and/or ADS-B procedures**

Nil

**5. 无线电通信失效程序**

无

**5. Radio communication failure procedures**

Nil

**6. 目视飞行程序**

6.1 经 ATC 告知，使用 03 号跑道落地时，严格控

**6. Procedures for VFR flights**

6.1 With ATC permission, landing aircraft to RWY03

制在 A 线 (N312530) 以北活动; 使用 21 号跑道  
落地时, 严格控制在 B 线 (N312700) 以北活动;

shall operate at the north of Line A(N312530) and  
landing aircraft to RWY21 shall operate at the north  
of Line B(N312700);

6.2 等待: 在跑道两侧按起落航线进行等待。

6.2 Holding at both sides of RWY in accordance  
with traffic circuits.

## 7. 目视飞行航线

## 7. VFR route

无

Nil

## 8. 目视参考点

## 8. Visual reference point

无

Nil

## 9. 其它规定

## 9. Other regulations

9.1 对机组的要求:

9.1 Requirements for pilots:

9.1.1 机组应听清并复诵管制员指令, 发现疑问及  
时证实;

9.1.1 Readback ATC instructions and verify any  
questions;

9.1.2 从停机位推出时, 向塔台证实使用跑道、推  
出方向;

9.1.2 While pushed back from parking stand, verify  
the pushing direction and the approved RWY  
designation to ATC;

9.1.3 航空器进入跑道前必须在指定的跑道等待  
位置等待, 得到塔台许可后方可进入。

9.1.3 Aircraft shall wait on designated RWY holding  
position until receiving ATC permission for entering  
RWY.

## 10. 区域导航飞行程序相关数据

## 10. Data for RNAV flight procedures

Waypoint list

ID	COORDINATES(WGS-84)	ID	COORDINATES(WGS-84)
WX202	N312449 E1202341	WX306	N314044 E1202508
WX203	N312017 E1202144	WX307	N314209 E1202000
WX204	N312209 E1201549	WX308	N313622 E1202315
WX205	N313054 E1201934	SUF	N3129.9 E12025.9
WX206	N313102 E1201843	VMB	N3144.6 E12011.5
WX210	N311824 E1202738	JTN	N3107.4 E12120.5
WX211	N312414 E1203942	PIMOL	N3214.8 E11945.7
WX212	N311718 E1205632	SASAN	N3135.4 E12019.2
WX213	N312940 E1203837	EKIMU	N3121.1 E12106.6
WX302	N313452 E1202800	ESBAG	N3137.2 E11940.4
WX303	N313924 E1202957		

## Waypoint sequence for RWY03 arrival

EKI-51F	(IF) EKIMU	WX213 ALT by ATC	SUF	WX205 (1800) MAX 380kmH	WX204 (900)	WX203 ↑(700)
EKI-53F (by ATC)	(IF) EKIMU	WX213 (1800) or by ATC MAX 380kmH	WX210 (900)	WX203 ↑(700)		
ESB-51F	(IF) ESBAG	SASAN 2400	WX205 (1800) MAX 380kmH	WX204 (900)	WX203 ↑(700)	

JTN-51F	(IF) JTN	WX212 3000-4200 or by ATC	WX211 ALT by ATC	SUF	WX205 (1800) MAX 380kmH	WX204 (900)
	WX203 ↑(700)					
JTN-53F (by ATC)	(IF) JTN	WX212 3000-4200 or by ATC	WX211 (1800) MAX 380kmH	WX210 (900)	WX203 ↑(700)	
PIM-51F	(IF) PIMOL	VMB	SASAN 2400	WX205 (1800) MAX 380kmH	WX204 (900)	WX203 ↑(700)

Waypoint sequence for RWY03 holding procedure (outbound time 1 min)

(HM) WX205	2100	Fly over point	205 ° (inbound angle)	Left turn direction	MAX 380kmH
---------------	------	----------------	--------------------------	------------------------	------------

Waypoint sequence for RWY03 departure

EKI-61X	(CF) WX302 Fly over point 025 ° ↑(300)	(DF) WX213 Right turn direction ↑(900) or by ATC MAX 380kmH	EKIMU		
ESB-61X	(CF) WX303 025 °	WX306 Left turn direction	SASAN 2100 +5.5%	ESBAG	

	+5.5%	MAX 350kmH +5.5%			
JTN-61X	(CF) WX302 Fly over point 025 ° ↑(300)	(DF) WX211 Right turn direction ↑(1200) or by ATC MAX 380kmH	WX212 3000-4200 or by ATC	JTN	
PIM-61X	(CF) WX303 025 ° +5.5%	WX306 Left turn direction MAX 350kmH +5.5%	SASAN 2100 +5.5%	VMB 2700	PIMOL
PIM-63X (by ATC)	(CF) WX303 025 ° +6.3%	WX306 Left turn direction MAX 350kmH +6.3%	WX307 ↑2100 +6.3%	VMB 2700	PIMOL

Waypoint sequence for RWY03 departure (For circling to climb altitude)

(HM) WX306	ALT by ATC	Fly over point	294 ° (inbound angle)	Left turn direction	MAX 350kmH
---------------	------------	----------------	--------------------------	------------------------	------------

Waypoint sequence for RWY21 arrival

EKI-52F	(IF) EKIMU	WX213 (1500) or by ATC	WX302	WX308 (1200)	WX306 ↑(900) MAX 380kmH	WX303 ↑(600)
ESB-52F	(IF)	SASAN	WX306	WX303		



	ESBAG	2400	↑(900) MAX 380kmH	↑(600)		
JTN-52F	(IF) JTN	WX212 3000-4200 or by ATC	WX211 (1800)	WX302	WX308 (1200)	WX306 ↑(900) MAX 380kmH
	WX303 ↑(600)					
PIM-52F	(IF) PIMOL	VMB 2700	SASAN 2400	WX306 ↑(900) MAX 380kmH	WX303 ↑(600)	
PIM-54F (by ATC)	(IF) PIMOL	VMB 2700	WX307 ↑2100	WX306 ↑(900) MAX 380kmH	WX303 ↑(600)	

Waypoint sequence for RWY21 holding procedure (outbound time 1 min)

(HM) WX306	(1200)	Fly over point	025 ° (inbound angle)	Right turn direction	MAX 380kmH
---------------	--------	----------------	--------------------------	-------------------------	------------

Waypoint sequence for RWY21 departure

EKI-62X	(CF) WX202 Fly over point 205 ° ↑(300)	(DF) SUF Right turn direction MAX 380kmH	WX213 ALT by ATC	EKIMU	
EKI-64X (by ATC)	(CF) WX202	(DF) WX213	EKIMU		

	Fly over point 205 ° ↑(300)	Left turn direction ↑(1200) or by ATC MAX 380kmH			
ESB-62X	(CF) WX202 Fly over point 205 ° ↑(300) +5.8%	(DF) WX206 Right turn direction MAX 380kmH +5.8%	SASAN 2100 +5.8%	ESBAG	
JTN-62X	(CF) WX202 Fly over point 205 ° ↑(300)	(DF) SUF Right turn direction MAX 380kmH	WX211 ALT by ATC	WX212 3000-4200 or by ATC	JTN
JTN-64X (by ATC)	(CF) WX202 Fly over point 205 ° ↑(300)	(DF) WX211 Left turn direction ↑(1200) or by ATC MAX 380kmH	WX212 3000-4200 or by ATC	JTN	
PIM-62X	(CF) WX202 Fly over point 205 ° ↑(300)	(DF) WX206 Right turn direction MAX 380kmH	SASAN 2100 +5.8%	VMB	PIMOL

	+5.8%	+5.8%			
--	-------	-------	--	--	--

Waypoint sequence for RWY21 departure (For circling to climb altitude)

(HM) WX206	ALT by ATC	Fly over point	011 ° (inbound angle)	Right turn direction	MAX 380kmH
---------------	------------	----------------	--------------------------	-------------------------	------------

Notes: The path code is TF except special explanation.

The navigation performance is RNP1.

## ZSWX AD 2.23 其它资料

## ZSWX AD 2.23 Other information

机场区域范围内全年有鸟类活动。

Activities of bird flocks are found all the year round  
in the vicinity of aerodrome.

Type of bird	Activity time	Activity area	Flight altitude
Spotted Dove	Whole year	East soil aera, low-thick grass	
Common Snipe	September-December	East&South waters, East soil aera	
Common Buzzard	September-October	Low&High altitude	
Kestrel	September-October	Low&High altitude	
Egrets	April-October	East&South waters, South soil aera	
Magpie	Whole year	Soil aera	
Turtle Dove	September-October	Soil aera	
Whitecheeked Starling	April-September	South soil aera, low altitude	
Barn swallow	March-April, July-August	Soil aera, low altitude	
Skylark	Whole year	Soil aera, low-thick grass	
Tree Sparrow	Whole year	Soil aera, low-thick grass	
Pigeon	Whole year	Low altitude	