

STANDARD DEPARTURE CHART-INSTRUMENT

VAR4° W

ATIS 127.05
APP01 119.625(132.15)
APP02 120.25(132.15)
TWR 118.875(118.2)

ZSWZ WENZHOU/Longwan
RNAV RWY21

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

SHENGZHOU
113.4 SHZ
CH 81X
N29 36.0E120 49.0

- GNSS REQUIRED
- RNP1



YUNHE
244 BZ
N28 06.1E119 33.7

WZ402
ALT by ATC

WZ422
112°

WENZHOU
116.4 WNZ
CH 111X
N27 55.8E120 51.8

BEGMO
9000
or by ATC

WZ401
5500
or by ATC
MAX 400kmH


DONGSHAN
109.2 DST
CH 29X
N27 45.0E120 37.8

Note:

- Turning is forbidden until DER.
- It is available to gain the ALT at WZ401 and WZ406 for holding pattern if cannot get the required ALT by ATC: BEG-62X, OKA-62X.

RUPOX
119 216°
LJG-61X
LJG-62X(by ATC)

LIANJIANG
117.6 LJG
CH 123X
N26 13.2E119 32.9



Changes: APP FREQ.