AERODROME CHART

D-ATIS 127.65
TWR 118.55(124.3) APN 121.8
GND 121.65 DELIVERY 121.9(DCL AVBL)

ZJHK HAIKOU/Meilan
N19° 56.0'E110° 27.6' ELEV 22.6m

RWY	Direction	Bearing strength(PCN)
09	091°	PCN 104/R/B/W/T: TWY B(W of TWY B6), B1(S of TWY B), B2-B5
		PCN 95/R/B/W/T: RWY, TWY A, A1-A7, B(E of TWY B6), B6-B12, B15-B17, S4
27	271°	PCN 92/R/B/W/T: TWY S2, S3
		PCN 62/R/B/W/T: TWY B1(N of TWY B)

BEARINGS ARE MAGNETIC
ALTITUDES, DISTANCES,
ELEVATIONS AND HEIGHTS
IN METERS

Note:
A/C are forbidden to enter RWY
via rapid exit TWYs.

ELEV 22.6

ILS/LOC 108.5 IPP

ILS/GP 332.9

3600X45 CONC
Strip 3720X300

ILS/GP 329.9

ELEV 19.7

ILS/LOC 111.5 IHH

450 0 450 900 1350m

PALS CAT II SFL

PAPI

PAPI

PALS CAT I SFL

	TAKE-OFF MINIMA(WITH RELIABLE ALTN)(m)			LIGHTS	
ACFT Type	RWY09/27		RWY09/27 LVP in force	RWY09	RWY27
	REDL	NIL(Day only)	REDL RCLL		
2 TURB ENG or 3&4 ENG A B C D	RVR400 VIS800	RVR500 VIS800	HUD RVR200	PALS CAT II SFL PAPI REDL RCLL TDZL	PALS CAT I SFL PAPI REDL RCLL
Other 1&2 ENG	VIS1600				
Note:					
Changes: NII.					