VAR1.8° W BEARINGS ARE MAGNETIC ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS DME DISTANCES IN NAUTICAL MILES DISTANCES IN KM 1. RNP1/RNAV1 TL 3600 2. GNSS REQUIRED TA 3000 3300(QNH ≥1031hPa) 2700(QNH ≤979hPa) 3. RADAR REQUIRED(RNAV1 ONLY) -SANJIANG-4200/4800 CAT C.D.E 116.8 SJG 3600 CAT B enroute ALT CAT A CH 115X ONEMI \odot N25 46.6E109 36.6 NOT TO SCALE Fix A **KL512** MAX230kt Fix C **KL419** -QIFENGLING-MAX230kt 097° KL516 417 Y QP-9Z MAX230kt 5.0% ONE-9Z N25 10.3E110 19.1 (20j. <u>3000</u> <u>2100</u> KL515 or by ATC MAX230kt for ONE-8Z(by <u>400</u> ONE-8Z(by ATC) 850 5.0% KL418 ERTANG 213 QP N24 40.2E110 46.6 093° 31 Fix B 3900/4500 CAT C.D.E 2700 CAT B enroute ALT CAT A KL407 мотом 2450 × 1700 LAIBIN ARP ←268° 113.7 LBN 1900 CH 84X \odot N23 45.8E109 08.8 MSA 46km Changes: Procedure.