

ELEV 479.1m N34° 26.7'E108° 45.0' BEARINGS ARE MAGNETIC ALTITUDES, DISTANCES, ELEVATIONS AND HEIGHTS IN METERS VAR3.4°W 44444444444444444444444444444 CAT PALS CAT SFL RWY23R PALS CAT CAT SFL PALS PAPI SFL RCLL REDL TDZL 727 ЯSZ \equiv $|\mathbf{l}|$ LIGHTS RWY05R CAT PAPI PALS PAPI SFL RCLL TDZL RWY05L/23L CAT Note: RWY 05R/23L marking is similar to RWY 05L/23R. PALS PAPI SFL RCLL REDL 3000×45 ASPHALT 3800x60 CONCRETE in force 05L/R, 23L/R **RVR150** REDL RCLL RENL ALTN)(m) RVR200 Idyd SR PAPI RELIABLE LVP 00 \odot NIL(Day only) RVR500 VIS800 444444444444444444444444444444444 05L RWY05L/R, 23L/R TAKE-OFF MINIMA(WITH VIS1600 ijΙ PALS CAT RVR400 VIS800 REDL 051 PALS CAT III SFL B Ö Ω ∢ Type ENG ENG ENG 182 Changes: NII. TURB . 3&4 ACFT Other Note: 2 2