Detection and Forgetting under Asymmetric Data Availability in Class-Incremental Network Intrusion Detection

Wu Liqiang

Research manuscript — evidence cutoff: 2026-10-19 20:53 MYT

Abstract

Class-incremental network intrusion detection must retain old attacks while adapting to new traffic. We study whether benign data remaining available outside attack replay memory improve detection without compromising retention. AA-CIL combines a refreshed, independently calibrated benign–attack gate with an attack-only family classifier. At a stagewise benign-calibration target of 2%, its UNSW-NB15 mean incremental balanced accuracy is 69.65%, final balanced accuracy is 55.05%, and forgetting is 20.04±1.16 percentage points. NSL-KDD forgetting is 11.12±2.70 points. Thus favorable detection does not establish successful class retention. UNSW-NB15 attack detection reaches 69.09%, but its advantage over the strongest registered comparator is only 1.15 points ($p = 0.0748$), failing the original superiority criterion. NSL-KDD test FPR is 6.15%, demonstrating calibration shift. A post-hoc exposure-matched control supports a dataset-dependent detection benefit, with unmatched total computation. A subsequent validation-only experiment compares five family-retention alternatives under gate distillation; its main version must meet explicit forgetting, final-accuracy and detection requirements before a method-benefit claim is allowed. We preserve negative and incomplete evidence and do not infer novelty or universal superiority. CIC-IDS-2017 AA-family coverage: 10/15 cells across AA-CIL ($n = 0/5$), TS-mem ($n = 5/5$), and AA-noAttMem ($n = 5/5$); Replay-BS is reported separately.. **Keywords:** continual learning; intrusion detection; benign data availability; false-positive calibration; replay memory.

1 Introduction

Intrusion detection models must recognize newly observed attack families without discarding knowledge of older ones. In class-incremental learning, historical attack records are represented by a limited replay memory, and inference must choose among all observed classes without a task identifier. This constraint is operationally meaningful when previous attack captures cannot be retained indefinitely or reacquired. It does not necessarily imply that benign traffic has the same availability: a monitored network may continue to provide benign examples.

The asymmetry is useful only under an explicit assumption. The learner must have access to a sufficiently clean, representative benign source, distinct from its test data. This paper does not assume that arbitrary production traffic is correctly labeled benign. Nor do we assume that a training-domain benign hold-out guarantees the same false-positive rate (FPR) after a distribution change. Both qualifications matter in our results.

Replay-based NIDS research includes class balancing, frequency-aware replacement, representative selection, and other memory designs [1–4]. Some multiclass formulations place Normal and attack classes in a common classifier and replay budget. However, this is not a universal description of the literature: binary and novelty-detection methods use different protocols, and prior domain-adaptation work has already used new benign data outside an old attack memory [5]. The question is therefore not whether benign data have ever been treated differently. It is whether a continuously refreshed, independently calibrated detector provides useful retention and detection behavior in a multistage class-incremental experiment.

We study availability-asymmetric class-incremental learning (AA-CIL). A binary gate G is updated using newly sampled benign data, current attacks, and stored old attacks. A separate classifier F predicts attack families. A benign-only calibration pool sets G's operating threshold without test labels. Memory allocation to attack families is evaluated as a secondary component rather than presented as the principal mechanism.

The contribution is an evidence-bounded experimental study:

- An explicit separation of persistent attack replay, refreshed benign training data, and permanent benign calibration data, with each storage and training cost disclosed.
- A modular gate/family design and matched-protocol comparisons that distinguish restricted benign refresh from attack-memory reallocation.
- A low-false-alarm evaluation reporting actual test FPR, binary attack detection, family-level performance, and negative registered outcomes rather than relying on aggregate accuracy alone.
- A separately identified post-hoc control, Replay-BS, demonstrating a dataset-dependent difference under matched benign exposure while retaining the limitation of unmatched total computation.

These are study contributions, not a declaration that the architecture or its components are individually novel. In particular, the registered strongest-comparator test includes the ablations, and its failure is retained throughout this paper.

2 Related Work

2.1 Replay and class-incremental bias

iCaRL combines exemplar retention with incremental representation learning [6]. Dark Experience Replay and DER++ preserve historical responses alongside supervised rehearsal [7]. These approaches motivate strong replay references, but results obtained with image architectures and original buffering schemes are not automatically reproduced by a tabular NIDS adaptation.

Several methods address old/new-class imbalance. BiC learns a post-training correction [8]; weight alignment adjusts classifier scale [9]; separated softmax and taskwise distillation reduce cross-task interference [10]; end-to-end incremental learning includes balanced fine-tuning [11]. Logit adjustment uses class-prior information to change decision scores [12]. We use these methods to contextualize earlier diagnostic experiments, not as evidence that a binary gate is a new idea. Adaptation details and their unsuccessful results are retained rather than generalized to the original algorithms.

2.2 Continual intrusion detection

CBRS-NIDS distinguishes within-attack and across-class balancing [1]. ECBRS uses frequency-driven replacement and minority protection, while PAPA addresses replay interference [2]. SSF selects and forgets examples according to their distributional relevance [3]. These are predefined *rules*, not necessarily numerically fixed class quotas. SPIDER combines semi-supervised learning and gradient-projection memory, retaining previous-task unlabeled information rather than implementing an all-history equal-class labeled buffer [13]. CND-IDS studies continual novelty detection with latent regularization and a benign reference set [14]. ACIL evaluates multiple memory strategies and reports class-level behavior [4]. Binary domain-incremental, novelty-detection, and multiclass class-incremental results must not be treated as interchangeable benchmarks.

Our targeted source review found that most of the inspected primary result tables did not separately report benign FPR at a specified operating point. ACIL provides partial or indirect benign-class reporting. This observation motivates explicit operating-point reporting here; it is not a field-wide prevalence estimate or a claim that prior work ignores false alarms.

2.3 The nearest availability and multi-stage precedents

Cerasuolo et al.'s attack-adaptive NIDS uses a multiclass incremental model with exemplars from old benign and attack classes [15]. Their adaptable and explainable NIDS also considers new-domain benign data; it is therefore incorrect to describe its benign information as restricted exclusively to old memory [16].

The closest availability precedent is their network-agnostic study [5]. Its adaptation experiment supplies new benign data outside an old memory containing only attacks. This defeats a broad claim that external benign data combined with attack-only old memory is unprecedented. In the inspected experiment, binary detection is derived from multiclass attack outputs, and the evaluation does not establish an independently trained gate that is repeatedly refreshed and FPR-calibrated across multiple attack increments. AA-CIL examines this narrower combination. The absence of an identical verified implementation is not proof of novelty, and a useful incremental contribution must still be isolated experimentally.

Wang and Cao's GLOBECOM paper describes a two-stage class-incremental approach [17]. Only its official abstract and publication record were available for this study. Its stages concern anti-forgetting learning and unbiased prediction; we cannot infer a binary-gate/family architecture, benign refresh policy, or replay exclusion rule from its title. The unavailable full text remains an explicit literature limitation. Finally, TS-mem below is our controlled restricted-refresh ablation, *not* a faithful reproduction of any of these papers.

3 Problem Analysis

3.1 A corrected experimental basis

The motivating experiments use a taskwise minimum-update schedule rather than only a small fixed number of epochs. This prevents late, rare attack tasks from receiving arbitrarily few optimizer updates. Old attack classes are accessible only through stored training and validation rows after their introduction. Frozen preparation and duplicate/conflict handling are retained across methods; "deduplicated UNSW-NB15" does not imply that every benchmark is free of feature collisions or label conflicts. Historical experiments that revisited complete old attack pools are not used as evidence for the present access-constrained protocol. That old-pool resampling was a bug in this project's earlier implementation. The undertraining and data-quality issues identified in that development history are not attributed to published methods without source-specific evidence.

3.2 False alarms are important, but not a universal root cause

An earlier decomposition of the historical S2000 DER++ final confusion matrices showed substantial Normal-origin false positives in CIC-IDS-2017 attack-family columns, including families with high recall but low precision. These DER++ proportions must not be assigned to every method. UNSW-NB15 also exhibited attack-to-attack confusions and lost attack recall. These observations justify measuring benign FPR

and attack detection separately, but do not identify inadequate benign coverage or Normal–attack memory competition as a universal causal explanation. The decomposition is arithmetic, not an intervention proving a mechanism.

Under the registered correction sweep, the best tested correction/base combinations closed only 4.92% and 19.23% of the positive Joint-minus-incremental Macro-F1 gaps on UNSW-NB15 and CIC-IDS-2017, respectively. This rejects the sufficiency of those specific adaptations and candidate ranges, not bias correction in general. Joint is an offline reference rather than a guaranteed numerical upper bound.

3.3 Why change the learning organization?

The preceding FARQ experiments adjusted shared replay allocation using measured validation false alarms. Their registered main criterion failed, and descriptive operating curves did not establish a universally superior false-alarm/detection frontier. Replay+LA and Replay share the same attainable predictions when the total adjustment is recalibrated; this does not make all allocation methods threshold-equivalent. WACB and Freq change the learned model and improve detection relative to Replay at evaluated matched-FPR points on UNSW-NB15 and CIC-IDS-2017. Memory reallocation can therefore improve the measured trade-off, although it does not close every offline-reference gap. These finite operating-point comparisons are not a global frontier theorem. AA-CIL tests a different learning organization, not a premise that every shared-classifier method merely moves along one common curve.

4 Method: AA-CIL

4.1 Data roles and access assumption

At update t, let $\mathcal{A}_t$ be the observed attack families and $\mathcal{N}_t$ the newly introduced attack families. The learner receives their current training data D_t^A, retained old attack training memory $R_{t-1}^{A,\mathrm{tr}}$, and a benign training source B^{tr}. A permanent benign calibration pool B^{cal} is disjoint from every optimizer input. We assume continued access to B^{tr} but not to the original pools of old attacks.

The benchmark simulates benign availability by drawing a task-dependent sample $B_t \subseteq B^{\mathrm{tr}}$ of up to 50000 rows. Samples may overlap across tasks; this is repeated access to a fixed prepared training source, not evidence from a newly collected live stream. The permanent split prevents a calibration row from later becoming a training row.

4.2 Independent detector and family learner

The gate is a binary MLP trained on

$$D_t^G = B_t \cup D_t^A \cup R_{t-1}^{A,\mathrm{tr}}. \tag{1}$$

Its labels are benign versus attack. The family MLP is trained on

$$D_t^F = D_t^A \cup R_{t-1}^{A,\mathrm{tr}}, \tag{2}$$

using attack-family labels only. Both use the existing class-balanced cross-entropy implementation and retain learned parameters between updates. Their optimizers and costs are separate. Neither model receives calibration data as optimization input.

For exact implementation fidelity, the family network is initialized with the benchmark's full attack-label output dimension. Training follows the shared replay cross-entropy implementation, while inference restricts the argmax to observed attack families. Thus this experiment assumes a known finite benchmark label universe; it is not a claim about an unbounded, dynamically expanding unknown-label vocabulary.

4.3 Attack replay allocation

Let $K_t = |\mathcal{A}_t| + 1$, including Normal, and let m be the common per-observed-class budget. The shared capacity is

$$M_t = mK_t, \qquad m = 200. \tag{3}$$

AA-CIL divides M_t among observed attacks: $q_{t,c} = \lfloor M_t/|\mathcal{A}_t| \rfloor$ plus one for the first remainder classes in ascending class-ID order. This is a capacity ceiling, not a promise of equal actual occupancy. Each class allocation contains separate training and validation slots; validation rows do not enter optimization. When a class is new, examples can be selected from its prepared training and validation partitions. Once it is old, the corresponding retained arrays are the only permissible source, even if a later quota exceeds available rows. Unused slots remain unused; old pools are never revisited to fill them.

This allocation transfers the nominal Normal share to attacks. It does not make benign data free in a physical-storage sense: both benign training samples and the permanent calibration pool are disclosed outside M_t. The no-transfer ablation tests whether this allocation adds value beyond benign refresh.

4.4 Calibration and inference

Let $s_G(x) = z_A(x) - z_B(x)$ be the gate's attack-minus-benign logit margin. For $n = |B^{\mathrm{cal}}|$, sort its margins as $s_{(1)} \le \cdots \le s_{(n)}$ and set

$$k_\alpha = \lfloor \alpha n \rfloor, \qquad q_{t,\alpha} = s_{(n-k_\alpha)}. \tag{4}$$

The strict decision $s_G(x) > q_{t,\alpha}$ bounds the empirical calibration false-alarm count by k_α, including ties. No randomized tie breaking is used. Prediction is

$$\hat{y}(x) = \begin{cases} \text{Normal}, & s_G(x) \le q_{t,\alpha}, \\ \arg\max_{c \in \mathcal{A}_t} F_c(x), & s_G(x) > q_{t,\alpha}. \end{cases} \tag{5}$$

This is an empirical training-holdout operating point, not a distribution-free guarantee on test or deployment FPR. Gate false negatives cannot be recovered by the downstream family classifier.




Figure 1: AA-CIL separates detection from family classification. The calibration pool never enters training. A single retained attack memory supplies both learners and is counted once; two networks and both training schedules are counted in cost.

Algorithm 1 One AA-CIL update

Require: Current attacks D_t^A; retained attack memory R_{t-1}^A; benign pools $B^{\text{tr}}, B^{\text{cal}}$

1: Sample B_t from B^{tr} only.
2: Train G on $B_t \cup D_t^A \cup R_{t-1}^{A,\text{tr}}$.
3: Train F on $D_t^A \cup R_{t-1}^{A,\text{tr}}$.
4: Allocate attack capacities $q_{t,c}$ within M_t.
5: **for** each observed attack c **do**
6: Select new-class rows, or subsample retained old rows; keep training and validation disjoint.
7: **end for**
8: Calibrate $q_{t,\alpha}$ on B^{cal}; do not update weights.
9: Save models, retained memory, allocation, costs, and operating-point confusion matrices.

4.5 Post-hoc retention extension: AA-CIL-KD

The original AA-CIL gate relies on attack replay without an explicit response-retention loss, and its family learner uses ordinary replay. AA-CIL-KD is a post-hoc extension to that study, with its protocol and success criteria registered before observing any KD results. It adds a gate loss

$$\mathcal{L}_G = \mathcal{L}_{\text{CE},G} + \lambda_G \, \mathcal{L}_{\text{MSE},G}. \tag{6}$$

For retained old attack training rows, the gate targets are the stored two-logit responses recorded when those rows entered memory. For the current benign sample, targets come from the frozen preceding-task gate. New attack rows have no old-class distillation target, and the first task has no preceding-task gate. Neither calibration rows nor attack validation rows become optimizer inputs.

The attack-only family learner uses a task-boundary DER++-objective adaptation: supervised learning is supplemented by replay cross-entropy and MSE against stored family logits. This is not a claim to reproduce the original DER++ online storage schedule. Gate and family logits are auxiliary records for the same attack rows, not two separately allocated sample memories; their storage and the two training costs must be disclosed. The update budgets, benign refresh, permanent holdout and threshold policy remain those of AA-CIL.

An initial development search used mean stagewise validation balanced accuracy and varied three distillation coefficients. It was superseded before formal KD results by the retention-constrained selection below. Its completed runs remain part of the development cost, but do not enter the new selection. The previously planned noGKD ablation is not one of the five family-model candidates in this revised experiment.

4.6 Post-hoc parameter isolation: AA-CIL-ISO

AA-CIL-ISO changes only the family learner relative to AA-CIL-KD: the gate, G-KD objective, benign refresh and calibration remain the same. It uses the existing MLP feature encoder, not a transplanted transformer pipeline. On the first task containing attacks, the encoder and that task's new family heads train jointly within one family-model update budget. The encoder is then frozen. Each new family c receives its own rank-8 residual adapter and two-logit binary head,

$$h_c = h + U_c V_c h, \qquad p_c(x) = \text{softmax}(H_c h_c)_1. \tag{7}$$

The head learns that family versus the other attacks available in the current task and legal old-attack replay. Multiple new families provide negatives for one another. Normal rows are not used as family-head negatives. After the task, its adapters and heads are frozen permanently; old attack pools are never reopened.

All heads introduced in one task share a single training loop: their class-balanced binary cross-entropies are averaged before each optimizer step. Each new head participates in the task's common $\max(8 \text{ epochs}, 2000 \text{ steps})$ schedule, rather than receiving an additional serial budget per head. The first encoder training has no separate pretraining budget. Joint family-loop time and shared steps are recorded once; exclusive per-head time is not inferred from that total. If the first task contains only one attack family, there are no other-attack negatives: this limitation is recorded explicitly, without invented negatives or benign substitution.

After the gate declares an attack, prediction is $\arg\max_{c \in \mathcal{A}_t} p_c(x)$ over independently normalized positive probabilities. This is head-only inference with no router and no cross-head softmax calibration. It adapts OFRA-style parameter isolation to the present backbone and protocol; historical OFRA forgetting values do not establish its performance here. ISO is evaluated under the newly registered retention and detection criteria, with descriptive paired comparisons against KD. No ISO success is inferred before those results are available.

4.7 Retention alternatives and validation-only selection

The revised experiment compares five family learners under the same G-KD gate: KD, ISO, weight alignment (WA), class-balanced fine-tuning (CBF), and nearest-class-mean prediction (NCM). WA rescales newly introduced classifier weights by the mean old-to-new weight-norm ratio after task training [9]. CBF adds small-learning-rate updates on balanced retained attack training memory [11]. NCM computes class prototypes from retained attack training rows encoded by the current family encoder and predicts by feature-space distance [6]. These are adaptations of established mechanisms, not claims of novel versions of the cited algorithms. Their additional time, steps, prototype storage and model storage are reported separately.

Only UNSW-NB15 development seeds $\{5, 6\}$ select hyperparameters and the main version. Each candidate uses $\lambda_G \in \{0.5, 1, 2\}$; KD fixes both family DER coefficients to one. CBF uses 0.1 times the base learning rate and either one or five fine-tuning epochs. A stratified permanent 10% attack holdout supplies fixed validation cohorts across stages; it is never optimized, is accessible only for this development evaluation, and its storage is disclosed outside the replay budget. The permanent Normal holdout supplies the gate threshold at $\alpha = 2\%$ and the Normal validation cohort. This development-only access exception does not reopen old attack training pools or change formal replay access.

For each version, eligible configurations have final validation balanced accuracy at least the original AA-CIL development mean minus three percentage points. The configuration with lowest mean validation forgetting is retained, and the lowest-forgetting eligible version is selected as the candidate main method. All choices are frozen across datasets before evaluation seeds $\{1, 2, 3, 4, 42\}$ are used. Every version is reported, not only the selected one. If no configuration is eligible, there is no eligible main method; any configuration retained for descriptive formal reporting is explicitly a fallback, not an eligibility success. Test labels never select the gate threshold, hyperparameters, or main version.

5 Experimental Setup

5.1 Benchmarks and task protocol

We use the prepared NSL-KDD, deduplicated UNSW-NB15, and CIC-IDS-2017 benchmarks [18–20]. Normal and an initial attack family appear in the first task, followed by the fixed attack-family sequence. The data manifest and generated protocol table specify label mappings, task groupings, split sizes, and feature dimensions. Test rows from unobserved classes are excluded at intermediate checkpoints; final metrics use the complete prepared test set. No test row is selected for training, memory construction, or primary calibration.

Training uses MLPs with two hidden layers of width 128, Adam with learning rate 0.001, and batch size 256. Each model/update receives

$$S_t = \max(2000, 8 \lceil |D_t|/256 \rceil) \tag{8}$$

optimizer steps. Consequently, matching this schedule does not imply identical realized steps when data exposure differs. Gate and family schedules are recorded separately. The registered seed set contains 5 seeds; tables report actual completed n where the cutoff prevents a complete group. Partial groups are not silently replaced with selected favorable seeds.

The observed local GPU is an NVIDIA GeForce RTX 4060 Ti with 8 GiB memory; the HPC execution environment uses NVIDIA A100 GPUs. HPC results are included only after completed execution, not merely submission or allocation. Heterogeneous hardware and shared local GPU use mean that reported runtimes are not a controlled hardware benchmark.

5.2 Comparators and ablations

The external comparison set is Replay, DER++, WACB, Freq, and Replay+LA. Replay uses the common tabular architecture. DER++ is the recorded tabular adaptation with classwise memory management, not an exact replication of the original vision protocol. WACB adapts benign-versus-combined-attack balancing to this multiclass setting. Freq is a simplified frequency-proportional allocation control, not an exact ECBRS reproduction. Replay+LA is a saved-model logit-adjustment evaluation; it is not an additional independently trained network. All primary operating thresholds are determined from the same permanent benign calibration pool.

TS-mem retains the same gate/family organization but restricts each task's benign refresh to the training

Table 1: Dataset/task and final-budget summary. Calibration bytes include float32 features and int64 row indices, exclude model state and dense labels. The pool is shared by all methods, excluded from optimization, and outside M.

Dataset	Classes	Tasks	M ceiling	Calib rows	Calib bytes
NSL-KDD	5	4	1000	6735	3178920
UNSW-NB15	10	5	2000	6825	1911000
CIC-IDS-2017	8	4	1600	181176	57251616

Table 2: Prepared split sizes, feature counts and fixed task groupings (class IDs). These are the exact prepared benchmark arrays, not an assertion of temporal deployment validity.

Dataset	TRAIN rows	TEST rows	Features	Task IDs (semicolon separates tasks)
NSL-KDD	125973	22544	116	0,1; 2; 3; 4
UNSW-NB15	120991	30248	68	0,1; 2,3; 4,5; 6,7; 8,9
CIC-IDS-2017	2262203	565673	77	0,1; 2,3; 4,5; 6,7

NSL-KDD: 0=Normal, 1=DoS, 2=Probe, 3=R2L, 4=U2R. UNSW-NB15: 0=Normal, 1=Generic, 2=Exploits, 3=Fuzzers, 4=DoS, 5=Reconnaissance, 6=Analysis, 7=Backdoor, 8=Shellcode, 9=Worms. CIC-IDS-2017: 0=Normal, 1=DoS, 2=DDoS, 3=Bruteforce, 4=PortScan, 5=WebAttack, 6=Botnet, 7=Infiltration.

portion of the ordinary Normal allocation, while sharing replay capacity between Normal and attacks. It therefore measures a restricted benign exposure policy, not the effect of a frozen benign subset alone. AA-noAttMem retains refreshed benign training and the independent gate but does not transfer the Normal allocation to attacks. Its name does not mean that attacks have no replay memory.

Joint trains with the offline data available under its recorded protocol and is reported as a reference. It is not a guaranteed upper bound, a matched-storage online learner, or a member of the strongest-baseline selection. FARQ is supplementary. The registered selection includes the external methods *and* TS-mem and AA-noAttMem; excluding those ablations after inspecting results would change the registered question.

5.3 Metrics and registered inference

For confusion counts C_{ij} with Normal index b, we report

$$\mathrm{FPR} = \frac{\sum_{j \neq b} C_{bj}}{\sum_j C_{bj}}, \tag{9}$$

$$\mathrm{ADR} = \frac{\sum_{i \neq b} \sum_{j \neq b} C_{ij}}{\sum_{i \neq b} \sum_j C_{ij}}. \tag{10}$$

ADR is binary attack detection, not correct-family recall. Macro-F1 and attack-family macro recall supplement it. The registered family-recall guard includes attack classes meeting the specified minimum test support; excluded rare classes remain visible in per-class evidence. Precision is undefined for a class with no predictions in a seed and is never changed to zero. Its group mean and sample standard deviation use only defined seed values, with the actual n_{defined} (`defined_n`) reported separately from the total seed count. If none are defined, the mean remains undefined; with fewer than two defined values, the sample standard deviation is undefined. Such a seed is not dropped from recall, forgetting, or other defined endpoints.

The primary calibration target is $\alpha = 2\%$. Actual test FPR is reported alongside it because equal calibration targets need not yield equal test FPR. The primary registered superiority criterion requires a one-sided paired test against the highest-mean registered comparator in at least two datasets. The comparator is chosen once per dataset and endpoint from whole-seed means, not separately per seed. Other criteria test Macro-F1 harm, the family-recall guard, the CIC gate-refresh ablation, and descriptive cost/Joint reporting. Paired differences, sample standard deviations, and effect sizes accompany tests where available. No multiplicity correction was registered; selection of the highest observed mean and the small seed count limit inferential strength. A nonsignificant difference is not an equivalence or noninferiority result.

6 Results

6.1 Class-incremental retention and forgetting

Class-incremental performance is evaluated before the false-alarm–detection comparison. For every saved checkpoint $t = 1, \ldots, T$, the operating threshold is determined anew from the same permanent Normal calibration pool at $\alpha = 2\%$, using that checkpoint's scores. The final threshold is not retrospectively applied to earlier models. For a seen class c, let $r_{c,t}$ denote its recall under this operating point and let $\mathcal{C}_t$ be the seen-class set. We report

$$B_t = \frac{1}{|\mathcal{C}_t|} \sum_{c \in \mathcal{C}_t} r_{c,t}, \qquad \overline{B}_{\text{inc}} = \frac{1}{T} \sum_{t=1}^{T} B_t, \tag{11}$$

together with final balanced accuracy B_T. Mean incremental balanced accuracy weights stages equally, rather than pooling their examples or reporting micro accuracy.

Let τ_c be the introduction stage of class c and $\mathcal{O} = \{c : \tau_c < T\}$. Signed final forgetting is

$$\mathcal{F} = \frac{1}{|\mathcal{O}|} \sum_{c \in \mathcal{O}} \left(\max_{\tau_c \leq t < T} r_{c,t} - r_{c,T} \right). \tag{12}$$

The historical maximum excludes the final stage; negative values therefore retain final improvement and are

not clipped to zero. The primary definition includes Normal whenever it belongs to $\mathcal{O}$; an attack-only version excludes Normal from this same set. Classes introduced in the final task have no subsequent update and are not assigned a forgetting value. No rare-class support filter is applied to these Class-IL summaries: the support filter belongs only to the separate attack-family safety guard. We report per-seed values and their mean and sample standard deviation, with forgetting in percentage points. Low forgetting alone is not a ranking of useful retention: a class that was never learned well has little recall to lose. It must be read together with final and mean incremental balanced accuracy for every method. Incomplete trajectories or seed groups remain explicitly incomplete.

The completed original-AA trajectories show why detection and retention must be separated. On UNSW-NB15, mean incremental BAcc is 69.65%, final BAcc is 55.05%, and signed forgetting is 20.04±1.16 percentage points. On NSL-KDD, the corresponding values are 74.24%, 58.26%, and 11.12±2.70 points. A higher trajectory average therefore coexists with substantial old-class recall loss; the new KD and ISO variants target that unresolved endpoint rather than converting the earlier detection gain into a retention claim.

For each old attack class, the confusion matrix partitions its error into a gate miss (prediction Normal) and a wrong attack-family prediction. At the same class-specific pre-final peak used above, the recall loss equals the increase in these two error rates. The decomposition uses their common class support and common peak checkpoint; it does not sum independently selected worst stages. It separates observed routing errors, not a causal proof that weight interference alone caused forgetting, because every checkpoint also receives its own calibrated threshold.

The revised pre-formal decision rule (Section 29.8 of the work order, superseding Section 29.4) makes retention mandatory. On both UNSW-NB15 and NSL-KDD, the validation-selected version must have no significantly greater forgetting than the lowest-forgetting external baseline, significantly higher final balanced accuracy than exposure-matched Replay-BS, and no significantly lower $\alpha = 2\%$ attack detection than original AA-CIL. The external set is Replay, DER++, WACB, Freq and Replay+LA; one comparator is chosen from each complete five-seed group mean, never per seed. Tests are paired, one-sided, at $p < 0.05$. CIC-IDS-2017 is reported as available and does not replace either required dataset. Mean incremental balanced accuracy, Macro-F1 and FPR remain mandatory descriptive outcomes. Failure of any necessary condition leaves the false-alarm–forgetting trade-off unresolved and precludes a successful method-contribution claim. Incomplete groups remain incomplete. This revised experiment cannot overwrite the failed original Section 27.8 test, and nonsignificant harm is not proof of equivalence or noninferiority.

UNSW training-validation seeds 5/6 locked AA-CIL-CBF ($\lambda_G = 2$, 1 CBF epoch(s), learning-rate multiplier 0.1) as the eligible main version. This is a development selection, not a formal test result; test outcomes cannot reselect the version. AA-CIL-KD, AA-CIL-ISO, AA-CIL-NCM remain mandatory descriptive formal fallbacks, not eligible successes. Complete formal five-seed groups in the saved assessment: UNSW 5/5 versions, NSL 1/5 versions. Incomplete groups have no aggregate performance or inferential conclusion in this presentation. On UNSW-NB15, AA-CIL-ISO recorded signed forgetting of 0.018±0.032 pp alongside final balanced accuracy of 19.67±0.02%; low forgetting alone does not establish effective class-incremental learning. ISO minus KD differences were -2.29±1.03 pp for forgetting ($p_< = 0.00385$) and -18.86±1.10 pp for mean incremental balanced accuracy ($p_< = 1.37 \times 10^{-6}$), using five paired seeds and unadjusted one-sided tests. These development-ineligible fallback contrasts do not alter the validation-locked main selection. Section 29.8 fails a necessary condition; the false-alarm–forgetting trade-off remains unresolved. Nonsignificant harm is not equivalence or noninferiority. The original Section 27.8 failure and its comparison set are unchanged.

6.2 Primary calibration-set operating points

Table 10 reports all available methods at the common calibration target, including actual test FPR and completed seed counts. CIC-IDS-2017 AA-family coverage: 10/15 cells across AA-CIL ($n = 0/5$), TS-mem ($n = 5/5$), and AA-noAttMem ($n = 5/5$); Replay-BS is reported separately.. The cutoff is 2026-10-19 20:53 MYT; an unavailable cell denotes unfinished evidence, not zero performance.

On UNSW-NB15, AA-CIL obtains ADR 69.09%, Macro-F1 41.18%, and test FPR 1.92%. Relative to the strongest *external* ADR baseline, the gain is 18.67 percentage points. This comparison is descriptive with an associated paired test, distinct from the registered strongest-comparator conclusion.

High binary detection does not imply accurate attack naming: AA-CIL's UNSW-NB15 Worms recall is 63.75%, but precision is only 3.52%; Fuzzers recall is 9.67%. The appendix retains these difficult-family results rather than using ADR to conceal family-level errors.

On NSL-KDD, AA-CIL reaches ADR 62.84%, compared with 69.67% for Freq. Its Macro-F1 is 55.66%, compared with 57.03% for WACB. Its test FPR, 6.15%, is substantially different from the calibration target. The method therefore neither wins across benchmarks nor delivers the nominal low-FPR operating point on this shifted test distribution.

CIC-IDS-2017 AA-CIL is incomplete ($n = 0/5$); available cells are descriptive and do not support a complete five-seed inference. The registered seven-comparator set is not yet complete for all five paired seeds; its CIC inference remains pending. The external-only comparator set is not yet complete for all five paired seeds; its CIC inference remains pending.

Table 3: NSL: checkpoint-calibrated Class-IL performance at $\alpha = 2\%$.

Method	n	Mean inc. BAcc	Final BAcc	Forget (all old)	Forget (old att.)	Final ADR	Final MF1
Replay	5	70.12±2.82	47.05±4.52	9.73±4.30	12.53±5.85	65.39±5.30	46.83±4.93
Replay+LA	5	70.12±2.82	47.05±4.52	9.73±4.30	12.53±5.85	65.39±5.30	46.83±4.93
DER++	5	68.13±2.81	50.11±2.97	0.91±5.03	1.04±6.67	65.28±2.73	50.46±3.15
WACB	5	73.98±2.05	56.69±5.22	4.16±2.86	5.43±3.67	66.83±3.77	57.03±3.91
Freq	5	74.82±2.70	61.82±2.44	5.25±2.76	6.35±3.65	69.67±2.53	56.84±4.32
AA-CIL	5	74.24±1.29	58.26±1.85	11.12±2.70	14.75±3.70	62.84±3.46	55.66±3.36
TS-mem	5	72.65±2.03	55.62±1.58	10.53±3.63	13.73±4.66	63.19±4.66	51.44±2.16
AA-noAttMem	5	74.31±1.46	56.97±2.69	13.78±3.47	18.82±4.61	60.29±3.16	56.67±3.34
Replay-BS (post hoc)	5	75.05±1.01	59.32±2.85	11.44±2.53	15.15±3.51	62.48±4.64	57.05±3.33
AA-CIL-KD	5	76.39±0.26	60.82±0.73	0.98±0.76	1.27±1.17	71.67±0.66	61.43±2.25
FARQ (supp.)	5	74.57±2.57	58.22±4.10	4.70±5.00	5.99±6.40	67.45±2.77	58.86±5.79
FARQ-all (supp.)	5	73.21±3.72	54.47±12.14	14.21±10.57	18.86±14.08	63.08±2.48	49.57±11.97
Joint (offline)	5	74.62±0.69	58.65±2.20	3.45±0.81	4.51±0.93	66.63±1.80	59.37±2.90

Mean±sample SD across the available seeds; accuracies are percentages and forgetting is in percentage points. Mean incremental BAcc averages all seen-class stage BAcc values. Signed forgetting compares each old class's best pre-final recall with its final recall; the primary scope includes Normal. Smaller forgetting alone is not superiority: inspect final and incremental BAcc together. Groups with $n < 5$ are incomplete, descriptive only. Joint is offline; FARQ is supplementary; Replay+LA shares Replay's calibrated total τ and incurs no separate inference. Section 29.8 reports all five F variants; the main variant is fixed by development seeds 5/6, not by this test table. These post-hoc stagewise summaries do not change the registered Section 27.8 decision.

Table 4: UNSW: checkpoint-calibrated Class-IL performance at $\alpha = 2\%$.

Method	n	Mean inc. BAcc	Final BAcc	Forget (all old)	Forget (old att.)	Final ADR	Final MF1
Replay	5	52.29±0.55	25.15±0.89	5.09±1.02	5.82±1.17	38.52±3.77	26.27±0.85
Replay+LA	5	52.29±0.55	25.15±0.89	5.09±1.02	5.82±1.17	38.52±3.77	26.27±0.85
DER++	5	38.73±1.38	14.43±1.03	16.16±1.80	18.44±2.04	18.48±4.12	14.47±1.44
WACB	5	55.12±1.53	29.96±1.30	3.48±2.45	3.97±2.81	48.97±4.14	32.81±1.18
Freq	5	55.83±1.60	28.93±1.40	5.50±1.25	6.27±1.43	50.42±2.93	31.22±1.73
AA-CIL	5	69.65±0.49	55.05±1.06	20.04±1.16	22.92±1.32	69.09±0.93	41.18±0.28
TS-mem	5	48.14±3.67	24.97±7.34	9.73±5.85	11.11±6.69	24.79±14.93	23.47±6.33
AA-noAttMem	5	69.28±0.39	53.98±1.02	22.02±0.87	25.16±0.99	67.94±1.58	40.43±0.51
Replay-BS (post hoc)	5	62.16±0.24	38.01±1.19	4.87±2.44	5.54±2.78	66.14±0.74	39.99±1.57
AA-CIL-KD	5	63.75±1.11	41.80±1.93	2.31±1.07	2.62±1.20	70.53±0.50	42.08±1.93
AA-CIL-ISO	5	44.89±0.03	19.67±0.02	0.02±0.03	0.01±0.02	71.01±1.16	11.47±0.01
AA-CIL-WA	5	68.25±0.47	54.24±0.79	16.21±1.09	18.51±1.25	71.01±1.16	41.35±0.32
AA-CIL-CBF	5	68.73±0.49	54.69±0.70	15.32±0.56	17.49±0.64	71.01±1.16	40.86±0.38
AA-CIL-NCM	5	68.18±0.16	51.32±1.10	18.12±2.76	20.69±3.15	70.53±0.50	38.22±1.08
FARQ (supp.)	5	54.99±1.32	27.90±1.46	6.43±2.31	7.35±2.63	45.10±4.20	30.25±1.68
FARQ-all (supp.)	5	50.90±2.38	23.24±3.19	8.41±3.96	9.58±4.51	34.56±10.80	24.30±3.56
Joint (offline)	5	62.06±0.52	35.38±0.67	5.35±1.10	6.10±1.26	67.11±1.45	37.22±1.00

Mean±sample SD across the available seeds; accuracies are percentages and forgetting is in percentage points. Mean incremental BAcc averages all seen-class stage BAcc values. Signed forgetting compares each old class's best pre-final recall with its final recall; the primary scope includes Normal. Smaller forgetting alone is not superiority: inspect final and incremental BAcc together. Groups with $n < 5$ are incomplete, descriptive only. Joint is offline; FARQ is supplementary; Replay+LA shares Replay's calibrated total τ and incurs no separate inference. Section 29.8 reports all five F variants; the main variant is fixed by development seeds 5/6, not by this test table. These post-hoc stagewise summaries do not change the registered Section 27.8 decision.

6.3 The registered conclusion remains negative

On UNSW-NB15, the strongest registered ADR comparator is AA-noAttMem, not Freq. AA-CIL's paired mean advantage is 1.15 percentage points, with one-sided $p = 0.0748$. It does not pass the registered significance criterion. NSL-KDD also fails the superiority requirement. Even a favorable CIC-IDS-2017 result cannot then provide superiority in the required majority of datasets. The primary registered criterion and conjunction are therefore negative; remaining individual criteria retain their actual complete or incomplete states.

This result is not revised by restricting the baseline set to external methods. The external comparison answers a useful but different question: whether the complete configuration improves upon the selected standard replay alternatives. Both comparisons are shown, and neither is described as a proof of equivalence.

6.4 What the ablations identify

The UNSW-NB15 contrast between TS-mem (ADR 24.79%) and AA-noAttMem (67.94%) is consistent with a substantial benefit from greater benign refresh within the two-model design. The latter retains ordinary attack allocations, so attack-memory transfer is not required to observe this particular gain. However, the comparison also changes benign sample exposure, realized gate updates, and temporary storage. It does not by itself prove that the architecture, rather than the additional training data, causes the improvement.

The AA-CIL–AA-noAttMem contrast is the evidence for attack-memory transfer. Its UNSW-NB15 detection difference is small relative to the external-baseline gap and is not significant in the registered one-sided test. This makes memory transfer a secondary, presently weakly supported component. It does not establish zero benefit, equivalence, or dispensability on every dataset.

Table 5: CIC17: checkpoint-calibrated Class-IL performance at $\alpha = 2\%$.

Method	n	Mean inc. BAcc	Final BAcc	Forget (all old)	Forget (old att.)	Final ADR	Final MF1
Replay	5	74.30±1.20	52.32±4.55	6.99±7.30	8.38±8.76	78.89±5.63	51.52±4.02
Replay+LA	5	74.30±1.20	52.32±4.55	6.99±7.30	8.38±8.76	78.89±5.63	51.52±4.02
DER++	5	76.85±0.97	48.44±2.90	17.52±6.03	21.02±7.23	89.29±3.01	48.85±3.19
WACB	5	77.43±1.19	63.02±1.31	1.97±3.48	2.36±4.17	88.91±2.30	57.84±1.13
Freq	5	76.38±1.80	64.03±2.62	4.71±9.31	5.63±11.16	88.55±2.32	57.97±4.33
TS-mem	5	66.04±1.55	40.34±2.01	26.70±3.69	32.03±4.42	49.51±3.90	34.63±2.25
AA-noAttMem	5	93.00±0.39	87.50±0.35	9.49±0.90	11.38±1.07	83.13±1.48	63.60±0.78
Replay-BS (post hoc)	4	91.17±1.90	79.39±4.16	5.35±10.84	6.41±13.01	92.62±1.24	69.03±1.05
FARQ (supp.)	5	75.72±1.79	57.54±5.40	1.20±7.71	1.43±9.25	85.40±5.48	55.13±2.26
FARQ-all (supp.)	5	71.58±3.86	50.30±9.58	8.28±15.62	9.93±18.73	74.49±10.03	48.47±6.84
Joint (offline)	5	93.83±0.80	78.68±3.54	13.14±2.71	15.75±3.26	98.19±1.94	68.43±1.30

Mean±sample SD across the available seeds; accuracies are percentages and forgetting is in percentage points. Mean incremental BAcc averages all seen-class stage BAcc values. Signed forgetting compares each old class's best pre-final recall with its final recall; the primary scope includes Normal. Smaller forgetting alone is not superiority: inspect final and incremental BAcc together. Groups with $n < 5$ are incomplete, descriptive only. Joint is offline; FARQ is supplementary; Replay+LA shares Replay's calibrated total τ and incurs no separate inference. Section 29.8 reports all five F variants; the main variant is fixed by development seeds 5/6, not by this test table. These post-hoc stagewise summaries do not change the registered Section 27.8 decision.

Table 6: NSL: AA-CIL old-attack recall-loss decomposition at $\alpha = 2\%$.

Old attack	n	Recall loss (pp)	Δ G miss (pp)	Δ F wrong (pp)
DoS	5	14.71±3.92	13.96±4.01	0.75±0.34
Probe	5	25.06±5.05	25.40±5.60	-0.34±1.31
R2L	5	4.49±9.23	-5.77±13.47	10.27±5.49

For each seed and class, the reference is its earliest highest-recall stage before the final task. Normal-miss and wrong-attack-family rates use all true-class rows as denominator; their signed changes add to recall loss. Means add, while component SDs do not. This observed confusion-matrix decomposition does not infer F behavior on G-rejected rows.

6.5 Post-hoc exposure-matched and shift analyses

Replay-BS was requested after the initial results. It supplies a single multiclass replay model with the same refreshed benign samples, attack-only memory capacity, current attacks, and calibration policy as AA-CIL. It is the necessary control for distinguishing decomposition from the broader benign-access setting. Its evidence is reported separately and cannot retroactively rescue the registered criterion.

The complete NSL-KDD and UNSW-NB15 groups now permit this comparison. On UNSW-NB15, AA-CIL improves attack detection over Replay-BS by 2.95 percentage points in the post-hoc paired test ($p = 0.0029$; Table 12), despite matching the additional benign exposure and replay-allocation rule. This supports an incremental benefit of the decomposed configuration beyond merely providing more benign examples under this protocol. On NSL-KDD, the difference is only 0.35 points ($p = 0.4052$), and AA-CIL has higher test FPR and lower Macro-F1 than Replay-BS. Hence the evidence is dataset dependent, not a general architectural advantage. Moreover, the two-model system still has a separate family-training budget, so this is not a compute-matched causal isolation of architecture.

The completed NSL sensitivity analysis contrasts thresholds calibrated using training-domain benign holdout data with thresholds estimated from test-domain Normal data. The latter deliberately uses test information and is therefore diagnostic only: it must not replace the primary result, be called a deployment-valid evaluation, or be used to select a favorable main threshold. Test-Normal calibration brings the measured false-alarm rate to the target by construction but reduces attack detection and Macro-F1 for the evaluated gate variants (Table 14). The original discrepancy is consequently not resolved as a free improvement: threshold tightening exposes a detection cost, while the same-population calibration cannot establish out-of-sample reliability.

The operating curves in Figs. 2–4 are also post hoc. A mean curve at a common threshold is not the same estimand as averaging per-seed interpolated detection at a fixed FPR. Finite-grid points without a bracket remain unavailable; they are not extrapolated to make all methods comparable. A visually favorable curve does not replace the calibration-holdout test or its registered inference.

6.6 Cost and storage

We charge the gate and family model separately and report their sum. Selection, calibration, evaluation, and additional benign sample storage are separate quantities. A common replay capacity does not make AA-CIL compute-matched to a single-network baseline. Nor does a common maximum memory establish equal occupancy: rare old classes may exhaust their retained samples and leave slots unused.

The permanent benign pool and the extra benign training inputs of AA-CIL, AA-noAttMem and Replay-BS are outside the replay ceiling but inside the disclosed total data footprint. TS-mem instead uses its retained Normal training rows within the ceiling. Normal validation rows already counted within TS-mem's replay allocation are not counted again as additional unique calibration rows. Successful optimization time excludes loading and serialization unless explicitly stated. Local GPU sharing and heterogeneous execution devices preclude interpreting raw runtime differences as an exclusive hardware benchmark. Failed, duplicate, or superseded executions are not scientific replicates and are accounted for separately from selected

Table 7: UNSW: AA-CIL old-attack recall-loss decomposition at $\alpha = 2\%$.

Old attack	n	Recall loss (pp)	Δ G miss (pp)	Δ F wrong (pp)
Generic	5	14.34±0.84	0.89±0.97	13.45±1.49
Exploits	5	43.78±3.40	4.31±1.91	39.46±5.06
Fuzzers	5	21.64±1.42	15.61±1.27	6.03±1.10
DoS	5	28.83±4.10	3.92±4.01	24.91±2.80
Reconnaissance	5	24.57±9.16	6.19±2.98	18.38±7.19
Analysis	5	25.56±8.35	26.67±7.93	-1.11±1.11
Backdoor	5	1.71±8.17	-8.29±6.88	10.00±3.64

For each seed and class, the reference is its earliest highest-recall stage before the final task. Normal-miss and wrong-attack-family rates use all true-class rows as denominator; their signed changes add to recall loss. Means add, while component SDs do not. This observed confusion-matrix decomposition does not infer F behavior on G-rejected rows.

Table 8: Locked Section 29.8 development selection; no test performance is shown here.

Version	λ_G	CBF epochs	CBF LR multiplier	Development role
AA-CIL-KD	0.5	–	–	ineligible fallback
AA-CIL-ISO	2	–	–	ineligible fallback
AA-CIL-WA	2	–	–	eligible alternative
AA-CIL-CBF	2	1	0.1	eligible main
AA-CIL-NCM	0.5	–	–	ineligible fallback

Selection uses UNSW training-validation seeds 5/6 only. DER weights are fixed at one. Ineligible versions are still reported on the five formal seeds, without converting fallback selection into eligibility.

successful-cell costs.

7 Discussion and Limitations

7.1 A useful result without a universal winner

The strongest supported observation is dataset dependent: independently calibrated benign-refresh models substantially improve the selected external-baseline comparison on UNSW-NB15, whereas NSL-KDD does not improve the relevant registered endpoints. The evidence does not support a blanket superiority claim. In particular, favorable binary ADR can coexist with poor family discrimination: detected attacks assigned to the wrong family count as detected in ADR but not as correct in the multiclass metrics.

The work also separates a design hypothesis from its identification. TS-mem shows the outcome of restricting benign refresh within a two-model architecture. The completed Replay-BS comparison strengthens the UNSW-NB15 evidence beyond an explanation based solely on additional benign exposure. Its NSL-KDD result does not support the same benefit, and its single network still receives less total model training than the gate-plus-family configuration. The supported claim is therefore an exposure-matched, dataset-dependent configuration benefit, not a compute-isolated causal estimate of decomposition.

The TS-mem comparison is incomplete (AA-CIL $n = 0/5$, TS-mem $n = 5/5$); no complete-group inference is made. The AA-noAttMem comparison is incomplete (AA-CIL $n = 0/5$, AA-noAttMem $n = 5/5$); no complete-group inference is made. The post-hoc Replay-BS comparison is incomplete (AA-CIL $n = 0/5$, Replay-BS (post hoc) $n = 4/5$); no complete-group inference is made. These contrasts do not establish causal component effects or equivalence; Replay-BS matches the specified benign exposure and replay allocation, not the combined G+F compute budget. Regardless of this additional comparison, the failed original superiority requirement is unchanged. A CIC-only gain would not establish a universal advantage, and a post-hoc curve or Replay-BS contrast would remain distinct from that registered decision.

7.2 Calibration and deployment assumptions

Clean labeled benign data are a substantial resource. They may be contaminated, costly to curate, or distributionally unrepresentative of future traffic. Refresh from a fixed training pool is only a benchmark surrogate for continuous benign availability. It does not validate resilience to poisoned benign pools, temporal drift, network migration, or delayed labels. NSL-KDD's calibration-to-test shift illustrates why a nominal calibration target must not be equated with realized deployment FPR.

7.3 Scope of statistical and architectural claims

The benchmark uses few paired seeds, fixed task orders, a finite known label universe, prepared tabular features, and a shared training implementation. These choices support controlled within-protocol comparisons but do not cover arbitrary task order, unseen network environments, or open-world label discovery. A matched schedule is not matched total computation or exposure. CSE-CIC-IDS2018 was not run for this study. Joint remains an offline reference whose available information differs from incremental methods.

The targeted literature review does not establish first-of-its-kind status. In particular, external benign data and attack-only old memory already appear in neighboring adaptation work. Our restricted-refresh ablation is not an implementation of that literature. Full-text unavailability for Wang and Cao further limits its precise differentiation. A novel substantive contribution would require verified distinction and an iden-

Table 9: Formal Section 29.8 results at stagewise Normal-holdout calibration target $\alpha = 2\%$.

Data	Version	n	Mean inc. BAcc	Final BAcc	Forget (pp)	ADR	MF1	FPR
UNSW	AA-CIL-KD	5	63.75±1.11	41.80±1.93	2.31±1.07	70.53±0.50	42.08±1.93	2.10±0.18
UNSW	AA-CIL-ISO	5	44.89±0.03	19.67±0.02	0.02±0.03	71.01±1.16	11.47±0.01	2.04±0.08
UNSW	AA-CIL-WA	5	68.25±0.47	54.24±0.79	16.21±1.09	71.01±1.16	41.35±0.32	2.04±0.08
UNSW	AA-CIL-CBF	5	68.73±0.49	54.69±0.70	15.32±0.56	71.01±1.16	40.86±0.38	2.04±0.08
UNSW	AA-CIL-NCM	5	68.18±0.16	51.32±1.10	18.12±2.76	70.53±0.50	38.22±1.08	2.10±0.18
NSL	AA-CIL-KD	5	76.39±0.26	60.82±0.73	0.98±0.76	71.67±0.66	61.43±2.25	7.94±0.45
NSL	AA-CIL-ISO	0	–	–	–	–	–	–
NSL	AA-CIL-WA	0	–	–	–	–	–	–
NSL	AA-CIL-CBF	0	–	–	–	–	–	–
NSL	AA-CIL-NCM	0	–	–	–	–	–	–

Only complete seeds 1/2/3/4/42 receive means and sample SD; incomplete groups show n and dashes. All outcomes come from formal test trajectories, never development selection metrics. Signed forgetting includes old Normal; rates/accuracies are percentages. Eligibility is a development property, not formal success.




Figure 2: NSL-KDD operating curves (post hoc). Threshold-sweep summaries are descriptive, not calibration-set operating points or the registered test. Missing methods or seeds are identified in the generated panel.

tifiable benefit beyond combining a gate, replay, and threshold calibration; neither architecture naming nor an external-baseline gain alone meets that standard.

7.4 Relation to the broader research questions

This manuscript addresses predictive retention, class-wise safety, and cost under class-incremental updates. It does not measure silent explanation drift across checkpoints, and it does not evaluate non-suppressive explanation governance. Those explanatory and governance questions remain unanswered by these experiments. Predictive gains alone cannot establish stable explanations or the safety of an explanation-governance mechanism.

8 Conclusion

AA-CIL makes an asymmetric data-access assumption explicit and combines repeated benign refresh, an independently calibrated binary gate, and attack-only family learning. Its UNSW-NB15 results motivate further examination of benign access, but the registered strongest-comparator superiority requirement fails and NSL-KDD exposes both limited detection and calibration shift. The UNSW-NB15 attack-memory contrast does not establish a significant incremental benefit. Post-hoc exposure matching supports a decomposed-configuration gain on UNSW-NB15, not NSL-KDD, while additional total computation remains a limitation. CIC AA-family coverage remains incomplete, but the original Section 27.8 overall decision remains FAIL. The separately reported external-only and post-hoc comparisons do not replace that decision, prove novelty or causal benefit, or constitute compute-matched evidence. We therefore present AA-CIL as a reproducible, qualified empirical study rather than a universally superior detector or established novel solution.

Reproducibility and evidence availability

Tables and numerical prose are generated from repository result files rather than manually transcribed. The companion code retains training configurations, seeds, taskwise confusion matrices, sample-access policies, and separate gate/family costs. Model payloads and datasets are not embedded in the manuscript. The evidence cutoff and actual group sizes are reported; unfinished results are not inferred from a running process or an anticipated completion time.

Table 10: Final-task test performance at a benign-holdout calibration target of $\alpha = 2\%$. Rates are percentages; mean ± sample SD. Actual test FPR is not fixed at 2%.

Data	Method	n	Test FPR	Attack detection	Macro-F1	BAcc	Attack guard
NSL	Replay	5	4.08±2.16	65.39±5.30	46.83±4.93	47.05±4.52	34.83±5.78
NSL	DER++	5	2.51±0.45	65.28±2.73	50.46±3.15	50.11±2.97	38.27±3.77
NSL	WACB	5	3.62±0.87	66.83±3.77	57.03±3.91	56.69±5.22	46.77±6.49
NSL	Freq	5	4.93±2.42	69.67±2.53	56.84±4.32	61.82±2.44	53.50±3.50
NSL	Replay+LA	5	4.08±2.16	65.39±5.30	46.83±4.93	47.05±4.52	34.83±5.78
NSL	TS-mem	5	4.41±2.12	63.19±4.66	51.44±2.16	55.62±1.58	45.62±1.92
NSL	AA-noAttMem	5	4.32±1.82	60.29±3.16	56.67±3.34	56.97±2.69	47.29±3.05
NSL	AA-CIL	5	6.15±1.79	62.84±3.46	55.66±3.36	58.26±1.85	49.36±1.98
NSL	Replay-BS (post hoc)	5	3.65±2.16	62.48±4.64	57.05±3.33	59.32±2.85	50.07±3.92
NSL	Joint (offline)	5	6.79±1.00	66.63±1.80	59.37±2.90	58.65±2.20	50.01±2.75
UNSW	Replay	5	1.78±0.20	38.52±3.77	26.27±0.85	25.15±0.89	17.04±0.98
UNSW	DER++	5	1.98±0.27	18.48±4.12	14.47±1.44	14.43±1.03	5.15±1.16
UNSW	WACB	5	1.93±0.24	48.97±4.14	32.81±1.18	29.96±1.30	22.39±1.46
UNSW	Freq	5	2.01±0.26	50.42±2.93	31.22±1.73	28.93±1.40	21.25±1.54
UNSW	Replay+LA	5	1.78±0.20	38.52±3.77	26.27±0.85	25.15±0.89	17.04±0.98
UNSW	TS-mem	5	1.98±0.12	24.79±14.93	23.47±6.33	24.97±7.34	16.85±8.15
UNSW	AA-noAttMem	5	1.94±0.19	67.94±1.58	40.43±0.51	53.98±1.02	49.09±1.12
UNSW	AA-CIL	5	1.92±0.15	69.09±0.93	41.18±0.28	55.05±1.06	50.27±1.18
UNSW	Replay-BS (post hoc)	5	2.13±0.17	66.14±0.74	39.99±1.57	38.01±1.19	31.36±1.31
UNSW	Joint (offline)	5	1.93±0.15	67.11±1.45	37.22±1.00	35.38±0.67	28.42±0.76
CIC17	Replay	5	1.95±0.06	78.89±5.63	51.52±4.02	52.32±4.55	47.87±6.55
CIC17	DER++	5	1.92±0.07	89.29±3.01	48.85±3.19	48.44±2.90	47.68±3.63
CIC17	WACB	5	1.92±0.06	88.91±2.30	57.84±1.13	63.02±1.31	59.90±0.67
CIC17	Freq	5	1.93±0.02	88.55±2.32	57.97±4.33	64.03±2.62	61.81±5.97
CIC17	Replay+LA	5	1.95±0.06	78.89±5.63	51.52±4.02	52.32±4.55	47.87±6.55
CIC17	TS-mem	5	1.89±0.06	49.51±3.90	34.63±2.25	40.34±2.01	26.88±2.99
CIC17	AA-noAttMem	5	1.94±0.03	83.13±1.48	63.60±0.78	87.50±0.35	89.21±0.46
CIC17	AA-CIL	0	–	–	–	–	–
CIC17	Replay-BS (post hoc)	4	1.94±0.03	92.62±1.24	69.03±1.05	79.39±4.16	82.56±5.86
CIC17	Joint (offline)	5	1.93±0.04	98.19±1.94	68.43±1.30	78.68±3.54	78.56±3.58

Replay+LA and Replay share the same calibrated total logit adjustment and weights. Joint has offline old-training access. Replay-BS is post hoc. A dash means unavailable; $n < 5$ is descriptive only. The guard alone excludes attack classes with test support below 20.

Exposure confound: AA-CIL and AA-noAttMem refresh up to 50,000 benign training rows per task outside replay memory. After Normal's introduction, ordinary replay controls use quota-limited Normal training memory. Their ADR differences therefore cannot be attributed wholly to the gate/family structure. Post-hoc Replay-BS matches the added benign exposure and attack allocation, but not the two-model total computation.

Table 11: Original registered superiority test and separately identified external-only comparison. The latter does not replace the former.

Data	Comparison set	Fixed mean winner	Δ ADR (pp)	$p_>$	d_z	Dataset test
NSL	registered	Freq	-6.829±3.350	0.99482	-2.039	Fail
NSL	external	Freq	-6.829±3.350	0.99482	-2.039	Fail
UNSW	registered	AA-noAttMem	1.154±1.450	0.07480	0.796	Fail
UNSW	external	Freq	18.671±3.277	0.00011	5.697	Pass
CIC17	registered	Pending	–	–	–	Pending
CIC17	external	Pending	–	–	–	Pending

Original Section 27.8 criteria 1–5: 1: FAIL, 2: PENDING, 3: PENDING, 4: PENDING, 5: PENDING. Overall registered decision: FAIL, because NSL and UNSW cannot contribute the required two significant wins. The registered set includes TS-mem and AA-noAttMem. No detected harm is not equivalence/noninferiority.

A Retention-extension paired comparisons

B Additional calibration targets

These results reuse the permanently held-out calibration source. They are sensitivity results, not a search over test thresholds. Actual test FPR accompanies each target, and an undefined per-class quantity remains undefined.

C Difficult-family performance

These selected families illustrate errors that binary attack detection alone cannot reveal. They are descriptive diagnostics, not a replacement endpoint or a selection rule for the main result; incomplete groups retain their actual seed counts.

D Registered safety contrasts and timing components

The timing components retain the measurement boundaries of their source records. In particular, a CPU analysis attempt and its nested inference or threshold-search components must not be summed twice.

Table 12: Ablations at $\alpha = 2\%$. Paired changes are AA-CIL minus the named ablation. Tests involving Replay-BS are post hoc; small groups do not amend registered decisions.

Data	Method	n	Detection (%)	MF1 (%)	Δ detection (pp)	$p_>$
NSL	AA-CIL	5	62.84±3.46	55.66±3.36	–	–
NSL	TS-mem	5	63.19±4.66	51.44±2.16	-0.35±4.01	0.5733
NSL	AA-noAttMem	5	60.29±3.16	56.67±3.34	2.54±3.42	0.0860
NSL	Replay-BS (post hoc)	5	62.48±4.64	57.05±3.33	0.35±3.09	0.4052
UNSW	AA-CIL	5	69.09±0.93	41.18±0.28	–	–
UNSW	TS-mem	5	24.79±14.93	23.47±6.33	44.30±15.74	0.0016
UNSW	AA-noAttMem	5	67.94±1.58	40.43±0.51	1.15±1.45	0.0748
UNSW	Replay-BS (post hoc)	5	66.14±0.74	39.99±1.57	2.95±1.23	0.0029
CIC17	AA-CIL	0	–	–	–	–
CIC17	TS-mem	5	49.51±3.90	34.63±2.25	–	–
CIC17	AA-noAttMem	5	83.13±1.48	63.60±0.78	–	–
CIC17	Replay-BS (post hoc)	4	92.62±1.24	69.03±1.05	–	–




Figure 3: UNSW-NB15 operating curves (post hoc). Threshold-sweep summaries are descriptive, not calibration-set operating points or the registered test. Missing methods or seeds are identified in the generated panel.

Table 13: Post-hoc Replay-BS: single multiclass model with the AA-CIL benign exposure and attack replay allocation. This control was added after the original primary result.

Data	n	Test FPR	Detection	MF1
NSL	5	3.65±2.16	62.48±4.64	57.05±3.33
UNSW	5	2.13±0.17	66.14±0.74	39.99±1.57
CIC17	4	1.94±0.03	92.62±1.24	69.03±1.05

Table 14: Post-hoc NSL-KDD calibration-distribution sensitivity at $\alpha = 2\%$. Test metrics are mean ± sample standard deviation in percent.

Method	Threshold calibration pool	n	Test FPR	ADR	MF1
AA-CIL	TRAIN Normal holdout	5	6.15±1.79	62.84±3.46	55.66±3.36
AA-CIL	TEST Normal (post hoc)	5	2.00±0.00	50.95±4.16	50.26±6.71
TS-mem	TRAIN Normal holdout	5	4.41±2.12	63.19±4.66	51.44±2.16
TS-mem	TEST Normal (post hoc)	5	2.00±0.00	53.55±3.31	47.81±1.00
AA-noAttMem	TRAIN Normal holdout	5	4.32±1.82	60.29±3.16	56.67±3.34
AA-noAttMem	TEST Normal (post hoc)	5	2.00±0.00	50.48±2.42	50.85±3.00

Each method uses the same paired seeds in both rows. TEST-Normal thresholds use test Normal labels and are evaluated on the same test population: this is a test-label-conditioned, non-deployable sensitivity analysis, not an independent evaluation. It does not change the registered Section 27.8 decisions. Incomplete seed groups remain descriptive.




Figure 4: CIC-IDS-2017 operating curves (post hoc). Threshold-sweep summaries are descriptive, not calibration-set operating points or the registered test. Missing methods or seeds are identified in the generated panel.

Table 15: Descriptive final-task differences from the offline Joint reference at $\alpha = 2\%$. Values are AA-CIL minus Joint in percentage points; mean ± sample SD across paired completed seeds.

Dataset	Paired n	Δ FPR	Δ detection	Δ MF1
NSL	5	-0.641±1.101	-3.795±4.125	-3.706±5.262
UNSW	5	-0.006±0.118	1.981±1.719	3.959±0.990
CIC17	0	–	–	–

Joint uses offline old-training access and is neither a matched deployment baseline nor a guaranteed empirical upper bound. These gaps have no success threshold.

Table 16: Per-seed total training seconds across tasks and final memory occupancy. G and F are separately trained models; single-classifier methods have no G/F split. Timing excludes data loading/saving and is not an exclusive-GPU benchmark.

Data	Method	n	G (s)	F (s)	Total (s)	Used rows	G/BS benign MiB
NSL	Replay	5	–	–	31.0±0.4	852±0	–
NSL	DER++	5	–	–	70.0±1.0	986±0	–
NSL	WACB	5	–	–	30.4±0.2	927±0	–
NSL	Freq	5	–	–	31.3±1.0	784±0	–
NSL	AA-CIL	5	35.2±1.4	32.0±1.4	67.1±2.7	802±0	22.51±0.00
NSL	TS-mem	5	31.7±1.0	31.3±1.3	63.0±2.0	852±0	0.08±0.00
NSL	AA-noAttMem	5	34.7±0.8	30.6±1.1	65.3±1.8	652±0	22.51±0.00
NSL	Replay-BS (post hoc)	5	–	–	31.5±3.0	802±0	22.51±0.00
NSL	Joint (offline)	5	–	–	45.7±0.8	86±0	–
UNSW	Replay	5	–	–	34.7±0.4	1927±0	–
UNSW	DER++	5	–	–	80.0±1.6	1993±0	–
UNSW	WACB	5	–	–	34.2±1.1	2000±0	–
UNSW	Freq	5	–	–	33.6±0.7	1589±0	–
UNSW	AA-CIL	5	41.0±1.1	37.8±1.0	78.8±1.9	1905±0	13.35±0.00
UNSW	TS-mem	5	39.5±1.1	39.5±1.3	78.9±2.2	1927±0	0.05±0.00
UNSW	AA-noAttMem	5	40.5±0.6	37.9±0.4	78.4±0.9	1727±0	13.35±0.00
UNSW	Replay-BS (post hoc)	5	–	–	40.4±1.4	1905±0	13.35±0.00
UNSW	Joint (offline)	5	–	–	52.5±0.6	193±0	–
CIC17	Replay	5	–	–	219.8±6.0	1430±0	–
CIC17	DER++	5	–	–	553.9±13.2	1585±0	–
CIC17	WACB	5	–	–	223.0±3.8	1516±0	–
CIC17	Freq	5	–	–	221.2±3.5	1452±0	–
CIC17	TS-mem	5	54.0±4.2	53.3±3.5	107.4±7.7	1430±0	0.05±0.00
CIC17	AA-noAttMem	5	70.9±2.8	53.0±1.9	123.9±4.3	1230±0	15.07±0.00
CIC17	Replay-BS (post hoc)	4	–	–	69.4±4.2	1402±0	15.07±0.00
CIC17	Joint (offline)	5	–	–	899.9±21.2	145±0	–

G/BS benign MiB reports final-task benign input feature-plus-index array bytes, not additional persistent storage. AA-CIL, AA-noAttMem and the single-model Replay-BS use up to 50,000 refreshed benign inputs outside M. TS-mem uses its retained training portion (normally 180 of 200 Normal slots) inside M; these bytes must not be added again to replay storage. Missing baseline byte records are shown as –, not zero. Dense-label materialization, permanent calibration features/indices, model weights and other transient copies are separate and excluded from this column; see the setup table. Joint is not a matched compute/storage baseline.

Table 17: Completed Section 29.8 necessary comparisons for the validation-selected main version.

Data	Criterion	Reference	n	Δ (pp)	One-sided p	Decision
UNSW	1	WACB	5	11.84±2.91	0.00041	fail
UNSW	2	Replay-BS (post hoc)	5	16.67±1.26	3.868×10^{-6}	pass
UNSW	3	AA-CIL	5	1.92±1.29	0.98539	pass

Candidate minus reference; exact five paired formal seeds. 1: all-old forgetting, $p_{>} < .05$ means harm/failure against the lowest-forgetting external baseline. 2: final BAcc, $p_{>} < .05$ is required against Replay-BS. 3: ADR, $p_{<} < .05$ means harm/failure against original AA-CIL. Only useful complete comparisons are shown; absent comparisons remain pending and are not passed. Both UNSW and NSL are required. No detected harm is not equivalence. Unadjusted tests.

Table 18: Completed descriptive AA-CIL-ISO minus AA-CIL-KD comparisons.

Data	Metric	n	Δ (pp)	$p_{<}$	$p_{>}$	p_{2s}
UNSW	Forget (all)	5	-2.29±1.03	0.00385	0.99615	0.00770
UNSW	Mean inc. BAcc	5	-18.86±1.10	1.365×10^{-6}	$1 - 1.365 \times 10^{-6}$	2.731×10^{-6}

Exact five paired formal seeds; mean±sample SD of differences in percentage points. These unadjusted comparisons neither select the main version nor add a success requirement. Undefined tests remain –; no seed is discarded. Prior Sections 27.8 and 29.4 are unchanged.

Table 19: Additional calibration targets: NSL-KDD. Rates in percent; mean ± sample SD.

Method	α	n	Test FPR	Detection	MF1
Replay	1	5	2.60±1.82	56.54±8.96	36.14±8.07
Replay	5	5	5.92±2.76	76.73±3.63	59.43±3.60
DER++	1	5	1.45±0.35	58.01±6.83	42.04±7.13
DER++	5	5	4.44±0.74	73.86±3.16	60.62±2.98
WACB	1	5	2.74±0.25	61.74±4.42	48.34±5.05
WACB	5	5	5.31±2.02	75.34±4.53	57.78±1.61
Freq	1	5	4.54±2.44	66.24±3.69	57.79±3.89
Freq	5	5	6.34±2.74	75.94±4.01	55.34±2.40
Replay+LA	1	5	2.60±1.82	56.54±8.96	36.14±8.07
Replay+LA	5	5	5.92±2.76	76.73±3.63	59.43±3.60
TS-mem	1	5	2.32±1.85	51.03±6.90	45.92±4.77
TS-mem	5	5	6.10±2.69	73.74±4.61	55.52±2.29
AA-noAttMem	1	5	3.59±1.57	57.20±1.49	56.68±3.42
AA-noAttMem	5	5	6.18±2.36	67.14±2.65	56.35±2.93
AA-CIL	1	5	4.89±1.91	58.93±2.19	53.54±2.62
AA-CIL	5	5	7.14±1.75	67.83±3.44	57.44±1.81
Replay-BS (post hoc)	1	5	3.16±1.58	59.01±4.04	58.43±2.41
Replay-BS (post hoc)	5	5	4.36±2.25	66.84±4.27	55.84±2.69
Joint (offline)	1	5	6.30±1.23	64.23±1.29	57.26±2.41
Joint (offline)	5	5	7.61±0.85	71.12±2.70	57.37±1.03

Table 20: Additional calibration targets: UNSW-NB15. Rates in percent; mean ± sample SD.

Method	α	n	Test FPR	Detection	MF1
Replay	1	5	0.86±0.18	28.97±4.87	23.40±0.90
Replay	5	5	4.80±0.19	56.73±2.53	32.85±1.80
DER++	1	5	0.99±0.14	9.69±5.65	11.23±2.31
DER++	5	5	4.87±0.42	40.57±6.65	26.89±5.22
WACB	1	5	0.95±0.05	39.02±5.88	27.80±2.02
WACB	5	5	4.90±0.35	65.89±1.88	42.17±0.72
Freq	1	5	0.98±0.17	41.24±3.41	26.95±2.00
Freq	5	5	5.00±0.33	65.64±1.99	41.21±1.82
Replay+LA	1	5	0.86±0.18	28.97±4.87	23.40±0.90
Replay+LA	5	5	4.80±0.19	56.73±2.53	32.85±1.80
TS-mem	1	5	0.96±0.09	11.78±10.64	17.15±6.58
TS-mem	5	5	5.22±0.35	55.95±5.94	34.85±1.90
AA-noAttMem	1	5	1.02±0.12	61.27±3.58	39.15±0.80
AA-noAttMem	5	5	5.07±0.30	76.24±0.75	40.96±0.34
AA-CIL	1	5	1.04±0.09	63.51±1.40	40.22±0.39
AA-CIL	5	5	5.05±0.17	76.83±0.62	41.67±0.50
Replay-BS (post hoc)	1	5	1.08±0.12	59.65±0.93	36.02±1.56
Replay-BS (post hoc)	5	5	5.13±0.29	75.85±1.11	47.54±1.61
Joint (offline)	1	5	1.00±0.10	61.09±1.83	33.36±0.46
Joint (offline)	5	5	5.08±0.33	77.39±1.51	41.60±0.74

Table 21: Additional calibration targets: CIC-IDS-2017. Rates in percent; mean ± sample SD.

Method	α	n	Test FPR	Detection	MF1
Replay	1	5	0.98±0.04	67.05±8.32	44.49±6.18
Replay	5	5	4.87±0.06	94.85±1.90	57.05±1.92
DER++	1	5	0.96±0.03	72.99±7.31	42.92±2.54
DER++	5	5	4.86±0.03	98.28±0.27	62.87±0.65
WACB	1	5	0.95±0.04	79.18±2.75	50.23±4.04
WACB	5	5	4.85±0.02	97.21±0.60	61.05±0.98
Freq	1	5	0.97±0.04	81.16±2.48	50.00±4.07
Freq	5	5	4.83±0.03	96.46±0.76	59.82±1.49
Replay+LA	1	5	0.98±0.04	67.05±8.32	44.49±6.18
Replay+LA	5	5	4.87±0.06	94.85±1.90	57.05±1.92
TS-mem	1	5	0.94±0.01	40.22±6.08	30.28±1.91
TS-mem	5	5	5.07±0.45	75.51±6.27	51.01±3.59
AA-noAttMem	1	5	0.98±0.01	78.32±1.40	64.10±1.21
AA-noAttMem	5	5	4.88±0.03	94.57±2.17	62.32±1.02
Replay-BS (post hoc)	1	4	0.95±0.03	87.25±1.74	59.51±6.41
Replay-BS (post hoc)	5	4	4.86±0.03	96.50±1.67	62.32±1.35
Joint (offline)	1	5	0.94±0.05	94.24±2.98	63.48±5.19
Joint (offline)	5	5	4.85±0.02	99.87±0.12	63.96±1.39

Table 22: Selected low-support or weak-family results at $\alpha = 2\%$, to expose failure modes hidden by binary detection. All classes remain in Macro-F1 and BAcc; only the attack guard excludes support below 20.

Data	Method	Class	n	Support	n_P	Precision	Recall	F1
NSL	AA-CIL	R2L	5	2885	5	79.21±20.34	19.34±5.56	30.98±8.50
NSL	AA-CIL	U2R	5	67	5	14.36±15.83	46.27±2.36	19.07±14.54
NSL	TS-mem	R2L	5	2885	5	49.71±22.71	9.74±4.42	16.03±6.95
NSL	TS-mem	U2R	5	67	5	6.68±2.86	40.30±8.31	11.24±4.03
NSL	AA-noAttMem	R2L	5	2885	5	79.36±13.06	15.45±4.49	25.71±6.83
NSL	AA-noAttMem	U2R	5	67	5	26.25±18.85	43.28±6.76	29.57±17.65
NSL	Replay-BS (post hoc)	R2L	5	2885	5	95.22±2.37	13.72±4.07	23.82±6.15
NSL	Replay-BS (post hoc)	U2R	5	67	5	25.86±22.55	47.76±8.24	27.30±16.01
UNSW	AA-CIL	Fuzzers	5	3750	5	69.58±4.05	9.67±1.14	16.94±1.67
UNSW	AA-CIL	Worms	5	32	5	3.52±0.45	63.75±6.09	6.68±0.83
UNSW	TS-mem	Fuzzers	5	3750	5	47.54±14.46	3.39±2.15	6.28±3.88
UNSW	TS-mem	Worms	5	32	5	7.62±3.64	21.88±15.78	9.00±1.30
UNSW	AA-noAttMem	Fuzzers	5	3750	5	67.67±4.11	9.11±0.37	16.06±0.67
UNSW	AA-noAttMem	Worms	5	32	5	3.73±0.57	64.38±8.44	7.06±1.06
UNSW	Replay-BS (post hoc)	Fuzzers	5	3750	5	68.07±5.79	12.20±3.50	20.45±4.99
UNSW	Replay-BS (post hoc)	Worms	5	32	1	100.00	0.62±1.40	1.21±2.71
CIC17	TS-mem	Botnet	5	370	5	0.72±0.29	5.73±2.00	1.25±0.48
CIC17	TS-mem	Infiltration	5	6	5	0.22±0.08	63.33±7.45	0.44±0.15
CIC17	AA-noAttMem	Botnet	5	370	5	6.50±1.01	96.05±2.38	12.15±1.74
CIC17	AA-noAttMem	Infiltration	5	6	5	3.36±2.00	66.67±0.00	6.31±3.53
CIC17	Replay-BS (post hoc)	Botnet	4	370	4	30.35±7.48	60.68±0.84	40.03±6.60
CIC17	Replay-BS (post hoc)	Infiltration	4	6	4	9.21±6.83	41.67±9.62	14.17±9.42

Precision uses defined seeds only; n_P is defined_n and n is the full completed seed count. Original null precision values remain null in the generated JSON. With no defined value the mean is –; with fewer than two the sample SD is undefined. No seed is removed from other defined endpoints. Complete per-class confusion matrices accompany the saved result JSON.

Table 23: Remaining registered contrasts. Differences are AA-CIL minus the named comparator. The harm tests use the less-than alternative; the CIC gate-refresh ablation uses the greater-than alternative.

Data	Endpoint	Comparator	Δ (pp)	p	Outcome
NSL	MF1 vs strongest	WACB	-1.365±5.922	0.31675	No detected harm
NSL	Guard vs Replay	Replay	14.534±7.440	0.99401	No detected harm
UNSW	MF1 vs strongest	AA-noAttMem	0.746±0.638	0.97037	No detected harm
UNSW	Guard vs Replay	Replay	33.232±0.851	1.00000	No detected harm
CIC17	MF1 vs strongest	Pending	–	–	Pending
CIC17	Guard vs Replay	Replay	–	–	Pending
CIC17	MF1 gate-refresh ablation	TS-mem	–	–	PENDING

Only complete five-seed groups determine these outcomes. No detected harm does not establish equivalence or noninferiority. Criterion 5 is descriptive completion of Joint-gap and cost reporting, not superiority over Joint.

Table 24: Per-seed recorded overhead across tasks (seconds, mean ± sample standard deviation). Separate post-training CPU analyses are shown without adding their nested subcomponents.

Data	Method	n	Selection	In-run calib.	In-run eval.	CPU curves	CPU ext. calib.
NSL	Replay	5	0.022±0.013	–	0.113±0.011	0.112±0.014	0.132±0.008
NSL	DER++	5	0.024±0.002	–	0.068±0.005	0.136±0.011	0.135±0.008
NSL	WACB	5	0.016±0.001	–	0.058±0.004	0.119±0.010	0.143±0.007
NSL	Freq	5	0.017±0.001	–	0.064±0.006	0.128±0.007	0.146±0.005
NSL	AA-CIL	5	0.082±0.003	0.025±0.010	0.081±0.013	0.058±0.004	–
NSL	TS-mem	5	0.027±0.001	0.020±0.003	0.079±0.006	0.063±0.017	–
NSL	AA-noAttMem	5	0.081±0.001	0.020±0.002	0.080±0.002	0.058±0.005	–
NSL	Replay-BS (post hoc)	5	0.083±0.004	0.325±0.016	0.058±0.004	0.110±0.028	–
NSL	Joint (offline)	5	0.012±0.001	–	0.059±0.003	0.149±0.019	0.154±0.007
UNSW	Replay	5	0.029±0.002	–	0.172±0.004	0.158±0.018	0.217±0.020
UNSW	DER++	5	0.036±0.003	–	0.085±0.008	0.197±0.017	0.236±0.022
UNSW	WACB	5	0.029±0.002	–	0.085±0.005	0.196±0.010	0.210±0.016
UNSW	Freq	5	0.027±0.001	–	0.080±0.004	0.184±0.009	0.197±0.015
UNSW	AA-CIL	5	0.074±0.006	0.022±0.001	0.118±0.007	0.061±0.004	–
UNSW	TS-mem	5	0.024±0.003	0.027±0.006	0.124±0.006	0.066±0.014	–
UNSW	AA-noAttMem	5	0.077±0.009	0.023±0.002	0.117±0.008	0.072±0.027	–
UNSW	Replay-BS (post hoc)	5	0.070±0.005	0.540±0.040	0.100±0.008	0.190±0.032	–
UNSW	Joint (offline)	5	0.022±0.002	–	0.087±0.003	0.228±0.006	0.213±0.019
CIC17	Replay	5	0.151±0.012	–	2.233±0.063	3.239±0.269	3.038±0.153
CIC17	DER++	5	0.187±0.021	–	1.246±0.099	3.674±0.131	3.257±0.176
CIC17	WACB	5	0.147±0.010	–	1.203±0.093	3.470±0.180	3.135±0.094
CIC17	Freq	5	0.149±0.006	–	1.204±0.068	3.623±0.061	3.170±0.173
CIC17	TS-mem	5	0.248±0.027	0.346±0.034	1.648±0.155	1.022±0.076	–
CIC17	AA-noAttMem	5	0.286±0.022	0.324±0.020	1.649±0.096	1.169±0.099	–
CIC17	Replay-BS (post hoc)	4	0.268±0.018	5.444±0.280	1.579±0.079	2.274±0.032	–
CIC17	Joint (offline)	5	0.032±0.001	–	1.198±0.023	3.672±0.124	3.216±0.149

Selection, in-run calibration and in-run evaluation use the recorded buffer-selection, calibration and evaluation totals respectively. A missing key is –, never an assumed zero. AA-family and Replay-BS CPU curves use the source-matched recorded cell-total seconds from the independent post-hoc curve ledger when available; missing or mismatched cell records remain –. For older baselines the separate CPU curve-analysis and extended-calibration elapsed totals are not embedded in the in-run columns; nested holdout/search/inference sub-timings must not be added again. Shared resume/render-attempt overhead remains in the independent curve ledger and is excluded here. These columns are not a single end-to-end walltime total and do not duplicate Replay+LA, which shares Replay weights and calibration.

References

[1] Suresh Kumar Amalapuram, Akash Tadwai, Reethu Vinta, et al. On handling class imbalance in continual learning based network intrusion detection systems. In *International Conference on AI-ML Systems*, 2021. doi: 10.1145/3486001.3486231. URL https://newslab.iith.ac.in/publications/on-handling-class-imbalance-in-continual-learning-based-network-intrusion-detection-systems/.

[2] Suresh Kumar Amalapuram, Bheemarjuna Reddy Tamma, and Sumohana S. Channappayya. Augmented memory replay-based continual learning approaches for network intrusion detection. In *Advances in Neural Information Processing Systems*, 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/3755a02b1035fbadd5f93a022170e46f-Paper-Conference.pdf.

[3] Xinchen Zhang, Running Zhao, Zhihan Jiang, Handi Chen, Yulong Ding, Edith C. H. Ngai, and Shuang-Hua Yang. Continual learning with strategic selection and forgetting for network intrusion detection. In *IEEE INFOCOM*, 2025. URL https://arxiv.org/abs/2412.16264.

[4] Anomaly-aware class-incremental learning (ACIL) framework for network intrusion detection systems. *International Journal of Machine Learning and Cybernetics*, 17:104, 2026. doi: 10.1007/s13042-025-02840-5. URL https://link.springer.com/article/10.1007/s13042-025-02840-5.

[5] Cerasuolo et al. Class incremental learning for network-agnostic intrusion detection systems. In *IEEE International Forum on Research and Technologies for Society and Industry*, pages 17–22, 2025. doi: 10.1109/RTSI64020.2025.11212335.

[6] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, Georg Sperl, and Christoph H. Lampert. iCaRL: Incremental classifier and representation learning. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 2001–2010, 2017.

[7] Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: A strong, simple baseline. In *Advances in Neural Information Processing Systems*, volume 33, pages 15920–15930, 2020.

[8] Wu et al. Large scale incremental learning, 2019. URL https://arxiv.org/abs/1905.13260.

[9] Zhao et al. Maintaining discrimination and fairness in class incremental learning, 2020. URL https://arxiv.org/abs/1911.07053.

[10] Ahn et al. SS-IL: Separated softmax for incremental learning, 2021. URL https://arxiv.org/abs/2003.13947.

[11] Castro et al. End-to-end incremental learning, 2018. URL https://arxiv.org/abs/1807.09536.

[12] Menon et al. Long-tail learning via logit adjustment, 2021. URL https://arxiv.org/abs/2007.07314.

[13] Suresh Kumar Amalapuram, Bheemarjuna Reddy Tamma, and Sumohana S. Channappayya. SPIDER: A semi-supervised continual learning-based network intrusion detection system. In *IEEE INFOCOM*, 2024. doi: 10.1109/INFOCOM52122.2024.10621428. URL https://newslab.iith.ac.in/media/publications/pdfs/SPIDER-Suresh.pdf.

[14] Sean Fuhrman, Onat Gungor, and Tajana Rosing. CND-IDS: Continual novelty detection for intrusion detection systems. In *ACM/IEEE Design Automation Conference*, 2025. URL https://arxiv.org/abs/2502.14094.

[15] Cerasuolo, Bovenzi, Ciuonzo, and Pescapè. Attack-adaptive network intrusion detection systems for IoT networks through class incremental learning. *Computer Networks*, 263:111228, 2025. doi: 10.1016/j.comnet.2025.111228.

[16] Cerasuolo, Bovenzi, Ciuonzo, and Pescapè. Adaptable, incremental, and explainable network intrusion detection systems for internet of things. *Engineering Applications of Artificial Intelligence*, 144:110143, 2025. doi: 10.1016/j.engappai.2025.110143.

[17] Wang and Cao. A two-stage class incremental learning approach for network intrusion detection. In *IEEE Global Communications Conference*, pages 2353–2358, 2024. doi: 10.1109/GLOBECOM52923.2024.10901809. Official abstract and author publication record consulted; full text unavailable.

[18] Mahbod Tavallaee, Ebrahim Bagheri, Wei Lu, and Ali A. Ghorbani. A detailed analysis of the KDD CUP 99 data set. In *IEEE Symposium on Computational Intelligence for Security and Defense Applications*, pages 1–6, 2009.

[19] Nour Moustafa and Jill Slay. UNSW-NB15: A comprehensive data set for network intrusion detection systems. In *Military Communications and Information Systems Conference*, pages 1–6, 2015.

[20] Iman Sharafaldin, Arash Habibi Lashkari, and Ali A. Ghorbani. Toward generating a new intrusion detection dataset and intrusion traffic characterization. In *International Conference on Information Systems Security and Privacy*, pages 108–116, 2018.