

Kinetis Software Development Kit Release Notes

1 Overview

These are the release notes for the Freescale Kinetis Software Development Kit (SDK) 1.0.0. The core of the Kinetis SDK is a set of drivers architected in two layers: the Hardware Abstraction Layer (HAL) and the Peripheral Driver Layer.

The HAL abstracts the hardware register accesses into a set of stateless functional primitives which provide the building blocks for high-level Peripheral Drivers or applications. The Peripheral Driver Layer implements use-case driven drivers by utilizing one or more HAL layer components, system services, and possibly other Peripheral Drivers.

The Kinetis SDK includes a set of example applications demonstrating the use of the Peripheral Drivers and other integrated software modules such as a Real-Time Operating System (RTOS) through an RTOS abstraction layer. The Kinetis SDK also integrates middleware such as the Freescale USB stack to provide an easy-to-use Software Development Kit for Kinetis microcontroller (MCU) product families.

Contents

1	Overview	1
2	Development Tools	2
3	Supported Development Systems.....	3
4	Release Contents	4
5	Kinetis SDK Release Overview.....	5
5.1	Kinetis MCU platform support	5
5.2	Board configuration.....	7
5.3	Demo applications	7
5.4	Other integrated software solutions	7
6	Known Issues.....	8
6.1	Maximum file path length in Windows® 7	8
6.2	No spaces in the Kinetis SDK installation	8
6.3	USB HUB Power Supply	8
6.4	USB Audio Noise on the TWR-K22F120M	8
6.5	Installer Issue.....	8
7	Revision History	8

2 Development Tools

The Kinetis SDK 1.0.0 was compiled and tested with these development tools:

- Kinetis Design Studio v1.1
- IAR Embedded Workbench for ARM® version 7.20.2
- MDK-ARM Microcontroller Development Kit (Keil) 5.11
- Makefiles support with GCC revision 4.8.3 from ARM Embedded
- Atollic 5.1.0

The following table provides a list of default debugger configurations for both the Freescale Tower System modules (TWR) and Freedom (FRDM) development systems. See Section 3, Supported Development Systems, for a list of Freescale development systems supported by this release of the Kinetis SDK.

Table 1. List of Default Debugger Configurations

IDE	Development System	
	Freedom	Tower
IAR Embedded Workbench for ARM® version 7.20.2	CMSIS-DAP	P&E Micro
MDK-ARM Microcontroller Development Kit (Keil) 5.11	CMSIS-DAP	P&E Micro
Kinetis Design Studio v1.1	J-Link	J-Link

3 Supported Development Systems

This release supports boards and devices listed in this table. Boards and devices in boldface were tested in this release:

Table 2. Supported MCU devices and development boards

Development boards	Kinetis MCU devices
TWR-K22F120M FRDM-K22F TWR-KV31F120M	MK22FN512VDC12 , MK22FN512VLL12, MK22FN512VLH12, MK22FN512VMP12, MKV31F512VLL12 , MKV31F512VLH12 MK22FN256VDC12 , MK22FN256VLL12, MK22FN256VMP12, MK22FN256VLH12, MKV31F256VLL12 , MKV31F256VLH12 MK22FN128VDC10 , MK22FN128VLL10, MK22FN128VMP10, MK22FN128VLH10, MKV31F128VLL10 , MKV31F128VLH10
TWR-K64F120M FRDM-K64F	MK24FN1M0VDC12, MK24FN1M0VLL12, MK24FN1M0VLQ12 MK63FN1M0VLQ12, MK63FN1M0VMD12 MK64FN1M0VDC12, MK64FN1M0VLL12 , MK64FN1M0VLQ12, MK64FN1M0VMD12 , MK64FX512VDC12, MK64FX512VLL12, MK64FX512VLQ12, MK64FX512VMD12
TWR-K24F120M	MK24F25612
TWR-K60D100M	MK60D10
FRDM-KL03Z48M	MKL03Z4
FRDM-KL46Z48M	MKL46Z4
TWR-KV10Z75M	MKV10Z7
FRDM-K22F120MK02 FRDM-K22120MK0264 TWR-K22F120MK02 TMR-KV31F120MKV30	MKV30F12810, MK02F12810

4 Release Contents

This table describes the release contents.

Table 3. Release Contents

Deliverable	Location
Specific content for the evaluation boards	<install_dir>/boards/...
Demo applications	<install_dir>/demos/...
Documentation	<install_dir>/doc/...
File System	<install_dir>/filesystem/...
Projects to build libraries	<install_dir>/lib/...
Common Make files	<install_dir>/mk/...
Driver library, startup code and utilities	<install_dir>/platform/...
Cortex Microcontroller Software Interface Standard (CMSIS) ARM Cortex®-M header files, DSP library source, and IP extension header files	<install_dir>/platform/CMSIS/...
Peripheral Drivers	<install_dir>/platform/drivers/...
Hardware Abstraction Layer	<install_dir>/platform/hal/...
Linker control files for each supported tool chain	<install_dir>/platform/linker/...
OS Abstraction for Bare Metal and RTOS	<install_dir>/platform/osa/...
CMSIS compliant Startup Code	<install_dir>/platform/startup/...
System Services such as clock manager, interrupt manager, unified hardware timer, and low power manager	<install_dir>/platform/system/...
Utilities such as debug console	<install_dir>/platform/utilities/...
RTOS Kernel Code, RTOS abstraction implementations, and RTOS kernel folders	<install_dir>/rtos/...
A Processor Expert service pack and MQX RTOS task-aware plugins for tool chains.	<install_dir>/tools
TCP/IP stacks	<install_dir>/tcpip/...
USB stack and demos	<install_dir>/usb/...

5 Kinetis SDK Release Overview

The Kinetis SDK is intended for use with Freescale's Kinetis MCU product family based on the ARM[®] Cortex-M series architectures. The release consists of:

- Kinetis MCU platform support
- Board configuration support
- Demo applications
- The FatFs FAT File System
- USB Host and Device stacks
- lwIP TCP/IP networking stack
- RTOS support components
- Documentation (Kinetis SDK reference manual and various user's guides)

5.1 Kinetis MCU platform support

The Kinetis SDK platform directory contains the startup code, operating system abstraction, system services, driver libraries for peripherals, header files, linker files, and utilities such as the debug console implementation.

5.1.1 Startup code

The Kinetis SDK includes simple CMSIS compliant startup code for the supported Kinetis MCUs which efficiently deliver the code execution to the `main()` function. An application can either include the startup code directly in the project space or include a prebuilt startup code library for a cleaner project space.

5.1.2 Operating system abstraction

The drivers are designed to work with or without an operating system through the Operating System Abstraction layer (OSA). The OSA defines a common set of services that abstract most of the OS kernel functionalities. The OSA either maps an OSA service to the target OS function, or implements the service when no OS is used (bare metal) or when the service does not exist in the target OS. The Kinetis SDK implements the OSA for Freescale MQX[™] RTOS, FreeRTOS, μ C/OS-II, μ C/OS-III, and for OS-less "bare metal" usage. The bare metal OSA implementation is selected as the default option.

5.1.3 System Services

The system services contain a set of software entities that can be used either by the Peripheral Drivers or with the HAL to build either Peripheral Drivers or an application directly. The system services include the interrupt manager, clock manager, low power manager, and the unified hardware timer interface.

5.1.4 Driver library

The Kinetis SDK provides a set of drivers for the Kinetis MCU product family on-chip peripherals. The drivers are designed and implemented around the peripheral hardware blocks rather than for a specific Kinetis MCU, and work with or without an OS through the OS Abstraction layer. The drivers are architected into two layers: the Hardware Abstraction Layer and the Peripheral Driver Layer.

The HAL is designed to abstract hardware register accesses into functional accesses. It is stateless and is intended to cover the entire hardware functionality.

The Peripheral Drivers are built on top of the HAL to provide a set of easy-to-use interfaces that handle high-level data and stateful transactions. They are designed for the most common use cases identified for the underlying hardware block and are reasonably efficient in terms of memory and performance. They are written in C language and can be easily ported from product to product as they are designed to be initialized at runtime based on the driver configuration passed in by the user. In most cases, the Peripheral Drivers can be used as is. However, if the Peripheral Driver does not address a particular target use case, it can either be modified/enhanced or completely rewritten to meet the target functionality and other requirements. In this case, the existing Peripheral Driver can be used as a reference to build a custom driver based on the HAL. For more details, see the *Architectural Overview* chapter in the *Kinetis SDK API Reference Manual*.

Detailed implementation of hardware peripheral functionality, for both the HAL and Peripheral Driver, is implemented in stages. For example, the current version of the UART driver does not support modem control and smart card features. Likewise, the current version of the I2C driver does not support the SMBUS feature. The features which are missing from the current driver versions may be implemented in future releases.

5.1.5 Header files

The Kinetis SDK CMSIS directory contains CMSIS-compliant device-specific header files which provide direct access to the Kinetis MCU peripheral registers. Each supported Kinetis MCU device in the Kinetis SDK has an overall System-on-Chip (SoC) memory-mapped header file. In addition to the overall SoC memory-mapped header file, the Kinetis SDK includes extension header files for each peripheral instantiated on the Kinetis MCU. Along with the SoC header files and peripheral extension header files, the Kinetis SDK also includes common CMSIS header files for the ARM Cortex-M core and DSP library from the ARM CMSIS version 4.0 release.

5.1.6 Linker files

The Kinetis SDK contains linker control files (or simply linker files) for each supported tool chain and Kinetis MCU device.

5.1.7 Utilities

The utilities directory contains useful software utilities such as a debug console.

5.2 Board configuration

The board directory in the Kinetis SDK is mainly used for the board-specific configuration and pin muxing. The board directory also contains software components specific to the boards such as Ethernet PHY, Accelerometer, and SPI Flash implementations.

5.3 Demo applications

The example applications demonstrate the usage of the driver libraries and other integrated software solutions on supported development systems. For details, see the *Kinetis SDK Demo Applications User's Guide* (document KSDKDEMOUG).

5.4 Other integrated software solutions

The Kinetis SDK is designed for easy integration with other software solutions such as OS kernels, USB stack, TCP/IP stack, and file systems.

5.4.1 USB stack

A Freescale USB stack is integrated with the Kinetis SDK and was tested both with and without an OS through the OS abstraction layer. For details, see the *Integration of the USB Stack and Kinetis SDK*.

5.4.2 TCP/IP stack

The lwIP TCP/IP stack is pre-integrated with Kinetis SDK and runs on top of the Kinetis SDK Ethernet driver with Ethernet-capable devices/boards. For details, see the *Lightweight TCPIP (lwIP) Stack and Kinetis SDK Integration User's Guide*.

5.4.3 File System

A FAT file system is integrated with Kinetis SDK and can be used to access either the SD card or the USB memory stick when the SD card driver or the USB Mass Storage Device class implementation is used.

5.4.4 RTOS

The Kinetis SDK is pre-integrated with Freescale MQX RTOS, FreeRTOS, μ C/OS-II, and μ C/OS-III. OS abstraction layers are implemented for these RTOSes.

6 Known Issues

6.1 Maximum file path length in Windows® 7

Windows 7 imposes a 260 character maximum length for file paths. When installing the Kinetis SDK, place it in a directory close to the root to prevent file paths from exceeding the maximum character length specified by Windows. The recommended location is the C:\Freescale folder.

6.2 No spaces in the Kinetis SDK installation

The Freescale MQX RTOS build uses batch files, which do not work when there are spaces in the file path.

6.3 USB HUB Power Supply

The external power supply of the USB HUB must be provided before it can be used.

6.4 USB Audio Noise on the TWR-K22F120M

There is noise when running the USB audio example on the TWR-K22F120M due to poor clock accuracy of the CSTCE8M00G55-R0 crystal oscillator.

6.5 Installer Issue

When installing KSDK + MQX first and then trying to install another RTOS, the installer hangs. This issue only occurs in this particular scenario. Additionally, note that the Linux installer was tested only on a host with Ubuntu 12.0.4.

7 Revision History

This table summarizes revisions to this document.

Revision History		
Revision number	Date	Substantial changes
1.0.0	7/2014	Initial release

How to Reach Us:

Home Page:

www.freescale.com

Web Support:

www.freescale.com/support

Information in this document is provided solely to enable system and software implementers to use Freescale products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document.

Freescale reserves the right to make changes without further notice to any products herein. Freescale makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in Freescale data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. Freescale does not convey any license under its patent rights nor the rights of others. Freescale sells products pursuant to standard terms and conditions of sale, which can be found at the following address: freescale.com/SalesTermsandConditions.

Freescale, the Freescale logo, and Kinetis are trademarks of Freescale Semiconductor, Inc., Reg. U.S. Pat. & Tm. Off. Tower is a trademark of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners. ARM and Cortex are registered trademarks of ARM Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved.

© 2014 Freescale Semiconductor, Inc. All rights reserved.

