

CV/CC control loop, Output enable
Down-programmer


TITLE: EEZ DIB DCP505 r1B2

Document Number:

REV:

Date: 7.1.2019. 13:12

Sheet: 2/6



Note 3.1: Use power resistors with the lowest possible TCR (± 50 ppm/oC or better), e.g. CRA2512-FZ-R020ELF

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)

More info at <http://www.envox.hr/eez>

Repository: <https://github.com/eez-open>

50mA/500mA/5A current autoranging

TITLE: EEZ DIB DCP505 r1B2

Document Number:


REV:

Date: 7.1.2019. 13:12

Sheet: 3/6

Digital control (SPI)

OE_TRIG



I/O Expander		
Bit	Function	Direction
0	Sense error	Input
1	CC	Input
2	CV	Input
3	Power good	Input
4	OVP fault	Input
5	OVP enable	Output
6	OE uncoupled LED	Output
7	OE coupled LED	Output
8	Down programmer disable	Output
9	Output enable	Output
10	Remote sense	Output
11	Remote programming	Output
12	Current range 5 A	Input
13	Current range 500 mA	Input
14	Current range 50 mA	Input
15	-	-

SPI I/O expander, DAC, ADC, Voltage reference
Remote programming

TITLE: EEZ DIB DCP505 r1B2


Document Number:

REV:


Date: 7.1.2019. 13:12

Sheet: 4/6

Constant Voltage (CV) and Constant Current (CC) mode detection and indication



Over-voltage protection (OVP)



CC/CV mode detection and indication, OVP

TITLE: EEZ DIB DCP505 r1B2

Document Number:

REV:

Date: 7.1.2019. 13:12

Sheet: 5/6

