

CV/CC control loop, Output enable
Down-programmer


TITLE: EEZ DIB DCP505 r1B2

Document Number:

REV:

Date: 3.1.2019. 09:14

Sheet: 2/6



Note 3.1: Use power resistors with the lowest possible TCR (± 50 ppm/oC or better), e.g. CRA2512-FZ-R020ELF

Licensed under the TAPR Open Hardware License (www.tapr.org/OHL)
 More info at <http://www.envox.hr/eez>
 Repository: <https://github.com/eez-open>

50mA/500mA/5A current autoranging

TITLE: EEZ DIB DCP505 r1B2

Document Number:


REV:

Date: 3.1.2019. 09:14

Sheet: 3/6

Digital control (SPI)

OE_TRIG



SPI I/O expander, DAC, ADC, Voltage reference
Remote programming

TITLE: EEZ DIB DCP505 r1B2


Document Number:

REV:


Date: 3.1.2019. 09:14

Sheet: 4/6

Constant Voltage (CV) and Constant Current (CC) mode detection and indication



Over-voltage protection (OVP)



CC/CV mode detection and indication, OVP

TITLE: EEZ DIB DCP505 r1B2

Document Number:

REV:

Date: 3.1.2019. 09:14

Sheet: 5/6

