

《Zabbix企业级分布式监控系统第2版》随书代码

代码仓库地址 https://github.com/zabbix-book/zabbix_v2

书籍购买地址 <https://item.jd.com/12653708.html>

549页

```
shell# yum -y install gcc gcc-c++ autoconf httpd php mariadb-server php-mysql
httpd-manual mod_ssl mod_perl mod_auth_mysql php-gd php-xml php-mbstring php-
ldap php-pear php-xmlrpc php-bcmath mysql-connector-odbc mysql-devel libdbi-
dbd-mysql net-snmp-devel curl-devel unixODBC-devel OpenIPMI-devel java-
devel pcre-devel libxml2-devel openldap-devel libevent-devel openssl-devel
libssh2-devel
```

```
shell# wget
https://sourceforge.net/projects/zabbix/files/ZABBIX%20Latest%20Stable/
4.0.0/zabbix-4.0.0.tar.gz #读者可以下载最新版本，写作本书时最新版本为zabbix 4.0.0
```

```
shell# groupadd zabbix -g 201 #添加zabbix用户组
shell# useradd -g zabbix -u 201 -m zabbix #增加zabbix用户
shell# tar xvf zabbix-4.0.0.tar.gz #解压缩包
shell# cd zabbix-4.0.0 #进入源码目录
shell# ./configure --prefix=/usr --exec-prefix=/usr --bindir=/usr/bin --
sbindir=/usr/sbin --sysconfdir=/etc --datadir=/usr/share --includedir=/usr/
include --libdir=/usr/lib64 --libexecdir=/usr/libexec --localstatedir=/var --
sharedstatedir=/var/lib --mandir=/usr/share/man --infodir=/usr/share/info --
sysconfdir=/etc/zabbix --libdir=/usr/lib64/zabbix --enable-server --enable-
agent --enable-proxy --enable-ipv6 --enable-java --with-net-snmp --with-ldap --
with-libcurl --with-openipmi --with-unixodbc --with-ssh2 --with-libxml2 --with-
libevent --with-libpcre --with-openssl --with-mysql=/usr/bin/mysql_config
#如果读者只需安装Zabbix-Server端，则开启--enable-server参数即可，其他参数可不用选。
#这里是为了后面的各项功能都可以使用，所以开启了非常多的参数
#如果缺少相应的软件包，在配置过程中会给出提示，使用yum安装所缺少的软件包即可顺利通过安装
shell# make
shell# make install
```

550页

将数据库添加到开机启动项中并启动服务，命令如下：

```
shell# systemctl enable mariadb #添加到开机启动项中
shell# systemctl start mariadb #启动服务
设置MySQL用户名和密码，命令如下：
```

```

shell# mysqladmin -uroot password 'mysql_pass'; #设置MySQL的root密码为mysql_pass
shell# mysql -uroot -p #登录数据库, 输入刚才设置的密码
mysql> create database zabbix character set utf8; #将zabbix库默认的字符集设置为UTF-8
mysql> grant all privileges on zabbix.* to zabbix@localhost identified by 'zabbix'; #设置zabbix库允许localhost这个IP地址访问, 用户名设置为zabbix, 密码设置为zabbix
mysql> flush privileges; #刷新权限
确保以上操作都正确, 测试数据库连接是否正常, 命令如下:

shell# mysql -uzabbix -pzabbix zabbix
导入MySQL库文件, 命令如下:

shell# cd zabbix-4.0.0 #进入Zabbix源码路径
shell# mysql -uzabbix -pzabbix zabbix < database/mysql/schema.sql

```

551页

如果安装Zabbix-Proxy, 则只导入schema.sql即可, 无须导入下面的SQL文件; 否则, Zabbix-Proxy无法正常工作。

```

shell# mysql -uzabbix -pzabbix zabbix < database/mysql/images.sql
shell# mysql -uzabbix -pzabbix zabbix < database/mysql/data.sql
创建日志保存目录, 并修改权限, 目录如下:

```

```

shell# mkdir /var/log/zabbix
shell# chown zabbix.zabbix /var/log/zabbix[这是什么命令, 缺少文字说明]

```

```

shell# cp misc/init.d/fedora/core/zabbix_* /etc/init.d/
shell# chmod 755 /etc/init.d/zabbix_*
shell# sed -i "s#BASEDIR=/usr/local#BASEDIR=/usr/#g" /etc/init.d/zabbix_server
shell# sed -i "s#BASEDIR=/usr/local#BASEDIR=/usr/#g" /etc/init.d/zabbix_agentd

```

```

shell# cp -r ./zabbix-X.X.X/frontends/php/ /var/www/html/zabbix
shell# chown -R apache.apache /var/www/html/zabbix

```

```

shell# chkconfig zabbix_server on
shell# service zabbix_server start
shell# systemctl enable httpd
shell# systemctl start httpd #如果启动失败, 请检查配置文件是否正确

```

```
shell# vim /etc/php.ini
max_execution_time=300
memory_limit=128M
post_max_size=16M
upload_max_filesize=2M
max_input_time=300
date.timezone=Asia/Shanghai
```

552页

```
hell# wget https://sourceforge.net/projects/zabbix/files/ZABBIX%20Latest%
20Stable/4.0.0/zabbix-4.0.0.tar.gz
shell# groupadd zabbix -g 201
shell# useradd -g zabbix -u 201 -m zabbix
shell# tar xvf zabbix-4.0.0.tar.gz
shell# cd zabbix-4.0.0
shell# ./configure --prefix=/usr --sysconfdir=/etc//zabbix --enable-agent
shell# make
shell# make install
shell# mkdir /var/log/zabbix
shell# chown zabbix.zabbix /var/log/zabbix
shell# cp misc/init.d/fedora/core/zabbix_agentd /etc/init.d/
shell# chmod 755 /etc/init.d/zabbix_agentd
shell# sed -i "s#BASEDIR=/usr/local#BASEDIR=/usr/#g" /etc/init.d/zabbix_agentd
shell# sed -i "s#tmp/zabbix_agentd.log#var/log/zabbix/zabbix_agentd.log#g"
/etc/zabbix/zabbix_agentd.conf
shell# sed -i "#UnsafeUserParameters=0#aUnsafeUserParameters=1\n"
/etc/zabbix/zabbix_agentd.conf
#/etc/zabbix/zabbix_agentd.conf配置可参看3.2.3节，这里的x.x.x.x为
#Zabbix-Server的IP地址
启动Zabbix-Agent服务的命令如下：

shell# chkconfig zabbix_agentd on
shell# service zabbix_agentd start
```

553页

<https://github.com/zabbix-book/zabbix-rpmbuild>

```
shell# yum install rpm-build
```

```
shell# yum install -y gcc make mysql-devel openldap-devel libssh2-devel net-
snmp-devel curl-devel unixODBC-devel OpenIPMI-devel java-devel postgresql-
devel net-snmp-devel openldap-devel gnutls-devel sqlite-devel curl-devel
OpenIPMI-devel libssh2-devel java-devel libxml2-devel libevent-devel openssl-
devel
shell# rpm -ivh http://repo.zabbix.com/non-supported/rhel/7/x86_64/fping-3.10-
1.el7.x86_64.rpm
```

554页

```
shell# useradd admin
```

```
shell# su - admin
shell# mkdir -pv rpmbuild/{BUILD,RPMS,SOURCES,SPECS,SRPMS}
shell# echo "% _topdir /home/admin/rpmbuild" > ~/.rpmmacros
```

```
shell# cd /home/admin
shell# wget https://raw.githubusercontent.com/zabbix-book/zabbix-rpmbuild/
master/src/zabbix-4.0.0-2.el7.src.rpm
shell# rpm -ivh /home/admin/zabbix-4.0.0-2.el7.src.rpm
```

```
shell# cd /home/admin/rpmbuild/SPECS
shell# rpmbuild -ba zabbix.spec #此处会提示需要依赖包，依次安装
Executing(%prep): /bin/sh -e /var/tmp/rpm-tmp.FK5o3t
+ umask 022
+ cd /home/admin/rpmbuild/BUILD
+ cd /home/admin/rpmbuild/BUILD
+ rm -rf zabbix-4.0.0
+ /usr/bin/gzip -dc /home/admin/rpmbuild/SOURCES/zabbix-4.0.0.tar.gz
+ /usr/bin/tar -xf -
+ STATUS=0
+ '[' 0 -ne 0 ']'
+ cd zabbix-4.0.0
.....省略输出内容.....
#打包生成如下RPM文件
Wrote: /home/admin/rpmbuild/SRPMS/zabbix-4.0.0-2.el7.centos.src.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-agent-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-get-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-sender-4.0.0-
2.el7.centos.x86_64.rpm
```

```
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-proxy-mysql-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-proxy-pgsql-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-proxy-sqlite3-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-java-gateway-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-server-mysql-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/x86_64/zabbix-server-pgsql-4.0.0-
2.el7.centos.x86_64.rpm
Wrote: /home/admin/rpmbuild/RPMS/noarch/zabbix-web-4.0.0-
2.el7.centos.noarch.rpm
Wrote: /home/admin/rpmbuild/RPMS/noarch/zabbix-web-mysql-4.0.0-
2.el7.centos.noarch.rpm
Wrote: /home/admin/rpmbuild/RPMS/noarch/zabbix-web-pgsql-4.0.0-
2.el7.centos.noarch.rpm
Wrote: /home/admin/rpmbuild/RPMS/noarch/zabbix-web-japanese-4.0.0-
2.el7.centos.noarch.rpm
Executing(%clean): /bin/sh -e /var/tmp/rpm-tmp.pDqbD3
+ umask 022
+ cd /home/admin/rpmbuild/BUILD
+ cd zabbix-4.0.0
+ rm -rf /home/admin/rpmbuild/BUILDROOT/zabbix-4.0.0-2.el7.centos.x86_64
+ exit 0
```

555页

```
shell# rpm2cpio zabbix-4.0.0-2.el7.src.rpm |cpio -div
warning: rpm2cpio: NOKEY, key ID a14fe591
config.patch
fonts-config.patch
fping3-sourceip-option.patch
zabbix-4.0.0.tar.gz
zabbix-agent.init
zabbix-agent.service
zabbix-java-gateway.init
zabbix-java-gateway.service
zabbix-logrotate.in
zabbix-proxy.init
zabbix-proxy.service
zabbix-server.init
zabbix-server.service
zabbix-tmpfiles.conf
zabbix-web22.conf
zabbix-web24.conf
zabbix.spec
```

556页

```
sed -i \
    -e 's|# PidFile=.*|PidFile=%{_localstatedir}/run/{name}/
zabbix_agentd.pid|g' \
    -e 's|^LogFile=.*|LogFile=%{_localstatedir}/log/{name}/
zabbix_agentd.log|g' \
    -e '/# UnsafeUserParameters=0/aUnsafeUserParameters=1\n' \
    -e '/# Include.*zabbix_agentd.conf.d//aInclude=/etc/zabbix/
zabbix_agentd.conf.d/>\n' \
    -e '/StartAgents=3/aStartAgents=5\n' \
    -e 's|# LogFileSize=.*|LogFileSize=0|g' \
    -e 's|Server=127.0.0.1$|Server=127.0.0.1,10.10.10.1|g' \
    -e 's|ServerActive=127.0.0.1$|ServerActive=127.0.0.1:10051,10.10.10.1:
10051|g' \
    -e 's|# EnableRemoteCommands=0|EnableRemoteCommands=1|g' \
    -e 's|# LogRemoteCommands=0|LogRemoteCommands=1|g' \
    -e 's|LogFileSize=0|LogFileSize=10|g' \
    -e 's|/usr/local|usr|g' \
    ${RPM_BUILD_ROOT}${_sysconfdir}/{name}/zabbix_agentd.conf

sed -i \
    -e 's|/usr/local|usr|g' \
    -e '/# UnsafeUserParameters=0/aUnsafeUserParameters=1\n' \
    -e 's@# Include=/usr/etc/zabbix_agentd.conf.d@Include=/etc/zabbix/
zabbix_agentd.conf.d@g' \
    ${RPM_BUILD_ROOT}${_sysconfdir}/{name}/zabbix_agent.conf
```

```
%post agent
if [ $1 -eq 1 ]; then
sed -i "s@Hostname=Zabbix server@Hostname=${HOSTNAME}@g" /etc/zabbix/
zabbix_agentd.conf
getent group zabbix >/dev/null || groupadd -r zabbix
getent passwd zabbix >/dev/null || useradd -r -g zabbix -d %{_sharedstatedir}/
zabbix -s /sbin/nologin -c "zabbix user" zabbix
/sbin/chkconfig zabbix-agent on
/sbin/service zabbix-agent start
chown root:zabbix /bin/netstat
chmod 4755 /bin/netstat
fi
```

557页

<https://www.elastic.co/downloads/elasticsearch>

```
shell# rpm -ivh https://artifacts.elastic.co/downloads/elasticsearch/elasticsearch-6.1.2.rpm
shell# yum install java-1.8.0 -y
```

```
shell# systemctl daemon-reload          #重新加载systemd进程
shell# systemctl enable elasticsearch    #开机自启动
shell# systemctl start elasticsearch     #启动服务
```

```
shell# tail -f /var/log/elasticsearch/elasticsearch.log
[2018-10-20T17:35:55,407][INFO ][o.e.x.m.j.p.l.CppLogMessageHandler]
[controller/3091] [Main.cc@109] controller (64 bit): Version 6.4.2 (Build
660eefe6f2ea55) Copyright (c) 2018 Elasticsearch BV
[2018-10-20T17:35:56,116][DEBUG][o.e.a.ActionModule ] Using REST wrapper from
plugin org.elasticsearch.xpack.security.Security
[2018-10-20T17:35:56,556][INFO ][o.e.d.DiscoveryModule ] [PYjVnDh] using
discovery type [zen]
[2018-10-20T17:35:57,924][INFO ][o.e.n.Node ] [PYjVnDh] initialized
[2018-10-20T17:35:57,925][INFO ][o.e.n.Node ] [PYjVnDh] starting ...
[2018-10-20T17:35:58,180][INFO ][o.e.t.TransportService ] [PYjVnDh]
publish_address {127.0.0.1:9300}, bound_addresses {127.0.0.1:9300}
```

558页

```
shell# netstat -nlput|grep 9200
tcp6          0      0 127.0.0.1:9200 :::*   LISTEN  3042/java
```

```
shell# vim /etc/elasticsearch/jvm.options
-Xms1g
-Xmx1g
```

第1~5部分

https://github.com/zabbix-book/es-mapping-create/blob/master/step-1-create_elastic_mapping.sh

第7部分

https://github.com/zabbix-book/es-mapping-create/blob/master/step-2-create_elastic_template.sh

第8部分

https://github.com/zabbix-book/es-mapping-create/blob/master/step-3-create_elastic_pipeline.sh

```
shell# curl -X PUT \
http://127.0.0.1:9200/uint \
-H 'content-type:application/json' \
-d '{
  "settings" : {
    "index" : {
      "number_of_replicas" : 1,
      "number_of_shards" : 5
    }
  },
  "mappings" : {
    "values" : {
      "properties" : {
        "itemid" : {
          "type" : "long"
        },
        "clock" : {
          "format" : "epoch_second",
          "type" : "date"
        },
        "value" : {
          "type" : "long"
        }
      }
    }
  }
}'
#创建成功, 提示如下
{"acknowledged":true,"shards_acknowledged":true,"index":"uint"}
```

559页

```
shell# curl -X PUT \
http://127.0.0.1:9200/db1 \
-H 'content-type:application/json' \
-d '{
  "settings" : {
    "index" : {
      "number_of_replicas" : 1,
      "number_of_shards" : 5
    }
  },
  "mappings" : {
    "values" : {
      "properties" : {
        "itemid" : {
          "type" : "long"
        }
      }
    }
  }
}'
```



```

    },
    "clock" : {
        "format" : "epoch_second",
        "type" : "date"
    },
    "value" : {
        "type" : "double"
    }
}
}
}
}'
#创建成功, 提示如下
{"acknowledged":true,"shards_acknowledged":true,"index":"dbl"}

```

560页

```

shell# curl -X PUT \
http://127.0.0.1:9200/str \
-H 'content-type:application/json' \
-d '{
    "settings" : {
        "index" : {
            "number_of_replicas" : 1,
            "number_of_shards" : 5
        }
    },
    "mappings" : {
        "values" : {
            "properties" : {
                "itemid" : {
                    "type" : "long"
                },
                "clock" : {
                    "format" : "epoch_second",
                    "type" : "date"
                },
                "value" : {
                    "fields" : {
                        "analyzed" : {
                            "index" : true,
                            "type" : "text",
                            "analyzer" : "standard"
                        }
                    }
                },
                "index" : false,
                "type" : "text"
            }
        }
    }
}

```

```

    }
  }
}
}'
#创建成功, 提示如下
{"acknowledged":true,"shards_acknowledged":true,"index":"str"}

```

561页

```

shell# curl -X PUT \
http://127.0.0.1:9200/text \
-H 'content-type:application/json' \
-d '{
  "settings" : {
    "index" : {
      "number_of_replicas" : 1,
      "number_of_shards" : 5
    }
  },
  "mappings" : {
    "values" : {
      "properties" : {
        "itemid" : {
          "type" : "long"
        },
        "clock" : {
          "format" : "epoch_second",
          "type" : "date"
        },
        "value" : {
          "fields" : {
            "analyzed" : {
              "index" : true,
              "type" : "text",
              "analyzer" : "standard"
            }
          },
          "index" : false,
          "type" : "text"
        }
      }
    }
  }
}'
#创建成功, 提示如下
{"acknowledged":true,"shards_acknowledged":true,"index":"text"}

```

562页

```
shell# curl -X PUT \
http://127.0.0.1:9200/log \
-H 'content-type:application/json' \
-d '{
  "settings" : {
    "index" : {
      "number_of_replicas" : 1,
      "number_of_shards" : 5
    }
  },
  "mappings" : {
    "values" : {
      "properties" : {
        "itemid" : {
          "type" : "long"
        },
        "clock" : {
          "format" : "epoch_second",
          "type" : "date"
        },
        "value" : {
          "fields" : {
            "analyzed" : {
              "index" : true,
              "type" : "text",
              "analyzer" : "standard"
            }
          },
          "index" : false,
          "type" : "text"
        }
      }
    }
  }
}'
#创建成功, 提示如下
{"acknowledged":true,"shards_acknowledged":true,"index":"log"}
```

563页

```

### Option: HistoryStorageDateIndex
#      Enable preprocessing of history values in history storage to store
values in different indices based on date.
#      0 - disable
#      1 - enable
#
# Mandatory: no
# Default:
HistoryStorageDateIndex=1 #开启按天索引的功能

```

```

#src/libs/zbxhistory/history_elastic.c
static int elastic_add_values(zbx_history_iface_t *hist, const
zbx_vector_ptr_t *history)
{
    .....省略部分代码.....
    zbx_json_init(&json_idx, ZBX_IDX_JSON_ALLOCATE);

    zbx_json_addobject(&json_idx, "index");
    zbx_json_addstring(&json_idx, "_index", value_type_str[hist->value_type],
ZBX_JSON_TYPE_STRING);
    zbx_json_addstring(&json_idx, "_type", "values", ZBX_JSON_TYPE_STRING);
    if (1 == CONFIG_HISTORY_STORAGE_PIPELINES)//pipeline的开关
    {
        zbx_snprintf(pipeline, sizeof(pipeline), "%s-pipeline", value_type_str
[hist->value_type]);
        zbx_json_addstring(&json_idx, "pipeline", pipeline,
ZBX_JSON_TYPE_STRING);
    }
    .....省略部分代码.....
}

```

564页

```

shell# curl -X PUT \
http://127.0.0.1:9200/_template/text_template \
-H 'content-type:application/json' \
-d '{
    "template": "text*",          #匹配的数据类型为text*, 其他数据类型类似
    "index_patterns": ["text*"],  #匹配的数据类型为text*, 其他数据类型类似
    "settings" : {
        "index" : {
            "number_of_replicas" : 1,
            "number_of_shards" : 5
        }
    },
    "mappings" : {

```

```

    "values" : {
      "properties" : {
        "itemid" : {
          "type" : "long"
        },
        "clock" : {
          "format" : "epoch_second",
          "type" : "date"
        },
        "value" : {
          "fields" : {
            "analyzed" : {
              "index" : true,
              "type" : "text",
              "analyzer" : "standard"
            }
          },
          "index" : false,
          "type" : "text"
        }
      }
    }
  }
}
}'
#创建成功, 提示如下
{"acknowledged":true}

```

565页

```

shell# curl -X PUT \
http://127.0.0.1:9200/_ingest/pipeline/uint-pipeline \
-H 'content-type:application/json' \
-d '{
  "description": "daily uint index naming",
  "processors": [
    {
      "date_index_name": {          #按日期对字段索引
        "field": "clock",          #匹配哪个字段
        "date_formats": ["UNIX"], #日期格式, 可用字段有ISO8601、UNIX、UNIX_MS和
TAI64N
        "index_name_prefix": "uint-", #索引名称前缀
        "date_rounding": "d" #可用字段有y(年)、M(月)、w(星期)、d(日)、h(小时)、m(分
钟)和s(秒)
      }
    }
  ]
}'
#创建成功, 提示如下

```

```
{"acknowledged":true}
```

<https://www.elastic.co/guide/en/elasticsearch/reference/6.3/date-index-name-processor.html>

配置Zabbix-Server, 命令如下:

```
shell# vim /etc/zabbix/zabbix_server.conf
### Option: HistoryStorageURL
# History storage HTTP[S] URL.
#
# Mandatory: no
# Default:
HistoryStorageURL=http://192.168.0.15:9200

### Option: HistoryStorageTypes
# Comma separated list of value types to be sent to the history storage.
#
# Mandatory: no
# Default:
HistoryStorageTypes=uint,dbl,str,log,text
HistoryStorageDateIndex=1
```

重启Zabbix-Server服务, 命令如下:

```
shell# systemctl restart zabbix-server
```

566页

```
shell# vim /etc/zabbix/web/zabbix.conf.php
global $DB, $HISTORY; //一定要加上$HISTORY, 否则无法生效
//$HISTORY['url'] = [
// 'uint' => 'http://localhost:9200',
// 'text' => 'http://localhost:9200'
//];
// Value types stored in Elasticsearch.
//$HISTORY['types'] = ['uint', 'text'];
$HISTORY['url'] = 'http://192.168.0.15:9200';
$HISTORY['types'] = ['uint', 'dbl', 'str', 'log', 'text'];
```