transfer?

(CO4)

(b) Describe Direct Memory Access (DMA)? How DMA is used to transfer data from (CO4) peripheral devices?

(c) Explain different Modes of Data transfer.

(CO4)

- (a) Explain Memory Hierarchy on the basis of speed, size and cost parameters. (CO5)
  - (b) Write short notes on the following: (CO5)
    - (i) RAM
    - (ii) ROM
    - (iii) Auxiliary memory
    - (iv) Virtual memory
  - (c) Write a short note on cache memory performance considerations. Explain what are the various methods to write into cache?

HINE ON THE STANDARD SERVICE

to the state of th

sol to man exercis and apprecia-

(CO5)

Roll No. ....

## TBC-304/TBI-302

B. C. A./B. SC. (IT) (THIRD SEMESTER) END SEMESTER **EXAMINATION, Jan., 2023** COMPUTER ORGANIZATION AND **ARCHITECTURE** 

> **Time: Three Hours** Maximum Marks: 100

- Note: (i) All questions are compulsory.
  - (ii) Answer any two sub-questions among (a), (b) and (c) in each main question.
  - (iii) Total marks in each main question are twenty.
  - (iv) Each sub-question carries 10 marks.
- 1. (a) The 8-bit register AR, BR, CR and DR initially have the values:

AR = 11110010, BR = 111111111,CR = 10111001, DR = 11101010

Determine the 8-bit values in each register after the execution of following sequence of microoperations: (CO1)

- (i)  $AR \leftarrow AR + BR$
- (ii)  $CR \leftarrow CR \lor DR$
- (iii) BR  $\leftarrow$  BR + 1
- (iv)  $DR \leftarrow AR \wedge DR$
- (b) Design and explain Shift microoperations with the help of its hardware (CO1) implementation.
- (c) A digital computer constructed with multiplexers has common bus system for 8 registers of 16 bits each:
  - (i) What is the size of multiplexers?
  - (ii) How many multiplexers are there in the bus?
  - (iii) How many selection inputs are there in each multiplexer?
- 2. (a) What is assembly language? Write assembly language program to subtract two 8 bits numbers stored in any memory locations.

- (b) Explain Micro-instruction Format? Write micro-program for FETCH routine. (CO2)
- (c) What is control unit? Explain two methods of implementing control unit.

(CO2)

3. (a) Write the program to evaluate the arithmetic statement:

$$X = (A + B) \times (C + D)$$

- (i) Using a general register computer with three address instruction.
- (ii) Using a general register computer with two address instruction.
- (iii) Using a Accumulator type computer with one address instruction.
- (iv) Using a Stack Organized computer with zero address instruction.
- (b) Discuss General register organization. Find the control word of microoperation  $R_1 \leftarrow R_2 - R_3$ ?
- (c) The time delay for four segments in the pipeline are as follows:

 $t_1 = 50$  ns  $t_2 = 30$  ns,  $t_3 = 95$  ns and  $t_4$ = 45 ns, the non-pipelined system takes 50 ns to process a task.

Determine the speedup ratio of the pipeline for 100 tasks. (CO3)