

CERTIFICATE OF APPROVAL No CF 5365

This is to certify that, in accordance with TS00 General Requirements for Certification of Fire Protection Products
The undermentioned products of

TREMCO CPG UK LIMITED

Coupland Road, Hindley Green, Wigan, WN2 4HT Tel: 01942 251400

Have been assessed against the requirements of the Technical Schedule(s) denoted below and are approved for use subject to the conditions appended hereto:

CERTIFIED PRODUCT

TECHNICAL SCHEDULE

Nullifire SC801-120

TS15 Intumescent Coatings for Steelwork

Signed and sealed for and on behalf of Warringtonfire Testing and Certification Limited

Paul Duggan

Certification Manager



Issued: 7th September 2015 Revised: 19th August 2020 Valid to: 5th April 2025

Page 1 of 34





Nullifire SC801-120

- This approval relates to the use of Nullifire SC801-120 for the fire protection of steel I-shaped beams and columns, circular and rectangular hollow column sections. The precise scope is given in Tables 1 to 24 which show the total dry film thickness of Nullifire SC801-120 (excluding primer and topcoat) required to provide fire resistance periods in accordance with BS476: Part 21: 1987 of 15 minutes up to 120 minutes for differing sections, section factors and design temperatures.
- This certification is provided to the client for their own purposes and we cannot opine on whether it will be accepted by Building Control authorities or any other third parties for any purpose.
- 3. The products are approved on the basis of:
 - i) Initial type testing.
 - ii) A design appraisal against TS15.
 - iii) Certification of quality management system to ISO 9001: 2008.
 - iv) Inspection and surveillance of factory production control.
 - v) Audit testing.
- 4. The data referring to three-sided fire exposure of beams relate to beams supporting concrete floor slabs. Separate consideration is required where this is not the case.
- 5. The data shown is applicable to steel sections blast cleaned to ISO 8501-1 SA $2^{1}/_{2}$ or equivalent and primed with a suitable and compatible primer. Specifications of surface preparations, primers and topcoats are available from the manufacturer whose responsibility is to ensure that Nullifire SC801-120 is compatible for use in respect of both ambient and fire conditions. The total dry film thickness of primer and topcoat together should not exceed that tested.
- 6. Specific data given in the tables applies to horizontal, vertical, flexural and compression members supporting loads up to the maximum design loads specified in BS449: Part 2.
- 7. The approval relates to on going production. Product and/or its immediate packaging is identified with the manufacturers' name, the product name or number, the CERTIFIRE name or name and mark, together with the CERTIFIRE certificate number and application where appropriate.
- 8. The data shown in the tables is based on assessments which comply with the criteria for acceptability now incorporated within the CERTIFIRE scheme.

Page 2 of 34 Signed E/200

Pel Rago-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Num				20		Table	1 SC801 - 1	20 I/H Bean	ns 15 minut	es						
					R		ickness (mm									
Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
100	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
125	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
130	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
135 140	0.454	0.454	0.454 0.454	0.454 0.454	0.454	0.454	0.454	0.454 0.454	0.454	0.454	0.454	0.454 0.454	0.454 0.454	0.454	0.454	0.454
140	0.454	0.454 0.454	0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454
150	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
155	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
160	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
165	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
170	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
175	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
180	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
185	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
190	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
195	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
200	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
205	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
210	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
215	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
220 225	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454 0.454	0.454 0.454	0.454	0.454	0.454 0.454
230	0.454	0.454 0.454	0.454	0.454	0.454 0.454	0.454 0.454	0.454									
235	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
240	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
245	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
250	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
255	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
260	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
265	0.462	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
270	0.473	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
275	0.484	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
280	0.495	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
285	0.506	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
290	0.517	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
295 300	0.527 0.538	0.454 0.454														
300	0.538	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
310	0.560	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
315	0.571	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
320	0.582	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
325	0.593	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
330	0.604	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
335	0.615	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
340	0.626	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
345	0.637	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
350	0.648	0.463	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
355	0.659	0.473	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
360 Toblo	0.670	0.482	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 3 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

								20 I/H Bean								
					F	Required Th	ickness (mr	n) for a Desi	gn Tempera	ature (°C)						
Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	0.569	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
100	0.587	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	0.606	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	0.624	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	0.643	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120	0.661	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
125	0.679	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
130	0.698	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
135	0.716	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
140	0.735	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
145	0.753	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
150	0.772	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
155	0.790	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
160	0.808	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
165	0.827	0.459	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
170	0.845	0.479	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
175	0.864	0.498	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
180	0.882	0.518	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
185	0.900	0.537	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
190	0.919	0.557	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
195	0.937	0.576	0.462	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
200	0.956	0.596	0.479	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
205	0.974	0.615	0.496	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
210	0.992	0.635	0.513	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
215	1.011	0.654	0.530	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
220	1.029	0.674	0.546	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
225	1.048	0.693	0.563	0.461	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
230	1.066	0.713	0.580	0.475	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
235	1.084	0.732	0.597	0.490	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
240	1.103	0.752	0.614	0.504	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
245	1.121	0.771	0.630	0.519	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
250	1.140	0.791	0.647	0.533	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
255	1.158	0.810	0.664	0.548	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
260	1.176	0.830	0.681	0.562	0.460	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
265	1.195	0.849	0.698	0.577	0.473	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
270	1.213	0.869	0.714	0.591	0.485	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
275	1.232	0.888	0.731	0.606	0.498	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
280	1.250	0.908	0.748	0.620	0.510	0.460	0.458	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
285	1.268	0.927	0.765	0.635	0.523	0.472	0.469	0.455	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
290	1.287	0.947	0.782	0.650	0.535	0.483	0.481	0.466	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
295	1.305	0.966	0.799	0.664	0.548	0.495	0.492	0.477	0.462	0.454	0.454	0.454	0.454	0.454	0.454	0.454
300	1.324	0.986	0.815	0.679	0.560	0.506	0.504	0.488	0.473	0.454	0.454	0.454	0.454	0.454	0.454	0.454
305	1.342	1.005	0.832	0.693	0.573	0.518	0.515	0.500	0.484	0.463	0.457	0.454	0.454	0.454	0.454	0.454
310	1.361	1.025	0.849	0.708	0.585	0.529	0.527	0.511	0.495	0.473	0.467	0.463	0.454	0.454	0.454	0.454
315	1.379	1.044	0.866	0.722	0.598	0.541	0.538	0.522	0.506	0.484	0.478	0.474	0.454	0.454	0.454	0.454
320	1.397	1.064	0.883	0.737	0.610	0.552	0.550	0.533	0.517	0.495	0.488	0.484	0.454	0.454	0.454	0.454
325	1.416	1.083	0.899	0.751	0.622	0.564	0.561	0.545	0.528	0.505	0.499	0.495	0.460	0.454	0.454	0.454
330	1.434	1.103	0.916	0.766	0.635	0.575	0.573	0.556	0.539	0.516	0.509	0.505	0.470	0.454	0.454	0.454
335	1.453	1.122	0.933	0.780	0.647	0.587	0.584	0.567	0.550	0.526	0.520	0.516	0.480	0.454	0.454	0.454
340	1.471	1.142	0.950	0.795	0.660	0.598	0.596	0.578	0.561	0.537	0.530	0.526	0.490	0.454	0.454	0.454
345	1.489	1.161	0.967	0.809	0.672	0.610	0.607	0.590	0.572	0.548	0.541	0.536	0.500	0.454	0.454	0.454
350	1.508	1.181	0.983	0.824	0.685	0.621	0.619	0.601	0.583	0.558	0.551	0.547	0.510	0.454	0.454	0.454
355	1.526	1.200	1.000	0.838	0.697	0.633	0.630	0.612	0.594	0.569	0.562	0.557	0.520	0.454	0.454	0.454
360	1.545	1.220	1.017	0.853	0.710	0.645	0.642	0.623	0.605	0.580	0.573	0.568	0.530	0.458	0.454	0.454
Table								ire and		oto clak			10.550			

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 4 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

						Table	3 SC801 - 1	L20 I/H Bear	ns 45 minut	es						
						Required Th										
Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	1.129	0.817	0.593	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	1.150	0.838	0.613	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
100	1.172	0.859	0.633	0.457	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	1.193	0.879	0.653	0.476	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	1.215	0.900	0.673	0.496	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	1.236	0.921	0.693	0.515	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120	1.258	0.942	0.713	0.534	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
125	1.280	0.963	0.733	0.554	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
130	1.301	0.983	0.753	0.573	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
135 140	1.323 1.344	1.004	0.773	0.593	0.454 0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454 0.454	0.454	0.454	0.454
145	1.366	1.046	0.793 0.813	0.612 0.632	0.454	0.454 0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454						
150	1.387	1.040	0.833	0.651	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
155	1.409	1.087	0.853	0.670	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
160	1.430	1.108	0.873	0.690	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
165	1.452	1.129	0.892	0.709	0.462	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
170	1.474	1.150	0.912	0.729	0.482	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
175	1.495	1.170	0.932	0.748	0.502	0.460	0.458	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
180	1.517	1.191	0.952	0.768	0.521	0.478	0.476	0.464	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
185	1.538	1.212	0.972	0.787	0.541	0.496	0.495	0.482	0.469	0.454	0.454	0.454	0.454	0.454	0.454	0.454
190	1.560	1.233	0.992	0.807	0.561	0.515	0.513	0.500	0.487	0.469	0.465	0.462	0.454	0.454	0.454	0.454
195	1.581	1.254	1.012	0.826	0.581	0.533	0.531	0.518	0.504	0.487	0.482	0.479	0.454	0.454	0.454	0.454
200	1.603	1.274	1.032	0.845	0.600	0.552	0.550	0.536	0.522	0.504	0.499	0.496	0.468	0.454	0.454	0.454
205	1.624	1.295	1.052	0.865	0.620	0.570	0.568	0.554	0.540	0.521	0.516	0.513	0.484	0.454	0.454	0.454
210	1.646	1.316	1.072	0.884	0.640	0.589	0.587	0.572	0.557	0.538	0.533	0.530	0.501	0.454	0.454	0.454
215	1.668	1.337	1.092 1.112	0.904	0.660	0.607	0.605	0.590	0.575	0.556	0.550	0.547	0.517	0.464 0.479	0.454	0.454
220 225	1.693 1.728	1.358 1.378	1.112	0.923	0.679	0.625 0.644	0.623 0.642	0.608 0.626	0.593 0.611	0.573 0.590	0.567 0.584	0.564 0.580	0.533 0.549	0.479	0.454 0.454	0.454 0.454
230	1.762	1.378	1.152	0.943	0.699	0.662	0.660	0.626	0.611	0.607	0.601	0.597	0.566	0.494	0.454	0.454
235	1.797	1.420	1.172	0.981	0.719	0.681	0.678	0.662	0.646	0.624	0.618	0.614	0.582	0.523	0.454	0.454
240	1.831	1.441	1.192	1.001	0.758	0.699	0.697	0.680	0.664	0.642	0.636	0.631	0.598	0.538	0.454	0.454
245	1.866	1.462	1.212	1.020	0.778	0.718	0.715	0.698	0.681	0.659	0.653	0.648	0.615	0.553	0.454	0.454
250	1.900	1.482	1.232	1.040	0.798	0.736	0.734	0.716	0.699	0.676	0.670	0.665	0.631	0.568	0.467	0.454
255	1.935	1.503	1.252	1.059	0.817	0.755	0.752	0.734	0.717	0.693	0.687	0.682	0.647	0.583	0.479	0.454
260	1.969	1.524	1.272	1.079	0.837	0.773	0.770	0.752	0.735	0.711	0.704	0.699	0.663	0.598	0.492	0.454
265	2.004	1.545	1.292	1.098	0.857	0.791	0.789	0.770	0.752	0.728	0.721	0.716	0.680	0.612	0.504	0.454
270	2.038	1.565	1.311	1.117	0.877	0.810	0.807	0.789	0.770	0.745	0.738	0.733	0.696	0.627	0.517	0.454
275	2.073	1.586	1.331	1.137	0.896	0.828	0.826	0.807	0.788	0.762	0.755	0.750	0.712	0.642	0.529	0.454
280	2.107	1.607	1.351	1.156	0.916	0.847	0.844	0.825	0.805	0.780	0.772	0.767	0.729	0.657	0.542	0.454
285	2.142	1.628	1.371	1.176	0.936	0.865	0.862	0.843	0.823	0.797	0.789	0.784	0.745	0.672	0.554	0.454
290	2.176	1.649	1.391	1.195	0.956	0.884	0.881	0.861	0.841	0.814	0.806	0.801	0.761	0.687	0.567	0.454
295	2.211	1.669	1.411	1.215	0.975	0.902	0.899	0.879	0.859	0.831	0.823	0.818	0.777	0.701	0.579	0.454
300	2.245	1.697	1.431	1.234	0.995	0.920	0.918	0.897	0.876	0.849	0.841	0.835	0.794	0.716	0.592	0.454
305 310	2.280	1.734 1.771	1.451 1.471	1.253 1.273	1.015 1.035	0.939 0.957	0.936 0.954	0.915 0.933	0.894 0.912	0.866 0.883	0.858 0.875	0.852 0.869	0.810 0.826	0.731 0.746	0.604 0.617	0.462 0.472
310	2.314	1.771	1.471	1.273	1.035	0.957	0.954	0.933	0.912	0.883	0.875	0.889	0.826	0.746	0.617	0.472
320	2.383	1.845	1.511	1.312	1.034	0.976	0.973	0.969	0.930	0.900	0.892	0.903	0.859	0.761	0.642	0.481
325	2.418	1.882	1.531	1.331	1.094	1.013	1.009	0.987	0.965	0.935	0.926	0.920	0.875	0.770	0.654	0.501
330	2.452	1.919	1.551	1.351	1.113	1.013	1.003	1.005	0.983	0.952	0.943	0.937	0.891	0.805	0.667	0.511
335	2.487	1.956	1.571	1.370	1.133	1.050	1.046	1.023	1.000	0.969	0.960	0.954	0.908	0.820	0.679	0.521
340	2.521	1.994	1.591	1.389	1.153	1.068	1.065	1.041	1.018	0.986	0.977	0.971	0.924	0.835	0.692	0.531
345	2.556	2.031	1.611	1.409	1.173	1.086	1.083	1.059	1.036	1.004	0.994	0.988	0.940	0.850	0.704	0.541
350	2.590	2.068	1.631	1.428	1.192	1.105	1.101	1.077	1.054	1.021	1.011	1.005	0.956	0.865	0.717	0.551
355	2.625	2.105	1.651	1.448	1.212	1.123	1.120	1.095	1.071	1.038	1.028	1.022	0.973	0.880	0.729	0.561
360	2.659	2.142	1.671	1.467	1.232	1.142	1.138	1.113	1.089	1.055	1.046	1.039	0.989	0.895	0.742	0.570

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 5 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

						Table	1 CC901 1	20 I/H Bean	nc 60 minut	oc						
								n) for a Desi								
Section Factor						lequireu III	ickiiess (iiiii	i) ioi a Desi	gii reilipera	iture (C)						
(m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	1.695	1.329	1.045	0.822	0.612	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	1.723	1.349	1.043	0.822	0.632	0.575	0.573	0.556	0.537	0.510	0.502	0.496	0.454	0.454	0.454	0.454
100	1.751	1.369	1.089	0.865	0.653	0.595	0.593	0.576	0.557	0.510	0.522	0.516	0.469	0.454	0.454	0.454
105	1.780	1.389	1.111	0.887	0.674	0.616	0.613	0.596	0.577	0.550	0.541	0.535	0.488	0.454	0.454	0.454
110	1.808	1.409	1.133	0.908	0.695	0.636	0.633	0.616	0.597	0.569	0.561	0.555	0.508	0.454	0.454	0.454
115	1.836	1.429	1.156	0.930	0.716	0.656	0.654	0.636	0.617	0.589	0.581	0.575	0.527	0.454	0.454	0.454
120	1.865	1.448	1.178	0.951	0.737	0.676	0.674	0.656	0.637	0.609	0.600	0.594	0.547	0.454	0.454	0.454
125	1.893	1.468	1.200	0.973	0.758	0.697	0.694	0.676	0.656	0.629	0.620	0.614	0.566	0.454	0.454	0.454
130	1.921	1.488	1.222	0.994	0.778	0.717	0.714	0.696	0.676	0.648	0.640	0.634	0.586	0.464	0.454	0.454
135	1.950	1.508	1.244	1.015	0.799	0.737	0.735	0.716	0.696	0.668	0.659	0.653	0.605	0.484	0.454	0.454
140	1.978	1.528	1.267	1.037	0.820	0.757	0.755	0.736	0.716	0.688	0.679	0.673	0.625	0.503	0.454	0.454
145	2.006	1.548	1.289	1.058	0.841	0.778	0.775	0.756	0.736	0.708	0.699	0.693	0.644	0.522	0.454	0.454
150	2.034	1.568	1.311	1.080	0.862	0.798	0.795	0.776	0.756	0.727	0.719	0.712	0.663	0.542	0.454	0.454
155	2.063	1.588	1.333	1.101	0.883	0.818	0.815	0.796	0.776	0.747	0.738	0.732	0.683	0.561	0.454	0.454
160	2.091	1.608	1.355	1.123	0.903	0.838	0.836	0.816	0.796	0.767	0.758	0.752	0.702	0.581	0.454	0.454
165	2.119	1.628	1.378	1.144	0.924	0.859	0.856	0.836	0.816	0.787	0.778	0.771	0.722	0.600	0.454	0.454
170	2.148	1.647	1.400	1.166	0.945	0.879	0.876	0.856	0.836	0.806	0.797	0.791	0.741	0.619	0.458	0.454
175	2.176	1.667	1.422	1.187	0.966	0.899	0.896	0.877	0.856	0.826	0.817	0.811	0.761	0.639	0.476	0.454
180	2.204	1.691	1.444	1.209	0.987	0.919	0.916	0.897	0.876	0.846	0.837	0.830	0.780	0.658	0.494	0.454
185	2.233	1.727	1.466	1.230	1.008	0.939	0.937	0.917	0.896	0.866	0.856	0.850	0.800	0.678	0.512	0.454
190	2.261	1.763	1.489	1.252	1.029	0.960	0.957	0.937	0.916	0.885	0.876	0.870	0.819	0.697	0.530	0.454
195	2.289	1.799	1.511	1.273	1.049	0.980	0.977	0.957	0.936	0.905	0.896	0.889	0.839	0.716	0.548	0.454
200	2.318	1.835	1.533	1.295	1.070	1.000	0.997	0.977	0.956	0.925	0.916	0.909	0.858	0.736	0.566	0.460
205	2.346	1.871	1.555	1.316	1.091	1.020	1.017	0.997	0.975	0.945	0.935	0.929	0.878	0.755	0.584	0.475
210	2.374	1.907	1.577	1.337	1.112	1.041	1.038	1.017	0.995	0.964	0.955	0.948	0.897	0.774	0.602	0.490
215	2.402	1.943	1.600	1.359	1.133	1.061	1.058	1.037	1.015	0.984	0.975	0.968	0.917	0.794	0.620	0.505
220	2.431	1.979 2.015	1.622 1.644	1.380	1.154	1.081	1.078 1.098	1.057	1.035	1.004 1.024	0.994 1.014	0.988	0.936	0.813 0.833	0.639	0.520
225 230	2.459	2.015	1.666	1.402 1.423	1.175 1.195	1.101 1.122	1.119	1.077 1.097	1.055 1.075	1.024	1.014	1.007 1.027	0.956 0.975	0.852	0.657 0.675	0.535 0.550
235	2.516	2.031	1.693	1.445	1.193	1.142	1.119	1.117	1.075	1.043	1.053	1.047	0.994	0.832	0.693	0.565
240	2.544	2.122	1.732	1.466	1.237	1.162	1.159	1.117	1.115	1.083	1.073	1.066	1.014	0.891	0.711	0.580
245	2.572	2.158	1.770	1.488	1.258	1.182	1.179	1.157	1.135	1.103	1.093	1.086	1.033	0.910	0.729	0.595
250	2.601	2.194	1.809	1.509	1.279	1.202	1.199	1.177	1.155	1.122	1.113	1.106	1.053	0.930	0.747	0.610
255	2.629	2.230	1.848	1.531	1.300	1.223	1.220	1.197	1.175	1.142	1.132	1.125	1.072	0.949	0.765	0.625
260	2.657	2.266	1.886	1.552	1.321	1.243	1.240	1.217	1.195	1.162	1.152	1.145	1.092	0.968	0.783	0.640
265	2.686	2.302	1.925	1.574	1.341	1.263	1.260	1.238	1.215	1.182	1.172	1.165	1.111	0.988	0.801	0.655
270	2.714	2.338	1.964	1.595	1.362	1.283	1.280	1.258	1.235	1.201	1.191	1.184	1.131	1.007	0.820	0.671
275	2.742	2.374	2.003	1.617	1.383	1.304	1.300	1.278	1.255	1.221	1.211	1.204	1.150	1.027	0.838	0.686
280	2.770	2.410	2.041	1.638	1.404	1.324	1.321	1.298	1.274	1.241	1.231	1.224	1.170	1.046	0.856	0.701
285	2.810	2.446	2.080	1.659	1.425	1.344	1.341	1.318	1.294	1.261	1.250	1.243	1.189	1.065	0.874	0.716
290	2.859	2.482	2.119	1.681	1.446	1.364	1.361	1.338	1.314	1.280	1.270	1.263	1.209	1.085	0.892	0.731
295	2.908	2.518	2.157	1.722	1.466	1.385	1.381	1.358	1.334	1.300	1.290	1.283	1.228	1.104	0.910	0.746
300	2.957	2.554	2.196	1.763	1.487	1.405	1.401	1.378	1.354	1.320	1.310	1.302	1.248	1.124	0.928	0.761
305	3.006	2.590	2.235	1.805	1.508	1.425	1.422	1.398	1.374	1.340	1.329	1.322	1.267	1.143	0.946	0.776
310	3.055	2.625	2.273	1.846	1.529	1.445	1.442	1.418	1.394	1.359	1.349	1.342	1.287	1.162	0.964	0.791
315	3.104	2.661	2.312	1.888	1.550	1.466	1.462	1.438	1.414	1.379	1.369	1.361	1.306	1.182	0.982	0.806
320	3.153	2.697	2.351	1.930	1.571	1.486	1.482	1.458	1.434 1.454	1.399 1.419	1.388 1.408	1.381	1.326	1.201	1.001	0.821
325 330	3.203 3.252	2.733 2.769	2.389 2.428	1.971 2.013	1.592	1.506	1.503	1.478 1.498	1.454	1.419	1.408	1.401 1.420	1.345 1.364	1.221 1.240	1.019	0.836
330	3.301	2.769	2.428	2.013	1.612 1.633	1.526 1.546	1.523 1.543	1.498	1.474	1.438	1.428	1.440	1.364	1.240	1.037 1.055	0.851 0.866
335	3.301	2.819	2.467	2.055	1.654	1.546	1.543	1.518	1.494	1.458	1.447	1.440	1.403	1.259	1.055	0.881
345	3.399	2.937	2.544	2.138	1.675	1.587	1.583	1.558	1.514	1.478	1.487	1.479	1.403	1.279	1.073	0.896
350	3.448	2.997	2.583	2.130	1.711	1.607	1.604	1.578	1.554	1.517	1.506	1.499	1.442	1.318	1.109	0.830
355	3.448	3.056	2.621	2.221	1.755	1.627	1.624	1.598	1.573	1.537	1.526	1.519	1.442	1.337	1.103	0.911
360	3.546	3.115	2.660	2.263	1.798	1.648	1.644	1.619	1.593	1.557	1.546	1.538	1.481	1.356	1.145	0.941
550	5.540	5.415	2.300	03	2.750	2.040	2.077	2.010	2.555	2.557	1.540	2.550	2.701	1.550	2.173	J.J-1

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 6 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Nulli			J 1 - 1.			Tabla	F CC001 1	20 1/11 Dans	75							
								.20 I/H Bean								
Cartian Factor					'	Required Th	ickness (mr	n) for a Desi	gn rempera	iture (C)			1			
Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	2.441	1.777	1.488	1.228	1.003	0.902	0.899	0.873	0.846	0.811	0.801	0.794	0.745	0.621	0.454	0.454
95	2.495	1.811	1.514	1.248	1.025	0.924	0.921	0.894	0.868	0.832	0.822	0.815	0.765	0.641	0.546	0.454
100	2.550	1.846	1.541	1.267	1.047	0.946	0.943	0.916	0.889	0.854	0.843	0.836	0.786	0.662	0.565	0.454
105	2.604	1.880	1.567	1.287	1.069	0.968	0.965	0.938	0.911	0.875	0.864	0.857	0.806	0.683	0.585	0.454
110	2.658	1.914	1.593	1.306	1.091	0.990	0.987	0.960	0.933	0.896	0.885	0.878	0.827	0.704	0.604	0.454
115	2.713	1.948	1.620	1.325	1.113	1.013	1.009	0.981	0.954	0.918	0.907	0.899	0.847	0.725	0.624	0.454
120	2.767	1.982	1.646	1.345	1.136	1.035	1.031	1.003	0.976	0.939	0.928	0.920	0.868	0.746	0.643	0.460
125	2.807	2.016	1.673	1.364	1.158	1.057	1.053	1.025	0.998	0.960	0.949	0.942	0.888	0.767	0.662	0.478
130	2.840	2.050	1.705	1.384	1.180	1.079	1.075	1.047	1.019	0.981	0.970	0.963	0.909	0.788	0.682	0.497
135	2.873	2.084	1.739	1.403	1.202	1.101	1.097	1.069	1.041	1.003	0.991	0.984	0.929	0.809	0.701	0.515
140	2.906	2.118	1.773	1.423	1.224	1.123	1.119	1.090	1.063	1.024	1.013	1.005	0.950	0.829	0.721	0.533
145	2.939	2.152	1.808	1.442	1.246	1.145	1.141	1.112	1.084	1.045	1.034	1.026	0.970	0.850	0.740	0.552
150	2.971	2.187	1.842	1.461	1.269	1.167	1.163	1.134	1.106	1.067	1.055	1.047	0.991	0.871	0.759	0.570
155	3.004	2.221	1.876	1.481	1.291	1.189	1.185	1.156	1.128	1.088	1.076	1.068	1.012	0.892	0.779	0.589
160	3.037	2.255	1.911	1.500	1.313	1.211	1.207	1.177	1.149	1.109	1.097	1.090	1.032	0.913	0.798	0.607
165	3.070	2.289	1.945	1.520	1.335	1.233	1.229	1.199	1.171	1.131	1.119	1.111	1.053	0.934	0.817	0.626
170	3.103	2.323	1.980	1.539	1.357	1.255	1.251	1.221	1.193	1.152	1.140	1.132	1.073	0.955	0.837	0.644
175	3.136	2.357	2.014	1.559	1.379	1.277	1.273	1.243	1.214	1.173	1.161	1.153	1.094	0.976	0.856	0.662
180	3.169	2.391	2.048	1.578	1.402	1.299	1.295	1.265	1.236	1.195	1.182	1.174	1.114	0.996	0.876	0.681
185	3.202	2.425	2.083	1.597	1.424	1.321	1.317	1.286	1.258	1.216	1.203	1.195	1.135	1.017	0.895	0.699
190	3.235	2.459	2.117	1.617	1.446	1.343	1.339	1.308	1.279	1.237	1.225	1.216	1.155	1.038	0.914	0.718
195	3.268	2.493	2.151	1.636	1.468	1.365	1.361	1.330	1.301	1.258	1.246	1.238	1.176	1.059	0.934	0.736
200	3.301	2.528	2.186	1.656	1.490	1.387	1.383	1.352	1.323	1.280	1.267	1.259	1.196	1.080	0.953	0.755
205	3.334	2.562	2.220	1.675	1.512	1.409	1.405	1.374	1.344	1.301	1.288	1.280	1.217	1.101	0.972	0.773
210	3.367	2.596	2.255	1.710	1.535	1.431	1.427	1.395	1.366	1.322	1.310	1.301	1.237	1.122	0.992	0.791
215	3.400	2.630	2.289	1.753	1.557	1.453	1.449	1.417	1.388	1.344	1.331	1.322	1.258	1.143	1.011	0.810
220	3.433	2.664	2.323	1.796	1.579	1.475	1.471	1.439	1.409	1.365	1.352	1.343	1.278	1.164	1.031	0.828
225	3.466	2.698	2.358	1.839	1.601	1.497	1.493	1.461	1.431	1.386	1.373	1.364	1.299	1.184	1.050	0.847
230	3.499	2.732	2.392	1.882	1.623	1.519	1.515	1.482	1.452	1.408	1.394	1.386	1.319	1.205	1.069	0.865
235	3.532	2.766	2.427	1.925	1.645	1.541	1.537	1.504	1.474	1.429	1.416	1.407	1.340	1.226	1.089	0.884
240	3.565	2.810	2.461	1.968	1.668	1.563	1.559	1.526	1.496	1.450	1.437	1.428	1.360	1.247	1.108	0.902
245	3.598	2.865	2.495	2.012	1.697	1.585	1.581	1.548	1.517	1.472	1.458	1.449	1.381	1.268	1.128	0.920
250	3.631	2.920	2.530	2.055	1.739	1.607	1.603	1.570	1.539	1.493	1.479	1.470	1.401	1.289	1.147	0.939
255	3.664	2.975	2.564	2.098	1.782	1.629	1.625	1.591	1.561	1.514	1.500	1.491	1.422	1.310	1.166	0.957
260	3.697	3.029	2.598	2.141	1.824	1.651	1.647	1.613	1.582	1.536	1.522	1.512	1.442	1.331	1.186	0.976
265	3.730	3.084	2.633	2.184	1.867	1.673	1.669	1.635	1.604	1.557	1.543	1.534	1.463	1.351	1.205	0.994
270	3.763	3.139	2.667	2.227	1.909	1.708	1.700	1.657	1.626	1.578	1.564	1.555	1.483	1.372	1.224	1.013
275	3.796	3.194	2.702	2.270	1.952	1.752	1.744	1.678	1.647	1.599	1.585	1.576	1.504	1.393	1.244	1.031
280	3.828	3.248	2.736	2.313	1.994	1.796	1.788	1.719	1.669	1.621	1.606	1.597	1.524	1.414	1.263	1.049
285	3.861	3.303	2.770	2.356	2.037	1.840	1.832	1.764	1.700	1.642	1.628	1.618	1.545	1.435	1.283	1.068
290	3.894	3.358	2.828	2.399	2.079	1.884	1.876	1.809	1.745	1.663	1.649	1.639	1.565	1.456	1.302	1.086
295	3.927	3.413	2.900	2.443	2.122	1.927	1.920	1.853	1.790	1.688	1.670	1.660	1.586	1.477	1.321	1.105
300	3.960	3.468	2.973	2.486	2.164	1.971	1.963	1.898	1.835	1.734	1.702	1.682	1.607	1.498	1.341	1.123
305	-	3.522	3.045	2.529	2.207	2.015	2.007	1.943	1.881	1.780	1.749	1.728	1.627	1.518	1.360	1.142
310	-	3.577	3.117	2.572	2.249	2.059	2.051	1.987	1.926	1.827	1.796	1.775	1.648	1.539	1.379	1.160
315	-	3.632	3.190	2.615	2.292	2.103	2.095	2.032	1.971	1.873	1.842	1.822	1.668	1.560	1.399	1.178
320	-	3.687	3.262	2.658	2.334	2.146	2.139	2.077	2.016	1.919	1.889	1.868	1.698	1.581	1.418	1.197
325	-	3.741	3.335	2.701	2.377	2.190	2.183	2.121	2.061	1.965	1.935	1.915	1.747	1.602	1.438	1.215
330	-	3.796	3.407	2.744	2.419	2.234	2.226	2.166	2.106	2.012	1.982	1.962	1.796	1.623	1.457	1.234
335	-	3.851	3.479	2.792	2.462	2.278	2.270	2.210	2.151	2.058	2.029	2.009	1.845	1.644	1.476	1.252
340	-	3.906	3.552	2.889	2.504	2.322	2.314	2.255	2.197	2.104	2.075	2.056	1.893	1.665	1.496	1.271
345	-	3.960	3.624	2.987	2.547	2.365	2.358	2.300	2.242	2.151	2.122	2.103	1.942	1.690	1.515	1.289
350	-	-	3.697	3.084	2.589	2.409	2.402	2.344	2.287	2.197	2.168	2.149	1.991	1.738	1.535	1.307
355	-	-	3.769	3.182	2.632	2.453	2.446	2.389	2.332	2.243	2.215	2.196	2.040	1.786	1.554	1.326
360	-	-	3.841	3.280	2.674	2.497	2.490	2.434	2.377	2.289	2.262	2.243	2.089	1.834	1.573	1.344

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 7 of 34 Signed E/200

Pol agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Mulli			<u> </u>			Table	. c c c c c c c c c c c c c c c c c c c	120 1/4 000	ms 00 minu	tor						
								120 I/H Bea m) for a Des								
Costion		I				Required II	lickness (mi	n) for a Des	ign remper	ature (C)	l	I	I			1
Section	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
Factor (m-1) 90	3.126	2.566	2.068	1.620	1.379	1.263	1.259	1.228	1.198	1.156	1.144	1.136	1.078	0.969	0.801	0.621
95	3.210	2.631	2.106	1.652	1.396	1.281	1.277	1.247	1.198	1.176	1.144	1.156	1.078	0.969	0.822	0.621
100	3.210	2.697	2.106	1.684	1.412	1.300	1.277	1.247	1.217	1.176	1.185	1.177	1.119	1.010	0.842	0.641
105	3.378	2.762	2.143	1.719	1.412	1.318	1.314	1.285	1.256	1.136	1.205	1.177	1.119	1.010	0.862	0.680
110	3.461	2.813	2.221	1.719	1.446	1.336	1.332	1.304	1.276	1.216	1.205	1.197	1.140	1.051	0.882	0.700
115	3.545	2.857	2.259	1.789	1.440	1.354	1.350	1.323	1.295	1.257	1.225	1.217	1.101	1.032	0.903	0.719
120	3.629	2.901	2.233	1.825	1.479	1.372	1.369	1.342	1.314	1.277	1.245	1.258	1.203	1.073	0.923	0.719
125	3.713	2.945	2.336	1.860	1.495	1.372	1.387	1.342	1.334	1.297	1.286	1.278	1.224	1.115	0.943	0.759
130	3.797	2.989	2.374	1.895	1.512	1.409	1.405	1.380	1.353	1.317	1.306	1.299	1.244	1.113	0.964	0.778
135	3.880	3.033	2.412	1.930	1.529	1.427	1.423	1.399	1.373	1.337	1.326	1.319	1.265	1.157	0.984	0.798
140	3.964	3.077	2.450	1.966	1.545	1.445	1.442	1.418	1.392	1.357	1.346	1.339	1.286	1.178	1.004	0.818
145	-	3.121	2.488	2.001	1.562	1.463	1.460	1.436	1.412	1.377	1.367	1.360	1.307	1.199	1.024	0.837
150	-	3.165	2.527	2.036	1.578	1.481	1.478	1.455	1.431	1.397	1.387	1.380	1.328	1.220	1.045	0.857
155	-	3.209	2.565	2.071	1.595	1.500	1.496	1.474	1.451	1.417	1.407	1.400	1.348	1.241	1.065	0.877
160	-	3.253	2.603	2.107	1.612	1.518	1.515	1.493	1.470	1.437	1.427	1.421	1.369	1.262	1.085	0.896
165	-	3.296	2.641	2.142	1.628	1.536	1.533	1.512	1.490	1.458	1.448	1.441	1.390	1.282	1.105	0.916
170	-	3.340	2.679	2.177	1.645	1.554	1.551	1.531	1.509	1.478	1.468	1.461	1.411	1.303	1.126	0.936
175	-	3.384	2.718	2.212	1.661	1.572	1.570	1.550	1.529	1.498	1.488	1.481	1.432	1.324	1.146	0.955
180	-	3.428	2.756	2.248	1.678	1.591	1.588	1.569	1.548	1.518	1.508	1.502	1.453	1.345	1.166	0.975
185	-	3.472	2.798	2.283	1.719	1.609	1.606	1.588	1.567	1.538	1.528	1.522	1.473	1.366	1.187	0.995
190	-	3.516	2.851	2.318	1.768	1.627	1.624	1.607	1.587	1.558	1.549	1.542	1.494	1.387	1.207	1.014
195	-	3.560	2.905	2.353	1.817	1.645	1.643	1.626	1.606	1.578	1.569	1.563	1.515	1.408	1.227	1.034
200	-	3.604	2.958	2.389	1.866	1.663	1.661	1.645	1.626	1.598	1.589	1.583	1.536	1.429	1.247	1.054
205	-	3.648	3.011	2.424	1.915	1.681	1.679	1.664	1.645	1.618	1.609	1.603	1.557	1.450	1.268	1.073
210	-	3.692	3.064	2.459	1.963	1.729	1.723	1.684	1.665	1.638	1.630	1.624	1.577	1.471	1.288	1.093
215	-	3.736	3.118	2.494	2.012	1.777	1.771	1.730	1.687	1.659	1.650	1.644	1.598	1.492	1.308	1.112
220	1	3.780	3.171	2.530	2.061	1.825	1.819	1.776	1.734	1.679	1.670	1.664	1.619	1.513	1.328	1.132
225	-	3.823	3.224	2.565	2.110	1.873	1.867	1.823	1.780	1.721	1.701	1.688	1.640	1.534	1.349	1.152
230	-	3.867	3.277	2.600	2.159	1.921	1.915	1.869	1.827	1.767	1.747	1.734	1.661	1.555	1.369	1.171
235	-	3.911	3.331	2.635	2.208	1.970	1.963	1.916	1.873	1.813	1.794	1.781	1.682	1.575	1.389	1.191
240	-	3.955	3.384	2.671	2.256	2.018	2.011	1.962	1.919	1.860	1.840	1.827	1.728	1.596	1.410	1.211
245	-	-	3.437	2.706	2.305	2.066	2.059	2.009	1.966	1.906	1.887	1.873	1.774	1.617	1.430	1.230
250	-	-	3.490	2.741	2.354	2.114	2.107	2.055	2.012	1.952	1.933	1.920	1.821	1.638	1.450	1.250
255	-	-	3.544	2.776	2.403	2.162	2.155	2.101	2.058	1.999	1.979	1.966	1.867	1.659	1.470	1.270
260	-	-	3.597	2.850	2.452	2.211	2.203	2.148	2.105	2.045	2.026	2.013	1.914	1.680	1.491	1.289
265	-	-	3.650	2.934	2.501	2.259	2.251	2.194	2.151	2.091	2.072	2.059	1.961	1.726	1.511	1.309
270	-	-	3.703	3.017	2.549	2.307	2.299	2.241	2.198	2.138	2.118	2.106	2.007	1.774	1.531	1.329
275	-	-	3.757	3.101	2.598	2.355	2.347	2.287	2.244	2.184	2.165	2.152	2.054	1.822	1.551	1.348
280	-	-	3.810	3.185	2.647	2.403	2.395	2.334	2.290	2.230	2.211	2.198	2.100	1.870	1.572	1.368
285 290			3.863	3.269	2.696	2.452 2.500	2.443	2.380	2.337	2.277	2.258	2.245	2.147 2.194	1.919	1.592	1.388
290	-	-	3.916 3.970	3.353 3.436	2.745 2.804	2.548	2.491 2.539	2.427 2.473	2.383 2.430	2.323	2.304 2.350	2.291 2.338	2.194	1.967	1.612	1.407
300	-	-	3.970	3.436	2.804			2.473		2.369	2.350	2.338	2.240	2.015	1.633	
300	-	-		3.520	3.003	2.596 2.644	2.587 2.635	2.519	2.476 2.522	2.416 2.462	2.397	2.430	2.287	2.063 2.111	1.653	1.447 1.466
310	-	-	-	3.688	3.102	2.693	2.683	2.566	2.522	2.462	2.443	2.430	2.333	2.111	1.673 1.710	1.486
310		-	-	3.688	3.102	2.693	2.683	2.659	2.569	2.508	2.490	2.477	2.380	2.160	1.710	1.486
315	<u> </u>	-	<u> </u>	3.772	3.302	2.741	2.731	2.705		2.555	2.536	2.523	2.427	2.208	1.761	1.506
325	-	-	-	3.855	3.401	2.796	2.779	2.752	2.662 2.708	2.647	2.582	2.570	2.473	2.256	1.811	1.525
330	-	-	-	3.939	3.501	3.042	3.018	2.825	2.754	2.694	2.675	2.663	2.566	2.352	1.912	1.565
335	-	-	-	-	3.600	3.165	3.143	2.960	2.833	2.740	2.721	2.709	2.613	2.332	1.912	1.584
340	-	-	-	-	3.700	3.288	3.267	3.096	2.970	2.740	2.721	2.755	2.660	2.449	2.012	1.604
345	-	-		-	3.800	3.410	3.391	3.231	3.106	2.791	2.708	2.733	2.706	2.449	2.012	1.624
350	-	-	-	-	3.899	3.533	3.515	3.366	3.243	3.067	3.010	2.972	2.753	2.545	2.113	1.643
355	-	-	-	-	3.033	3.656	3.639	3.502	3.379	3.205	3.147	3.109	2.733	2.593	2.113	1.663
360	-	-	-		-	3.779	3.763	3.637	3.516	3.343	3.284	3.245	2.969	2.642	2.214	1.683
Tobl			ootion k			doc fire	3.703	100 and	0.0000	roto olo				intumor	2.214	1.003

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 8 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

						Table 7	SC801 - 12	0 I/H Beam	ıs 105 minu	ites						
					Req	uired Thic	kness (mm) for a Des	ign Tempe	rature (°C)						
Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
90	-	3.189	2.716	2.238	1.737	1.610	1.605	1.573	1.542	1.498	1.486	1.478	1.416	1.290	1.093	0.917
95	-	3.280	2.785	2.284	1.778	1.638	1.634	1.600	1.566	1.520	1.507	1.498	1.432	1.307	1.113	0.937
100	-	3.371	2.854	2.331	1.818	1.667	1.662	1.627	1.591	1.542	1.528	1.518	1.448	1.324	1.133	0.957
105	-	3.462	2.923	2.378	1.859	1.701	1.694	1.653	1.615	1.563	1.548	1.538	1.464	1.341	1.153	0.977
110	-	3.553	2.992	2.424	1.900	1.741	1.734	1.680	1.639	1.585	1.569	1.558	1.480	1.358	1.173	0.996
115	-	3.644	3.061	2.471	1.941	1.781	1.774	1.720	1.664	1.607	1.589	1.578	1.496	1.375	1.193	1.016
120	-	3.735	3.129	2.518	1.982	1.821	1.814	1.761	1.692	1.628	1.610	1.597	1.512	1.392	1.213	1.036
125	-	3.825	3.198	2.564	2.022	1.861	1.854	1.802	1.732	1.650	1.631	1.617	1.528	1.409	1.233	1.056
130	-	3.916	3.267	2.611	2.063	1.901	1.894	1.843	1.773	1.672	1.651	1.637	1.544	1.426	1.253	1.075
135	-	-	3.336	2.658	2.104	1.941	1.934	1.884	1.813	1.704	1.672	1.657	1.561	1.443	1.273	1.095
140	-	-	3.405	2.704	2.145	1.981	1.975	1.925	1.854	1.746	1.704	1.677	1.577	1.460	1.293	1.115
145	-	-	3.473	2.751	2.186	2.021	2.015	1.966	1.894	1.789	1.747	1.714	1.593	1.476	1.313	1.134
150	-	-	3.542	2.798	2.226	2.061	2.055	2.007	1.934	1.831	1.790	1.758	1.609	1.493	1.333	1.154
155	-	-	3.611	2.848	2.267	2.101	2.095	2.048	1.975	1.873	1.833	1.802	1.625	1.510	1.353	1.174
160	-	-	3.680	2.897	2.308	2.141	2.135	2.089	2.015	1.915	1.876	1.846	1.641	1.527	1.373	1.194
165	-	-	3.749	2.947	2.349	2.181	2.175	2.130	2.056	1.958	1.920	1.890	1.657	1.544	1.393	1.213
170	-	-	3.818	2.996	2.390	2.221	2.215	2.171	2.096	2.000	1.963	1.934	1.673	1.561	1.413	1.233
175	-	-	3.886	3.045	2.430	2.261	2.255	2.212	2.137	2.042	2.006	1.978	1.705	1.578	1.433	1.253
180	-	-	3.955	3.095	2.471	2.302	2.296	2.253	2.177	2.084	2.049	2.022	1.757	1.595	1.453	1.273
185	-	-	-	3.144	2.512	2.342	2.336	2.294	2.217	2.126	2.092	2.066	1.808	1.612	1.473	1.292
190	-	-	-	3.194	2.553	2.382	2.376	2.335	2.258	2.169	2.135	2.110	1.860	1.629	1.494	1.312
195	-	-	-	3.243	2.594	2.422	2.416	2.376	2.298	2.211	2.178	2.154	1.912	1.646	1.514	1.332
200	-	-	-	3.292	2.634	2.462	2.456	2.417	2.339	2.253	2.222	2.198	1.964	1.663	1.534	1.352
205	-	-	-	3.342	2.675	2.502	2.496	2.458	2.379	2.295	2.265	2.242	2.016	1.680	1.554	1.371
210	-	-	-	3.391	2.716	2.542	2.536	2.500	2.419	2.338	2.308	2.286	2.068	1.729	1.574	1.391
215	-	-	-	3.441	2.757	2.582	2.577	2.541	2.460	2.380	2.351	2.330	2.120	1.784	1.594	1.411
220	-	-	-	3.490	2.810	2.622	2.617	2.582	2.500	2.422	2.394	2.374	2.172	1.839	1.614	1.431
225	-	-	-	3.539	2.887	2.662	2.657	2.623	2.541	2.464	2.437	2.418	2.223	1.894	1.634	1.450
230	-	-	-	3.589	2.964	2.702	2.697	2.664	2.581	2.506	2.480	2.462	2.275	1.948	1.654	1.470
235	-	-	-	3.638	3.041	2.742	2.737	2.705	2.622	2.549	2.524	2.505	2.327	2.003	1.674	1.490
240	-	-	-	3.688	3.118	2.782	2.777	2.746	2.662	2.591	2.567	2.549	2.379	2.058	1.710	1.510
245	-	-	-	3.737	3.195	2.864	2.854	2.790	2.702	2.633	2.610	2.593	2.431	2.113	1.759	1.529
250	-	-	-	3.786	3.272	2.949	2.939	2.874	2.743	2.675	2.653	2.637	2.483	2.168	1.808	1.549
255	-	-	-	3.836	3.349	3.033	3.024	2.958	2.783	2.718	2.696	2.681	2.535	2.222	1.857	1.569
260	-	-	-	3.885	3.426	3.118	3.108	3.042	2.875	2.760	2.739	2.725	2.587	2.277	1.906	1.589
265	-	-	-	3.934	3.503	3.203	3.193	3.126	2.967	2.824	2.782	2.769	2.639	2.332	1.955	1.608
270	-	-	-	3.984	3.580	3.287	3.277	3.209	3.059	2.919	2.876	2.847	2.690	2.387	2.004	1.628
275	-	-	-	-	3.657	3.372	3.362	3.293	3.151	3.014	2.971	2.942	2.742	2.441	2.053	1.648
280	-	-	-	-	3.734	3.457	3.447	3.377	3.244	3.109	3.066	3.037	2.804	2.496	2.102	1.668
285	-	-	-	-	3.811	3.541	3.531	3.461	3.336	3.204	3.161	3.132	2.906	2.551	2.151	1.696
290	-	-	-	-	3.888	3.626	3.616	3.545	3.428	3.299	3.257	3.228	3.009	2.606	2.199	1.746
295	-	-	-	-	3.965	3.711	3.701	3.629	3.521	3.394	3.352	3.323	3.111	2.661	2.248	1.797
300	-	-	-	-	-	3.795	3.785	3.713	3.613	3.489	3.447	3.418	3.213	2.715	2.297	1.848
305	-	-	-	-	-	3.880	3.870	3.797	3.705	3.584	3.542	3.513	3.315	2.770	2.346	1.899
310	-	-	-	-	-	3.964	3.954	3.881	3.797	3.679	3.637	3.608	3.418	2.879	2.395	1.950
315	-	-	-	-	-	-	-	3.965	3.890	3.774	3.732	3.703	3.520	3.007	2.444	2.001
320	-	-	-	-	-	-	-	-	3.982	3.869	3.828	3.799	3.622	3.135	2.493	2.052
325	-	-	-	-	-	-	-	-	-	3.964	3.923	3.894	3.724	3.263	2.542	2.103
330	-	-	-	-	-	-	-	-	-	-	-	3.989	3.827	3.391	2.591	2.154
335	-	-	-	-	-	-	-	-	-	-	-	-	3.929	3.519	2.640	2.204
340	-	-	-	-	-	-	-	-	-	-	-	-	-	3.647	2.689	2.255
345	-	-	-	-	-	-	-	-	-	-	-	-	-	3.774	2.738	2.306
350	-	-	-	-	-	-	-	-	-	-	-	-	-	3.902	2.794	2.357
355	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2.983	2.408
360	-	-	- oction b	-	-	-	-	-	-	- oto clak	-	-	-	-	3.172	2.459

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 9 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Section Sect									20 I/H Bean								
Second S							Required Th	ickness (mi	n) for a Des	ign Temper	ature (°C)						
99	Section Factor (m-1)	350°C	400°C	450°C	500°C	550°C	575°C	576°C	583°C	590°C	600°C	603°C	605°C	620°C	650°C	700°C	750°C
100	90	-	-	3.278	2.851	2.400	2.180	2.171	1.919	1.877	1.835	1.823	1.816	1.743	1.599	1.391	1.190
105 3577 3.088 2.561 2.300 2.298 2.062 2.008 1.963 1.969 1.984 1.867 1.675 1.433 1.144 1.151 1.0 3.677 3.161 2.615 2.344 2.346 2.115 2.095 2.088 2.035 2.026 1.950 1.733 1.447 1.261 1.155 3.777 3.288 2.669 2.885 2.374 2.157 2.095 2.088 2.035 2.026 1.950 1.795 1.461 1.279 1.275 1.261 1.275	95	-	-	3.377	2.929	2.453	2.221	2.212	1.967	1.921	1.877	1.866	1.858	1.784	1.625	1.405	1.208
110	100		-	3.477	3.006	2.507	2.262	2.253	2.014	1.964	1.920	1.908	1.900	1.826	1.650	1.419	1.226
115 .	105		-	3.577	3.083	2.561	2.303	2.293	2.062	2.008	1.963	1.950	1.942	1.867	1.675	1.433	1.244
120	110	-	-	3.677	3.161	2.615	2.344	2.334	2.110	2.051	2.005	1.993	1.984	1.909	1.713	1.447	1.261
125	115	-	-	3.777	3.238	2.669	2.385	2.374	2.157	2.095	2.048	2.035	2.026	1.950	1.755	1.461	1.279
130	120	-	-	3.876	3.316	2.722	2.426	2.415	2.205	2.138	2.091	2.078	2.069	1.992	1.797	1.474	1.297
135	125	-	-	3.976	3.393	2.776	2.467	2.455	2.252	2.182	2.133	2.120	2.111	2.033	1.840	1.488	1.315
140	130	-	-	-	3.470	2.829	2.509	2.496	2.300	2.225	2.176	2.162	2.153	2.074	1.882	1.502	1.333
140	135	-	-	-	3.548	2.882	2.550	2.537	2.348	2.269	2.219	2.205	2.195	2.116	1.924	1.516	1.351
145		-	-	-													
150		-	-	-													
155		-	-	-	3.780				2.490			2.332			2.051		
160		-	-	-													
165			-														
170			-	-													
175																	
180																	
185																	
190			_														
195																	
200																	
205			-		_												
210																	
215 - - - 3.728 3.386 3.372 3.247 3.103 2.999 2.968 2.945 2.778 2.600 1.959 1.637 220 - - - 3.781 3.745 3.432 3.315 3.180 3.078 3.047 3.024 2.855 2.642 2.028 1.655 225 - - - 3.884 3.503 3.491 3.382 3.256 3.156 3.156 3.105 3.103 2.937 2.685 2.097 1.673 230 - - 3.887 3.561 3.550 3.450 3.333 3.234 3.204 3.183 3.019 2.727 2.166 1.707 235 -																	
220			-	-	-												
225 - - - 3.834 3.503 3.491 3.382 3.256 3.156 3.126 3.103 2.937 2.685 2.097 1.673		-	-	-	-												
230 - - - - 3.887 3.561 3.550 3.450 3.333 3.234 3.204 3.183 3.019 2.727 2.166 1.707 235 - - - 3.940 3.620 3.610 3.518 3.409 3.312 3.283 3.262 3.101 2.769 2.236 1.758 240 - - - - 3.737 3.728 3.659 3.586 3.485 3.390 3.362 3.341 3.182 2.841 2.305 1.809 245 - - - - 3.737 3.728 3.653 3.562 3.469 3.440 3.420 3.264 2.929 2.374 1.860 250 - - - - 3.795 3.788 3.721 3.638 3.547 3.519 3.499 3.346 3.017 2.443 1.912 255 - - - - - 3.854 3.847 3.789 3.715 3.625 3.598 3.578 3.428 3.105 2.512 1.963 260 - - - - 3.911 3.966 3.924 3.867 3.781 3.755 3.536 3.592 3.281 2.651 2.065 270 - - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.736 3.592 3.281 2.651 2.065 270 - - - - - - - - -																	
235 - - - 3.940 3.620 3.610 3.518 3.409 3.312 3.283 3.262 3.101 2.769 2.236 1.758 240																	
240 - - - - 3.678 3.669 3.586 3.485 3.390 3.362 3.341 3.182 2.841 2.305 1.809 245 - - - - 3.779 3.728 3.653 3.563 3.547 3.549 3.440 3.420 3.264 2.929 2.374 1.860 250 - - - - 3.739 3.788 3.721 3.638 3.547 3.519 3.499 3.346 3.017 2.443 1.912 255 - - - - 3.912 3.907 3.857 3.791 3.703 3.677 3.657 3.510 3.193 2.581 2.014 260 - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.510 3.193 2.581 2.661 2.065 270 - - - - 3.941 3.861 3.674																	
245 - - - 3.737 3.728 3.653 3.562 3.469 3.440 3.264 2.929 2.374 1.860 250 - - - - - 3.795 3.788 3.721 3.638 3.547 3.519 3.499 3.346 3.017 2.443 1.912 255 - - - - - 3.854 3.878 3.715 3.638 3.578 3.428 3.105 2.512 1.963 260 - - - - - 3.912 3.907 3.857 3.578 3.428 3.105 2.512 1.963 260 - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.510 3.193 2.581 2.661 2.065 270 - - - - 3.944 3.859 3.834 3.816 3.674 3.369 2.720 2.166			-	-	_												
250 - - - - - 3.795 3.788 3.721 3.638 3.547 3.519 3.499 3.346 3.017 2.443 1.912 255 - - - - 3.854 3.847 3.789 3.715 3.625 3.598 3.578 3.428 3.105 2.512 1.963 260 - - - - - 3.912 3.907 3.857 3.791 3.793 3.667 3.510 3.193 2.581 2.014 265 - - - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.755 3.598 3.587 3.592 3.281 2.661 2.065 270 - - - - - - - - -			-	-	-	-											
255 - - - - 3.854 3.847 3.789 3.715 3.625 3.598 3.578 3.428 3.105 2.512 1.963 260 - - - - 3.912 3.907 3.857 3.791 3.703 3.677 3.657 3.510 3.193 2.581 2.014 265 - - - - - - - - 3.944 3.867 3.781 3.755 3.736 3.592 3.81 2.651 2.065 270 - - - - - - - 3.944 3.859 3.834 3.816 3.674 3.369 2.720 2.116 275 - - - - - - - 3.938 3.913 3.895 3.755 3.457 2.792 2.167 280 - - - - - - - 3.991 3.633			-	-	-	-											
260 - - - 3.912 3.907 3.857 3.791 3.703 3.677 3.657 3.510 3.193 2.581 2.014 265 - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.736 3.592 3.281 2.651 2.065 270 - - - - - - 3.944 3.859 3.834 3.816 3.674 3.369 2.720 2.116 280 - - - - - - - - 3.938 3.913 3.895 3.575 3.457 2.792 2.167 280 - - - - - - - - 3.931 3.895 3.575 3.487 2.270 280 - - - - - - - - 3.91 3.932 3.241 3.241 3.241 3.241			-	-		-											
265 - - - - 3.971 3.966 3.924 3.867 3.781 3.755 3.736 3.592 3.281 2.651 2.065 270 - - - - - - - 3.944 3.859 3.834 3.816 3.674 3.369 2.720 2.116 275 - - - - - - - - - 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 2.067 3.991 3.974 3.837 3.545 2.899 2.218 2.282 2.218 2.282 2.218 2.282 2.218 2.282 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2.292 2.218 2					_	-											
270 - - - - - - 3.944 3.859 3.834 3.816 3.674 3.369 2.720 2.116 275 - - - - - - - 3.938 3.913 3.895 3.755 3.457 2.792 2.167 280 - - - - - - - - 3.991 3.974 3.837 3.545 2.899 2.218 285 - - - - - - - - 3.991 3.974 3.837 3.545 2.899 2.218 290 - - - - - - - - 3.919 3.633 3.005 2.270 295 - - - - - - - 3.809 3.219 2.372 300 - - - - - - - -																	
275 - - - - - - 3.938 3.913 3.895 3.755 3.457 2.792 2.167 280 - - - - - - - 3.991 3.974 3.837 3.545 2.899 2.218 285 - - - - - - - - 3.919 3.633 3.005 2.270 290 -				-		-											
280 - - - - - - - 3.991 3.974 3.837 3.545 2.899 2.218 285 - - - - - - - 3.919 3.633 3.005 2.270 290 - - - - - - - - 3.919 3.633 3.005 2.270 295 - - - - - - - - 3.809 3.212 2.321 300 - - - - - - - - 3.809 3.219 2.372 300 - - - - - - - - - 3.809 3.219 2.372 305 - - - - - - - - 3.985 3.433 2.474 310 - - - - - </td <td></td> <td></td> <td></td> <td>-</td> <td></td> <td>-</td> <td></td>				-		-											
285 - - - - - - - - 3.919 3.633 3.005 2.270 290 - - - - - - - - 3.721 3.112 2.321 295 - - - - - - - - 3.809 3.219 2.372 300 - - - - - - - - - - - 3.809 3.219 2.372 305 - <td></td>																	
290 -												3.991					
295 -												-					
300 - - - - - - - - 3.897 3.326 2.423 305 - - - - - - - - - 3.985 3.433 2.474 310 -																	
305 - - - - - - - - 3.985 3.433 2.474 310 -						-								-			
310 - - - - - - - - - 3.540 2.525 315 - - - - - - - - - 3.647 2.576 320 - - - - - - - - - 3.754 2.628 325 - - - - - - - - - - - 3.861 2.679 330 - - - - - - - - - - 3.861 2.679 335 -						-								-			
315 -		-	-	-	-	-	-	-		-		-	-	-	3.985		
320 - - - - - - - - - 3.754 2.628 325 - - - - - - - - - 3.861 2.679 330 - - - - - - - - - - 3.968 2.730 335 - <td></td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td></td> <td>-</td> <td></td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td></td> <td></td>		-	-	-	-	-	-	-		-		-	-	-	-		
325 - - - - - - - - 3.861 2.679 330 - - - - - - - - - - 3.968 2.730 335 - <						-	-							-	-		
330 - - - - - - - 3.968 2.730 335 - - - - - - - - - 2.781 340 -			-	-		-	-	-				-		-	-		
335 -		-	-	-	-	-	-	-				-	-	-	-		
340 - - - - - - - - - - - 3.085 345 -		-	-	-	-	-	-	-	-	-	-	-	-	-	-	3.968	2.730
345 - - - - - - - - - - - 3.406 350 -	335	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2.781
350 3.727 355		-	-	-	-	-	-	-	-	-	-	-	-	-	-		
355		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	350	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3.727
360	355	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	360	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Table applies to I-section beams with 3 sides fire exposure and a concrete slab on top. Thickness is intumescent only.

Page 10 of 34 Signed E/200

Pol agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Required Third-cones Immily For a Design Temperature (**)						Table	9 SC801 - 12	20 I/H Colur	mns 15 min	utes					
95		350°C	400°C	450°C		1			i i		600°C	620°C	650°C	700°C	750°C
95		0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	95	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	100	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	105	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120															
125															
130															
135															
140															
145															
155															
155															
165															
165															
1770 0.454 0.454 0.4554															
175															
185															
190 0.454 0	180	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
195	185	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
200 0.454 0	190	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
205 0.454 0	195	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
210 0.454 0															
215 0.454 0															
220 0.454 0															
225 0.454 0															
230 0.454 0															
235 0.454 0															
240 0.454 0															
245 0.454 0															
250 0.454 0															
255 0.454 0															
260 0.454 0															
270 0.473 0.454 0		0.454	0.454	0.454	0.454		0.454			0.454	0.454		0.454	0.454	0.454
275 0.484 0.454 0	265	0.462	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
280 0.495 0.454 0	270	0.473	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
285 0.506 0.454 0		0.484	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
290 0.517 0.454 0			0.454								0.454				
295 0.527 0.454 0															
300 0.538 0.454 0															
305 0.549 0.454 0															
310 0.560 0.454 0															
315 0.571 0.454 0															
320 0.582 0.454 0															
325 0.593 0.454 0															
330 0.604 0.454 0															
335 0.615 0.454 0															
340 0.626 0.454 0															
345 0.637 0.454 0															
350 0.648 0.463 0.454 0.															
355 0.659 0.473 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454															
360 0.670 0.482 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454 0.454															
	360	0.670	0.482	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454

Table applies to I-section columns with protection to four sides. Thickness is intumescent only.

Table also applies to I-section beams protected on four sides.

Page 11 of 34 Signed E/200

Pel agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Numm			0	•	Table 1	10 SC801 - 1	30 I/H Col	mne 30 min	uitos					
						ickness (mr								
Section								ĺ						
Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	0.569	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
100	0.587	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	0.606	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	0.624	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	0.643	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120 125	0.661 0.679	0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454 0.454
130	0.679	0.454 0.454	0.454 0.454	0.454	0.454	0.454	0.454	0.454	0.454 0.454	0.454	0.454	0.454	0.454	0.454
135	0.716	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
140	0.735	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
145	0.753	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
150	0.772	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
155	0.790	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
160	0.808	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
165	0.827	0.459	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
170	0.845	0.479	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
175	0.864	0.498	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
180	0.882	0.518	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
185	0.900	0.537	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
190	0.919	0.557	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
195 200	0.937 0.956	0.576 0.596	0.462 0.479	0.454 0.454										
205	0.956	0.596	0.479	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
210	0.974	0.635	0.496	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
215	1.011	0.654	0.513	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
220	1.029	0.674	0.546	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
225	1.048	0.693	0.563	0.461	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
230	1.066	0.713	0.580	0.475	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
235	1.084	0.732	0.597	0.490	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
240	1.103	0.752	0.614	0.504	0.465	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
245	1.121	0.771	0.630	0.519	0.479	0.460	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
250	1.140	0.791	0.647	0.533	0.493	0.473	0.455	0.454	0.454	0.454	0.454	0.454	0.454	0.454
255	1.158	0.810	0.664	0.548	0.506	0.486	0.468	0.454	0.454	0.454	0.454	0.454	0.454	0.454
260	1.176	0.830	0.681	0.562	0.520	0.500	0.481	0.460	0.454	0.454	0.454	0.454	0.454	0.454
265 270	1.195 1.213	0.849 0.869	0.698 0.714	0.577 0.591	0.534 0.547	0.513	0.494 0.507	0.473	0.454 0.461	0.454 0.454	0.454 0.454	0.454 0.454	0.454 0.454	0.454
275	1.213	0.888	0.714	0.606	0.561	0.526 0.539	0.520	0.485 0.498	0.461	0.454	0.454	0.454	0.454	0.454 0.454
280	1.250	0.908	0.748	0.620	0.575	0.553	0.533	0.510	0.485	0.454	0.454	0.454	0.454	0.454
285	1.268	0.927	0.765	0.635	0.588	0.566	0.546	0.523	0.497	0.454	0.454	0.454	0.454	0.454
290	1.287	0.947	0.782	0.650	0.602	0.579	0.559	0.535	0.509	0.454	0.454	0.454	0.454	0.454
295	1.305	0.966	0.799	0.664	0.616	0.593	0.571	0.548	0.521	0.454	0.454	0.454	0.454	0.454
300	1.324	0.986	0.815	0.679	0.629	0.606	0.584	0.560	0.533	0.454	0.454	0.454	0.454	0.454
305	1.342	1.005	0.832	0.693	0.643	0.619	0.597	0.573	0.545	0.463	0.454	0.454	0.454	0.454
310	1.361	1.025	0.849	0.708	0.657	0.632	0.610	0.585	0.557	0.473	0.454	0.454	0.454	0.454
315	1.379	1.044	0.866	0.722	0.670	0.646	0.623	0.598	0.569	0.484	0.454	0.454	0.454	0.454
320	1.397	1.064	0.883	0.737	0.684	0.659	0.636	0.610	0.581	0.495	0.454	0.454	0.454	0.454
325	1.416	1.083	0.899	0.751	0.698	0.672	0.649	0.622	0.593	0.505	0.460	0.454	0.454	0.454
330	1.434	1.103	0.916	0.766	0.711	0.685	0.662	0.635	0.605	0.516	0.470	0.454	0.454	0.454
335	1.453 1.471	1.122	0.933	0.780 0.795	0.725	0.699	0.675	0.647	0.617	0.526	0.480	0.454 0.454	0.454	0.454
340 345	1.471	1.142 1.161	0.950 0.967	0.795	0.739 0.752	0.712 0.725	0.688 0.701	0.660 0.672	0.629 0.641	0.537 0.548	0.490 0.500	0.454	0.454 0.454	0.454 0.454
350	1.489	1.181	0.987	0.809	0.752	0.725	0.701	0.672	0.653	0.548	0.500	0.454	0.454	0.454
355	1.526	1.200	1.000	0.838	0.780	0.752	0.713	0.697	0.665	0.569	0.520	0.454	0.454	0.454
360	1.545	1.220	1.000	0.853	0.780	0.765	0.726	0.697	0.663	0.580	0.520	0.458	0.454	0.454
300		•	lion to Lo	ootion o	•		oction to	four oid			ntum.co	ont only	0.434	0.434

Table applies to I-section columns with protection to four sides. Thickness is intumescent only.

Table also applies to I-section beams protected on four sides.

Page 12 of 34 Signed E/200

Pol Ryg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

					Table 1:	1 SC801 - 12	0 I/H Colur	nns 45 mini	utes					
				R		ickness (mm								
Section Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	1.129	0.817	0.593	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
95	1.150	0.838	0.613	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
100	1.172	0.859	0.633	0.457	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
105	1.193	0.879	0.653	0.476	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
110	1.215	0.900	0.673	0.496	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
115	1.236	0.921	0.693	0.515	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
120	1.258	0.942	0.713	0.534	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
125	1.280	0.963	0.733	0.554	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
130	1.301	0.983	0.753	0.573	0.470	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
135	1.323	1.004	0.773	0.593	0.490	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
140	1.344	1.025	0.793	0.612	0.510	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
145	1.366	1.046	0.813	0.632	0.529	0.466	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
150 155	1.387 1.409	1.067 1.087	0.833 0.853	0.651 0.670	0.549 0.569	0.486 0.506	0.454 0.454							
160	1.430	1.1087	0.853	0.670	0.588	0.526	0.454	0.454	0.454	0.454	0.454	0.454	0.454	0.454
165	1.452	1.108	0.873	0.890	0.588	0.546	0.480	0.454	0.454	0.454	0.454	0.454	0.454	0.454
170	1.474	1.129	0.892	0.709	0.628	0.566	0.480	0.482	0.461	0.454	0.454	0.454	0.454	0.454
175	1.495	1.170	0.932	0.748	0.647	0.586	0.521	0.502	0.480	0.454	0.454	0.454	0.454	0.454
180	1.517	1.191	0.952	0.768	0.667	0.606	0.541	0.521	0.499	0.454	0.454	0.454	0.454	0.454
185	1.538	1.212	0.972	0.787	0.687	0.625	0.562	0.541	0.518	0.454	0.454	0.454	0.454	0.454
190	1.560	1.233	0.992	0.807	0.706	0.645	0.582	0.561	0.538	0.469	0.454	0.454	0.454	0.454
195	1.581	1.254	1.012	0.826	0.726	0.665	0.602	0.581	0.557	0.487	0.454	0.454	0.454	0.454
200	1.603	1.274	1.032	0.845	0.746	0.685	0.623	0.600	0.576	0.504	0.468	0.454	0.454	0.454
205	1.624	1.295	1.052	0.865	0.765	0.705	0.643	0.620	0.595	0.521	0.484	0.454	0.454	0.454
210	1.646	1.316	1.072	0.884	0.785	0.725	0.663	0.640	0.614	0.538	0.501	0.454	0.454	0.454
215	1.668	1.337	1.092	0.904	0.805	0.745	0.684	0.660	0.633	0.556	0.517	0.464	0.454	0.454
220	1.693	1.358	1.112	0.923	0.824	0.765	0.704	0.679	0.652	0.573	0.533	0.479	0.454	0.454
225	1.728	1.378	1.132	0.943	0.844	0.785	0.724	0.699	0.671	0.590	0.549	0.494	0.454	0.454
230	1.762	1.399	1.152	0.962	0.864	0.805	0.745	0.719	0.690	0.607	0.566	0.508	0.454	0.454
235 240	1.797 1.831	1.420 1.441	1.172 1.192	0.981 1.001	0.883	0.825 0.845	0.765 0.785	0.739 0.758	0.709 0.728	0.624 0.642	0.582 0.598	0.523 0.538	0.454 0.454	0.454 0.454
245	1.866	1.441	1.192	1.001	0.903	0.865	0.806	0.738	0.728	0.659	0.598	0.553	0.454	0.454
250	1.900	1.482	1.232	1.040	0.942	0.885	0.826	0.778	0.747	0.676	0.631	0.568	0.467	0.454
255	1.935	1.503	1.252	1.059	0.962	0.905	0.846	0.817	0.785	0.693	0.647	0.583	0.479	0.454
260	1.969	1.524	1.272	1.079	0.982	0.925	0.866	0.837	0.804	0.711	0.663	0.598	0.492	0.454
265	2.004	1.545	1.292	1.098	1.001	0.945	0.887	0.857	0.823	0.728	0.680	0.612	0.504	0.454
270	2.038	1.565	1.311	1.117	1.021	0.965	0.907	0.877	0.842	0.745	0.696	0.627	0.517	0.454
275	2.073	1.586	1.331	1.137	1.041	0.985	0.927	0.896	0.861	0.762	0.712	0.642	0.529	0.454
280	2.107	1.607	1.351	1.156	1.060	1.005	0.948	0.916	0.881	0.780	0.729	0.657	0.542	0.454
285	2.142	1.628	1.371	1.176	1.080	1.025	0.968	0.936	0.900	0.797	0.745	0.672	0.554	0.454
290	2.176	1.649	1.391	1.195	1.099	1.045	0.988	0.956	0.919	0.814	0.761	0.687	0.567	0.454
295	2.211	1.669	1.411	1.215	1.119	1.065	1.009	0.975	0.938	0.831	0.777	0.701	0.579	0.454
300	2.245	1.697	1.431	1.234	1.139	1.084	1.029	0.995	0.957	0.849	0.794	0.716	0.592	0.454
305	2.280	1.734	1.451	1.253	1.158	1.104	1.049	1.015	0.976	0.866	0.810	0.731	0.604	0.462
310	2.314	1.771	1.471	1.273	1.178	1.124	1.070	1.035	0.995	0.883	0.826	0.746	0.617	0.472
315 320	2.349	1.808 1.845	1.491 1.511	1.292 1.312	1.198 1.217	1.144 1.164	1.090 1.110	1.054 1.074	1.014 1.033	0.900 0.917	0.842 0.859	0.761 0.776	0.629 0.642	0.481 0.491
325	2.383	1.845	1.511	1.312	1.217	1.184	1.110	1.074	1.033	0.917	0.859	0.776	0.654	0.491
330	2.418	1.919	1.551	1.351	1.257	1.104	1.151	1.113	1.032	0.953	0.873	0.791	0.667	0.501
335	2.432	1.956	1.571	1.370	1.276	1.224	1.171	1.113	1.071	0.969	0.908	0.820	0.679	0.511
340	2.521	1.994	1.591	1.389	1.276	1.244	1.171	1.153	1.109	0.986	0.924	0.835	0.692	0.531
345	2.556	2.031	1.611	1.409	1.316	1.264	1.212	1.173	1.128	1.004	0.940	0.850	0.704	0.541
350	2.590	2.068	1.631	1.428	1.335	1.284	1.232	1.192	1.147	1.021	0.956	0.865	0.717	0.551
355	2.625	2.105	1.651	1.448	1.355	1.304	1.253	1.212	1.166	1.038	0.973	0.880	0.729	0.561
360	2.659	2.142	1.671	1.467	1.375	1.324	1.273	1.232	1.185	1.055	0.989	0.895	0.742	0.570

Table applies to I-section columns with protection to four sides. Thickness is intumescent only.

Table also applies to I-section beams protected on four sides.

Page 13 of 34 Signed E/200

Pel agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

				R				nns 60 minu gn Tempera						
Section Factor							ĺ	ĺ						
(m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	1.695	1.329	1.045	0.822	0.743	0.652	0.633	0.612	0.582	0.454	0.454	0.454	0.454	0.454
95	1.723	1.349	1.067	0.844	0.763	0.674	0.655	0.632	0.603	0.510	0.454	0.454	0.454	0.454
100	1.751	1.369	1.089	0.865	0.784	0.695	0.676	0.653	0.623	0.530	0.469	0.454	0.454	0.454
105	1.780	1.389	1.111	0.887	0.804	0.717	0.697	0.674	0.644	0.550	0.488	0.454	0.454	0.454
110	1.808	1.409	1.133	0.908	0.825	0.738	0.718	0.695	0.664	0.569	0.508	0.454	0.454	0.454
115	1.836	1.429	1.156	0.930	0.845	0.759	0.739	0.716	0.685	0.589	0.527	0.454	0.454	0.454
120	1.865	1.448	1.178	0.951	0.866	0.781	0.760	0.737	0.705	0.609	0.547	0.454	0.454	0.454
125	1.893	1.468	1.200	0.973	0.886	0.802	0.782	0.758	0.726	0.629	0.566	0.454	0.454	0.454
130	1.921	1.488	1.222	0.994	0.907	0.824	0.803	0.778	0.746	0.648	0.586	0.464	0.454	0.454
135	1.950	1.508	1.244	1.015	0.927	0.845	0.824	0.799	0.767	0.668	0.605	0.484	0.454	0.454
140	1.978	1.528	1.267	1.037	0.948	0.867	0.845	0.820	0.788	0.688	0.625	0.503	0.454	0.454
145	2.006	1.548	1.289	1.058	0.968	0.888	0.866	0.841	0.808	0.708	0.644	0.522	0.454	0.454
150	2.034	1.568	1.311	1.080	0.989	0.910	0.888	0.862	0.829	0.727	0.663	0.542	0.454	0.454
155	2.063	1.588	1.333	1.101	1.009	0.931	0.909	0.883	0.849	0.747	0.683	0.561	0.454	0.454
160	2.091	1.608	1.355	1.123	1.030	0.953	0.930	0.903	0.870	0.767	0.702	0.581	0.454	0.454
165	2.119	1.628	1.378	1.144	1.050	0.974	0.951	0.924	0.890	0.787	0.722	0.600	0.454	0.454
170	2.148	1.647	1.400	1.166	1.071	0.995	0.972	0.945	0.911	0.806	0.741	0.619	0.458	0.454
175	2.176	1.667	1.422	1.187	1.091	1.017	0.993	0.966	0.931	0.826	0.761	0.639	0.476	0.454
180	2.204	1.691	1.444	1.209	1.111	1.038	1.015	0.987	0.952	0.846	0.780	0.658	0.494	0.454
185	2.233	1.727	1.466	1.230	1.132	1.060	1.036	1.008	0.972	0.866	0.800	0.678	0.512	0.454
190	2.261	1.763	1.489	1.252	1.152	1.081	1.057	1.029	0.993	0.885	0.819	0.697	0.530	0.454
195	2.289	1.799	1.511	1.273	1.173	1.103	1.078	1.049	1.014	0.905	0.839	0.716	0.548	0.454
200	2.318	1.835	1.533	1.295	1.193	1.124	1.099	1.070	1.034	0.925	0.858	0.736	0.566	0.460
205	2.346	1.871	1.555	1.316	1.214	1.146	1.121	1.091	1.055	0.945	0.878	0.755	0.584	0.475
210	2.374	1.907	1.577	1.337	1.214	1.140	1.142	1.112	1.075	0.964	0.897	0.774	0.602	0.473
215	2.402	1.943	1.600	1.359	1.255	1.189	1.142	1.112	1.075	0.984	0.837	0.774	0.620	0.505
220	2.431	1.979	1.622	1.380	1.275	1.210	1.184	1.154	1.116	1.004	0.936	0.813	0.639	0.520
225	2.459	2.015	1.644	1.402	1.296	1.231	1.205	1.175	1.137	1.024	0.956	0.833	0.657	0.535
230	2.487	2.051	1.666	1.423	1.316	1.253	1.226	1.195	1.157	1.043	0.975	0.852	0.675	0.550
235	2.516	2.087	1.693	1.445	1.337	1.274	1.248	1.216	1.178	1.063	0.994	0.871	0.693	0.565
240	2.544	2.122	1.732	1.466	1.357	1.296	1.269	1.237	1.199	1.083	1.014	0.891	0.711	0.580
245	2.572	2.158	1.770	1.488	1.378	1.317	1.290	1.258	1.219	1.103	1.033	0.910	0.729	0.595
250	2.601	2.194	1.809	1.509	1.398	1.339	1.311	1.279	1.240	1.122	1.053	0.930	0.747	0.610
255	2.629	2.230	1.848	1.531	1.419	1.360	1.332	1.300	1.260	1.142	1.072	0.949	0.765	0.625
260	2.657	2.266	1.886	1.552	1.439	1.382	1.354	1.321	1.281	1.162	1.092	0.968	0.783	0.640
265	2.686	2.302	1.925	1.574	1.460	1.403	1.375	1.341	1.301	1.182	1.111	0.988	0.801	0.655
270	2.714	2.338	1.964	1.595	1.480	1.424	1.396	1.362	1.322	1.201	1.131	1.007	0.820	0.671
275	2.742	2.374	2.003	1.617	1.501	1.446	1.417	1.383	1.342	1.221	1.150	1.027	0.838	0.686
280	2.770	2.410	2.041	1.638	1.521	1.467	1.438	1.404	1.363	1.241	1.170	1.046	0.856	0.701
285	2.810	2.446	2.080	1.659	1.542	1.489	1.459	1.425	1.383	1.261	1.189	1.065	0.874	0.716
290	2.859	2.482	2.119	1.681	1.562	1.510	1.481	1.446	1.404	1.280	1.209	1.085	0.892	0.731
295	2.908	2.518	2.157	1.722	1.583	1.532	1.502	1.466	1.425	1.300	1.228	1.104	0.910	0.746
300	2.957	2.554	2.196	1.763	1.603	1.553	1.523	1.487	1.445	1.320	1.248	1.124	0.928	0.761
305	3.006	2.590	2.235	1.805	1.624	1.575	1.544	1.508	1.466	1.340	1.267	1.143	0.946	0.776
310	3.055	2.625	2.273	1.846	1.644	1.596	1.565	1.529	1.486	1.359	1.287	1.162	0.964	0.791
315	3.104	2.661	2.312	1.888	1.665	1.618	1.587	1.550	1.507	1.379	1.306	1.182	0.982	0.806
320	3.153	2.697	2.351	1.930	1.689	1.639	1.608	1.571	1.527	1.399	1.326	1.201	1.001	0.821
325	3.203	2.733	2.389	1.971	1.734	1.660	1.629	1.592	1.548	1.419	1.345	1.221	1.019	0.836
330	3.252	2.769	2.428	2.013	1.778	1.682	1.650	1.612	1.568	1.438	1.364	1.240	1.037	0.851
335	3.301	2.819	2.467	2.055	1.823	1.727	1.671	1.633	1.589	1.458	1.384	1.259	1.055	0.866
340	3.350	2.878	2.505	2.096	1.868	1.772	1.704	1.654	1.609	1.478	1.403	1.279	1.073	0.881
345	3.399	2.937	2.544	2.138	1.913	1.817	1.748	1.675	1.630	1.478	1.423	1.298	1.073	0.896
350	3.448	2.997	2.544	2.130	1.913	1.862	1.748	1.711	1.651	1.517	1.423	1.318	1.1091	0.896
355	3.448	3.056	2.621	2.221	2.002	1.907	1.837	1.755	1.671	1.517	1.442	1.337	1.109	0.911
360	3.546	3.115	2.660	2.263	2.047	1.952	1.881	1.798	1.702	1.557	1.481	1.356	1.145	0.941

Table applies to I-section columns with protection to four sides. Thickness is intumescent only.

Table also applies to I-section beams protected on four sides.

Page 14 of 34 Signed E/200

Pol Ryg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

		000.	- 120	<u> </u>	Table	12.00001 1	20 1/11 Cal.	7F						
						13 SC801 - 1 nickness (mr								
Section			1		Required II	iickness (mi	n) for a Des	ign remper	ature (C)	l	l	l		T
Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	2.441	1.777	1.488	1.228	1.132	1.088	1.048	1.003	0.949	0.811	0.745	0.621	0.454	0.454
95	2.495	1.811	1.514	1.248	1.153	1.110	1.070	1.025	0.971	0.832	0.765	0.641	0.546	0.454
100	2.550	1.846	1.541	1.267	1.174	1.131	1.092	1.047	0.994	0.854	0.786	0.662	0.565	0.454
105	2.604	1.880	1.567	1.287	1.195	1.153	1.114	1.069	1.016	0.875	0.806	0.683	0.585	0.454
110	2.658	1.914	1.593	1.306	1.216	1.174	1.135	1.091	1.038	0.896	0.827	0.704	0.604	0.454
115	2.713	1.948	1.620	1.325	1.237	1.195	1.157	1.113	1.061	0.918	0.847	0.725	0.624	0.454
120	2.767	1.982	1.646	1.345	1.258	1.217	1.179	1.136	1.083	0.939	0.868	0.746	0.643	0.460
125	2.807	2.016	1.673	1.364	1.279	1.238	1.201	1.158	1.106	0.960	0.888	0.767	0.662	0.478
130	2.840	2.050	1.705	1.384	1.300	1.260	1.223	1.180	1.128	0.981	0.909	0.788	0.682	0.497
135	2.873	2.084	1.739	1.403	1.321	1.281	1.245	1.202	1.151	1.003	0.929	0.809	0.701	0.515
140	2.906	2.118	1.773	1.423	1.342	1.303	1.267	1.224	1.173	1.024	0.950	0.829	0.721	0.533
145	2.939	2.152	1.808	1.442	1.363	1.324	1.289	1.246	1.195	1.045	0.970	0.850	0.740	0.552
150	2.971	2.187	1.842	1.461	1.384	1.346	1.311	1.269	1.218	1.067	0.991	0.871	0.759	0.570
155	3.004	2.221	1.876	1.481	1.405	1.367	1.332	1.291	1.240	1.088	1.012	0.892	0.779	0.589
160	3.037	2.255	1.911	1.500	1.426	1.389	1.354	1.313	1.263	1.109	1.032	0.913	0.798	0.607
165	3.070	2.289	1.945	1.520	1.447	1.410	1.376	1.335	1.285	1.131	1.053	0.934	0.817	0.626
170 175	3.103 3.136	2.323 2.357	1.980 2.014	1.539 1.559	1.468 1.489	1.431 1.453	1.398 1.420	1.357 1.379	1.308 1.330	1.152 1.173	1.073 1.094	0.955 0.976	0.837 0.856	0.644 0.662
180			2.014	1.559		1.453	1.420	1.402	1.352	1.173	1.094	0.976	0.856	0.681
185	3.169 3.202	2.391 2.425	2.048	1.578	1.510	1.474	1.442	1.402	1.352	1.195		1.017		
190	3.202	2.425	2.083	1.617	1.531 1.552	1.496	1.486	1.424	1.375	1.216	1.135 1.155	1.017	0.895 0.914	0.699 0.718
190	3.268	2.459	2.117	1.636	1.552	1.517	1.486	1.446	1.420	1.258	1.155	1.038	0.914	0.718
200	3.301	2.493	2.131	1.656	1.594	1.560	1.529	1.490	1.442	1.230	1.176	1.039	0.953	0.755
205	3.334	2.562	2.220	1.675	1.615	1.582	1.551	1.512	1.442	1.301	1.196	1.101	0.933	0.733
210	3.367	2.596	2.255	1.710	1.636	1.603	1.573	1.535	1.487	1.322	1.217	1.101	0.972	0.773
215	3.400	2.630	2.233	1.753	1.657	1.625	1.595	1.557	1.510	1.344	1.258	1.122	1.011	0.731
220	3.433	2.664	2.323	1.796	1.678	1.646	1.617	1.579	1.532	1.365	1.278	1.164	1.031	0.828
225	3.466	2.698	2.358	1.839	1.716	1.667	1.639	1.601	1.554	1.386	1.299	1.184	1.050	0.847
230	3.499	2.732	2.392	1.882	1.759	1.696	1.661	1.623	1.577	1.408	1.319	1.205	1.069	0.865
235	3.532	2.766	2.427	1.925	1.802	1.739	1.683	1.645	1.599	1.429	1.340	1.226	1.089	0.884
240	3.565	2.810	2.461	1.968	1.845	1.781	1.726	1.668	1.622	1.450	1.360	1.247	1.108	0.902
245	3.598	2.865	2.495	2.012	1.888	1.824	1.768	1.697	1.644	1.472	1.381	1.268	1.128	0.920
250	3.631	2.920	2.530	2.055	1.930	1.867	1.811	1.739	1.667	1.493	1.401	1.289	1.147	0.939
255	3.664	2.975	2.564	2.098	1.973	1.909	1.853	1.782	1.695	1.514	1.422	1.310	1.166	0.957
260	3.697	3.029	2.598	2.141	2.016	1.952	1.896	1.824	1.738	1.536	1.442	1.331	1.186	0.976
265	3.730	3.084	2.633	2.184	2.059	1.995	1.938	1.867	1.780	1.557	1.463	1.351	1.205	0.994
270	3.763	3.139	2.667	2.227	2.101	2.037	1.981	1.909	1.823	1.578	1.483	1.372	1.224	1.013
275	3.796	3.194	2.702	2.270	2.144	2.080	2.024	1.952	1.865	1.599	1.504	1.393	1.244	1.031
280	3.828	3.248	2.736	2.313	2.187	2.123	2.066	1.994	1.908	1.621	1.524	1.414	1.263	1.049
285	3.861	3.303	2.770	2.356	2.230	2.166	2.109	2.037	1.950	1.642	1.545	1.435	1.283	1.068
290	3.910	3.358	2.828	2.399	2.272	2.208	2.151	2.079	1.993	1.663	1.565	1.456	1.302	1.086
295	4.165	3.413	2.900	2.443	2.315	2.251	2.194	2.122	2.035	1.688	1.586	1.477	1.321	1.105
300	4.419	3.468	2.973	2.486	2.358	2.294	2.236	2.164	2.078	1.734	1.607	1.498	1.341	1.123
305	4.674	3.522	3.045	2.529	2.401	2.336	2.279	2.207	2.120	1.780	1.627	1.518	1.360	1.142
310	4.928	3.577	3.117	2.572	2.444	2.379	2.321	2.249	2.163	1.827	1.648	1.539	1.379	1.160
315	5.183	3.632	3.190	2.615	2.486	2.422	2.364	2.292	2.205	1.873	1.668	1.560	1.399	1.178
320	-	3.687	3.262	2.658	2.529	2.464	2.406	2.334	2.248	1.919	1.698	1.581	1.418	1.197
325	-	3.741	3.335	2.701	2.572	2.507	2.449	2.377	2.290	1.965	1.747	1.602	1.438	1.215
330	-	3.796	3.407	2.744	2.615	2.550	2.491	2.419	2.332	2.012	1.796	1.623	1.457	1.234
335	-	3.851	3.479	2.792	2.657	2.593	2.534	2.462	2.375	2.058	1.845	1.644	1.476	1.252
340	-	3.934	3.552	2.889	2.700	2.635	2.577	2.504	2.417	2.104	1.893	1.665	1.496	1.271
345	-	4.103	3.624	2.987	2.743	2.678	2.619	2.547	2.460	2.151	1.942	1.690	1.515	1.289
350	-	4.271	3.697	3.084	2.788	2.721	2.662	2.589	2.502	2.197	1.991	1.738	1.535	1.307
355	-	4.439	3.769	3.182	2.891	2.763	2.704	2.632	2.545	2.243	2.040	1.786	1.554	1.326
360	-	4.608	3.841	3.280	2.993	2.838	2.747	2.674	2.587	2.289	2.089	1.834	1.573	1.344

Table applies to I-section columns with protection to four sides. Thickness is intumescent only. Table also applies to I-section beams protected on four sides up to a limiting nominal protection thickness of 3.99mm.

Page 15 of 34 Signed E/200

Pol Ragg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

							20 I/H Colur							
				F	equired Th	ickness (mn	n) for a Desi	gn Tempera	ture (°C)	-				
Section Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	3.126	2.566	2.068	1.620	1.518	1.471	1.428	1.379	1.318	1.156	1.078	0.969	0.801	0.621
95	3.210	2.631	2.106	1.652	1.544	1.493	1.448	1.396	1.335	1.176	1.099	0.990	0.822	0.641
100	3.294	2.697	2.145	1.684	1.569	1.516	1.468	1.412	1.352	1.196	1.119	1.010	0.842	0.660
105	3.378	2.762	2.183	1.719	1.594	1.538	1.488	1.429	1.369	1.216	1.140	1.031	0.862	0.680
110	3.461	2.813	2.221	1.754	1.620	1.561	1.507	1.446	1.386	1.237	1.161	1.052	0.882	0.700
115	3.545	2.857	2.259	1.789	1.645	1.583	1.527	1.462	1.403	1.257	1.182	1.073	0.903	0.719
120	3.629	2.901	2.297	1.825	1.671	1.605	1.547	1.479	1.420	1.277	1.203	1.094	0.923	0.739
125	3.713	2.945	2.336	1.860	1.703	1.628	1.567	1.495	1.436	1.297	1.224	1.115	0.943	0.759
130	3.797	2.989	2.374	1.895	1.741	1.650	1.586	1.512	1.453	1.317	1.244	1.136	0.964	0.778
135	3.880	3.033	2.412	1.930	1.778	1.673	1.606	1.529	1.470	1.337	1.265	1.157	0.984	0.798
140	3.973	3.077	2.450	1.966	1.816	1.705	1.626	1.545	1.487	1.357	1.286	1.178	1.004	0.818
145	4.067	3.121	2.488	2.001	1.853	1.744	1.646	1.562	1.504	1.377	1.307	1.199	1.024	0.837
150	4.162	3.165	2.527	2.036	1.891	1.783	1.665	1.578	1.521	1.397	1.328	1.220	1.045	0.857
155	4.256	3.209	2.565	2.071	1.928	1.822	1.689	1.595	1.537	1.417	1.348	1.241	1.065	0.877
160	4.351	3.253	2.603	2.107	1.966	1.862	1.731	1.612	1.554	1.437	1.369	1.262	1.085	0.896
165	4.445	3.296	2.641	2.142	2.003	1.901	1.773	1.628	1.571	1.458	1.390	1.282	1.105	0.916
170	4.539	3.340	2.679	2.177	2.041	1.940	1.816	1.645	1.588	1.478	1.411	1.303	1.126	0.936
175	4.634	3.384	2.718	2.212	2.078	1.979	1.858	1.661	1.605	1.498	1.432	1.324	1.146	0.955
180	4.728	3.428	2.756	2.248	2.116	2.018	1.900	1.678	1.622	1.518	1.453	1.345	1.166	0.975
185	4.822	3.472	2.798	2.283	2.153	2.057	1.942	1.719	1.638	1.538	1.473	1.366	1.187	0.995
190	4.917	3.516	2.851	2.318	2.191	2.097	1.985	1.768	1.655	1.558	1.494	1.387	1.207	1.014
195	5.011	3.560	2.905	2.353	2.228	2.136	2.027	1.817	1.672	1.578	1.515	1.408	1.227	1.034
200	5.105	3.604	2.958	2.389	2.266	2.175	2.069	1.866	1.703	1.598	1.536	1.429	1.247	1.054
205	5.200	3.648	3.011	2.424	2.303	2.214	2.112	1.915	1.753	1.618	1.557	1.450	1.268	1.073
210	5.294	3.692	3.064	2.459	2.341	2.253	2.154	1.963	1.804	1.638	1.577	1.471	1.288	1.093
215	5.388	3.736	3.118	2.494	2.378	2.292	2.196	2.012	1.855	1.659	1.598	1.492	1.308	1.112
220	5.483	3.780	3.171	2.530	2.416	2.331	2.238	2.061	1.905	1.679	1.619	1.513	1.328	1.132
225	-	3.823	3.224	2.565	2.453	2.371	2.281	2.110	1.956	1.721	1.640	1.534	1.349	1.152
230	-	3.867	3.277	2.600	2.491	2.410	2.323	2.159	2.006	1.767	1.661	1.555	1.369	1.171
235	-	3.943	3.331	2.635	2.528	2.449	2.365	2.208	2.057	1.813	1.682	1.575	1.389	1.191
240	-	4.061	3.384	2.671	2.566	2.488	2.407	2.256	2.107	1.860	1.728	1.596	1.410	1.211
245	-	4.178	3.437	2.706	2.603	2.527	2.450	2.305	2.158	1.906	1.774	1.617	1.430	1.230
250	-	4.295	3.490	2.741	2.641	2.566	2.492	2.354	2.209	1.952	1.821	1.638	1.450	1.250
255	-	4.413	3.544	2.776	2.678	2.606	2.534	2.403	2.259	1.999	1.867	1.659	1.470	1.270
260	-	4.530	3.597	2.850	2.716	2.645	2.577	2.452	2.310	2.045	1.914	1.680	1.491	1.289
265	-	4.647	3.650	2.934	2.753	2.684	2.619	2.501	2.360	2.091	1.961	1.726	1.511	1.309
270	-	4.764	3.703	3.017	2.800	2.723	2.661	2.549	2.411	2.138	2.007	1.774	1.531	1.329
275	-	4.882	3.757	3.101	2.885	2.762	2.703	2.598	2.462	2.184	2.054	1.822	1.551	1.348
280	-	4.999	3.810	3.185	2.971	2.824	2.746	2.647	2.512	2.230	2.100	1.870	1.572	1.368
285	-	5.116	3.863	3.269	3.056	2.914	2.793	2.696	2.563	2.277	2.147	1.919	1.592	1.388
290	-	5.234	3.939	3.353	3.142	3.004	2.887	2.745	2.613	2.323	2.194	1.967	1.612	1.407
295	-	5.351	4.040	3.436	3.227	3.095	2.980	2.804	2.664	2.369	2.240	2.015	1.633	1.427
300	-	5.468	4.142	3.520	3.313	3.185	3.074	2.903	2.714	2.416	2.287	2.063	1.653	1.447
305	-	-	4.244	3.604	3.398	3.275	3.168	3.003	2.765	2.462	2.333	2.111	1.673	1.466
310	-	-	4.346	3.688	3.484	3.365	3.262	3.102	2.853	2.508	2.380	2.160	1.710	1.486
315	-	-	4.448	3.772	3.569	3.455	3.355	3.202	2.962	2.555	2.427	2.208	1.761	1.506
320	-	-	4.549	3.855	3.655	3.545	3.449	3.302	3.072	2.601	2.473	2.256	1.811	1.525
325	-	-	4.651	3.951	3.740	3.635	3.543	3.401	3.182	2.647	2.520	2.304	1.861	1.545
330	-	-	4.753	4.054	3.826	3.725	3.637	3.501	3.292	2.694	2.566	2.352	1.912	1.565
335	-	-	4.855	4.158	3.915	3.815	3.731	3.600	3.402	2.740	2.613	2.401	1.962	1.584
340	-	-	4.957	4.262	4.018	3.907	3.824	3.700	3.511	2.791	2.660	2.449	2.012	1.604
345	-	-	5.059	4.366	4.121	4.009	3.920	3.800	3.621	2.929	2.706	2.497	2.063	1.624
350	-	-	5.160	4.469	4.224	4.110	4.020	3.899	3.731	3.067	2.753	2.545	2.113	1.643
355	-	-	5.262	4.573	4.327	4.212	4.120	3.998	3.841	3.205	2.830	2.593	2.163	1.663
360	-	-	5.364	4.677	4.430	4.314	4.220	4.097	3.945	3.343	2.969	2.642	2.214	1.683
			columne									alco apr		

Table applies to I-section columns with protection to four sides. Thickness is intumescent only. Table also applies to I-section beams protected on four sides up to a limiting nominal protection thickness of 3.99mm.

Page 16 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Numm					Table 1	5 SC801 - 1	20 I/H Colur	mns 105 mii	nutes					
					Required Th									
Section	25226	40000	45000							50000	52010	55000	=0000	75000
Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	-	3.189	2.716	2.238	1.886	1.835	1.792	1.737	1.663	1.498	1.416	1.290	1.093	0.917
95	-	3.280	2.785	2.284	1.931	1.878	1.833	1.778	1.704	1.520	1.432	1.307	1.113	0.937
100	-	3.371	2.854	2.331	1.977	1.920	1.875	1.818	1.744	1.542	1.448	1.324	1.133	0.957
105	-	3.462	2.923	2.378	2.022	1.963	1.917	1.859	1.784	1.563	1.464	1.341	1.153	0.977
110	-	3.553	2.992	2.424	2.068	2.006	1.959	1.900	1.824	1.585	1.480	1.358	1.173	0.996
115	-	3.644	3.061	2.471	2.114	2.049	2.000	1.941	1.864	1.607	1.496	1.375	1.193	1.016
120	-	3.735	3.129	2.518	2.159	2.092	2.042	1.982	1.904	1.628	1.512	1.392	1.213	1.036
125	-	3.825	3.198	2.564	2.205	2.134	2.084	2.022	1.944	1.650	1.528	1.409	1.233	1.056
130	-	3.916	3.267	2.611	2.250	2.177	2.126	2.063	1.984	1.672	1.544	1.426	1.253	1.075
135	-	4.008	3.336	2.658	2.296	2.220	2.167	2.104	2.024	1.704	1.561	1.443	1.273	1.095
140	-	4.099	3.405	2.704	2.341	2.263	2.209	2.145	2.064	1.746	1.577	1.460	1.293	1.115
145	-	4.190	3.473	2.751	2.387	2.306	2.251	2.186	2.104	1.789	1.593	1.476	1.313	1.134
150	-	4.281	3.542	2.798	2.433	2.348	2.293	2.226	2.144	1.831	1.609	1.493	1.333	1.154
155	-	4.372	3.611	2.848	2.478	2.391	2.334	2.267	2.184	1.873	1.625	1.510	1.353	1.174
160	-	4.463	3.680	2.897	2.524	2.434	2.376	2.308	2.224	1.915	1.641	1.527	1.373	1.194
165	-	4.555	3.749	2.947	2.569	2.477	2.418	2.349	2.264	1.958	1.657	1.544	1.393	1.213
170	-	4.646	3.818	2.996	2.615	2.520	2.460	2.390	2.304	2.000	1.673	1.561	1.413	1.233
175	-	4.737	3.886	3.045	2.661	2.562	2.501	2.430	2.344	2.042	1.705	1.578	1.433	1.253
180	-	4.828	3.960	3.095	2.706	2.605	2.543	2.471	2.384	2.084	1.757	1.595	1.453	1.273
185	-	4.919	4.034	3.144	2.752	2.648	2.585	2.512	2.424	2.126	1.808	1.612	1.473	1.292
190	-	5.010	4.108	3.194	2.803	2.691	2.627	2.553	2.464	2.169	1.860	1.629	1.494	1.312
195	-	5.102	4.182	3.243	2.869	2.734	2.668	2.594	2.504	2.211	1.912	1.646	1.514	1.332
200	-	5.193	4.256	3.292	2.935	2.777	2.710	2.634	2.544	2.253	1.964	1.663	1.534	1.352
205	-	5.284	4.330	3.342	3.001	2.843	2.752	2.675	2.584	2.295	2.016	1.680	1.554	1.371
210	-	5.375	4.404	3.391	3.067	2.914	2.801	2.716	2.624	2.338	2.068	1.729	1.574	1.391
215	-	-	4.478	3.441	3.133	2.986	2.875	2.757	2.664	2.380	2.120	1.784	1.594	1.411
220	-	-	4.552	3.490	3.199	3.057	2.949	2.810	2.704	2.422	2.172	1.839	1.614	1.431
225	-	-	4.626	3.539	3.265	3.129	3.023	2.887	2.744	2.464	2.223	1.894	1.634	1.450
230	-	-	4.700	3.589	3.330	3.200	3.097	2.964	2.784	2.506	2.275	1.948	1.654	1.470
235	-	-	4.774	3.638	3.396	3.271	3.171	3.041	2.865	2.549	2.327	2.003	1.674	1.490
240	-	-	4.848	3.688	3.462	3.343	3.245	3.118	2.946	2.591	2.379	2.058	1.710	1.510
245	-	-	4.922	3.737	3.528	3.414	3.319	3.195	3.028	2.633	2.431	2.113	1.759	1.529
250	-	-	4.996	3.786	3.594	3.486	3.393	3.272	3.109	2.675	2.483	2.168	1.808	1.549
255	-	-	5.070	3.836	3.660	3.557	3.468	3.349	3.190	2.718	2.535	2.222	1.857	1.569
260	-	-	5.144	3.885	3.726	3.628	3.542	3.426	3.271	2.760	2.587	2.277	1.906	1.589
265	-	-	5.218	3.982	3.792	3.700	3.616	3.503	3.352	2.824	2.639	2.332	1.955	1.608
270	-	-	5.293	4.088	3.858	3.771	3.690	3.580	3.433	2.919	2.690	2.387	2.004	1.628
275	-	-	5.367	4.193	3.938	3.843	3.764	3.657	3.514	3.014	2.742	2.441	2.053	1.648
280	-	-	5.441	4.298	4.035	3.922	3.838	3.734	3.595	3.109	2.804	2.496	2.102	1.668
285	-	-	5.515	4.403	4.132	4.021	3.919	3.811	3.676	3.204	2.906	2.551	2.151	1.696
290	-	-	-	4.508	4.230	4.119	4.019	3.888	3.757	3.299	3.009	2.606	2.199	1.746
295	-	-	-	4.613	4.327	4.217	4.118	3.988	3.838	3.394	3.111	2.661	2.248	1.797
300	-	-	-	4.718	4.424	4.316	4.218	4.090	3.928	3.489	3.213	2.715	2.297	1.848
305	1	-	-	4.823	4.521	4.414	4.317	4.191	4.033	3.584	3.315	2.770	2.346	1.899
310	1	-	-	4.928	4.618	4.512	4.417	4.293	4.138	3.679	3.418	2.879	2.395	1.950
315	-	-	-	5.034	4.715	4.611	4.517	4.395	4.243	3.774	3.520	3.007	2.444	2.001
320	-	-	-	5.139	4.812	4.709	4.616	4.496	4.348	3.869	3.622	3.135	2.493	2.052
325	1	-	-	5.244	4.909	4.807	4.716	4.598	4.453	3.980	3.724	3.263	2.542	2.103
330	-	-	-	5.349	5.006	4.906	4.815	4.699	4.558	4.096	3.827	3.391	2.591	2.154
335	-	-	-	5.454	5.103	5.004	4.915	4.801	4.663	4.212	3.935	3.519	2.640	2.204
340	-	-	-	-	5.200	5.102	5.015	4.903	4.768	4.328	4.054	3.647	2.689	2.255
345	-	-	-	-	5.297	5.201	5.114	5.004	4.873	4.444	4.173	3.774	2.738	2.306
350	-	-	-	-	5.394	5.299	5.214	5.106	4.978	4.560	4.292	3.901	2.794	2.357
355	1	-	-	-	5.491	5.397	5.313	5.207	5.083	4.676	4.411	4.014	2.983	2.408
360	_	_				5.496	5.413	5.309	5.188	4.792	4.531	4.128	3.172	2.459
Table and	olioo to I	coction	aalumna	with pro	tootion t	•	•		•			•	•	•

Table applies to I-section columns with protection to four sides. Thickness is intumescent only. Table also applies to I-section beams protected on four sides up to a limiting nominal protection thickness of 3.99mm.

Page 17 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

						SC801 - 12						•		
				R	equired Thi	ckness (mm) for a Desig	gn Tempera	ture (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	520°C	530°C	539°C	550°C	563°C	600°C	620°C	650°C	700°C	750°C
90	-	-	3.278	2.851	2.671	2.579	2.498	2.400	2.285	1.835	1.743	1.599	1.391	1.190
95	-	-	3.377	2.929	2.741	2.644	2.557	2.453	2.332	1.877	1.784	1.625	1.405	1.208
100	-	-	3.477	3.006	2.812	2.708	2.617	2.507	2.379	1.920	1.826	1.650	1.419	1.226
105	-	-	3.577	3.083	2.883	2.773	2.677	2.561	2.426	1.963	1.867	1.675	1.433	1.244
110	-	-	3.677	3.161	2.954	2.840	2.736	2.615	2.474	2.005	1.909	1.713	1.447	1.261
115	-	-	3.776	3.238	3.025	2.908	2.797	2.669	2.521	2.048	1.950	1.755	1.461	1.279
120	-	-	3.876	3.316	3.096	2.976	2.860	2.722	2.568	2.091	1.992	1.797	1.474	1.297
125	-	-	3.976	3.393	3.168	3.044	2.924	2.776	2.615	2.133	2.033	1.840	1.488	1.315
130	-	-	4.075	3.470	3.239	3.112	2.988	2.829	2.662	2.176	2.074	1.882	1.502	1.333
135	-	-	4.175	3.548	3.310	3.180	3.051	2.882	2.710	2.219	2.116	1.924	1.516	1.351
140	-	-	-	3.625	3.381	3.248	3.115	2.935	2.757	2.261	2.157	1.966	1.530	1.369
145	-	-	-	3.702	3.452	3.316	3.178	2.988	2.806	2.304	2.199	2.009	1.544	1.387
150	-	-	-	3.780	3.523	3.384	3.242	3.041	2.856	2.347	2.240	2.051	1.557	1.405
155	-	-	-	3.857	3.594	3.452	3.306	3.094	2.907	2.389	2.281	2.093	1.571	1.422
160	-	-	-	3.933	3.665	3.520	3.369	3.146	2.958	2.432	2.323	2.135	1.585	1.440
165	-	-	-	4.007	3.736	3.588	3.433	3.199	3.009	2.475	2.364	2.178	1.599	1.458
170	-	-	-	4.082	3.807	3.656	3.497	3.252	3.059	2.517	2.406	2.220	1.613	1.476
175	-	-	-	4.156	3.878	3.725	3.560	3.305	3.110	2.560	2.447	2.262	1.627	1.494
180	-	-	-	4.231	3.952	3.793	3.624	3.358	3.161	2.603	2.489	2.304	1.641	1.512
185	-	-	-	4.305	4.027	3.861	3.688	3.411	3.212	2.645	2.530	2.347	1.654	1.530
190	-	-	-	4.380	4.101	3.934	3.751	3.464	3.262	2.688	2.571	2.389	1.668	1.548
195	-	-	-	4.455	4.176	4.011	3.815	3.517	3.313	2.731	2.613	2.431	1.682	1.566
200	-	-	-	4.529	4.251	4.088	3.879	3.569	3.364	2.774	2.654	2.473	1.751	1.583
205	-	-	-	4.604	4.325	4.165	3.958	3.622	3.415	2.843	2.696	2.516	1.820	1.601
210	-	-	-	4.678	4.400	4.243	4.042	3.675	3.465	2.921	2.737	2.558	1.890	1.619
215	-	-	-	4.753	4.475	4.320	4.126	3.728	3.516	2.999	2.778	2.600	1.959	1.637
220	-	-	-	4.827	4.549	4.397	4.210	3.781	3.567	3.078	2.855	2.642	2.028	1.655
225	-	-	-	4.902	4.624	4.474	4.294	3.834	3.618	3.156	2.937	2.685	2.097	1.673
230	-	-	-	4.976	4.699	4.552	4.378	3.887	3.668	3.234	3.019	2.727	2.166	1.707
235	-	-	-	5.051	4.773	4.629	4.462	3.998	3.719	3.312	3.101	2.769	2.236	1.758
240	-	-	-	5.125	4.848	4.706	4.546	4.115	3.770	3.390	3.182	2.841	2.305	1.809
245	-	-	-	5.200	4.923	4.783	4.630	4.233	3.821	3.469	3.264	2.929	2.374	1.860
250	-	-	-	5.274	4.997	4.861	4.713	4.351	3.871	3.547	3.346	3.017	2.443	1.912
255	-	-	-	5.349	5.072	4.938	4.797	4.468	3.981	3.625	3.428	3.105	2.512	1.963
260	-	-	-	5.423	5.147	5.015	4.881	4.586	4.132	3.703	3.510	3.193	2.581	2.014
265	-	-	-	-	5.221	5.092	4.965	4.704	4.283	3.781	3.592	3.281	2.651	2.065
270	-	-	-	-	5.296	5.170	5.049	4.821	4.433	3.859	3.674	3.369	2.720	2.116
275	-	-	-	-	5.371	5.247	5.133	4.939	4.584	3.965	3.755	3.457	2.792	2.167
280	-	-	-	-	5.445	5.324	5.217	5.057	4.735	4.090	3.837	3.545	2.899	2.218
285	-	-	-	-	5.520	5.401	5.301	5.174	4.885	4.216	3.932	3.633	3.005	2.270
290	-	-	-	-	-	5.479	5.385	5.292	5.036	4.341	4.053	3.721	3.112	2.321
295	-	-	-	-	-	-	5.469	5.410	5.187	4.466	4.175	3.809	3.219	2.372
300	-	-	-	-	-	-	5.553	5.527	5.337	4.591	4.296	3.899	3.326	2.423
305	-	-	-	-	-	-	-	-	5.488	4.717	4.417	4.022	3.433	2.474
310	-	<u> </u>	<u> </u>	-	-	-	-	-	-	4.842	4.538	4.145	3.540	2.525
315	-	-	-	-	-	-	-	-	-	4.967	4.660	4.268	3.647	2.576
320	-	-	-	-	-	-	-	-	-	5.092	4.781	4.391	3.754	2.628
325	-	-	-	-	-	-	-	-	-	5.218	4.902	4.514	3.861	2.679
330	-	-	-	-	-	-	-	-	-	5.343	5.023	4.637	3.969	2.730
335	-	-	-	-	-	-	-	-	-	-	5.144	4.760	4.079	2.781
340	-	-	-	-	-	-	-	-	-	-	5.266	4.883	4.188	3.085
345	-	-	-	-	-	-	-	-	-	-	5.387	5.006	4.298	3.406
350	-	-	<u> </u>	-	-	-	-	-	-	-	5.508	5.129	4.407	3.727
355	-	-	-	-	-	-	-	-	-	-	-	5.252	4.517	3.936
360	-	-	-	-	-	-	-	-	intumes	-	-	5.375	4.626	4.028

Table applies to I-section columns with protection to four sides. Thickness is intumescent only. Table also applies to I-section beams protected on four sides up to a limiting nominal protection thickness of 3.99mm.

Page 18 of 34 Signed E/200

Pel agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Nullill	16 3	COU	1-120	,	T-1-1-17	CC001 12)	l 15						
						SC801 - 12 nickness (mi								
Section		1	1		Requirea ir	lickness (mi	n) for a Des	ign remper	ature (C)			1	1	1
Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
70	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
75	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
80	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
85	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
90	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
95	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
100	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
105	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
110	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
115	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
120	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
125	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
130	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
135	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
140	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
145	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
150	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
155	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
160	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
165	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
170	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
175	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
180	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
185	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
190	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
195	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
200	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
205	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
210 215	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781
220	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
225	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
230	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
235	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
240	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
245	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
250	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
255	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
260	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
265	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
270	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
275	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
280	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
285	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
290	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
295	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
300	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781

Tabulated values continued overleaf

Page 19 of 34 Signed E/200

Pol Ryg-



Nullifire SC801-120

					Table 17	SC801 - 120) Hollow Co	lumns 15 m	inutes					
					Required Th	ickness (mr	n) for a Des	ign Temper	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
310	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
315	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
320	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
325	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
330	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
335	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
340	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
345	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
350	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
355	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
360	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
365	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
370	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
375	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
380	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
385	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
390	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
395	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
400	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
405	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
410	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
415	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
420	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
425	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
430	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
435	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 20 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Section Soft						Table 18	SC801 - 120) Hollow Co	lumns 30 m	inutes					
40 1.781		350°C	400°C	450°C		1	1				600°C	620°C	650°C	700°C	750°C
Section 1.781 1.	40	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
Section 1781	45	1.781	1.781	1.781		1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65 1.781															
Fig. 1.781									1.781						
The color The															
This 1781															
90															
98															
90															
95															
1781 1781															
105															
1.781 1.78															
1781 1781															
1.781 1.78															
1781 1781															
1.781 1.78															
1781 1.781															
140															
145															
150															
155															
160															
165															
170															
180 1.781 1	170	1.781	1.781	1.781	1.781		1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
185 1.781 1	175	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
190 1.781 1	180	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
195 1.781 1	185	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781		1.781	1.781	1.781	1.781	1.781
200 1.781 1	190	1.781		1.781	1.781	1.781		1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
205 1.781 1															
210 1.781 1															
215 1.781 1															
220 1.805 1.781 1															
225 1.839 1.781 1															
230 1.874 1.781 1															
235 1.908 1.781 1															
240 1.942 1.781 1															
245 1.976 1.781 1															
250 2.011 1.781 1															
255 2.045 1.781 1															
260 2.079 1.781 1															
265 2.114 1.809 1.781 1															
270 2.148 1.844 1.781 1															
275 2.182 1.880 1.781 1															
280 2.216 1.916 1.781 1															
285 2.251 1.951 1.781 1															
290 2.285 1.987 1.781 1															
295 2.319 2.022 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781 1.781															
الا/.1 الا/.1 الا/.1 الا/.1 الا/.1 الا/.1 الا/.1 10/.1 10/.1 10/.1 10/.1 0כك. ا صود	300	2.353	2.058	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781

Tabulated values continued overleaf

Page 21 of 34 Signed E/200

Pol Agg-



Nullifire SC801-120

					Table 18	SC801 - 120	Hollow Co	lumns 30 m	inutes					
				-	Required Th	ickness (mr	n) for a Des	ign Tempera	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	2.388	2.093	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
310	2.422	2.129	1.801	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
315	2.456	2.164	1.838	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
320	2.491	2.200	1.874	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
325	2.525	2.235	1.910	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
330	2.559	2.271	1.946	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
335	2.593	2.306	1.982	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
340	2.628	2.342	2.018	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
345	2.662	2.377	2.055	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
350	2.696	2.413	2.091	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
355	2.731	2.449	2.127	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
360	2.765	2.484	2.163	1.792	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
365	2.799	2.520	2.199	1.828	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
370	2.833	2.555	2.235	1.863	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
375	2.868	2.591	2.272	1.898	1.805	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
380	2.902	2.626	2.308	1.934	1.840	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
385	2.936	2.662	2.344	1.969	1.875	1.804	1.797	1.781	1.781	1.781	1.781	1.781	1.781	1.781
390	2.970	2.697	2.380	2.005	1.910	1.838	1.831	1.781	1.781	1.781	1.781	1.781	1.781	1.781
395	3.005	2.733	2.416	2.040	1.945	1.873	1.866	1.781	1.781	1.781	1.781	1.781	1.781	1.781
400	3.039	2.768	2.453	2.075	1.980	1.908	1.900	1.781	1.781	1.781	1.781	1.781	1.781	1.781
405	3.073	2.804	2.489	2.111	2.015	1.942	1.935	1.781	1.781	1.781	1.781	1.781	1.781	1.781
410	3.108	2.839	2.525	2.146	2.050	1.977	1.969	1.781	1.781	1.781	1.781	1.781	1.781	1.781
415	3.142	2.875	2.561	2.181	2.084	2.011	2.004	1.786	1.781	1.781	1.781	1.781	1.781	1.781
420	3.176	2.910	2.597	2.217	2.119	2.046	2.038	1.819	1.795	1.781	1.781	1.781	1.781	1.781
425	3.210	2.946	2.633	2.252	2.154	2.080	2.072	1.852	1.827	1.781	1.781	1.781	1.781	1.781
430	3.245	2.982	2.670	2.287	2.189	2.115	2.107	1.885	1.860	1.781	1.781	1.781	1.781	1.781
435	3.279	3.017	2.706	2.323	2.224	2.149	2.141	1.918	1.893	1.781	1.781	1.781	1.781	1.781

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 22 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

Nullill		300 I	120		Table 10	SC801 - 120) Hallow Co	lumns 45 m	inutes					
					Required Th									
Section Factor						, , , , , , , , , , , , , , , , , , ,	ĺ	Ĭ	l ` ´					
(m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
70	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
75	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
80	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
85	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
90	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
95	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
100	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
105	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
110	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
115	1.811	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
120	1.902	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
125	1.993	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
130	2.084	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
135	2.175	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
140	2.265	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
145	2.356	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
150	2.447	1.815	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
155	2.538	1.933	1.781	1.781	1.781 1.781	1.781	1.781 1.781	1.781	1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781	1.781
160 165	2.628 2.719	2.052 2.170	1.781 1.781	1.781 1.781	1.781	1.781 1.781	1.781	1.781 1.781	1.781 1.781	1.781	1.781	1.781	1.781 1.781	1.781 1.781
170	2.810	2.288	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
175	2.901	2.407	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
180	2.991	2.525	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
185	3.082	2.644	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
190	3.173	2.762	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
195	3.264	2.881	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
200	3.354	2.999	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
205	3.445	3.118	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
210	3.489	3.236	1.818	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
215	3.530	3.354	1.934	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
220	3.571	3.457	2.051	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
225	3.612	3.491	2.167	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
230	3.653	3.525	2.284	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
235	3.694	3.558	2.400	1.795	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
240	3.734	3.592	2.517	1.861	1.789	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
245	3.775	3.626	2.633	1.928	1.846	1.791	1.785	1.781	1.781	1.781	1.781	1.781	1.781	1.781
250	3.816	3.659	2.749	1.994	1.904	1.845	1.839	1.781	1.781	1.781	1.781	1.781	1.781	1.781
255	3.857	3.693	2.866	2.061	1.962	1.899	1.893	1.781	1.781	1.781	1.781	1.781	1.781	1.781
260	3.898	3.727	2.982	2.127	2.020	1.953	1.946	1.781	1.781	1.781	1.781	1.781	1.781	1.781
265	3.939	3.760	3.099	2.194	2.078	2.007	2.000	1.808	1.787	1.781	1.781	1.781	1.781	1.781
270	3.980	3.794	3.215	2.260	2.136	2.061	2.054	1.860	1.839	1.781	1.781	1.781	1.781	1.781
275	4.021	3.828	3.332	2.327	2.193	2.115	2.108	1.912	1.891	1.781	1.781	1.781	1.781	1.781
280	4.061	3.862	3.448	2.394	2.251	2.169	2.162	1.964	1.942	1.781	1.781	1.781	1.781	1.781
285	4.102	3.895	3.488	2.460	2.309	2.223	2.216	2.016	1.994	1.781	1.781	1.781	1.781	1.781
290	4.143	3.929	3.525	2.527	2.367	2.277	2.270	2.068	2.046	1.781	1.781	1.781	1.781	1.781
295	4.184	3.963	3.563	2.593	2.425	2.331	2.323	2.121	2.097	1.781	1.781	1.781	1.781	1.781
300	4.225	3.996	3.601	2.660	2.483	2.385	2.377	2.173	2.149	1.781	1.781	1.781	1.781	1.781

Tabulated values continued overleaf

Page 23 of 34 Signed E/200

Pol Agg-



Nullifire SC801-120

					Table 19	SC801 - 120	Hollow Col	umns 45 m	inutes					
				F	Required Th	ickness (mn	n) for a Desi	gn Tempera	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	4.266	4.030	3.638	2.726	2.540	2.439	2.431	2.225	2.200	1.801	1.781	1.781	1.781	1.781
310	4.307	4.064	3.676	2.793	2.598	2.493	2.485	2.277	2.252	1.845	1.781	1.781	1.781	1.781
315	4.348	4.097	3.714	2.859	2.656	2.547	2.539	2.329	2.304	1.890	1.781	1.781	1.781	1.781
320	4.388	4.131	3.751	2.926	2.714	2.601	2.593	2.381	2.355	1.935	1.781	1.781	1.781	1.781
325	4.429	4.165	3.789	2.992	2.772	2.655	2.647	2.433	2.407	1.980	1.813	1.781	1.781	1.781
330	4.470	4.198	3.827	3.059	2.830	2.709	2.701	2.485	2.459	2.024	1.855	1.781	1.781	1.781
335	4.511	4.232	3.864	3.125	2.887	2.763	2.754	2.537	2.510	2.069	1.896	1.781	1.781	1.781
340	4.552	4.266	3.902	3.192	2.945	2.817	2.808	2.589	2.562	2.114	1.938	1.781	1.781	1.781
345	4.593	4.300	3.940	3.259	3.003	2.871	2.862	2.641	2.614	2.158	1.979	1.781	1.781	1.781
350	4.634	4.333	3.977	3.325	3.061	2.925	2.916	2.693	2.665	2.203	2.021	1.781	1.781	1.781
355	4.674	4.367	4.015	3.392	3.119	2.979	2.970	2.745	2.717	2.248	2.062	1.781	1.781	1.781
360	4.715	4.401	4.053	3.456	3.177	3.033	3.024	2.797	2.768	2.293	2.104	1.798	1.781	1.781
365	4.756	4.434	4.090	3.503	3.235	3.087	3.078	2.849	2.820	2.337	2.145	1.835	1.781	1.781
370	4.797	4.468	4.128	3.550	3.292	3.141	3.131	2.901	2.872	2.382	2.186	1.871	1.781	1.781
375	4.838	4.502	4.166	3.597	3.350	3.195	3.185	2.953	2.923	2.427	2.228	1.908	1.781	1.781
380	4.879	4.535	4.203	3.644	3.408	3.249	3.239	3.005	2.975	2.471	2.269	1.945	1.781	1.781
385	4.925	4.569	4.241	3.691	3.464	3.303	3.293	3.057	3.027	2.516	2.311	1.982	1.781	1.781
390	4.975	4.603	4.279	3.738	3.515	3.357	3.347	3.109	3.078	2.561	2.352	2.019	1.781	1.781
395	5.025	4.637	4.316	3.785	3.567	3.411	3.401	3.161	3.130	2.606	2.394	2.055	1.781	1.781
400	5.075	4.670	4.354	3.832	3.618	3.465	3.455	3.213	3.181	2.650	2.435	2.092	1.781	1.781
405	5.125	4.704	4.392	3.879	3.669	3.519	3.509	3.265	3.233	2.695	2.477	2.129	1.781	1.781
410	5.174	4.738	4.429	3.926	3.720	3.574	3.564	3.317	3.285	2.740	2.518	2.166	1.781	1.781
415	5.224	4.771	4.467	3.973	3.772	3.628	3.618	3.369	3.336	2.784	2.560	2.203	1.781	1.781
420	5.274	4.805	4.505	4.019	3.823	3.683	3.672	3.421	3.388	2.829	2.601	2.239	1.781	1.781
425	5.324	4.839	4.542	4.066	3.874	3.737	3.727	3.474	3.440	2.874	2.642	2.276	1.781	1.781
430	5.374	4.872	4.580	4.113	3.926	3.792	3.781	3.528	3.493	2.919	2.684	2.313	1.781	1.781
435	5.424	4.912	4.617	4.160	3.977	3.846	3.836	3.581	3.546	2.963	2.725	2.350	1.781	1.781

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 24 of 34 Signed E/200

Pol Ryg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

					Table 20 S	C801 - 120	Hollow Colu	ımns 60 mi	nutes					
				R				gn Tempera						
Section Factor					Ι .	,	Ĺ	i i	<u> </u>					
(m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
70	1.854	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
75	1.944	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
80	2.034	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
85	2.124	1.812	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
90	2.215	1.893	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
95	2.305	1.973	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
100	2.395	2.053	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
105	2.485	2.134	1.845	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
110	2.575	2.214	1.931	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
115	2.666	2.295	2.017	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
120	2.756	2.375	2.103	1.793	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
125	2.846	2.455	2.188	1.885	1.808	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
130	2.936	2.536	2.274	1.977	1.902	1.783	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
135	3.027	2.616	2.360	2.069	1.995	1.882	1.864	1.781	1.781	1.781	1.781	1.781	1.781	1.781
140	3.117	2.697	2.446	2.161	2.089	1.980	1.963	1.781	1.781	1.781	1.781	1.781	1.781	1.781
145	3.207	2.777	2.532	2.253	2.182	2.079	2.063	1.781	1.781	1.781	1.781	1.781	1.781	1.781
150	3.297	2.857	2.617	2.346	2.276	2.177	2.162	1.781	1.781	1.781	1.781	1.781	1.781	1.781
155	3.388	2.938	2.703	2.438	2.369	2.276	2.261	1.781	1.781	1.781	1.781	1.781	1.781	1.781
160	3.498	3.018	2.789	2.530	2.463	2.374	2.361	1.781	1.781	1.781	1.781	1.781	1.781	1.781
165	3.657	3.099	2.875	2.622	2.556	2.473	2.460	1.845	1.781	1.781	1.781	1.781	1.781	1.781
170	3.815	3.179	2.960	2.714	2.650	2.572	2.560	1.983	1.865	1.781	1.781	1.781	1.781	1.781
175	3.974	3.259	3.046	2.807	2.744	2.670	2.659	2.120	2.006	1.781	1.781	1.781	1.781	1.781
180 185	4.132 4.291	3.340	3.132 3.218	2.899 2.991	2.837	2.769 2.867	2.759 2.858	2.257	2.146	1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781
		3.420			2.931			2.395	2.286	1.781				
190 195	4.449 4.608	3.612 3.874	3.303 3.389	3.083 3.175	3.024 3.118	2.966 3.064	2.957 3.057	2.532 2.669	2.427 2.567	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781
200	4.767	4.135	3.491	3.267	3.211	3.163	3.156	2.806	2.707	1.781	1.781	1.781	1.781	1.781
205	4.903	4.133	3.635	3.360	3.305	3.261	3.256	2.806	2.847	1.781	1.781	1.781	1.781	1.781
210	4.946	4.658	3.780	3.451	3.398	3.360	3.355	3.081	2.988	1.781	1.781	1.781	1.781	1.781
215	4.946	4.898	3.924	3.510	3.473	3.454	3.453	3.218	3.128	1.781	1.781	1.781	1.781	1.781
220	5.032	4.898	4.068	3.569	3.522	3.499	3.497	3.356	3.268	1.781	1.781	1.781	1.781	1.781
225	5.076	4.966	4.212	3.628	3.572	3.544	3.541	3.463	3.409	1.781	1.781	1.781	1.781	1.781
230	5.119	5.000	4.212	3.687	3.621	3.589	3.586	3.502	3.478	1.827	1.781	1.781	1.781	1.781
235	5.162	5.034	4.500	3.746	3.671	3.634	3.630	3.541	3.518	1.960	1.781	1.781	1.781	1.781
240	5.205	5.069	4.644	3.805	3.720	3.679	3.675	3.580	3.557	2.093	1.839	1.781	1.781	1.781
245	5.248	5.103	4.788	3.864	3.770	3.724	3.719	3.619	3.596	2.226	1.923	1.781	1.781	1.781
250	5.291	5.137	4.904	3.922	3.819	3.769	3.763	3.659	3.636	2.359	2.007	1.781	1.781	1.781
255	5.334	5.171	4.938	3.981	3.869	3.814	3.808	3.698	3.675	2.492	2.091	1.791	1.781	1.781
260	5.377	5.205	4.972	4.040	3.918	3.859	3.852	3.737	3.714	2.625	2.175	1.843	1.781	1.781
265	5.420	5.239	5.007	4.099	3.968	3.904	3.896	3.776	3.754	2.759	2.259	1.895	1.781	1.781
270	5.463	5.273	5.041	4.158	4.017	3.949	3.941	3.815	3.793	2.892	2.343	1.946	1.781	1.781
275	5.506	5.307	5.075	4.217	4.067	3.994	3.985	3.854	3.832	3.025	2.427	1.998	1.781	1.781
280	5.549	5.341	5.109	4.276	4.116	4.039	4.030	3.893	3.872	3.158	2.511	2.050	1.781	1.781
285	5.593	5.375	5.143	4.335	4.166	4.084	4.074	3.933	3.911	3.291	2.595	2.102	1.781	1.781
290	5.636	5.409	5.178	4.393	4.215	4.129	4.118	3.972	3.950	3.424	2.679	2.154	1.781	1.781
295	5.679	5.443	5.212	4.452	4.265	4.174	4.163	4.011	3.990	3.488	2.763	2.206	1.781	1.781
300	5.722	5.477	5.246	4.511	4.314	4.219	4.207	4.050	4.029	3.534	2.847	2.257	1.781	1.781

Tabulated values continued overleaf

Page 25 of 34 Signed E/200

Pol Agg-



Nullifire SC801-120

					Table 20 S	C801 - 120	Hollow Colu	ımns 60 mi	nutes					
				R	equired Thi	ckness (mm) for a Desi	gn Tempera	ture (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	5.765	5.511	5.280	4.570	4.364	4.264	4.252	4.089	4.068	3.581	2.931	2.309	1.813	1.781
310	5.808	5.545	5.315	4.629	4.413	4.309	4.296	4.128	4.108	3.627	3.015	2.361	1.855	1.781
315	5.851	5.579	5.349	4.688	4.463	4.354	4.340	4.167	4.147	3.674	3.099	2.413	1.897	1.781
320	5.894	5.614	5.383	4.747	4.512	4.399	4.385	4.206	4.186	3.720	3.183	2.465	1.939	1.781
325	5.937	5.648	5.417	4.806	4.562	4.444	4.429	4.246	4.226	3.766	3.267	2.517	1.982	1.781
330	5.980	5.682	5.451	4.864	4.611	4.489	4.473	4.285	4.265	3.813	3.351	2.568	2.024	1.781
335	6.023	5.716	5.486	4.916	4.661	4.534	4.518	4.324	4.304	3.859	3.436	2.620	2.066	1.781
340	6.066	5.750	5.520	4.961	4.710	4.579	4.562	4.363	4.344	3.905	3.497	2.672	2.108	1.784
345	6.110	5.784	5.554	5.005	4.760	4.623	4.607	4.402	4.383	3.952	3.554	2.724	2.150	1.813
350	6.153	5.818	5.588	5.049	4.809	4.668	4.651	4.441	4.422	3.998	3.611	2.776	2.192	1.843
355	6.196	5.852	5.623	5.093	4.859	4.713	4.695	4.480	4.462	4.045	3.668	2.828	2.234	1.872
360	6.239	5.886	5.657	5.138	4.908	4.758	4.740	4.519	4.501	4.091	3.725	2.879	2.276	1.902
365	6.282	5.920	5.691	5.182	4.958	4.803	4.784	4.559	4.540	4.137	3.782	2.931	2.319	1.931
370	6.325	5.954	5.725	5.226	5.007	4.848	4.829	4.598	4.580	4.184	3.839	2.983	2.361	1.961
375	6.429	5.988	5.759	5.270	5.057	4.893	4.873	4.637	4.619	4.230	3.896	3.035	2.403	1.990
380	6.547	6.022	5.794	5.315	5.106	4.946	4.922	4.676	4.658	4.277	3.953	3.087	2.445	2.020
385	6.666	6.056	5.828	5.359	5.156	5.000	4.976	4.715	4.698	4.323	4.010	3.139	2.487	2.049
390	6.784	6.090	5.862	5.403	5.205	5.053	5.030	4.754	4.737	4.369	4.067	3.190	2.529	2.079
395	6.902	6.125	5.896	5.447	5.255	5.106	5.084	4.793	4.776	4.416	4.123	3.242	2.571	2.108
400	7.021	6.159	5.931	5.492	5.304	5.159	5.138	4.832	4.816	4.462	4.180	3.294	2.613	2.137
405	7.139	6.193	5.965	5.536	5.354	5.213	5.192	4.872	4.855	4.509	4.237	3.346	2.655	2.167
410	7.257	6.227	5.999	5.580	5.403	5.266	5.246	4.918	4.894	4.555	4.294	3.398	2.698	2.196
415	7.375	6.261	6.033	5.624	5.452	5.319	5.300	4.976	4.951	4.601	4.351	3.450	2.740	2.226
420	7.494	6.295	6.067	5.669	5.502	5.373	5.354	5.034	5.009	4.648	4.408	3.545	2.782	2.255
425	7.612	6.329	6.102	5.713	5.551	5.426	5.407	5.092	5.067	4.694	4.465	3.641	2.824	2.285
430	7.730	6.462	6.136	5.757	5.601	5.479	5.461	5.150	5.125	4.740	4.522	3.738	2.866	2.314
435	7.849	6.608	6.170	5.801	5.650	5.533	5.515	5.207	5.182	4.787	4.579	3.834	2.908	2.344

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 26 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

					Table 21	SC801 - 12	0 Hollow Co	lumns 75 m	inutes					
					Required Th	nickness (mı	m) for a Des	ign Temper	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	1.892	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	2.020	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	2.148	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	2.277	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	2.405	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	2.533	1.860	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
70	2.661	1.985	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
75	2.790	2.110	1.833	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
80	2.918	2.235	1.929	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
85	3.046	2.360	2.024	1.808	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
90	3.175	2.485	2.120	1.890	1.841	1.804	1.799	1.781	1.781	1.781	1.781	1.781	1.781	1.781
95	3.303	2.610	2.215	1.973	1.924	1.887	1.883	1.781	1.781	1.781	1.781	1.781	1.781	1.781
100	3.431	2.735	2.310	2.055	2.007	1.970	1.966	1.851	1.838	1.781	1.781	1.781	1.781	1.781
105	3.650	2.860	2.406	2.138	2.090	2.054	2.050	1.936	1.923	1.781	1.781	1.781	1.781	1.781
110 115	3.885 4.120	2.985 3.110	2.501 2.597	2.220 2.302	2.173 2.255	2.137 2.220	2.133 2.216	2.020 2.105	2.007 2.092	1.781 1.850	1.781 1.781	1.781 1.781	1.781 1.781	1.781 1.781
120	4.120	3.235	2.692	2.302	2.338	2.304	2.300	2.103	2.092	1.938	1.822	1.781	1.781	1.781
125	4.591	3.360	2.787	2.363	2.336	2.304	2.383	2.190	2.261	2.026	1.912	1.781	1.781	1.781
130	4.826	3.482	2.883	2.550	2.504	2.470	2.467	2.359	2.346	2.113	2.002	1.781	1.781	1.781
135	5.061	3.597	2.978	2.632	2.587	2.554	2.550	2.443	2.430	2.201	2.091	1.781	1.781	1.781
140	5.297	3.711	3.074	2.715	2.669	2.637	2.633	2.528	2.515	2.289	2.181	1.781	1.781	1.781
145	5.532	3.826	3.169	2.797	2.752	2.720	2.717	2.612	2.600	2.377	2.271	1.781	1.781	1.781
150	5.767	3.941	3.265	2.879	2.835	2.804	2.800	2.697	2.684	2.465	2.361	1.781	1.781	1.781
155	6.002	4.055	3.360	2.962	2.918	2.887	2.884	2.781	2.769	2.552	2.450	1.797	1.781	1.781
160	6.238	4.170	3.459	3.044	3.001	2.971	2.967	2.866	2.854	2.640	2.540	1.928	1.781	1.781
165	6.364	4.285	3.634	3.127	3.083	3.054	3.050	2.950	2.938	2.728	2.630	2.058	1.781	1.781
170	6.416	4.399	3.809	3.209	3.166	3.137	3.134	3.035	3.023	2.816	2.720	2.188	1.781	1.781
175	6.468	4.514	3.983	3.292	3.249	3.221	3.217	3.119	3.108	2.904	2.810	2.318	1.781	1.781
180	6.521	4.628	4.158	3.374	3.332	3.304	3.300	3.204	3.192	2.992	2.899	2.448	1.781	1.781
185	6.573	4.743	4.333	3.470	3.415	3.387	3.384	3.288	3.277	3.079	2.989	2.578	1.781	1.781
190	6.625	4.858	4.508	3.752	3.611	3.519	3.507	3.373	3.361	3.167	3.079	2.708	1.781	1.781
195	6.677	5.438	4.683	4.034	3.897	3.807	3.795	3.473	3.446	3.255	3.169	2.838	1.781	1.781
200	6.729	6.243	4.857	4.316	4.183	4.095	4.084	3.769	3.731	3.343	3.258	2.969	1.781	1.781
205	6.781	6.375	4.984	4.599	4.470	4.383	4.372	4.066	4.028	3.431	3.348	3.099	1.781	1.781
210	6.834	6.422	5.098	4.881	4.756	4.671	4.660	4.362	4.325	3.531	3.438	3.229	1.781	1.781
215	6.886	6.469	5.211	4.936	4.915	4.903	4.902	4.659	4.623	3.636	3.518	3.359	1.781	1.781
220	6.938	6.516	5.325	4.980	4.953	4.941	4.940	4.902	4.898	3.741	3.597	3.467	1.781	1.781
225	6.990	6.563	5.438	5.024	4.992	4.979	4.978	4.938	4.934	3.846	3.676	3.522	1.781	1.781
230	7.042	6.610	5.552	5.068	5.031	5.017	5.016	4.974	4.969	3.950	3.754	3.576	1.781	1.781
235	7.094	6.657	5.665	5.111	5.069	5.055	5.054	5.010	5.005	4.055	3.833	3.631	1.781	1.781
240	7.147	6.704	5.779	5.155	5.108	5.093	5.091	5.046	5.040	4.160	3.912	3.686	1.838	1.781
245	7.199	6.751	5.892	5.199	5.146	5.131	5.129	5.081	5.076	4.265	3.990	3.740	1.921	1.781
250	7.251	6.798	6.006	5.242	5.185	5.169	5.167	5.117	5.112	4.370	4.069	3.795	2.004	1.781
255	7.303	6.845	6.120	5.286	5.224	5.207	5.205	5.153	5.147	4.474	4.148	3.850	2.087	1.798
260	7.355	6.892	6.233	5.330	5.262	5.245	5.243	5.189	5.183	4.579	4.226	3.904	2.170	1.837
265	7.407	6.939	6.341	5.373	5.301	5.283	5.281	5.225	5.218	4.684	4.305	3.959	2.253	1.877
270	7.460	6.986	6.403	5.417	5.339	5.321	5.319	5.261	5.254	4.789	4.384	4.013	2.336	1.916
275	7.512	7.033	6.465	5.461	5.378	5.359	5.357	5.296	5.290	4.893	4.462	4.068	2.419	1.956
280	7.564	7.080	6.528	5.504	5.417	5.397	5.395	5.332	5.325	4.935	4.541	4.123	2.501	1.995
285	7.616	7.127	6.590	5.548	5.455	5.435	5.433	5.368	5.361	4.975	4.620	4.177	2.584	2.035
290 295	7.668	7.174 7.221	6.652	5.592	5.494	5.473 5.511	5.470 5.508	5.404 5.440	5.396 5.432	5.015	4.698 4.777	4.232 4.287	2.667 2.750	2.075
300	7.720 7.773	7.221	6.715 6.777	5.635 5.679	5.532 5.571	5.511	5.508	5.440	5.432	5.055 5.095	4.777	4.287	2.750	2.114 2.154
300	1.//3	7.268	0.///	5.0/9	5.5/1	5.549	5.546	5.4/5	5.468	5.095	4.856	4.341	2.833	2.154

Tabulated values continued overleaf

Page 27 of 34 Signed E/200

Pol Ryg-



Nullifire SC801-120

					Table 21	SC801 - 12	O Hollow Co	lumns 75 m	inutes					
					Required Th	nickness (mı	n) for a Des	ign Temper	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	7.825	7.315	6.840	5.723	5.610	5.587	5.584	5.511	5.503	5.136	4.917	4.396	2.916	2.193
310	7.877	7.362	6.902	5.766	5.648	5.625	5.622	5.547	5.539	5.176	4.960	4.451	2.999	2.233
315	7.929	7.409	6.964	5.810	5.687	5.663	5.660	5.583	5.575	5.216	5.003	4.505	3.082	2.272
320	7.981	7.456	7.027	5.854	5.725	5.701	5.698	5.619	5.610	5.256	5.047	4.560	3.165	2.312
325	8.033	7.503	7.089	5.897	5.764	5.739	5.736	5.655	5.646	5.296	5.090	4.615	3.248	2.351
330	8.086	7.551	7.152	5.941	5.803	5.777	5.774	5.690	5.681	5.336	5.133	4.669	3.331	2.391
335	8.138	7.598	7.214	5.985	5.841	5.815	5.812	5.726	5.717	5.377	5.177	4.724	3.413	2.431
340	8.190	7.645	7.276	6.028	5.880	5.853	5.849	5.762	5.753	5.417	5.220	4.778	3.500	2.470
345	8.242	7.692	7.339	6.072	5.918	5.891	5.887	5.798	5.788	5.457	5.263	4.833	3.591	2.510
350	-	7.739	7.401	6.116	5.957	5.929	5.925	5.834	5.824	5.497	5.306	4.888	3.681	2.549
355	-	7.786	7.464	6.159	5.996	5.967	5.963	5.869	5.859	5.537	5.350	4.939	3.771	2.589
360	-	7.833	7.526	6.203	6.034	6.005	6.001	5.905	5.895	5.578	5.393	4.989	3.862	2.628
365	-	7.880	7.588	6.247	6.073	6.043	6.039	5.941	5.931	5.618	5.436	5.040	3.952	2.668
370	-	7.927	7.651	6.290	6.111	6.081	6.077	5.977	5.966	5.658	5.480	5.091	4.042	2.708
375	-	7.974	7.713	6.338	6.150	6.119	6.115	6.013	6.002	5.698	5.523	5.141	4.132	2.747
380	-	8.021	7.776	6.526	6.189	6.157	6.153	6.049	6.037	5.738	5.566	5.192	4.223	2.787
385	-	8.068	7.838	6.714	6.227	6.195	6.191	6.084	6.073	5.779	5.610	5.242	4.313	2.826
390	-	8.115	7.900	6.902	6.266	6.233	6.228	6.120	6.109	5.819	5.653	5.293	4.403	2.866
395	-	8.162	7.963	7.091	6.304	6.271	6.266	6.156	6.144	5.859	5.696	5.344	4.494	2.905
400	-	8.209	8.025	7.279	6.418	6.309	6.304	6.192	6.180	5.899	5.740	5.394	4.584	2.945
405	-	8.256	8.088	7.467	6.749	6.451	6.413	6.228	6.215	5.939	5.783	5.445	4.674	2.984
410	-	-	8.150	7.655	7.080	6.784	6.745	6.263	6.251	5.979	5.826	5.495	4.765	3.024
415	-	-	8.212	7.843	7.411	7.116	7.077	6.299	6.287	6.020	5.870	5.546	4.855	3.064
420	-	-	8.275	8.032	7.741	7.449	7.409	6.354	6.322	6.060	5.913	5.597	4.927	3.103
425	-	-	8.337	8.220	8.072	7.781	7.741	6.708	6.581	6.100	5.956	5.647	4.984	3.143
430	-	-	8.400	8.408	8.403	8.114	8.073	7.062	6.937	6.140	6.000	5.698	5.041	3.182
435	-	-	-	-	-	8.447	8.404	7.415	7.292	6.180	6.043	5.748	5.098	3.222

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 28 of 34 Signed E/200

Pol Ryg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

					Table 22	SC801 - 120	Hollow Col	umns 90 mi	inutes					
					Required Th									
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	2.875	2.043	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	2.967	2.181	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	3.058	2.320	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	3.150	2.458	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	3.241	2.596	1.866	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	3.333	2.734	2.018	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
70	3.424	2.873	2.170	1.838	1.793	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
75	3.581	3.011	2.322	1.963	1.911	1.874	1.870	1.785	1.781	1.781	1.781	1.781	1.781	1.781
80	3.764	3.149	2.474	2.089	2.029	1.988	1.984	1.883	1.872	1.781	1.781	1.781	1.781	1.781
85	3.947	3.287	2.626	2.215	2.147	2.102	2.097	1.981	1.968	1.793	1.781	1.781	1.781	1.781
90	4.130	3.426	2.778	2.340	2.265	2.215	2.210	2.079	2.065	1.877	1.794	1.781	1.781	1.781
95	4.313	3.728	2.930	2.466	2.383	2.329	2.323	2.177	2.162	1.960	1.878	1.781	1.781	1.781
100	4.496	4.068	3.082	2.591	2.500	2.443	2.436	2.275	2.259	2.044	1.962	1.835	1.781	1.781
105	4.679	4.408	3.234	2.717	2.618	2.557	2.549	2.374	2.355	2.127	2.047	1.921	1.781	1.781
110	4.862	4.747	3.386	2.843	2.736	2.670	2.662	2.472	2.452	2.211	2.131	2.006	1.781	1.781
115	5.087	5.087	3.630	2.968	2.854	2.784	2.776	2.570	2.549	2.295	2.216	2.092	1.826	1.781
120	5.228	5.426	3.943	3.094	2.972	2.898	2.889	2.668	2.645	2.378	2.300	2.177	1.912	1.781
125	-	5.766	4.256	3.220	3.089	3.012	3.002	2.766	2.742	2.462	2.385	2.262	1.999	1.781
130	-	6.106	4.569	3.345	3.207	3.125	3.115	2.864	2.839	2.545	2.469	2.348	2.086	1.781
135 140	-	6.353	4.881	3.493	3.325	3.239	3.228	2.962	2.935	2.629	2.554	2.433	2.173	1.781
140		6.413 6.473	5.194 5.507	3.753 4.014	3.443 3.578	3.353 3.471	3.341 3.455	3.061 3.159	3.032 3.129	2.712 2.796	2.638	2.518 2.604	2.260 2.346	1.781 1.781
150		6.534	5.820	4.014	3.578	3.471	3.455	3.159	3.129	2.796	2.722	2.689	2.433	1.781
155		6.594	6.133	4.274	3.850	3.756	3.743	3.355	3.322	2.963	2.891	2.775	2.433	1.781
160		6.654	6.355	4.796	3.986	3.899	3.887	3.455	3.419	3.046	2.976	2.860	2.607	1.781
165		6.714	6.417	5.056	4.122	4.042	4.031	3.636	3.575	3.130	3.060	2.945	2.693	1.781
170		6.775	6.479	5.317	4.259	4.185	4.175	3.817	3.762	3.213	3.145	3.031	2.780	1.781
175		6.835	6.541	5.578	4.395	4.328	4.319	3.999	3.949	3.297	3.229	3.116	2.867	1.781
180	-	6.895	6.602	5.838	4.531	4.471	4.463	4.180	4.136	3.380	3.313	3.202	2.954	1.781
185	-	6.955	6.664	6.099	4.667	4.613	4.606	4.361	4.322	3.494	3.398	3.287	3.041	1.781
190	-	7.016	6.726	6.339	4.803	4.756	4.750	4.542	4.509	3.778	3.557	3.372	3.127	1.781
195	-	7.076	6.788	6.403	5.378	4.916	4.894	4.723	4.696	4.061	3.841	3.474	3.214	1.781
200	-	7.136	6.849	6.466	6.356	5.668	5.591	4.907	4.882	4.344	4.126	3.767	3.301	1.781
205	-	7.196	6.911	6.529	6.420	6.340	6.291	5.136	5.089	4.628	4.411	4.061	3.388	1.781
210	-	7.257	6.973	6.592	6.484	6.405	6.394	5.365	5.298	4.899	4.696	4.354	3.482	1.781
215	-	7.317	7.035	6.655	6.548	6.469	6.458	5.595	5.506	4.971	4.911	4.647	3.597	1.781
220	-	7.377	7.096	6.718	6.612	6.534	6.523	5.824	5.714	5.044	4.964	4.901	3.712	1.907
225	-	7.437	7.158	6.781	6.676	6.598	6.587	6.053	5.923	5.116	5.018	4.940	3.827	2.043
230	-	7.498	7.220	6.844	6.739	6.663	6.652	6.283	6.131	5.189	5.071	4.980	3.941	2.178
235	-	7.558	7.282	6.907	6.803	6.727	6.717	6.387	6.335	5.261	5.125	5.019	4.056	2.313
240	-	7.618	7.343	6.970	6.867	6.792	6.781	6.456	6.405	5.333	5.178	5.058	4.171	2.448
245	-	7.678	7.405	7.034	6.931	6.856	6.846	6.526	6.476	5.406	5.232	5.097	4.286	2.583
250	-	7.739	7.467	7.097	6.995	6.921	6.910	6.595	6.546	5.478	5.285	5.137	4.401	2.719
255	-	7.799	7.529	7.160	7.059	6.985	6.975	6.664	6.616	5.551	5.338	5.176	4.515	2.854
260	-	7.859	7.590	7.223	7.123	7.050	7.040	6.734	6.687	5.623	5.392	5.215	4.630	2.989
265	-	7.919	7.652	7.286	7.187	7.114	7.104	6.803	6.757	5.695	5.445	5.254	4.745	3.124
270	-	7.980	7.714	7.349	7.251	7.179	7.169	6.872	6.827	5.768	5.499	5.294	4.860	3.260
275	-	8.040	7.776	7.412	7.315	7.244	7.233	6.942	6.898	5.840	5.552	5.333	4.925	3.395
280	-	8.100	7.837	7.475	7.379	7.308	7.298	7.011	6.968	5.913	5.605	5.372	4.968	3.508
285	-	8.160	7.899	7.538	7.443	7.373	7.362	7.080	7.038	5.985	5.659	5.412	5.011	3.605
290	-	8.221	7.961	7.602	7.507	7.437	7.427	7.150	7.109	6.057	5.712	5.451	5.053	3.703
295	-	-	8.023	7.665	7.571	7.502	7.492	7.219	7.179	6.130	5.766	5.490	5.096	3.800
300	-	-	8.084	7.728	7.635	7.566	7.556	7.288	7.249	6.202	5.819	5.529	5.139	3.897

Tabulated values continued overleaf

Page 29 of 34 Signed E/200

Pol Ryg-



Nullifire SC801-120

					Table 22	SC801 - 120	Hollow Co	umns 90 m	inutes					
				F	Required Th	ickness (mn	n) for a Des	ign Tempera	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	-	-	8.146	7.791	7.699	7.631	7.621	7.358	7.320	6.274	5.873	5.569	5.182	3.995
310	-	-	8.208	7.854	7.763	7.695	7.685	7.427	7.390	6.353	5.926	5.608	5.225	4.092
315	-	-	8.270	7.917	7.827	7.760	7.750	7.496	7.460	6.456	5.979	5.647	5.268	4.189
320	-	-	-	7.980	7.891	7.824	7.815	7.566	7.531	6.559	6.033	5.686	5.311	4.287
325	-	-	-	8.043	7.955	7.889	7.879	7.635	7.601	6.662	6.086	5.726	5.354	4.384
330	-	-	-	8.106	8.019	7.953	7.944	7.704	7.671	6.766	6.140	5.765	5.397	4.481
335	-	-	-	8.169	8.083	8.018	8.008	7.774	7.742	6.869	6.193	5.804	5.440	4.579
340	-	-	-	8.233	8.147	8.082	8.073	7.843	7.812	6.972	6.247	5.843	5.482	4.676
345	-	-	-	8.296	8.211	8.147	8.137	7.912	7.882	7.075	6.300	5.883	5.525	4.773
350	-	-	-	-	8.275	8.211	8.202	7.982	7.953	7.179	6.389	5.922	5.568	4.871
355	-	-	-	-	8.338	8.276	8.267	8.051	8.023	7.282	6.537	5.961	5.611	4.936
360	-	-	-	-		8.340	8.331	8.120	8.093	7.385	6.684	6.000	5.654	4.990
365	-	-	-	-		-	-	8.190	8.164	7.488	6.832	6.040	5.697	5.044
370	-	-	-	-	-	-	-	8.259	8.234	7.592	6.979	6.079	5.740	5.099
375	-	-	-	-	-	-	-	8.328	8.304	7.695	7.127	6.118	5.783	5.153
380	-	-	-	-	-	-	-	-	8.375	7.798	7.274	6.158	5.826	5.207
385	-	-	-	-	1	-	-	-	8.445	7.901	7.422	6.197	5.869	5.262
390	-	-	-	-	•	-	-	-	-	8.005	7.569	6.236	5.912	5.316
395	-	-	-	-		-	-	-	-	8.108	7.717	6.275	5.954	5.371
400	-	-	-	-		-	-	-	-	8.211	7.864	6.315	5.997	5.425
405	-	-	-	-		-	-	-	-	8.314	8.012	6.559	6.040	5.479
410	-	-	-	-	-	-	-	-	-	8.418	8.160	6.986	6.083	5.534
415	-	-	-	-	-	-	-	-	-	8.521	8.307	7.413	6.126	5.588
420	-	-	-	-	-	-	-	-	-	8.624	8.455	7.840	6.169	5.642
425	-	-	-	-	-	-	-	-	-	-	8.602	8.267	6.212	5.697
430	-	-	-	-	-	-	-	-	-	-	-	-	6.255	5.751
435	-	-	-	-	-	-	-	-	-	-	-	-	6.298	5.805

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 30 of 34 Signed E/200

Pol Agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

Nullifire SC801-120

					Table 23 S	C801 - 120	Hollow Colu	ımns 105 m	ninutes					
				F	Required Th									
Section Factor	350°C	400°C	450°C	500°C	512°C	520°C	F218C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
(m-1)	350 C	400 C	450 C	500 C	512 C	520 C	521°C	547 C	550 C	600 C	620 C	650 C	700 C	750 C
40	3.893	2.968	2.177	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
45	4.076	3.049	2.320	1.786	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
50	4.260	3.131	2.462	1.935	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
55	4.443	3.212	2.605	2.084	1.855	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
60	4.627	3.294	2.748	2.234	2.014	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781	1.781
65	4.810	3.376	2.890	2.383	2.174	1.948	1.938	1.811	1.796	1.781	1.781	1.781	1.781	1.781
70	4.984	3.476	3.033	2.533	2.333	2.124	2.113	1.967	1.950	1.781	1.781	1.781	1.781	1.781
75	5.149	3.806	3.175	2.682	2.493	2.300	2.289	2.124	2.105	1.871	1.795	1.781	1.781	1.781
80	5.314	4.137	3.318	2.832	2.652	2.476	2.465	2.280	2.260	1.992	1.906	1.806	1.781	1.781
85	5.480	4.467	3.482	2.981	2.812	2.652	2.641	2.436	2.414	2.114	2.017	1.902	1.781	1.781
90	5.645	4.798	3.947	3.131	2.972	2.828	2.816	2.592	2.569	2.236	2.128	1.997	1.790	1.781
95	5.811	5.158	4.413	3.280	3.131	3.004	2.992	2.748	2.723	2.358	2.239	2.093	1.876	1.781
100	5.976	5.530	4.878	3.429	3.291	3.180	3.168	2.904	2.878	2.479	2.350	2.189	1.963	1.781
105	6.141	5.902	5.343	3.824	3.450	3.357	3.343	3.060	3.032	2.601	2.460	2.285	2.049	1.781
110	6.307	6.273	5.808	4.259	3.878	3.645	3.613	3.216	3.187	2.723	2.571	2.380	2.135	1.849
115	6.425	6.403	6.274	4.695	4.306	4.065	4.032	3.372	3.342	2.845	2.682	2.476	2.222	1.935
120	6.534	6.485	6.396	5.130	4.734	4.484	4.450	3.642	3.562	2.966	2.793	2.572	2.308	2.022
125	6.643	6.568	6.468	5.566	5.162	4.903	4.869	4.027	3.940	3.088	2.904	2.667	2.394	2.109
130	6.753	6.651	6.539	6.001	5.591	5.323	5.287	4.413	4.319	3.210	3.015	2.763	2.481	2.195
135 140	6.862 6.971	6.734 6.817	6.611 6.683	6.350 6.420	6.019 6.352	5.742 6.161	5.706 6.124	4.798 5.183	4.697 5.076	3.332 3.457	3.126 3.237	2.859 2.954	2.567 2.653	2.282 2.368
140	7.081	6.899	6.755	6.489	6.421	6.374	6.368	5.183	5.455	3.457	3.348	3.050	2.739	2.368
150	7.190	6.982	6.827	6.559	6.491	6.444	6.437	5.953	5.833	4.063	3.462	3.146	2.826	2.433
155	7.190	7.065	6.899	6.629	6.561	6.513	6.507	6.334	6.212	4.366	3.613	3.242	2.912	2.628
160	7.409	7.148	6.971	6.699	6.630	6.583	6.576	6.404	6.380	4.669	3.765	3.337	2.998	2.715
165	7.518	7.231	7.042	6.769	6.700	6.652	6.646	6.473	6.450	4.972	3.917	3.433	3.085	2.802
170	7.627	7.313	7.114	6.839	6.770	6.722	6.715	6.543	6.520	5.275	4.069	3.608	3.171	2.888
175	7.737	7.396	7.186	6.909	6.839	6.791	6.785	6.613	6.590	5.578	4.221	3.801	3.257	2.975
180	7.846	7.479	7.258	6.979	6.909	6.861	6.854	6.682	6.659	5.881	4.373	3.995	3.344	3.061
185	7.955	7.562	7.330	7.049	6.979	6.930	6.924	6.752	6.729	6.184	4.525	4.188	3.430	3.148
190	8.064	7.645	7.402	7.119	7.048	7.000	6.993	6.821	6.799	6.370	4.677	4.382	3.651	3.235
195	8.174	7.727	7.474	7.188	7.118	7.070	7.063	6.891	6.869	6.442	4.829	4.575	3.915	3.321
200	8.283	7.810	7.545	7.258	7.188	7.139	7.132	6.961	6.938	6.515	5.514	4.768	4.179	3.408
205	-	7.893	7.617	7.328	7.257	7.209	7.202	7.030	7.008	6.587	6.352	4.975	4.443	3.528
210	-	7.976	7.689	7.398	7.327	7.278	7.271	7.100	7.078	6.660	6.427	5.206	4.707	3.682
215	-	8.059	7.761	7.468	7.397	7.348	7.341	7.170	7.148	6.733	6.502	5.437	4.917	3.836
220	-	8.141	7.833	7.538	7.467	7.417	7.411	7.239	7.217	6.805	6.577	5.669	4.992	3.990
225	-	8.224	7.905	7.608	7.536	7.487	7.480	7.309	7.287	6.878	6.652	5.900	5.067	4.144
230	-	8.307	7.977	7.678	7.606	7.556	7.550	7.379	7.357	6.950	6.726	6.131	5.142	4.298
235	-	-	8.048	7.748	7.676	7.626	7.619	7.448	7.426	7.023	6.801	6.343	5.217	4.452
240	-	-	8.120	7.818	7.745	7.696	7.689	7.518	7.496	7.095	6.876	6.425	5.292	4.606
245	-	-	8.192	7.887	7.815	7.765	7.758	7.588	7.566	7.168	6.951	6.507	5.367	4.760
250	-	-	8.264	7.957	7.885	7.835	7.828	7.657	7.636	7.240	7.026	6.589	5.442	4.901
255	-	-	-	8.027	7.954	7.904	7.897	7.727	7.705	7.313	7.101	6.670	5.517	4.948
260	-	-	-	8.097	8.024	7.974	7.967	7.796	7.775	7.385	7.176	6.752	5.592	4.995
265	-	-	-	8.167	8.094	8.043	8.036	7.866	7.845	7.458	7.251	6.834	5.667	5.042
270	-	-	-	8.237	8.163	8.113	8.106	7.936	7.915	7.530	7.326	6.915	5.742	5.090
275	-	-	-	8.307	8.233	8.182	8.175	8.005	7.984	7.603	7.401	6.997	5.817	5.137
280	-	-	-	-	8.303	8.252	8.245	8.075	8.054	7.676	7.476	7.079	5.892	5.184
285	-	-	-	-	-	8.321	8.314	8.145	8.124	7.748	7.551	7.161	5.967	5.231
290	-	-	-	-	-	-	-	8.214	8.194	7.821	7.626	7.242	6.042	5.278
295	-	-	-	-	-	-	-	8.284	8.263	7.893	7.701	7.324	6.117	5.325
300	-	-	-	-	-	-	-	-	-	7.966	7.775	7.406	6.192	5.372

Tabulated values continued overleaf

Page 31 of 34 Signed E/200

Pol Agg-



Nullifire SC801-120

					Table 23 S	C801 - 120	Hollow Col	ımns 105 m	ninutes					
				F	Required Th	ickness (mn	n) for a Desi	gn Tempera	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	1	-	-	-	-	-	1	1	-	8.038	7.850	7.487	6.267	5.420
310	-	-	-	-	-	-	-	-	-	8.111	7.925	7.569	6.347	5.467
315	-	-	-	-	-	-	-	-	-	8.183	8.000	7.651	6.466	5.514
320	-	-	-	-	-	-	-	-	-	8.256	8.075	7.733	6.585	5.561
325	-	-	-	-	-	-	-	-	-	8.328	8.150	7.814	6.703	5.608
330	-	-	-	-	-	-	-	-	-	8.401	8.225	7.896	6.822	5.655
335	-	-	-	-	-	-	-	-	-	-	8.300	7.978	6.941	5.703
340	1	-	-	-	-	-	1	1	-	-	8.375	8.059	7.059	5.750
345	1	-	-	-	-	-	1	1	-	-	-	8.141	7.178	5.797
350	1	-	-	-	-	-	1	1	-	-	1	8.223	7.297	5.844
355	1	-	-	-	-	-	1	1	-	-	1	8.305	7.416	5.891
360	1	-	-	-	-	-	1	1	-	-	1	8.386	7.534	5.938
365	1	-	-	-	-	-	1	1	-	-	1	8.468	7.653	5.985
370	-	-	-	-	-	-	-	-	-	-	-	-	7.772	6.033
375	-	-	-	-	-	-	-	-	-	-	-	-	7.890	6.080
380	-	-	-	-	-	-	-	-	-	-	-	-	8.009	6.127
385	-	-	-	-	-	-	-	-	-	-	-	-	8.128	6.174
390	-	-	-	-	-	-	-	-	-	-	-	-	8.246	6.221
395	-	-	-	-	-	-	-	-	-	-	-	-	8.365	6.268
400	1	-	-	-	-	-	1	1	-	-	1	-	8.484	6.315
405	1	-	-	-	-	-	1	1	-	-	1	-	8.602	6.694
410	-	-	-	-	-	-	-	-	-	-	-	-	-	7.269
415	-	-	-	-	-	-	-	-	-	-	-	-	-	7.845
420	,	-	-	-	-	-	-	-	-	-	-	-	-	8.420
425		-	-	-	-	-	-	-	-	-	•	-	•	-
430	-	-	-	-	-	-	-	-	-	-	-	-	-	-
435	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 32 of 34 Signed E/200

Pol agg-

CERTIFICATE No CF 5365 TREMCO CPG UK LIMITED

					Table 24	SC801 - 120	Hollow Col	umns 120 m	ninutes					
					Required Th	ickness (mr	n) for a Desi	ign Temper	ature (°C)					
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
40	5.700	4.406	3.050	2.287	2.204	2.147	2.141	1.891	1.781	1.781	1.781	1.781	1.781	1.781
45	5.700	4.406	3.122	2.432	2.348	2.291	2.284	2.039	2.002	1.781	1.781	1.781	1.781	1.781
50	5.700	4.406	3.194	2.577	2.492	2.434	2.427	2.187	2.152	1.781	1.781	1.781	1.781	1.781
55	5.700	4.406	3.265	2.722	2.635	2.578	2.571	2.335	2.301	1.781	1.781	1.781	1.781	1.781
60	6.204	4.828	3.337	2.867	2.779	2.721	2.714	2.483	2.450	1.781	1.781	1.781	1.781	1.781
65	6.381	4.987	3.409	3.012	2.923	2.865	2.858	2.631	2.600	1.880	1.781	1.781	1.781	1.781
70	6.558	5.146	3.698	3.157	3.067	3.008	3.001	2.778	2.749	2.060	1.946	1.812	1.781	1.781
75	6.735	5.305	4.303	3.302	3.211	3.152	3.145	2.926	2.899	2.240	2.111	1.957	1.781	1.781
80	6.912	5.464	4.900	3.447	3.355	3.295	3.288	3.074	3.048	2.421	2.277	2.102	1.854	1.781
85	7.089	5.623	5.133	3.763	3.546	3.439	3.431	3.222	3.198	2.601	2.442	2.247	1.969	1.781
90	7.266	5.782	5.365	4.084	3.971	3.971	3.946	3.370	3.347	2.781	2.608	2.391	2.084	1.832
95	7.443	5.941	5.598	4.539	4.539	4.539	4.520	3.720	3.629	2.961	2.773	2.536	2.200	1.920
100	7.620	6.100	5.831	5.106	5.106	5.106	5.094	4.314	4.214	3.142	2.938	2.681	2.315	2.008
105	7.797	6.259	6.063	5.674	5.674	5.674	5.667	4.907	4.799	3.322	3.104	2.826	2.430	2.096
110	7.974	6.441	6.296	6.242	6.242	6.242	6.241	5.501	5.384	3.597	3.269	2.971	2.545	2.184
115	8.151	6.642	6.421	6.405	6.400	6.400	6.400	6.094	5.970	4.112	3.434	3.116	2.660	2.272
120	8.328	6.843	6.526	6.491	6.480	6.480	6.479	6.379	6.362	4.627	3.877	3.261	2.775	2.359
125	-	7.045	6.631	6.576	6.559	6.559	6.559	6.456	6.439	5.143	4.351	3.406	2.890	2.447
130	-	7.246	6.736	6.662	6.639	6.639	6.638	6.533	6.516	5.658	4.824	3.726	3.005	2.535
135	-	7.447	6.841	6.748	6.719	6.719	6.717	6.610	6.593	6.173	5.298	4.125	3.120	2.623
140	-	7.649	6.945	6.833	6.799	6.799	6.797	6.687	6.670	6.385	5.772	4.524	3.235	2.711
145	-	7.850	7.050	6.919	6.878	6.878	6.876	6.764	6.747	6.461	6.245	4.922	3.350	2.799
150	-	8.051	7.155	7.005	6.958	6.958	6.956	6.841	6.824	6.537	6.395	5.321	3.469	2.886
155	-	8.253	7.260	7.090	7.038	7.038	7.035	6.918	6.901	6.613	6.471	5.719	3.613	2.974
160	-	8.454	7.365	7.176	7.118	7.118	7.115	6.995	6.978	6.689	6.547	6.118	3.756	3.062
165	-	-	7.470	7.262	7.197	7.197	7.194	7.072	7.055	6.765	6.623	6.369	3.900	3.150
170	-	-	7.575	7.347	7.277	7.277	7.273	7.149	7.132	6.841	6.699	6.446	4.044	3.238
175	-	-	7.679	7.433	7.357	7.357	7.353	7.226	7.209	6.916	6.775	6.523	4.188	3.326
180	-	-	7.784	7.518	7.437	7.437	7.432	7.303	7.286	6.992	6.851	6.600	4.332	3.413
185	-	-	7.889	7.604	7.516	7.516	7.512	7.381	7.363	7.068	6.927	6.677	4.476	3.593
190	-	-	7.994	7.690	7.596	7.596	7.591	7.458	7.440	7.144	7.004	6.755	4.620	3.840
195 200	-	-	8.099 8.204	7.775 7.861	7.676 7.756	7.676 7.756	7.671 7.750	7.535 7.612	7.517 7.594	7.220 7.296	7.080 7.156	6.832 6.909	4.764 5.042	4.088 4.336
205	-	-	8.309	7.947	7.835	7.835	7.829	7.689	7.671 7.748	7.372	7.232	6.986	6.354	4.584
210	-	-	-	8.032	7.915	7.915	7.909	7.766		7.448	7.308	7.064	6.440	4.831
215 220	-	-	-	8.118 8.204	7.995 8.074	7.995 8.074	7.988 8.068	7.843 7.920	7.825 7.902	7.523 7.599	7.384 7.460	7.141 7.218	6.526 6.612	4.985 5.105
225	-	-	-	8.204	8.074	8.074	8.147	7.920	7.902	7.599	7.460	7.218	6.698	5.105
230	-	-	-	- 0.209	8.234	8.234	8.227	8.074	8.056	7.751	7.612	7.293	6.783	5.346
235			H		0.234	0.234	8.306	8.151	8.133	7.731	7.612	7.373	6.869	5.467
240	-	-	-	-	-	-	- 0.300	8.228	8.210	7.903	7.764	7.430	6.955	5.588
245	-	-	<u> </u>	-	-	-	-	-	8.210	7.979	7.704	7.604	7.041	5.708
250	-	-	-	-	-	-	-	-	0.207	8.055	7.840	7.604	7.041	5.829
255	-	-		-	-	-	-	-	-	8.131	7.916	7.759	7.127	5.950
260	-	-	-	-		-	-	-	H	8.206	8.068	7.739	7.212	6.070
265	-	-	-	-	-	-	-	-	-	8.282	8.145	7.913	7.238	6.191
270		_	-	-		_		_	_	- 0.202	8.221	7.990	7.470	6.312
275	-	-	-	-	-	-	-	-	-	-	8.221	8.068	7.556	6.442
280	-	-	-	-	-	-	-	-	-	-	-	8.145	7.641	6.574
285	-	-	-	-	-	-	-	-	-	-	_	8.222	7.727	6.706
290	-	-	-	-	-	-	-	-	-	-	-	8.299	7.813	6.838
295	-	-	-	-	-	-	-	-	-	_	-	-	7.899	6.971
300	-	_	<u> </u>	_	_	_	_	_	-	-	_	-	7.985	7.103
300	l	1		1	l	l	l	l			l	l	7.505	7.105

Tabulated values continued overleaf

Page 33 of 34 Signed E/200

Pol Agg-



					Table 24 S0	C801 - 120 H	Hollow Col	umns 120 r	minutes				-	
				Red	quired Thic	kness (mn	n) for a Des	ign Tempe	rature (°C)				
Section Factor (m-1)	350°C	400°C	450°C	500°C	512°C	520°C	521°C	547°C	550°C	600°C	620°C	650°C	700°C	750°C
305	-	-	-	-	-	-	-	-	-	-	-	-	8.071	7.235
310	-	-	-	-	-	-	-	-	-	-	-	-	8.156	7.367
315	-	-	-	-	-	-	-	-	-	-	-	-	8.242	7.500
320	-	-	-	-	-	-	-	-	-	-	-	-	8.328	7.632
325	-	-	-	-	-	-	-	-	-	-	-	-	8.414	7.764
330		-	-		-	-	-	-	-	-	-	-	8.500	7.896
335	-	-	-	-	-	-	-	-	-	-	-	-	-	8.029
340		-	-		-	-	-	-	-	-	-	-	-	8.161
345	-	-	-	-	-	-	-	-	-	-	-	-	-	8.293
350	ı	-	-	1	-	-	-	-	-	-	-	-	-	8.425
355		-	-	,	-	-	-		-			-	-	8.558
360	-	-	-	-	-	-	-	-	-	-	-	-	-	-
365	1	-	-	-	-	-	-	-	-	-	-	-	-	-
370		-	-	,	-	-		-		-		-	-	-
375	1	-	-	-	-	-	-	-	-	-	-	-	-	-
380		-	-	,	-	-		-		-		-	-	-
385	ı	-	-	1	-	-	-	-	-	-	-	-	-	-
390		-	-	,	-	-	-		-			-	-	-
395		-		,	-	-					,	-	-	-
400	ı	-	-	1	-	-	-	-	-	-	-	-	-	-
405	-	-	-	-	-	-	-	-	-	-	-	-	-	-
410	-	-	-	-	-	-	-	-	-	-	-	-	-	-
415		-	-	,	-	-		-		-		-	-	-
420	-	-	-	-	-	-	-	-	-	-	-	-	-	-
425	-	-	-	-	-	-	-	-	-	-	-	-	-	-
430	-	-	-	-	-	-	-	-	-	-	-	-	-	-
435	1	-	-	-	-	-	-	-	-	-	-	-	-	-

Table applies to fully exposed circular and rectangular hollow columns with all round protection. Thickness is intumescent only.

Page 34 of 34 Signed E/200

Pol Agg-