



The Quite OK Image Format Specification

Version 1.0, 2021.12.20

A QOI file consists of a 14-byte header, followed by any number of data “chunks” and an 8-byte end marker.

```
qoi_header {
    char    magic[4]; // magic bytes "qoif"
    uint32_t width;   // image width in pixels (BE)
    uint32_t height;  // image height in pixels (BE)
    uint8_t  channels; // 3 = RGB, 4 = RGBA
    uint8_t  colorspace; // 0 = sRGB with linear alpha
                          // 1 = all channels linear
};
```

The colorspace and channel fields are purely informative. They do not change the behavior of the en-/decoder.

Images are encoded from top to bottom, left to right. The decoder and encoder start with {**r: 0, g: 0, b: 0, a: 255**} as the previous pixel value. An image is complete when all pixels specified by **width * height** have been covered. Pixels are encoded as:

- a run of the previous pixel
- an index into an array of previously seen pixels
- a difference to the previous pixel value in r,g,b
- full r,g,b or r,g,b,a values

The color channels are assumed to not be premultiplied with the alpha channel (“un-premultiplied alpha”).

A running **array[64]** (zero-initialized) of previously seen pixel values is maintained by the encoder and decoder. Each pixel that is seen by the encoder and decoder is put into this array at the position formed by a hash function of the color value. In the encoder, if the pixel value at the index matches the current pixel, this index position is written to the stream as **QOI_OP_INDEX**. The hash function for the index is:

$$\text{index_position} = (r * 3 + g * 5 + b * 7 + a * 11) \% 64$$

Each chunk starts with a 2- or 8-bit tag, followed by a number of data bits. The bit length of chunks is divisible by 8 - i.e. all chunks are byte aligned. All values encoded in these data bits have the most significant bit on the left.

The 8-bit tags have precedence over the 2-bit tags. A decoder must check for the presence of an 8-bit tag first.

The byte stream's end is marked with 7 **0x00** bytes followed by a single **0x01** byte.

The possible chunks are:

QOI_OP_RGB								Byte[1]		Byte[2]	Byte[3]
Byte[0]								7	..	7	..
7	6	5	4	3	2	1	0	7	..	7	..
1	1	1	1	1	1	1	0	red		green	blue

8-bit tag b11111110
8-bit red channel value
8-bit green channel value
8-bit blue channel value

QOI_OP_RGBA								Byte[1]	Byte[2]	Byte[3]	Byte[4]
Byte[0]								7	..	7	..
7	6	5	4	3	2	1	0	7	..	7	..
1	1	1	1	1	1	1	1	red	green	blue	alpha

8-bit tag b11111111
8-bit red channel value
8-bit green channel value
8-bit blue channel value
8-bit alpha channel value

QOI_OP_INDEX								Byte[0]	
								7	6
								5	4
								3	2
								1	0
0	0	index							

2-bit tag b00
6-bit index into the color index array: 0..63

A valid encoder must not issue 7 or more consecutive **QOI_OP_INDEX** chunks to the index 0, to avoid confusion with the end marker.

QOI_OP_DIFF								Byte[0]	
								7	6
								5	4
								3	2
								1	0
0	1	dr	dg	db					

2-bit tag b01
2-bit red channel difference from the previous pixel -2..1
2-bit green channel difference from the previous pixel -2..1
2-bit blue channel difference from the previous pixel -2..1

The difference to the current channel values are using a wraparound operation, so **1 - 2** will result in **255**, while **255 + 1** will result in **0**.

Values are stored as unsigned integers with a bias of **2**. E.g. **-2** is stored as **0 (b00)**. **1** is stored as **3 (b11)**.

QOI_OP_LUMA								Byte[0]		Byte[1]	
								7	6	7	6
								5	4	5	4
								3	2	3	2
								1	0	1	0
1	0	diff green		dr - dg		db - dg					

2-bit tag b10
6-bit green channel difference from the previous pixel -32..31
4-bit red channel difference minus green channel difference -8..7
4-bit blue channel difference minus green channel difference -8..7

The green channel is used to indicate the general direction of change and is encoded in 6 bits. The red and blue channels (dr and db) base their diffs off of the green channel difference. I.e.:

$$\begin{aligned} \text{dr_dg} &= (\text{last_px.r} - \text{cur_px.r}) - (\text{last_px.g} - \text{cur_px.g}) \\ \text{db_dg} &= (\text{last_px.b} - \text{cur_px.b}) - (\text{last_px.g} - \text{cur_px.g}) \end{aligned}$$

The difference to the current channel values are using a wraparound operation, so **10 - 13** will result in **253**, while **250 + 7** will result in **1**.

Values are stored as unsigned integers with a bias of **32** for the green channel and a bias of **8** for the red and blue channel.

QOI_OP_RUN								Byte[0]	
								7	6
								5	4
								3	2
								1	0
1	1	run							

2-bit tag b11
6-bit run-length repeating the previous pixel: 1..62

The run-length is stored with a bias of **-1**. Note that the run-lengths **63** and **64 (b111110 and b111111)** are illegal as they are occupied by the **QOI_OP_RGB** and **QOI_OP_RGBA** tags.