

Lattice-Boltzmann simulations of the thermally driven 2D square cavity at high Rayleigh numbers



Dario Contrino^a, Pierre Lallemand^b, Pietro Asinari^a, Li-Shi Luo^{c,b,*}

^a Energy Department, Politecnico di Torino, Torino 10129, Italy

^b Beijing Computational Science Research Center, Beijing 100084, China

^c Department of Mathematics & Statistics, Old Dominion University, Norfolk, VA 23529, USA

ARTICLE INFO

Article history:

Received 12 September 2013

Received in revised form 18 June 2014

Accepted 23 June 2014

Available online 9 July 2014

Keywords:

Steady convective flow

2D square cavity with differentially heated vertical walls

Lattice Boltzmann equation

Benchmark solutions

ABSTRACT

The thermal lattice Boltzmann equation (TLBE) with multiple-relaxation-times (MRT) collision model is used to simulate the steady thermal convective flows in the two-dimensional square cavity with differentially heated vertical walls at high Rayleigh numbers. The MRT-TLBE consists of two sets of distribution functions, i.e., a D2Q9 model for the mass-momentum equations and a D2Q5 model for the temperature equation. The dimensionless flow parameters are the following: the Prandtl number $Pr = 0.71$ and the Rayleigh number $Ra = 10^6, 10^7$, and 10^8 . The D2Q9 + D2Q5 MRT-TLBE is shown to be second-order accurate and to be capable of yielding results of benchmark quality, including various Nusselt numbers and local hydrodynamic intensities. Our results also agree well with existing benchmark data obtained by other methods.

© 2014 Elsevier Inc. All rights reserved.

1. Introduction

There has been a systematic effort to construct the lattice Boltzmann equation (LBE) for thermal hydrodynamics since the inception of the lattice Boltzmann method (LBM). From early on, it was realized that, while the LBE with energy conservation can lead to the correct macroscopic equations (cf., e.g., [1]), the energy-conserving lattice Boltzmann (LB) models are plagued with severe numerical instability [2], hence they are of little practical use.

It was found that in addition to being prone to numerical instabilities, energy-conserving LBE is also plagued with spurious couplings between energy and shear modes of the linearized evolution operator [2]. To remove this spurious coupling between energy and shear modes, the energy-conservation law must be separated from the mass and momentum conservation laws and there exist at least two approaches to accomplish this goal. The first approach is to use two sets of distribution functions, one for the mass-momentum conservations and the other for the energy conservation (cf., e.g., [3,4]); and the second is a hybrid approach with the LBE for the mass-momentum conservations and a finite-difference (FD) scheme for the temperature equation [2,5]. Both these approaches effectively remove the spurious energy-shear mode coupling. However, the hybrid thermal LBE encounters a new problem – it is difficult to realize the temperature boundary conditions which are consistent with the LB boundary conditions for mass-momentum equations. Consequently, the approach of dual distributions becomes the prevailing one.

* Corresponding author.

E-mail address: lluo@odu.edu (L.-S. Luo).

In this work we will use the thermal lattice Boltzmann equation (TLBE) with dual distributions and the multiple-relaxation-time collision model to simulate internal thermal flows in two-dimensions (2D). The TLBE consists of a D2Q9 MRT-LBE [6,7] for the mass-momentum conservations and a D2Q5 MRT-LBE [8–13] for the advection–diffusion equation for the temperature. The TLBE with D2Q9 and D2Q5 LB models has been validated for its accuracy and stability [4]. In particular, we will use the D2Q9 + D2Q5 TLBE to simulate the thermally driven convective flow in the 2D square cavity with differentially heated vertical walls [14,15]. This flow has been used to validate various numerical methods including pseudo-spectral (PS) [16], finite difference (FD) [15,17], finite element (FE) [18,19], finite volume (FV) [20,21], and control volume (CV) [22] methods. In fact, the 2D square cavity with differentially heated vertical walls has become a standard benchmark problem for incompressible thermal flows, and the MRT-TLBE scheme has been used to simulate the flow [4,23]. One of the primary purpose of the present work is to reproduce benchmark quality results for the thermally driven steady 2D cavity flow at high Rayleigh numbers ($Ra = 10^6, 10^7$, and 10^8) by using the MRT-TLBE model we have developed [4].

The remainder of the paper is organized as follows. Section 2 provides a detailed description of the D2Q9 + D2Q5 MRT-TLBE for thermal flows [4], including specifically the details of the MRT-TLBE and the corresponding macroscopic hydrodynamic equations, and the implementation of the TLBE algorithm. Section 3 discusses the flow configuration of the 2D square cavity with differentially heated vertical walls. We pay a special attention to the boundary conditions in the flow and their LB implementations. Section 4 describes the numerical procedures for post-processing, which are used to measure various quantities in the simulations. Section 5 presents our numerical results. We first present a study on the effect of a parameter in the MRT-TLBE which determines the heat diffusivity κ and the effect of some relaxation parameters on Nusselt numbers; we also conduct a convergence study of the flow fields, Nusselt numbers, and some local hydrodynamic intensities; we then compare our results with existing benchmark data. Finally, Section 6 concludes the paper with a summary.

2. The lattice Boltzmann model for incompressible thermal flows

The lattice Boltzmann model for incompressible thermal flows consisting of two sets of distributions and their corresponding evolution equations – one for conservations of mass and momentum and the other for the temperature – was first proposed by Eggels and Somers [3]. This model assumes Boussinesq approximation, i.e., the temperature T is a passive scalar and its influence to the velocity field $\mathbf{u}$ is through the buoyancy term. We will use the LBE with MRT-LBE [6,7,24,25] throughout this work. The MRT-LBE for thermal hydrodynamics has been developed in our previous work [4]. To make the present work self-contained, we will provide the details of the LBE model and its implementation in what follows.

2.1. D2Q9 model for mass and momentum conservations

The D2Q9 model will be used for the mass and momentum conservations. The discrete velocity set, $\{\mathbf{c}_i | i = 0, 1, \dots, 8\}$, for the D2Q9 model is

$$\mathbf{c}_i = \begin{cases} (0, 0), & i = 0, \\ (\pm 1, 0)c, (0, \pm 1)c, & i = 1-4, \\ (\pm 1, \pm 1)c, & i = 5-8, \end{cases} \quad (1)$$

where $c := \delta_x / \delta_t$, and δ_x and δ_t are the grid spacing and the time-step size, respectively. The evolution equation is written in general as the following:

$$\mathbf{f}(\mathbf{x}_j + \mathbf{c}_i \delta_t, t_n + \delta_t) = \mathbf{f}(\mathbf{x}_j, t_n) - \mathbf{M}^{-1} \cdot \mathbf{S} \cdot [\mathbf{m} - \mathbf{m}^{(0)}](\mathbf{x}_j, t_n) + \mathbf{F}(\mathbf{x}_j, t_n), \quad (2)$$

where the bold-face font denotes 9-dimensional vectors:

$$\begin{aligned} \mathbf{f}(\mathbf{x}_j + \mathbf{c}_i \delta_t, \cdot) &:= (f_0(\mathbf{x}_j, \cdot), f_1(\mathbf{x}_j + \mathbf{c}_1 \delta_t, \cdot), \dots, f_8(\mathbf{x}_j + \mathbf{c}_8 \delta_t, \cdot))^\dagger, \\ \mathbf{f}(\mathbf{x}_j, \cdot) &:= (f_0(\mathbf{x}_j, \cdot), f_1(\mathbf{x}_j, \cdot), \dots, f_8(\mathbf{x}_j, \cdot))^\dagger, \\ \mathbf{m}(\mathbf{x}_j, \cdot) &:= (m_0(\mathbf{x}_j, \cdot), m_1(\mathbf{x}_j, \cdot), \dots, m_8(\mathbf{x}_j, \cdot))^\dagger, \end{aligned}$$

$\mathbf{f}$ and $\mathbf{m}$ are vectors of the discrete-velocity distributions and corresponding moments, respectively, $\mathbf{m}^{(0)}$ is the vector of the equilibrium moments, and $\mathbf{F}$ is the vector of external forcing, which is implemented according to the procedure to be discussed later in Section 2.4.

The transformation matrix $\mathbf{M}$ maps the distributions $\{f_i | i = 0, 1, \dots, 8\}$ to the corresponding moments $\{m_i | i = 0, 1, \dots, 8\}$, i.e.,

$$\mathbf{m} = \mathbf{M} \cdot \mathbf{f}, \quad \mathbf{f} = \mathbf{M}^{-1} \cdot \mathbf{m}. \quad (3)$$

Specifically, we use the following M :

$$M = \begin{pmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 0 & 1 & 0 & -1 & 0 & 1 & -1 & -1 & 1 \\ 0 & 0 & 1 & 0 & -1 & 1 & 1 & -1 & -1 \\ -4 & -1 & -1 & -1 & -1 & 2 & 2 & 2 & 2 \\ 0 & 1 & -1 & 1 & -1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & -1 & 1 & -1 \\ 0 & -2 & 0 & 2 & 0 & 1 & -1 & -1 & 1 \\ 0 & 0 & -2 & 0 & 2 & 1 & 1 & -1 & -1 \\ 4 & -2 & -2 & -2 & -2 & 1 & 1 & 1 & 1 \end{pmatrix} \quad (4)$$

With M given above, the ordering of the moments is, as in [4]:

$$\mathbf{m} = (\rho, j_x, j_y, e, p_{xx}, p_{xy}, Q_x, Q_y, \epsilon)^\dagger \quad (5)$$

where ρ is the mass density, $\mathbf{j} = \rho \mathbf{u}$ is the flow momentum and $\mathbf{u}$ is the flow velocity; e is the second-order moment corresponding to energy; p_{xx} and p_{xy} are two independent components of the stress tensor (diagonal and off-diagonal, respectively); Q_x and Q_y are the third-order moments corresponding to the x and y components of the energy flux, respectively; and ϵ is the fourth-order moment [6,7]. The diagonal relaxation matrix is given by:

$$S = \text{diag}(1, 1, 1, s_e, s_\nu, s_\nu, s_q, s_q, s_\epsilon), \quad s_i \in (0, 2) \quad \forall i. \quad (6)$$

In what follows we will use both the two-relaxation-time (TRT) model due to Ginzburg [8,26,27] and the MRT model due to d'Humières [6,7]. More specifically, we choose to use the following relationship between two relaxation rates:

$$s_e = s_\epsilon = s_\nu = \frac{2}{6\nu + 1}, \quad (7a)$$

$$s_q = 8 \frac{(2 - s_\nu)}{(8 - s_\nu)}, \quad (7b)$$

where ν is the shear viscosity, and the MRT model with more than two relaxation rates [7,28,29]. The TRT and MRT models ensure accurate flow boundary conditions as well as adequate numerical stability [4,28–30].

The equilibrium moments $\{m_i^{(0)} | i = 0, 1, \dots, 8\}$ are given by

$$m_0^{(0)} = \delta\rho, \quad m_1^{(0)} = \rho_0 u, \quad m_2^{(0)} = \rho_0 v, \quad (8a)$$

$$m_3^{(0)} = -2\delta\rho + 3\rho_0(u^2 + v^2), \quad m_4^{(0)} = \rho_0(u^2 - v^2), \quad m_5^{(0)} = \rho_0 u v, \quad (8b)$$

$$m_6^{(0)} = -\rho_0 u, \quad m_7^{(0)} = -\rho_0 v, \quad (8c)$$

$$m_8^{(0)} = \delta\rho - 3\rho_0(u^2 + v^2). \quad (8d)$$

Note that the so-called incompressible approximation [31] has been used in the equilibria above, that is, it is assumed that $\rho = \rho_0 + \delta\rho$ with $\rho_0 = 1$, and the nonlinear term $\delta\rho \cdot \mathbf{u}$ and higher order nonlinear terms have been neglected [31]. With the above equilibria, the speed of sound in the system is

$$c_s = \frac{1}{\sqrt{3}}c. \quad (9)$$

The kinematic shear and bulk viscosity coefficients ν and ζ of the system are:

$$\nu = \zeta = \frac{1}{3} \left(\frac{1}{s_\nu} - \frac{1}{2} \right). \quad (10)$$

2.2. D2Q5 model for the temperature

We use the D2Q5 LB model to simulate the advection–diffusion equation for the temperature:

$$\mathbf{g}(\mathbf{x}_j + \mathbf{c}\delta_t, t_n + \delta_t) = \mathbf{g}(\mathbf{x}_j, t_n) - \mathbf{N}^{-1} \cdot \mathbf{Q} \cdot [\mathbf{n} - \mathbf{n}^{(0)}](\mathbf{x}_j, t_n), \quad (11)$$

where the notations similar to that in Eq. (2) are used, i.e., bold-face font denotes 5-dimensional vectors. The discrete velocities in the D2Q5 model are the first five in the D2Q9 model, specified in Eq. (1). The temperature T is the sole conserved quantity in the D2Q5 model and it is given by

$$T = \sum_{i=0}^4 g_i. \quad (12)$$

The equilibrium moments $\{n_i^{(0)} | i = 0, 1, \dots, 4\}$ are given by

$$n_0^{(0)} = T, \quad n_1^{(0)} = uT, \quad n_2^{(0)} = vT, \quad n_3^{(0)} = aT, \quad n_4^{(0)} = 0, \quad (13)$$

where u and v are the velocity components obtained from the D2Q9 model for the flow fields, and $a \in (-4, 1)$ is a parameter the effect of which is to be studied later in Section 5.1.

The transformation matrix N maps the distribution functions $\{g_i | i = 0, 1, \dots, 4\}$ to the corresponding moments $\{n_i | i = 0, 1, \dots, 4\}$ and is given by

$$N = \begin{pmatrix} 1 & 1 & 1 & 1 & 1 \\ 0 & 1 & 0 & -1 & 0 \\ 0 & 0 & 1 & 0 & -1 \\ -4 & 1 & 1 & 1 & 1 \\ 0 & 1 & -1 & 1 & -1 \end{pmatrix}. \quad (14)$$

The diagonal relaxation matrix Q is given by

$$Q = \text{diag}(1, \sigma_\kappa, \sigma_\kappa, \sigma_e, \sigma_v). \quad (15)$$

The heat diffusivity κ is given by

$$\kappa = \frac{(4+a)}{10} \left(\frac{1}{\sigma_\kappa} - \frac{1}{2} \right). \quad (16)$$

2010JSP

It should be noted that the parameter $c_e := (4+a)/10$ has been analyzed by Ginzburg et al. [13] for the D2Q5 model for the scalar diffusion equation, including its rigorous stability criteria and necessary and sufficient stability conditions for the advection velocity $u(c_e)$.

To achieve the isotropy of the fourth-order error term in the D2Q5 model, it is required that

$$\Lambda_\sigma := \left(\frac{1}{\sigma_v} - \frac{1}{2} \right) \left(\frac{1}{\sigma_\kappa} - \frac{1}{2} \right) = \frac{1}{6} \quad \text{or} \quad \sigma_v = 6 \frac{(2 - \sigma_\kappa)}{(6 - \sigma_\kappa)}. \quad (17)$$

With the above relationship between σ_κ and σ_v , one can eliminate the fourth-order term in the equivalent equations for the D2Q5 model with the following relationship between σ_e and σ_κ [32]:

$$\sigma_e = \frac{6(1-a)(2-\sigma_\kappa)\sigma_\kappa}{(7+3a)(\sigma_\kappa-6)\sigma_\kappa+12(4+a)}. \quad (18)$$

Eq. 55 on Page 15

If and only if σ_κ takes the following special value

$$\frac{1}{\sigma_\kappa} = \frac{1}{2} + \frac{\sqrt{3}}{6}, \quad (19)$$

sigma_k = 3-sqrt(3)

sigma_e = 4*sqrt(3)-6

the relationship (18) between σ_e and σ_κ is much simplified and σ_e becomes a constant, i.e.,

$$\sigma_e = 2(2\sqrt{3}-3),$$

consequently σ_e and σ_v become equal to the following value:

$$\left(\frac{1}{\sigma_e} - \frac{1}{2} \right) = \left(\frac{1}{\sigma_v} - \frac{1}{2} \right) = \frac{\sqrt{3}}{3}. \quad (20)$$

With σ_κ fixed at the value specified by Eq. (19), κ depends only on the parameter a :

$$\kappa = \frac{\sqrt{3}}{60} (4+a). \quad (21)$$

Thus, with the special values of σ_κ given by Eq. (19) and $\sigma_e = \sigma_v$ given by Eq. (20), we have the D2Q5 TRT model [8–12] without the fourth-order error term in its equivalent equation for the temperature [32]. Unless otherwise specified, we use the special value of σ_κ given by Eq. (19) in our simulations.

A brief discussion about the numerical errors in the LBE models is in order. It is well known that both D2Q9 and D2Q5 models have two major defects due to their discrete nature. First, the equivalent equations of these models include higher order space derivatives. And second, the effective transport coefficients in these models depend on the local flow velocity or the Mach number Ma and the Ma^2 terms are non-isotropic, i.e., they depend on the direction with respect to the lattice line [7]. The former can be reduced by proper choice of the relaxation rates which do not affect the shear viscosity ν and the thermal diffusivity κ . The latter can be mitigated by using more discrete velocities and corresponding nonlinear terms in the equilibria [2,32–34].

We note that the D2Q5 model does not have sufficient degrees of freedom to eliminate both the third- and fourth-order errors simultaneously. We choose to eliminate the fourth-order error because it can be easily achieved with the relationship (17). In addition, tests show that the LB models with more discrete velocities make little difference on integrated quantities such as Nusselt numbers. We therefore use the D2Q5 model for the sake of computational efficiency.

2.3. Macroscopic equations

In incompressible thermal flows, thermal convection is due to the buoyancy effect induced by the density variation caused by the temperature variation. The density variation due to temperature change is approximated by the Boussinesq approximation:

$$\rho = \rho_0[1 + \alpha(T - T_0)], \quad (22)$$

where ρ_0 is the reference density at the temperature T_0 , T_0 is a reference temperature, and α is the thermal expansion coefficient under constant pressure:

$$\alpha := \frac{1}{\rho_0} \left. \frac{\partial \rho}{\partial T} \right|_p. \quad (23)$$

With the Boussinesq approximation, the viscous heat dissipation and compression work due to pressure are neglected, and all the transport coefficients (ν and κ) and α are constants. The buoyancy force is therefore given by

$$\mathbf{F} = \rho_0 \alpha (T - T_0) g \hat{\mathbf{g}}, \quad (24)$$

where g is the gravity and $\hat{\mathbf{g}}$ is the unit vector along the direction of the gravitational force.

The macroscopic equations derived from the D2Q9 + D2Q5 LBE system are the following:

$$\partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho_0} \nabla p + \nu \nabla^2 \mathbf{u} + \alpha (T - T_0) g \hat{\mathbf{g}}, \quad (25a)$$

$$\nabla \cdot \mathbf{u} = 0, \quad (25b)$$

$$\partial_t T + \mathbf{u} \cdot \nabla T = \kappa \nabla^2 T. \quad (25c)$$

Eqs. (25b) and (25c) can be non-dimensionalized by choosing a characteristic length L and temperature T_0 , while the velocity is normalized by κ/L and the pressure by $\rho_0 c^2$ ($c := \delta_x/\delta_t$):

$$\partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} = -\nabla p + \text{Pr} \nabla^2 \mathbf{u} + \text{Ra} \text{Pr} \theta \hat{\mathbf{g}}, \quad (26)$$

$$\nabla \cdot \mathbf{u} = 0, \quad (27)$$

$$\partial_t \theta + \mathbf{u} \cdot \nabla \theta = \nabla^2 \theta, \quad (28)$$

where $\theta := (T - T_0)/T_0$, $\text{Pr} := \nu/\kappa$ is the Prandtl number which is fixed at the value of 0.71 (for air) unless otherwise specified, $\text{Ra} = \text{Pr} \cdot \text{Gr}$ is the Rayleigh number, and Gr is the Grashof number:

$$\text{Gr} := \frac{\alpha g \Delta T L^3}{\nu^2}, \quad (29)$$

where ΔT is the reference temperature difference. The thermal diffusivity κ and the shear viscosity ν can also be given by

$$\kappa = \sqrt{\frac{\alpha g \Delta T L^3}{\text{Pr} \cdot \text{Ra}}}, \quad \nu = \text{Pr} \cdot \kappa. \quad (30)$$

The characteristic velocity due to thermal convection is

$$U = \sqrt{\alpha g \Delta T L} = \sqrt{\frac{\text{Ra}}{\text{Pr}}} \frac{\nu}{L}. \quad (31)$$

The Mach number Ma based on the thermal convective velocity U has to be kept small enough in order to maintain the stability criterion for the LBE, which can be expressed as an upper bound for the viscosity ν :

$$\nu < \frac{\text{Ma}^*}{\sqrt{3}} \sqrt{\frac{\text{Pr}}{\text{Ra}}} L, \quad (32)$$

where Ma^* is the critical Mach number. If we choose $\text{Ma}^* \approx 0.3$ and the minimum length $L \approx 13\delta_x$, then the upper bound for ν is given by

$$\nu < \min \left[\frac{\text{Ma}}{\sqrt{3}} \sqrt{\frac{\text{Pr}}{\text{Ra}}} L, \sqrt{\frac{3.6}{\text{Ra}}} \right]. \quad (33)$$

The upper bound of ν is particularly important when L is small. Note that for small Prandtl number, the thermal diffusivity κ may become so large that $a > 1$ in Eq. (21), thus violating the stability condition of the D2Q5 model.

In the LBE, the Mach number Ma plays the role of Courant–Friedrichs–Lewy (CFL) number. It has been shown [4] that for the D2Q9 + D2Q5 TLBE for incompressible thermal flows, the Mach number Ma determines dimensionless time-step size, hence the computational efficiency, but it has little effect on the accuracy of results. In what follows, we will use $\text{Ma} = 0.1$ in our simulations unless otherwise specified. The upper bound for viscosity ν given by Eq. (32) is used to ensure the numerical stability of the simulations especially when small grid sizes are used.




Fig. 1. (Left) A schematic of the 2D square cavity of dimension $L \times H$ with differentially heated vertical walls and other boundary conditions. (Right) A schematic of a mesh: the boundary nodes are marked with solid discs $\bullet$, the boundary conditions are satisfied on the dashed line, nodes outside the dashed line are used as buffer layer.

2.4. Implementation of the LB algorithm

We provide a step-by-step implementation of the MRT-LB algorithm as the following:

1. Compute the conserved quantities $\delta\rho$ and $\mathbf{u}$ from $\{f_i\}$, and T from $\{g_i\}$;
2. Compute the force of Eq. (24) with the local temperature $T(\mathbf{x}_j, t_n)$;
3. Update the velocity: $\mathbf{u}^* = \mathbf{u} + \mathbf{F}\delta t/2\rho_0$;
4. Compute the equilibrium moments $\{m_i^{(0)}\}$ with $\delta\rho$ and $\mathbf{u}^*$, and $\{n_i^{(0)}\}$ with T ;
5. Compute the changes of the nonequilibrium moments $\{m_i | i = 3, \dots, 8\}$ for the D2Q9 model and that for the D2Q5 model, i.e., $\delta\mathbf{m} = -\mathbf{S} \cdot [\mathbf{m} - \mathbf{m}^{(0)}]$ and $\delta\mathbf{n} = -\mathbf{Q} \cdot [\mathbf{n} - \mathbf{n}^{(0)}]$;
6. Update the velocity again: $\mathbf{u}^{**} = \mathbf{u}^* + \mathbf{F}\delta t/2\rho_0 = \mathbf{u} + \mathbf{F}\delta t/\rho_0$;
7. Compute the changes of the distribution functions due to collisions and forcing, i.e., $\delta\mathbf{f} = \mathbf{M}^{-1} \cdot \delta\mathbf{m}$ and $\delta\mathbf{g} = \mathbf{N}^{-1} \cdot \delta\mathbf{n}$, then compute the post-collision distributions: $\mathbf{f}^* = \mathbf{f} + \delta\mathbf{f}$ and $\mathbf{g}^* = \mathbf{g} + \delta\mathbf{g}$ in the fluid nodes;
8. Advect $\{f_i\}$ and $\{g_i\}$, with special rules at boundaries.

A few remarks are in order here. First, the forcing term $\mathbf{F}$ is split into two halves according to Strang splitting so a second-order accuracy can be achieved (see the proof in [35]). The most important point is that one has to use $\mathbf{u} + \mathbf{F}\delta t/2\rho_0$ for the relaxation (collision) step. Secondly, the MRT collision model is based on the projection method. The forcing term $\mathbf{F}$ is correctly projected on whatever modes (or moments) which the force is supposed to affect directly. This implementation is thus free of the numerical artifacts generated by the force term implemented in the discrete velocity space, i.e., $\{f_i\}$, in the LBGK schemes [36]. And thirdly, the collision and the advection steps, i.e., steps 7 and 8 in the procedure described above, should be combined together in one step in order to improve computational efficiency. If the collision and advection are executed separately in two steps, then the same data will have to be read and written into memory twice, which can severely degrade the computational efficiency due to unnecessary memory I/O. This problem can be rather severe when the data array size is so large that it cannot fit in cache.

Finally, we would like to point out that the TRT model in the present work is simply realized by adjusting relaxation rates in the MRT model. Obviously, this is not the most efficient way to implement the TRT model. However, this does provide the flexibility of our code. Furthermore, given the fact that the LBE algorithms are mainly bandwidth limited, as opposed to FLOPs limited, we do not expect that an optimized TRT code can significantly enhance the efficiency.

3. Two-dimensional square cavity with differentially heated vertical walls

3.1. Flow configuration

The flow configuration for the 2D square cavity with differentially heated vertical walls is shown in Fig. 1(left). The dimension of the cavity is $L \times H$. In this work, we set $L = H$. The left and right vertical walls of the cavity are kept at constant temperatures $\theta_h = +0.5$ and $\theta_c = -0.5$, respectively, while the top and bottom walls are adiabatic. All walls are impenetrable, rigid and no-slip. The system is subject to gravity $\hat{\mathbf{g}}$ with the downward direction $-\hat{\mathbf{y}}$, as shown in Fig. 1(left). In the normalized coordinates $(x, y) \in \Omega := [0, 1] \times [0, 1]$, the boundary conditions are given by:

$$\mathbf{u}|_{\mathbf{x} \in \partial\Omega} = \mathbf{0}, \quad (34a)$$

$$\theta|_{x=0} = +0.5, \quad \theta|_{x=1} = -0.5, \quad (34b)$$

$$\partial_{\hat{\mathbf{n}}}\theta|_{y=0} = \partial_{\hat{\mathbf{n}}}\theta|_{y=1} = 0, \quad (34c)$$

where $\hat{\mathbf{n}}$ is the unit out-normal vector to the boundary $\partial\Omega$.

The initial state of the flow is quiescent and isothermal, i.e., $\mathbf{u}(\mathbf{x}_j, t_0) = \mathbf{0}$, $\delta\rho(\mathbf{x}_j, t_0) = 0$, and $\theta(\mathbf{x}_j, t_0) = 0$ for all $\mathbf{x}_j$. The Prandtl number is fixed at $\text{Pr} = 0.71$ (for air), and the values of the Rayleigh number are $\text{Ra} = 10^6, 10^7$, and 10^8 . The flow remains time-independent under these conditions (cf., e.g., [16]).

We use meshes of uniform Cartesian grid of size $(N_x + 2) \times (N_y + 2)$ for our simulations, as illustrated in Fig. 1(right). The flow domain $L \times H$ is covered by the fluid nodes $(i, j) \in [1, N_x] \times [1, N_y]$. The flow domain is wrapped with a buffer layer, i.e., $i = 0$ and $i = (N_x + 1)$, $j = 0$, and $j = (N_y + 1)$, as shown in Fig. 1(right), for the convenience of storing the outgoing distribution functions during the advection step.

3.2. Boundary conditions

For the velocity field $\mathbf{u}$, only the no-slip boundary conditions are used for all four walls of the cavity. The no-slip boundary conditions can be realized by the bounce-back (BB) boundary conditions, that is, when a particle hits the wall, it reverses its momentum as the following:

$$f_i(\mathbf{x}_B, t_n + \delta_t) = f_i^*(\mathbf{x}_B, t_n), \quad (35)$$

where $\mathbf{x}_B$ is a fluid node adjacent to a boundary, i.e., a boundary node (indicated by $\bullet$ in Fig. 1(right)), f_i corresponds to $\mathbf{c}_i := -\mathbf{c}_i$, $f_i^*(\mathbf{x}_B, t_n)$ denotes the post collision value of the distribution function. The bounce-back boundary conditions are applied to the distributions in the directions not parallel to a wall.

As for the temperature field θ (or T), there are two types of boundary conditions, i.e., one with prescribed temperature and the other adiabatic. The adiabatic boundary conditions are Neumann boundary conditions for θ (zero heat fluxes) which can be realized by the bounce-back boundary conditions for the distributions g_i , as prescribed by Eq. (35). The temperature boundary conditions are the Dirichlet boundary conditions for θ which can be realized by the anti-bounce-back boundary conditions:

$$g_i(\mathbf{x}_B, t_n + \delta_t) = -g_i^*(\mathbf{x}_B, t_n) + \frac{4+a}{10}\theta_w, \quad (36)$$

where θ_w is the wall temperature. It should be noted that as far as θ is concerned, the four corners of the square belong to the vertical walls. However, these points are not used in the D2Q5 model.

We would like to emphasize that the MRT-LBE (or TRT-LBE) is imperative to achieve accurate and consistent boundary conditions for both $\mathbf{u}$ and θ imposed exactly at the same location, i.e., one-half grid spacing, $\delta_x/2$, beyond the last fluid nodes (or the boundary nodes) for straight boundaries parallel to lattice lines, such is the case for the cavity flow [4,9]. For the lattice Bhatnagar–Gross–Krook (LBGK) models, the exact boundary location depends on both relaxation parameters for f_i and g_i , so its results depend on the grid size and cannot converge [29,30].

4. Post processing and measurements

Various averaged and local quantities are measured in order to gauge the quality of simulations and different numerical methods can be compared. We are only concerned with the steady state solutions of the problem. To achieve a steady state, the following criteria are used in our simulations [4]:

$$\frac{\sum_j \|\mathbf{u}(\mathbf{x}_j, t_{n+1000}) - \mathbf{u}(\mathbf{x}_j, t_n)\|_2}{\sum_j \|\mathbf{u}(\mathbf{x}_j, t_{n+1000})\|_2} < 10^{-12}, \quad (37)$$

$$\|\theta(\mathbf{x}_j, t_{n+1000}) - \theta(\mathbf{x}_j, t_n)\|_\infty < 10^{-6}, \quad (38)$$

where $\|\cdot\|_2$ and $\|\cdot\|_\infty$ denote the Euclidean L_2 norm and L_∞ norm, respectively.

For the steady convective flow in the 2D square with differentially heated vertical walls, the averaged quantities of interest are various Nusselt numbers. In addition, there are also some local hydrodynamic quantities and their precise locations. We will provide a succinct description of measuring these quantities in what follows.

4.1. Nusselt numbers

The dimensionless local heat flux in the horizontal direction $\hat{\mathbf{x}}$ between two differentially heated vertical walls is given by

$$q_x = u\theta - \partial_x\theta, \quad (39)$$

which will be used to compute various Nusselt numbers. We will compute three Nusselt numbers: one averaged over the entire flow domain, one averaged over left wall at $x = 0$, and one averaged over the vertical symmetric line of the cavity, denoted by $\langle \text{Nu} \rangle$, $\langle \text{Nu} \rangle_0$, and $\langle \text{Nu} \rangle_{1/2}$, respectively. The volume average Nusselt number $\langle \text{Nu} \rangle$ is given by

$$\langle \text{Nu} \rangle = \frac{1}{LH\Delta\theta} \int_0^L \int_0^H q_x \, dx \, dy \approx \frac{1}{N_x N_y \Delta\theta} \sum_{i,j=1}^{N_x, N_y} q_x(i, j), \quad (40)$$

where $\Delta\theta := \theta(x=0) - \theta(x=1) = 1$. Similarly, $\langle \text{Nu} \rangle_0$ and $\langle \text{Nu} \rangle_{1/2}$ are computed as the following:

$$\langle \text{Nu} \rangle_0 \approx \frac{1}{N_y \Delta\theta} \sum_{j=1}^{N_y} q_x(x=0, j), \quad (41a)$$

$$\langle \text{Nu} \rangle_{1/2} \approx \frac{1}{N_y \Delta\theta} \sum_{j=1}^{N_y} q_x(x=1/2, j). \quad (41b)$$

In theory, all three Nusselt numbers should be equal. Thus, differences among them measure the numerical inconsistency in the energy conservation.

Except for the boundary nodes, the heat flux is computed by the following central-differencing formula

$$q_x(i, j) = [u\theta](i, j) + \frac{\theta(i-1, j) - \theta(i+1, j)}{2\delta_x}, \quad 1 < i < N_x, \quad 1 \leq j \leq N_y, \quad (42)$$

where $[u\theta](i, j) := u(i, j)\theta(i, j)$. For the boundary nodes at $i=1$, which are marked by solid discs at the left edge in Fig. 1(right), the heat flux is approximated by:

$$q_x(i, j) = [u\theta](i, j) + \frac{4\theta(i, j) - \theta(i+1, j) - 3\theta_h}{3\delta_x}, \quad i=1, \quad 1 \leq j \leq N_y, \quad (43)$$

where $\theta_h := \theta|_{x=0} = 0.5$ is the temperature at the left wall, and the above formula is based on the assumption that the distance between the left wall and the fluid nodes is only $\delta_x/2$. The heat flux at $i=N_x$ is evaluated similarly.

To obtain $\langle \text{Nu} \rangle_0$, we need to compute q_x at $x=0$ as the following:

$$q_x(x=0, j) = \frac{2[\theta(1, j) - \theta_h]}{\delta_x}, \quad 1 \leq j \leq N_y. \quad (44)$$

To compute q_x at two corners on the left, i.e., $(x, y) = (0, 0)$ and $(x, y) = (0, 1)$, the temperature at the horizontal walls $y=0$ and $y=1$ are evaluated by using four points along each vertical lattice line and nearest to the horizontal walls to fit the following temperature profile [4] with the least-square method:

$$\theta(y) = c_0 + c_2(y - y_0)^2, \quad (45)$$

where $y_0 = 0$ (or 1) is the position of the bottom (or top) horizontal wall. Then q_x along two horizontal walls can be evaluated according to Eq. (44).

We also compute the maximum and minimum Nusselt numbers $\text{Nu}_{\max}$ and $\text{Nu}_{\min}$ at the hot wall on the left ($x=0$). To find $\text{Nu}_{\max}$, we first identify the maximum value of Nu on a grid, then fit the values of Nu on five points about the grid with a parabola by using least-square method. The fitted parabola is then used to interpolate $\text{Nu}_{\max}$ and its position on the left wall.

As for $\text{Nu}_{\min}$, since its location is always very close to the top left corner (in fact results converge towards the top left corner), only grid points located before the minimum value are used to find the interpolating polynomial.

4.2. Hydrodynamic intensities

The hydrodynamic quantities of interest include the value of the stream-function at the cavity center ψ_{mid} , the maximum magnitude of the stream-function $|\psi|_{\max}$ and its location, the maximum x -component of the velocity on the vertical center-line $u_{\max}$, and the maximum y -component of the velocity on the horizontal center-line $v_{\max}$. The maximum velocities and their positions are calculated in the same way as the maximum Nusselt number $\text{Nu}_{\max}$ is done.

We also compute the maximum of the stream function ψ and its value at the center of the cavity. The stream-function is defined as

$$\psi(x, y) = \int_0^y u(x, \mu) d\mu = - \int_0^x v(\eta, y) d\eta. \quad (46)$$

The integral is approximated by the third-order Simpson's rule of cumulative summation using second-order polynomial interpolation coefficients. The maximum magnitude of the stream-function, $|\psi|_{\max}$, is obtained on a fine mesh of 10001×10001 equidistant points, as in [16]. The values of ψ on this fine mesh are obtained by using a cubic spline interpolation of the LB data on coarser meshes.




Fig. 2. The maximum oscillation magnitude of $\langle Nu \rangle_y$, $\max |\delta \langle Nu \rangle_y|$, as a function of the parameter a . $Ma = 0.1$, $Ra = 10^7$, $N^2 = 251^2$ and 379^2 .

5. The results

The LB algorithm has been implemented on both CPU and GPU. With a mesh of size $N^2 = 2043^2$, the LB code running on an Intel Core-I7 CPU and on a Quadro-6000 GPU can achieve about, respectively, 12 and 1080 millions site updates per second in single precision and 9 and 560 millions per second in double precision. For a smaller mesh size of 256^2 ; the speed on the Quadro-6000 GPU is 617 and 396 millions site updates per second in single and double precision, respectively. The GPU allows us to obtain the results of steady-state with a mesh size as large as 2043^2 within 15 h.

The simulations are conducted with the following formula to determine the parameter a , which is obtained by using $\kappa = \nu / Pr$, the special value of σ_κ given by Eq. (19), and the upper bound of ν given by Eq. (32):

$$a \leq \frac{20 \cdot Ma \cdot N}{\sqrt{Pr \cdot Ra}} - 4, \quad \text{since } \kappa = (4+a)/10 \cdot (1/\sigma_\kappa - 1/2) \quad (47)$$

$\downarrow$
 $0 < (4+a)/10 < 1/2;$

with the condition $-4 < a < 1$ for the stability of the D2Q5 model. The bounds on the parameter a can be easily obtained by the Fourier (von Neumann) analysis [2,7]. The lower bound -4 corresponds to a positivity of κ in Eq. (21) in the long-wave limit of $k = 0$, k being the wave-number, while the upper bound $+1$ corresponds to stability limit of the checkers-board mode at the short-wave limit $k = \pi$, i.e., if $a > 1$, the checkers-board mode blows up. In our simulations, the Mach number Ma is fixed at 0.1 unless otherwise specified, and $Pr = 0.71$, the equality usually holds. Thus, with the Rayleigh number Ra and the resolution N given, the parameter a is determined, and so are the heat diffusivity κ and the viscosity ($\nu = Pr \kappa$), the value of ν is also checked against the stability criterion of Eq. (33).

5.1. Effect of the parameter a

The parameter a , which determines the heat diffusivity κ [cf. Eqs. (16) and (21)], may affect the numerical stability, among other things. It is clear from Eq. (47) that the parameter a has to be a variable: the Prandtl number Pr is fixed, the Mach number Ma is chosen in consideration of computational efficiency [4], and with a given Rayleigh number Ra , the parameter a varies with the grid resolution N . It has been observed that the main effect of the parameter a is on the magnitude of the spatial oscillations of the heat flux q_x near boundaries [4]. To quantify the effect due to a , similar to the way $\langle Nu \rangle_0$ and $\langle Nu \rangle_{1/2}$ are computed, we compute the Nusselt number $\langle Nu \rangle_y(x)$ averaged over y along each grid line as a function of x defined as the following:

$$\langle Nu \rangle_y(x) \approx \frac{1}{N_y \Delta \theta} \sum_{j=1}^{N_y} q_x(x, j). \quad (48)$$

We then compute the maximum oscillation magnitude, $\max |\delta \langle Nu \rangle_y|$, of $\langle Nu \rangle_y(x)$ as a function of a , with given Ra and resolution N^2 .

To conduct a parametric study on the effect of a , we cannot use the equality of Eq. (47) for a , that is, we cannot fix σ_κ with the value of Eq. (19). Instead, with Eqs. (16) and (30), we have

$$a = \frac{10 \cdot N}{\sqrt{Pr \cdot Ra}} \left(\frac{1}{\sigma_\kappa} - \frac{1}{2} \right)^{-1} - 4 = \frac{20 \cdot N}{\sqrt{Pr \cdot Ra}} \frac{\sigma_\kappa}{(2 - \sigma_\kappa)} - 4. \quad (49)$$

Thus, with $Pr = 0.71$ fixed, and N and Ra given, we can adjust a by varying $\sigma_\kappa \in (0, 2)$. In Fig. 2 we show $\max |\delta \langle Nu \rangle_y|$ as a function of a with $Ra = 10^7$ and two different resolutions $N^2 = 251^2$ and 379^2 . It is clearly seen from Fig. 2 that, independent of the resolution N^2 , the maximum oscillation magnitude $\max |\delta \langle Nu \rangle_y|$ monotonically decreases as a decreases

Table 1 Λ_σ -dependence of $\langle \text{Nu} \rangle$, $0.1 \leq \Lambda_s \leq 0.5$, $\text{Ra} = 10^5$ and 10^6 .

N	$\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$	
	$\text{Ra} = 10^5$	$\text{Ra} = 10^6$
61	0.002165	0.065570
125	0.000589	0.017451
253	0.000140	0.004367

Table 2 Λ_s -dependence of $\langle \text{Nu} \rangle$, $0.1 \leq \Lambda_s \leq 0.5$, $\text{Ra} = 10^5$ and 10^6 .

N	$\partial \langle \text{Nu} \rangle / \partial \Lambda_s$	
	$\text{Ra} = 10^5$	$\text{Ra} = 10^6$
61	0.084391	0.529743
125	0.020307	0.127900
253	0.005007	0.031433

from 1 to reach a minimum at about $a \approx -3.90$, then rapidly increases as a approaches to -4 – the stability limit at $k = 0$. It should be noted that the accuracy of the LBE is not affected by the value of a , so long as the LBE is stable.

5.2. Effect of some relaxation parameters

For the D2Q5 model, we choose the parameter $\Lambda_\sigma = 1/6$, as given in Eq. (17). The choice of Λ_σ is not unique. Our choice is made by eliminating the fourth-order term in the equivalent equation [32], while some stability optimization leads to the choice of $\Lambda_\sigma = 1/4$ [13]. However, the parameter Λ_σ has a very little effect on the numerical results of our simulation. To make this point, we compute the volume average Nusselt number $\langle \text{Nu} \rangle$ as a function of Λ_σ with $0.1 \leq \Lambda_\sigma \leq 0.5$, $\text{Ra} = 10^5$, and the mesh size $N = 61, 125$, and 253 . We observe that $\langle \text{Nu} \rangle$ linearly depends on Λ_σ , hence we compute $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$ as a function of N and the results are given in Table 1.

The values of $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$ are rather small, indicating that the effect of Λ_σ on $\langle \text{Nu} \rangle$ is rather weak. For example, for the case of $N = 61$ and $\text{Ra} = 10^5$, $\langle \text{Nu} \rangle$ is equal to 4.50880383 and 4.50898425 for $\Lambda_\sigma = 1/6$ and $1/4$, respectively – the variation of $\langle \text{Nu} \rangle$ takes place at the fifth significant digit when Λ_σ increases from $1/6$ to $1/4$ (the converged result is 4.5216 [4]). It is also noted that $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$ increases with Ra . The effect of Ra on the errors of the flow fields is to be discussed later.

For the D2Q9 model, the relationship between s_q and s_v , given by Eq. (7b) leads to

$$\Lambda_s := \left(\frac{1}{s_v} - \frac{1}{2} \right) \left(\frac{1}{s_q} - \frac{1}{2} \right) = \frac{3}{16}. \quad (50)$$

Similar to Λ_σ , the choice of Λ_s is also not unique and it depends on the type of driving force for the Poiseuille flow – the uniform body force [30,37] and the pressure boundary conditions [38] lead to $\Lambda_s = 3/16$ and $3/8$, respectively. We choose $\Lambda_s = 3/16$ because the flow is driven by a body force.

Similar to the data in Table 2, we compute the dependence of $\langle \text{Nu} \rangle$ on Λ_s , with $0.1 \leq \Lambda_s \leq 0.5$ and $\Lambda_\sigma = 1/6$ fixed. We find that $\langle \text{Nu} \rangle$ also depends on Λ_s linearly, and the results of $\partial \langle \text{Nu} \rangle / \partial \Lambda_s$ are given in Table 2. Clearly, with everything equal, $\partial \langle \text{Nu} \rangle / \partial \Lambda_s$ is more than one order of magnitude larger than $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$, indicating that $\partial \langle \text{Nu} \rangle / \partial \Lambda_s$ has a more significant effect on the numerical results.

Finally, the results in Tables 1 and 2 clearly show that

$$\frac{\partial \langle \text{Nu} \rangle}{\partial \Lambda} \propto O(1/N^2), \quad (51)$$

where Λ is either Λ_σ or Λ_s . This suggests that the order of convergence is independent of both Λ_σ or Λ_s . Also, both $\partial \langle \text{Nu} \rangle / \partial \Lambda_s$ and $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$ increase monotonically as Ra increases, however, $\partial \langle \text{Nu} \rangle / \partial \Lambda_\sigma$ does increase faster.

5.3. Global convergence of flow fields

We conduct a convergence study by using a number of mesh sizes $N_x \times N_y = N^2$ ($N_x = N_y = N$) between 251^2 and 2043^2 . We compute the L_2 errors in the velocity $\mathbf{u}$ and the temperature θ as the following:

$$\|\delta \mathbf{u}\|_2 := \frac{\sum_j \|\mathbf{u}(\mathbf{x}_j) - \mathbf{u}^*(\mathbf{x}_j)\|_2}{\sum_j \|\mathbf{u}^*(\mathbf{x}_j)\|_2}, \quad (52a)$$

$$\|\delta \theta\|_2 := \frac{\sum_j \|\theta(\mathbf{x}_j) - \theta^*(\mathbf{x}_j)\|_2}{\sum_j \|\theta^*(\mathbf{x}_j)\|_2}, \quad (52b)$$

Table 3The viscosity ν used with different the mesh size N^2 and the Rayleigh number Ra.

N^2	Ra		
	10^6	10^7	10^8
763^2	0.050	0.050	0.025
1019^2	0.050	0.050	0.025
1531^2	0.050	0.050	0.025
2043^2	0.070	0.070	0.035

Table 4The Reynolds number dependence of the global convergence of the velocity $\mathbf{u}$, the pressure p , and the temperature θ with the L_2 -norm. $Ma = 0.1$.

N^2	Ra		
	10^6	10^7	10^8
	$\ \delta \mathbf{u}\ _2$		
379^2	$1.6249 \cdot 10^{-2}$	$2.7804 \cdot 10^{-2}$	$7.1627 \cdot 10^{-2}$
507^2	$1.1210 \cdot 10^{-2}$	$1.9019 \cdot 10^{-2}$	$4.5857 \cdot 10^{-2}$
763^2	$6.2005 \cdot 10^{-3}$	$1.0560 \cdot 10^{-2}$	$2.3677 \cdot 10^{-2}$
1019^2	$3.7144 \cdot 10^{-3}$	$6.2934 \cdot 10^{-3}$	$1.3401 \cdot 10^{-2}$
1531^2	$1.2367 \cdot 10^{-3}$	$2.0827 \cdot 10^{-3}$	$4.1838 \cdot 10^{-3}$
n	1.7977	1.8339	1.9843
	$\ \delta p\ _2$		
379^2	$6.1420 \cdot 10^{-3}$	$6.4071 \cdot 10^{-3}$	$7.5728 \cdot 10^{-3}$
507^2	$4.2252 \cdot 10^{-3}$	$4.3714 \cdot 10^{-3}$	$5.1218 \cdot 10^{-3}$
763^2	$2.3276 \cdot 10^{-3}$	$2.3820 \cdot 10^{-3}$	$2.5378 \cdot 10^{-3}$
1019^2	$1.3927 \cdot 10^{-3}$	$1.4198 \cdot 10^{-3}$	$1.4947 \cdot 10^{-3}$
1531^2	$4.6299 \cdot 10^{-4}$	$4.7030 \cdot 10^{-4}$	$4.9116 \cdot 10^{-4}$
n	1.8077	1.8271	1.9291
	$\ \delta \theta\ _2$		
379^2	$1.2298 \cdot 10^{-2}$	$1.6245 \cdot 10^{-2}$	$2.1559 \cdot 10^{-2}$
507^2	$8.4736 \cdot 10^{-3}$	$1.1182 \cdot 10^{-2}$	$1.4804 \cdot 10^{-2}$
763^2	$4.6861 \cdot 10^{-3}$	$6.1771 \cdot 10^{-3}$	$8.1582 \cdot 10^{-3}$
1019^2	$2.8052 \cdot 10^{-3}$	$3.6958 \cdot 10^{-3}$	$4.8752 \cdot 10^{-3}$
1531^2	$9.3279 \cdot 10^{-4}$	$1.2284 \cdot 10^{-3}$	$1.6186 \cdot 10^{-3}$
n	1.8000	1.8022	1.8073

where the reference solutions $\mathbf{u}^*(\mathbf{x}_j)$ and $\theta^*(\mathbf{x}_j)$ are obtained with the largest mesh of the size $N^2 = 2043^2$.

For the larger mesh sizes $N^2 \geq 763^2$, we carried out the simulations on a GPU [39–42] and use the MRT model with the following values for the relaxation rates: $s_e = 1.20$, $s_\epsilon = 1.30$, s_q given by Eq. (7b), and the values of s_ν are given in Table 3. The values given in Table 3 satisfy the stability condition of Eq. (32).

Because the boundary conditions for both $\mathbf{u}$ and θ are satisfied at the locations $\delta_x/2$ beyond the last fluid nodes, the meshes of different sizes have no overlapping grid points except the boundaries. To compute the differences of the flow fields on difference meshes, we interpolate the data on the finest mesh to coarser meshes by using a cubic spline interpolation. The errors and the corresponding the order of accuracy n are summarized in Table 4. If no interpolation is performed, i.e., the closest points in the meshes are used to compute the errors, the order of accuracy would appear to be significantly lower [4].

The order of accuracy, n , is about 1.8 or better for all cases in Table 4, indicating that the method is indeed second-order accurate. We also observe that the L_2 errors of $\mathbf{u}$ and θ increase with the Rayleigh number Ra. In fact, the data in Table 4 show that

$$\|\delta \mathbf{u}\|_2 \propto Ra^{1+\varepsilon}, \quad \|\delta \theta\|_2 \propto Ra, \quad (53)$$

where $\varepsilon > 0$ depends on N . The behavior of the L_2 errors of the pressure p is similar to that of the velocity $\mathbf{u}$, it increases with Ra faster than linearly. The above scalings corroborate previous results [4].

The contours of the stream function ψ , the temperature θ , the pressure p , and the vorticity ω obtained with the finest mesh of $N^2 = 2043^2$ are shown in Fig. 3. The vorticity $\omega := (\partial_x v - \partial_y u)$ is computed with a second-order central finite-difference scheme. The figures show the changes of flow features as the Rayleigh number Ra increases. Clearly the contours are centro-symmetric.




Fig. 3. Contours of flow fields. From left to right: streamlines (ψ), isotherms (θ), isobars (p), and the vorticity contours (ω). From top to bottom: $Ra = 10^6$, 10^7 , and 10^8 . $N = 2043^2$, $Ma = 0.1$.

Table 5
Convergence behavior of the averaged Nusselt numbers $\langle Nu \rangle$, $\langle Nu \rangle_0$, and $\langle Nu \rangle_{1/2}$, and the local Nusselt numbers $Nu_{\max}$ and $Nu_{\min}$ with their vertical positions on the left (hot) wall.

Ra	N^2	$\langle Nu \rangle$	$\langle Nu \rangle_0$	$\langle Nu \rangle_{1/2}$	$Nu_{\max}$	y	$Nu_{\min}$	y
10^6	251^2	8.8231	8.8288	8.8253	17.6252	0.0386	0.9774	0.9986
	379^2	8.8243	8.8265	8.8252	17.5802	0.0388	0.9795	0.9972
	507^2	8.8246	8.8258	8.8252	17.5622	0.0390	0.9794	0.9978
	763^2	8.8250	8.8255	8.8252	17.5482	0.0391	0.9794	0.9984
	1019^2	8.8251	8.8253	8.8252	17.5430	0.0391	0.9794	0.9987
	1531^2	8.8251	8.8253	8.8252	17.5392	0.0392	0.9794	0.9991
	2043^2	8.8252	8.8252	8.8252	17.5378	0.0392	0.9794	0.9993
	∞	8.8252	8.8252	8.8252	17.5360	0.0392	0.9795	0.9994
	n	1.9526	2.2612	2.9656	1.8743	1.7717	1.7464	1.8427
10^7	251^2	16.5229	16.5579	16.5286	39.9459	0.0176	1.4185	0.9965
	379^2	16.5229	16.5357	16.5255	39.7402	0.0175	1.3903	0.9952
	507^2	16.5229	16.5292	16.5244	39.6199	0.0176	1.3783	0.9964
	763^2	16.5230	16.5254	16.5237	39.5085	0.0178	1.3696	0.9979
	1019^2	16.5230	16.5242	16.5234	39.4628	0.0178	1.3679	0.9984
	1531^2	16.5231	16.5235	16.5232	39.4628	0.0179	1.3669	0.9989
	2043^2	16.5231	16.5233	16.5232	38.4132	0.0179	1.3666	0.9992
	∞	16.5231	16.5230	16.5231	39.3950	0.0180	1.3659	0.9994
	n	1.9291	2.2244	2.0256	1.8066	1.6538	2.1473	1.8590
10^8	379^2	30.2412	30.3314	30.2573	88.5991	0.0084	2.2745	0.9925
	507^2	30.2337	30.2779	30.2428	88.5233	0.0082	2.1062	0.9946
	763^2	30.2287	30.2444	30.2328	88.0838	0.0081	1.9882	0.9964
	1019^2	30.2271	30.2345	30.2294	87.8022	0.0082	1.9551	0.9973
	1531^2	30.2259	30.2286	30.2269	87.5323	0.0083	1.9336	0.9981
	2043^2	30.2255	30.2268	30.2261	87.4178	0.0083	1.9265	0.9986
	∞	30.2251	30.2241	30.2251	87.2454	1.9063	1.9195	0.9990
	n	2.0832	2.2076	2.0326	1.6819	1.4232	2.3431	1.6294

Note: The data that do not fit well with the interpolating polynomial have been excluded from the computation of the asymptotic values.

5.4. Convergence of Nusselt numbers

Table 5 shows the convergence behavior of the Nusselt numbers. The asymptotic values of the Nusselt numbers are obtained by using the least-square fitting with the cubic polynomial

Table 6Convergence behaviors of $|\psi_{\text{mid}}|$, $|\psi|_{\text{max}}$ and its position, u_{max} and v_{max} as well as their positions.

Ra	N^2	$ \psi_{\text{mid}} $	$ \psi _{\text{max}}$	x	y	u_{max}	y	v_{max}	x
10^6	251^2	16.4010	16.8308	0.1490	0.5471	64.8223	0.8497	220.5259	0.0378
	379^2	16.3965	16.8283	0.1494	0.5472	64.8295	0.8498	220.5370	0.0378
	507^2	16.3920	16.8207	0.1497	0.5470	64.8341	0.8499	220.5429	0.0378
	763^2	16.3902	16.8184	0.1499	0.5469	64.8332	0.8499	220.5539	0.0378
	1019^2	16.3885	16.8152	0.1500	0.5469	64.8337	0.8499	220.5589	0.0378
	1531^2	16.3874	16.8130	0.1501	0.5468	64.8342	0.8499	220.5624	0.0378
	2043^2	16.3871	16.8125	0.1502	0.5468	64.8342	0.8499	220.5631	0.0378
	∞	16.3869	16.8121	0.1502	0.5468	64.8344	0.8499	220.5638	0.0378
	n	2.2038	2.2245	1.9492	1.8542	2.1090	2.0112	2.1261	2.0008
10^7	251^2	29.4723*	30.3375*	0.0843	0.5571*	148.3414	0.8795	699.0722	0.0214
	379^2	29.4574*	30.3489*	0.0848	0.5578*	148.4833	0.8794	699.1096	0.0214
	507^2	29.4153	30.2674	0.0851	0.5569	148.5291	0.8794	699.2071	0.0213
	763^2	29.4012	30.2469	0.0854	0.5567	148.5610	0.8793	699.2341	0.0213
	1019^2	29.3838	30.2104	0.0856	0.5562	148.5718	0.8793	699.2763	0.0213
	1531^2	29.3715	30.1846	0.0857	0.5559	148.5795	0.8793	699.3063	0.0213
	2043^2	29.3689	30.1798	0.0858	0.5558	148.5821	0.8793	699.3121	0.0213
	∞	29.3667	30.1760	0.0858	0.5558	148.5852	0.8793	699.3166	0.0213
	n	2.1845	2.2415	2.1515	2.1638	2.0724	2.0389	2.2358	2.1612
10^8	379^2	52.8567	54.8698	0.0469	0.5594	315.0766	0.9239	2221.4020	0.0121
	507^2	52.6243	54.4205	0.0473	0.5564	317.7138	0.9256	2221.8299	0.0120
	763^2	52.5458	54.3077*	0.0476	0.5560*	319.8787	0.9268	2221.9532*	0.0120
	1019^2	52.4478	54.1060	0.0478	0.5545	320.7388	0.9273	2222.1450	0.0120
	1531^2	52.3780	53.9625	0.0480	0.5533	321.3676	0.9276	2222.2806	0.0120
	2043^2	52.3634	53.9352	0.0480	0.5532	321.5900	0.9277	2222.3043	0.0120
	∞	52.3508	53.9149	0.0481	0.5530	321.9075	0.9278	2222.3279	0.0119
	n	2.1639	2.2447	1.7227	2.2573	1.8611	1.9051	2.1692	1.8226

Note: The data that do not fit well with the interpolating polynomial have been excluded from the computation of the asymptotic values and they are marked with asterisk *.

$$f(h) = f_{\infty} + a_2 h^2 + a_3 h^3, \quad (54)$$

where $h = 1/N$ is the grid spacing, and f_{∞} is the asymptotic value for $h \rightarrow 0$, i.e., $N \rightarrow \infty$. The asymptotic values of Nu 's are the reference values to compute the errors of Nu 's, which are then used to compute the order of accuracy n . Both the asymptotic values and the order of accuracy n are given in Table 5.

All the averaged Nusselt numbers, including $\langle Nu \rangle$, $\langle Nu \rangle_0$, and $\langle Nu \rangle_{1/2}$, clearly achieve a second-order accuracy. It is also noticed that $\langle Nu \rangle$ and $\langle Nu \rangle_{1/2}$ agree with each other better than their agreement with $\langle Nu \rangle_0$. As for the local Nusselt numbers Nu_{max} and Nu_{min} and their locations on the left wall, the accuracy is nominally second-order with L_{∞} -norm, which is a much more stringent measure than L_2 -norm. The worst case is the location of Nu_{max} , which becomes closer and closer to the lower-left corner of the cavity as Ra increases. It is clearly the case that the meshes are not fine enough to sufficiently resolve the region of high gradient near the vertical walls, especially at the lower-left and upper-right corners (cf. Fig. 3).

To further investigate possible sources of error in computing the local Nusselt numbers, in Fig. 4 we show the y variation of the heat flux on the left (hot) wall, $q_x(x=0, y)$, and the x variation of the Nusselt number averaged over y along each grid line, i.e., $\langle Nu \rangle_y(x)$. We only show $\langle Nu \rangle_y(x)$ for $0 \leq x \leq 1/2$ because $\langle Nu \rangle_y(x)$ is anti-symmetric about $\langle Nu \rangle_y(1/2)$, i.e.,

$$\langle Nu \rangle_y(1/2 + x) + \langle Nu \rangle_y(1/2 - x) = 2\langle Nu \rangle_y(1/2),$$

for $0 \leq x \leq 1/2$. Clearly, as Ra increases, not only the maximum of q_x increases, but also the thermal boundary layer, which varies as $Ra^{-1/4}$, becomes thinner as the gradient $\partial_x \theta$ becomes steeper near the lower-left corner, as shown in the figures of q_x in Fig. 4. The oscillation in $\langle Nu \rangle_y(x)$ is clearly due to lack of mesh resolution – the magnitude of the oscillation indeed diminishes as the grid resolution N^2 increases.

5.5. Convergence of local hydrodynamic quantities

Table 6 summarizes the convergence behavior of various local hydrodynamic intensities including the magnitude the stream-function ψ at the cavity center, $|\psi_{\text{mid}}|$, the maximum magnitude of ψ , $|\psi|_{\text{max}}$ as well as its position, the maximum x and y velocity components, u_{max} and v_{max} , on the vertical and horizontal symmetric centerline, respectively, as well as their positions. The asymptotic values of these local hydrodynamic intensities are obtained by using the least-square fit with the cubic polynomial of Eq. (54), and will be used as the reference solutions to compute the errors. With few exceptions, most measured quantities exhibit a second-order accuracy with the L_{∞} -norm.




Fig. 4. From left to right: the heat flux q_x along the hot wall at $x = 0$ and an enlarged figure about its maximum near the lower-left corner, and the Nusselt number $\langle \text{Nu} \rangle_y(x)$ averaged over y as a function of x . From top to bottom: $Ra = 10^6$, 10^7 , and 10^8 .

5.6. Benchmark results

We now compare our results of the Nusselt numbers and the hydrodynamic quantities with existing benchmark data. The second-order finite difference (FD) solutions of de Vahl Davis [15] for the lower Rayleigh numbers $Ra = 10^3, 10^4, 10^5$, and 10^6 remain a comprehensive benchmark. To our knowledge, the Chebyshev pseudo-spectral (PS) solutions of Le Quéré [16] are the most accurate ones for higher Rayleigh numbers $Ra = 10^7$ and 10^8 . There exist more recent results by using the finite element (FE) method [19], finite difference method [15,17], and the lattice Boltzmann method with coarser meshes [4]. Table 7 compiles the data for the Nusselt numbers and their positions obtained with various methods. The LB results of the present work are the asymptotic values in Table 7, obtained by using the Richardson extrapolation. With the exception of two cases ($\text{Nu}_{\min}$ at $Ra = 10^7$ and $\langle \text{Nu} \rangle$ at $Ra = 10^8$) which miss the last significant digit, our LB results and the pseudo-spectral benchmark data [16] agree with each other in all significant digits.

Table 8 compiles the data for the measured hydrodynamic intensities and their positions obtained with various methods. It should also be noted that in Le Quéré's work [16], the velocity is normalized by $\sqrt{Ra\kappa/L}$, as opposed to κ/L . Thus the values of the stream-function ψ and the velocity $\mathbf{u}$ in Le Quéré's work [16] given in Table 8 have been multiplied by

Table 7

Comparison of the Nusselt numbers and their locations with existing benchmark data.

Ra	Method	$\langle Nu \rangle$	Nu_0	$Nu_{1/2}$	$Nu_{\max}$	y	$Nu_{\min}$
10^6	Present	8.8252	8.8252	8.8252	17.5360	0.0392	0.9795
	PS [16]	–	8.825	8.825	17.536	0.039	0.9795
	FD [15]	8.800	8.817	8.799	17.925	0.0378	0.989
	FD [17]	–	8.8216	–	17.5087	0.0396	0.9787
	LB [4]	8.8253	8.8192	8.8254	17.5274	0.0392	0.9769
	FE [19]	–	8.8811	–	17.5308	0.0377	0.9845
10^7	Present	16.5231	16.5230	16.5231	39.3950	0.0180	1.3659
	PS [16]	–	16.523	16.523	39.39	0.018	1.366
	FD [17]	–	16.5106	–	39.2540	0.0179	1.3655
	FE [19]	–	16.3869	–	41.0247	0.0390	1.3799
10^8	Present	30.2251	30.2241	30.2251	87.2454	0.0083	1.9195
	PS [16]	–	30.225	30.225	87.24	0.008	1.919
	FE [19]	–	29.6256	–	91.2095	0.0067	2.0440

Table 8

Comparison of the measured hydrodynamic intensities with existing benchmark data.

Ra	Method	$ \psi _{\text{mid}}$	$ \psi _{\text{max}}$	x	y	$u_{\max}$	y	$v_{\max}$	x
10^6	Present	16.3868	16.8118	0.1502	0.5468	64.8344	0.8499	220.5644	0.0378
	PS [16]	16.386	16.811	0.150	0.547	64.83	0.850	220.6	0.038
	FD [15]	16.32	16.750	0.151	0.547	64.63	0.850	219.36	0.0379
	FE [18]	16.3860	16.8110	0.1504	0.5470	64.8340	0.8499	220.5650	0.0378
	LB [4]	16.3868	16.8149	0.1503	0.5468	64.8336	0.8499	220.5658	0.0378
	FD [17]	16.3863	16.8107	–	–	64.8308	0.8501	220.5675	0.0377
	FE [19]	–	–	–	–	64.6912	0.8460	220.8331	0.0380
10^7	Present	29.3653	30.1760	0.0858	0.5558	148.5852	0.8793	699.3224	0.0213
	PS [16]	29.3617	30.1649	0.086	0.556	148.5954	0.879	699.1795	0.021
	FD [17]	29.3562	30.1553	–	–	148.5695	0.8794	699.2991	0.0213
	FE [19]	–	–	–	–	145.2666	0.8845	703.2526	0.0215
10^8	Present	52.3508	53.9149	0.0481	0.5530	321.9063	0.9279	2222.3279	0.0120
	PS [16]	52.32	53.85	0.048	0.553	321.9	0.928	2222.	0.012
	FE [19]	–	–	–	–	283.0689	0.9455	2223.4424	0.0130

$\sqrt{\text{Ra}}$. For the case of $\text{Ra} = 10^6$, the present LB results and the PS data [16] are essentially identical. And for the cases of $\text{Ra} = 10^7$ and 10^8 , the present LB results and the PS data [16] agree with each other with at least three significant digits except for the case of $|\psi|_{\text{max}}$ at $\text{Ra} = 10^8$, for which the LB result differs from the PS data for about 0.12%.

6. Conclusions

In this work we use the multiple-relaxation-time lattice Boltzmann model with dual distributions [4] to simulate thermal flows in the two-dimensional square cavity with differentially heated vertical walls. The MRT-TLBE uses the D2Q9 model and D2Q5 model for mass-momentum and temperature conservations, respectively. The D2Q9 + D2Q5 MRT-LB model essentially solves the thermal fluid system with the Boussinesq approximation. The flow parameters are the Prandtl number $\text{Pr} = 0.71$ (for air) and the Rayleigh number $\text{Ra} = 10^6, 10^7$, and 10^8 . The Mach number is fixed to be $\text{Ma} = 0.1$ in our simulations. With the given Rayleigh numbers, the flow is steady.

We now summarize our observations in this work as the following. First, we emphasize that the MRT collision model is imperative to achieve accurate boundary conditions and numerical stability, which can be achieved through judicious choosing the values of relaxation rates (cf. e.g., [29]). We would also like to point out that the LBGK model fails in both these aspects. Second, with the given flow conditions, we have shown that the MRT-TLBE model is second-order accurate for flow fields with L_2 -norm, global quantities, such as Nusselt numbers, and local hydrodynamic intensities as well as their positions, with L_∞ -norm. Third, our results demonstrate that the MRT-TLBE model can reproduce numerical results of benchmark quality for internal (near) incompressible thermal flows. Our results agree well with existing benchmark data obtained by using traditional methods. Finally, the LB algorithm has been implemented on GPU, and can achieve a speed of 560 million millions site-updates per second with double precision (1080 millions site-updates per second with single precision), which allows us to complete the simulations on a mesh as large as 2043^2 within 15 h.

Acknowledgements

PA would like to acknowledge the support of the Italian Ministry of Research (FIRB grant RBFR10VZUG). LSL would like to acknowledge the support from a grant from NASA Langley Research Center through the SSAI Contract NNL08AA00C,

the Hardware Donation Program of Nvidia, and the Richard F. Barry Jr. Endowment at the Old Dominion University. LSL would also like to acknowledge a visiting fellowship from the Isaac Newton Institute of Mathematical Sciences, University of Cambridge, UK, for the period of July 6–August 3, 2013, during which part of this work was carried out.

References

- [1] G. McNamara, A. Garcia, B. Alder, A hydrodynamically correct thermal lattice Boltzmann model, *J. Stat. Phys.* 87 (5/6) (1997) 1111–1121.
- [2] P. Lallemand, L.-S. Luo, Theory of the lattice Boltzmann method: acoustic and thermal properties in two and three dimensions, *Phys. Rev. E* 68 (3) (2003) 036706.
- [3] J.G.M. Eggels, J.A. Somers, Numerical-simulation of free convective flow using the lattice-Boltzmann scheme, *Int. J. Heat Fluid Flow* 16 (5) (1995) 357–364.
- [4] J. Wang, D. Wang, P. Lallemand, L.-S. Luo, Lattice Boltzmann simulations of thermal convective flows in two dimensions, *Comput. Math. Appl.* 65 (2) (2013) 262–286, <http://dx.doi.org/10.1016/j.camwa.2012.07.001>.
- [5] P. Lallemand, L.-S. Luo, Hybrid finite-difference thermal lattice Boltzmann equation, *Int. J. Mod. Phys. B* 17 (1/2) (2003) 41–47.
- [6] D. d'Humières, Generalized lattice-Boltzmann equations, in: B.D. Shizgal, D.P. Weave (Eds.), *Rarefied Gas Dynamics: Theory and Simulations*, in: *Prog. Astronaut. Aeronaut.*, vol. 159, AIAA, Washington, DC, 1992, pp. 450–458.
- [7] P. Lallemand, L.-S. Luo, Theory of the lattice Boltzmann method: dispersion, dissipation, isotropy, Galilean invariance, and stability, *Phys. Rev. E* 61 (6) (2000) 6546–6562.
- [8] I. Ginzburg, Equilibrium-type and link-type lattice Boltzmann models for generic advection and anisotropic-dispersion equation, *Adv. Water Resour.* 28 (11) (2005) 1171–1195.
- [9] I. Ginzburg, Generic boundary conditions for lattice Boltzmann models and their application to advection and anisotropic dispersion equations, *Adv. Water Resour.* 28 (11) (2005) 1196–1216.
- [10] I. Ginzburg, Variably saturated flow described with the anisotropic lattice Boltzmann methods, *Comput. Fluids* 35 (8–9) (2006) 831–848.
- [11] I. Ginzburg, D. d'Humières, Lattice Boltzmann and analytical modeling of flow processes in anisotropic and heterogeneous stratified aquifers, *Adv. Water Resour.* 30 (11) (2007) 2202–2234.
- [12] I. Ginzburg, Lattice Boltzmann modeling with discontinuous collision components: hydrodynamic and advection–diffusion equations, *J. Stat. Phys.* 126 (1) (2007) 157–206.
- [13] I. Ginzburg, D. d'Humières, A. Kuzmin, Optimal stability of advection–diffusion lattice Boltzmann models with two relaxation times for positive/negative equilibrium, *J. Stat. Phys.* 139 (6) (2010) 1090–1143.
- [14] G. de Vahl Davis, I.P. Jones, Natural-convection in a square cavity: a comparison exercise, *Int. J. Numer. Meth. Fluids* 3 (3) (1983) 227–248.
- [15] G. de Vahl Davis, Natural-convection of air in a square cavity: a bench-mark numerical-solution, *Int. J. Numer. Meth. Fluids* 3 (3) (1983) 249–264.
- [16] P. Le Quééré, Accurate solutions to the square thermally driven cavity at high Rayleigh number, *Comput. Fluids* 20 (1) (1991) 29–41.
- [17] Z. Tian, Y. Ge, A fourth-order compact finite difference scheme for the steady stream function-vorticity formulation of the Navier–Stokes/Boussinesq equations, *Int. J. Numer. Meth. Fluids* 41 (5) (2003) 495–518, <http://dx.doi.org/10.1002/flid.444>.
- [18] J.T. Holdeman, J.W. Kim, Computation of incompressible thermal flows using Hermite finite elements, *Comput. Methods Appl. Mech. Eng.* 199 (49–52) (2010) 3297–3304, <http://dx.doi.org/10.1016/j.cma.2010.06.036>.
- [19] D. Mayne, A.S. Usmani, M. Crapper, *h*-Adaptive finite element solution of high Rayleigh number thermally driven cavity problem, *Int. J. Numer. Meth. Heat Fluid Flow* 10 (5–6) (2000) 598–615.
- [20] M. Hortmann, M. Perić, G. Scheuerer, Finite volume multigrid prediction of laminar natural-convection: bench-mark solutions, *Int. J. Numer. Meth. Fluids* 11 (2) (1990) 189–207.
- [21] R. Henkes, C. Hoogendoorn, Scaling of the laminar natural-convection flow in a heated square cavity, *Int. J. Heat Mass Trans.* 36 (11) (1993) 2913–2925, [http://dx.doi.org/10.1016/0017-9310\(93\)90110-R](http://dx.doi.org/10.1016/0017-9310(93)90110-R).
- [22] N. Mai-Duy, T. Tran-Cong, A control volume technique based on integrated RBFNs for the convection–diffusion equation, *Numer. Methods Partial Differ. Equ.* 26 (2) (2010) 426–447, <http://dx.doi.org/10.1002/num.20444>.
- [23] A. Mezrhab, M.A. Moussaoui, M. Jami, H. Naji, M. Bouzidi, Double MRT thermal lattice Boltzmann method for simulating convective flows, *Phys. Lett. A* 374 (34) (2010) 3499–3507.
- [24] D. d'Humières, M. Bouzidi, P. Lallemand, Thirteen-velocity three-dimensional lattice Boltzmann model, *Phys. Rev. E* 63 (2001) 066702.
- [25] D. d'Humières, I. Ginzburg, M. Krafczyk, P. Lallemand, L.-S. Luo, Multiple-relaxation-time lattice Boltzmann models in three-dimensions, *Philos. Trans. R. Soc. Lond. Ser. A* 360 (1792) (2002) 437–451.
- [26] I. Ginzburg, F. Verhaeghe, D. d'Humières, Two-relaxation-time lattice Boltzmann scheme: about parametrization, velocity, pressure and mixed boundary conditions, *Commun. Comput. Phys.* 3 (2008) 427–478.
- [27] I. Ginzburg, F. Verhaeghe, D. d'Humières, Study of simple hydrodynamic solutions with the two-relaxation-times lattice Boltzmann scheme, *Commun. Comput. Phys.* 3 (3) (2008) 519–581.
- [28] C. Pan, L.-S. Luo, C. Miller, An evaluation of lattice Boltzmann schemes for porous medium flow simulation, *Comput. Fluids* 35 (8/9) (2006) 898–909.
- [29] L.-S. Luo, W. Liao, X. Chen, Y. Peng, W. Zhang, Numerics of the lattice Boltzmann method: effects of collision models on the lattice Boltzmann simulations, *Phys. Rev. E* 83 (5) (2011) 056710.
- [30] I. Ginzburg, D. d'Humières, Multireflection boundary conditions for lattice Boltzmann models, *Phys. Rev. E* 68 (6) (2003) 066614.
- [31] X. He, L.-S. Luo, Lattice Boltzmann model for the incompressible Navier–Stokes equation, *J. Stat. Phys.* 88 (3/4) (1997) 927–944.
- [32] F. Dubois, P. Lallemand, Towards higher order lattice Boltzmann schemes, *J. Stat. Mech.* (2009) P06006.
- [33] Y.H. Qian, Y. Zhou, Complete Galilean-invariant lattice BGK models for the Navier–Stokes equation, *Europhys. Lett.* 42 (4) (1998) 359–364, <http://dx.doi.org/10.1209/epl/i1998-00255-3>.
- [34] I. Ginzburg, Truncation errors, exact and heuristic stability analysis of two-relaxation-times lattice Boltzmann schemes for anisotropic advection–diffusion equation, *Commun. Comput. Phys.* 11 (5) (2012) 1439–1502.
- [35] P.J. Dellar, An interpretation and derivation of the lattice Boltzmann method using Strang splitting, *Comput. Math. Appl.* 65 (2013) 129–141.
- [36] Z.L. Guo, C.G. Zheng, B.C. Shi, Discrete lattice effects on the forcing term in the lattice Boltzmann method, *Phys. Rev. E* 65 (2002) 046308.
- [37] I. Ginzburg, P.M. Adler, Boundary flow condition analysis for the three-dimensional lattice Boltzmann model, *J. Phys. II* 4 (2) (1994) 191–214.
- [38] F. Dubois, P. Lallemand, M. Tekitek, On a superconvergent lattice Boltzmann boundary scheme, *Comput. Math. Appl.* 59 (7) (2010) 2141–2149.
- [39] J. Tölke, M. Krafczyk, TeraFLOP computing on a desktop PC with GPUs for 3D CFD, *Int. J. Comput. Fluid Dyn.* 22 (7) (2008) 443–456, <http://dx.doi.org/10.1080/10618560802238275>.
- [40] F. Kuznik, C. Obrecht, G. Rusaouen, J.-J. Roux, LBM based flow simulation using GPU computing processor, *Comput. Math. Appl.* 59 (7) (2010) 2380–2392, <http://dx.doi.org/10.1016/j.camwa.2009.08.052>.
- [41] C. Obrecht, F. Kuznik, B. Tourancheau, J.-J. Roux, A new approach to the lattice Boltzmann method for graphics processing units, *Comput. Math. Appl.* 61 (12) (2011) 3628–3638, <http://dx.doi.org/10.1016/j.camwa.2010.01.054>.
- [42] C. Obrecht, F. Kuznik, B. Tourancheau, J.-J. Roux, The TheLMA project: a thermal lattice Boltzmann solver for the GPU, *Comput. Fluids* 54 (2012) 118–126.