

Efficient Performance Evaluation of Long Short-Term Memory Algorithm and Recurrent Neural Network Algorithm in Prediction of Water Inundation Frequency


INTRODUCTION

- The term "water inundation frequency" describes how often flooding or water inundation occurs in a certain area.
- The project’s aim is to improve the accuracy of flood predictions by refining forecasts regarding water inundation frequency, employing cutting-edge deep learning techniques such as Long Short-Term Memory (LSTM) and Recurrent Neural Network (RNN).
- The utilization of deep learning techniques to improve flood forecasting is what makes this project significant; it intends to reduce risks, save lives, minimize the socio-economic effect of flooding, and promote sustainable communities.
- Applications include catastrophe prevention, urban development, and infrastructural robustness.
- For flood prediction, long-term relationships and temporal dynamics are best captured by LSTM networks, whereas RNN uses recurrent connections to demonstrate obscure trends. Because RNN has trouble in processing sequential data.
- The dataset utilized for this project is related to the 2018 Kerala floods and includes self-explanatory column names along with statistics on rainfall, warnings, casualties, and warnings broken down by district.



Water Inundation affected area

MATERIALS AND METHODS




By contrasting the predictive performance of LSTM and RNN architectures, the study will identify the most effective method for filling the research gap in water inundation frequency prediction. This comparison will take into account variables like forecasting water inundation frequency accuracy, computing efficiency, and robustness.

RESULTS

		Levene's Test for Equality of Variances		t-test for Equality of Means						
		F	Sig.	t	df	Sig. (2-tailed)	Mean Difference	Std. Error Difference	95% Confidence Interval of the Difference	
									Lower	Upper
Accuracy	Equal variances assumed	6.00	0.019	6.16	38	0.000	5.97500	0.96922	4.0129	7.93709
	Equal variances not assumed			6.16	31.16	0.000	5.97500	0.96922	3.9986	7.95132

The independent sample t-test for Equality of Means is given with the Equal variances assumed and also Equal variances not assumed.



Mean accuracy comparison between LSTM algorithm and RNN algorithm.

- After gathering a sample size of 20 accuracies for each algorithm, a paired sample t-test was conducted in SPSS to compare them. The mean accuracy and standard deviation were calculated for both LSTM and RNN.
- A statistically significant difference in the mean accuracies of the two algorithms in predicting the frequency of water inundations is indicated by the computed significance value of 0.019.
- This implies that one approach performs noticeably better than the other, highlighting the need to select the algorithm with more accuracy for real-world application or future advancements in water inundation frequency analysis.

DISCUSSION AND CONCLUSION

- The LSTM model achieved a mean accuracy of 93.0095, with a standard deviation of 2.23460, surpassing the RNN model, which attained a mean accuracy of 87.0345 with a standard deviation of 3.71408.
- Looking forward, the project's findings offer promising implications for the future of flood prediction methodologies. These discoveries could expand the application of such methods to climate modeling, disaster preparedness, and infrastructure risk assessment, promoting a more resilient approach to natural disaster management.
- However, despite its potential benefits, challenges persist. The accuracy of predictive models remains contingent upon the availability and quality of historical flood data, while the computational requirements associated with training deep learning models like LSTM and RNN pose additional obstacles.
- In conclusion, LSTM's proficiency in capturing long-term dependencies in time series data provides a significant advantage in forecasting water inundation frequency, particularly concerning historical hydrological patterns and natural catastrophes.

BIBLIOGRAPHY

- Asanjan, Ata Akbari, Tiantian Yang, Kuolin Hsu, Soroosh Sorooshian, Junqiang Lin, and Qidong Peng. 2023. “Short-Term Precipitation Forecast Based on the PERSIANN System and LSTM Recurrent Neural Networks.” Journal of Geophysical Research, D: Atmospheres 123 (22): 12,543–12,563.DOI:10.1029/2018JD028375
- Anaraki, Mahdi Valikhan, Saeed Farzin, Sayed-Farhad Mousavi, and Hojat Karami. 2022. “Uncertainty Analysis of Climate Change Impacts on Flood Frequency by Using Hybrid Machine Learning Methods.” Water Resources Management 35 (1): 199–223. DOI: 10.1007/s11269-020-02719-w
- Bowes, Benjamin D., Jeffrey M. Sadler, Mohamed M. Morsy, Madhur Behl, and Jonathan L. Goodall. 2019. “Forecasting Groundwater Table in a Flood Prone Coastal City with Long Short-Term Memory and Recurrent Neural Networks.” WATER 11 (5): 1098.DOI:10.3390/w11051098
- Liu, Moyang, Yingchun Huang, Zhijia Li, Bingxing Tong, Zhentao Liu, Mingkun Sun, Feiqing Jiang, and Hanchen Zhang. 2023. “The Applicability of LSTM-KNN Model for Real-Time Flood Forecasting in Different Climate Zones in China.” WATER 12 (2): 440. DOI:10.3390/w12020440