```
 C002        | statistics  |       50 |
 C021        | programming |       60 |
+------------+-------------+----------+
2 rows in set (0.00 sec)

mysql> insert into course(courseNo,courseName,scores)values('C002','statistics'
,70),('C021','programming',75),('C002','statistics',78),('C021','programming',7
6);
Query OK, 4 rows affected (0.00 sec)
Records: 4  Duplicates: 0  Warnings: 0

mysql> select * from course;
+------------+-------------+----------+
| courseNo   | courseName  | scores   |
+------------+-------------+----------+
| C002       | statistics  |       50 |
| C021       | programming |       60 |
| C002       | statistics  |       70 |
| C021       | programming |       75 |
| C002       | statistics  |       78 |
| C021       | programming |       76 |
+------------+-------------+----------+
6 rows in set (0.00 sec)

mysql> select avg(scores) from course where courseNo like 'C002';
+-------------+
| avg(scores) |
+-------------+
|     66.0000 |
+-------------+
1 row in set (0.00 sec)

mysql> select max(scores),min(scores) from course;
+-------------+-------------+
| max(scores) | min(scores) |
+-------------+-------------+
|          78 |          50 |
+-------------+-------------+
1 row in set (0.01 sec)

mysql> select max(scores),min(scores),avg(scores) from course;
+-------------+-------------+-------------+
| max(scores) | min(scores) | avg(scores) |
+-------------+-------------+-------------+
|          78 |          50 |     68.1667 |
+-------------+-------------+-------------+
1 row in set (0.00 sec)

mysql>
```

```
C002      | statistics  |    78 |
C021      | programming |    76 |
---------+------------+-------+
 rows in set (0.00 sec)

ysql> select avg(scores) from course where courseNo like 'C002';
-----------+
 avg(scores) |
-----------+
     66.0000 |
-----------+
 row in set (0.00 sec)

ysql> select max(scores),min(scores) from course;
-----------+------------+
 max(scores) | min(scores) |
-----------+------------+
          78 |          50 |
-----------+------------+
 row in set (0.01 sec)

mysql> select max(scores),min(scores),avg(scores) from course;
-----------+------------+------------+
 max(scores) | min(scores) | avg(scores) |
-----------+------------+------------+
          78 |          50 |    68.1667 |
-----------+------------+------------+
 row in set (0.00 sec)

mysql> select avg(scores) from  course;
+------------+
 avg(scores) |
+------------+
     68.1667 |
+------------+
 row in set (0.00 sec)

mysql> select avg(scores) from course where courseNo like 'C0%';
+------------+
 avg(scores) |
+------------+
     68.1667 |
+------------+
 row in set (0.00 sec)

mysql>
```

```
|              78 |           50 |      68.1667 |
+----------------+--------------+--------------+
1 row in set (0.00 sec)

mysql> select avg(scores) from  course;
+-------------+
| avg(scores) |
+-------------+
|     68.1667 |
+-------------+
1 row in set (0.00 sec)

mysql> select avg(scores) from course where courseNo like 'C0%';
+-------------+
| avg(scores) |
+-------------+
|     68.1667 |
+-------------+
1 row in set (0.00 sec)

mysql> select sum(scores) from course;
+-------------+
| sum(scores) |
+-------------+
|         409 |
+-------------+
1 row in set (0.00 sec)

mysql> select coursedesc,count(courseName) from course;
ERROR 1054 (42S22): Unknown column 'coursedesc' in 'field list'
mysql> select count(courseName) from course;
+-------------------+
| count(courseName) |
+-------------------+
|                 6 |
+-------------------+
1 row in set (0.01 sec)

mysql> select count(courseName) from course where courseName='statistics';
+-------------------+
| count(courseName) |
+-------------------+
|                 3 |
+-------------------+
1 row in set (0.00 sec)

mysql>
```