

The MATLAB interface displays the following code in the editor:

```
6 % Network Throughput (Mbps)
7 Throughput = [120 135 150 165 180 195 210 225 240 255];
8 % Network Utilization (%)
9 Utilization = [60 65 70 74 78 82 86 90 94 98];
10 figure
11 % ----- Graph 1 -----
12 subplot(2,1,1)
13 plot(t,Throughput,'-o','LineWidth',2)
14 title('AI-Based Network Throughput')
15 xlabel('Time Interval')
16 ylabel('Throughput (Mbps)')
17 grid on
18
19 % ----- Graph 2 -----
20 subplot(2,1,2)
21 plot(Throughput,Utilization,'-s','LineWidth',2)
22 title('Throughput vs Network Utilization')
23 xlabel('Network Throughput (Mbps)')
24 ylabel('Network Utilization (%)')
25 grid on
26 disp('Time Throughput(Mbps) Utilization(%)')
27 disp([t Throughput Utilization])
```

The Command Window shows the output of the code:

```
>>
Time Throughput(Mbps) Utilization(%)
9 240 94
10 255 98
```

The figure window displays two subplots:

- AI-Based Network Throughput**: A line plot showing Throughput (Mbps) on the y-axis (ranging from 100 to 250) versus Time Interval on the x-axis (ranging from 1 to 10). The data points are connected by a blue line with circular markers.
- Throughput vs Network Utilization**: A line plot showing Network Utilization (%) on the y-axis (ranging from 60 to 100) versus Network Throughput (Mbps) on the x-axis (ranging from 120 to 260). The data points are connected by a blue line with square markers.



30°C Partly cloudy Search 61 ENG IN 20:48 01-09-2026



