

The MATLAB interface displays two subplots of throughput versus SNR. The top subplot, titled "NB-IoT Throughput vs SNR", shows throughput in Mbps on the y-axis (ranging from 0 to 0.05) against signal-to-noise ratio in dB on the x-axis (ranging from 0 to 30). The bottom subplot, titled "LTE-M Throughput vs SNR", shows throughput in Mbps on the y-axis (ranging from 0 to 1) against signal-to-noise ratio in dB on the x-axis (ranging from 0 to 30). Both plots show a blue line with markers representing the throughput, which increases as SNR increases. The Command Window shows the MATLAB code used to generate the plots, including the definition of SNR, the calculation of NB-IoT and LTE-M throughput, and the plotting commands.

SNR (dB)	NB-IoT Throughput (Mbps)	LTE-M Throughput (Mbps)
0	0.0000	0.0000
5	0.0232	0.5577
10	0.0359	0.8439
15	0.0417	0.9813
20	0.0448	1.0478
25	0.0468	1.0717
30	0.0478	1.0717

The screenshot displays the MATLAB environment with the following components:

- Script Editor:** Contains a MATLAB script for simulating packet delivery ratios. The script defines SNR values, simulated packet delivery ratios for NB-IoT and LTE-M, and plots them.
- Workspace:** Lists variables: LTE_M (double), NB_IoT (double), and SNR (double).
- Figure Window:** Displays two subplots:
 - Graph 1:** "NB-IoT Packet Delivery Ratio vs SNR". The x-axis is "Signal-to-Noise Ratio (dB)" from 0 to 30, and the y-axis is "Packet Delivery Ratio (%)" from 80 to 100. The plot shows a blue line with circle markers.
 - Graph 2:** "LTE-M Packet Delivery Ratio vs SNR". The x-axis is "Signal-to-Noise Ratio (dB)" from 0 to 30, and the y-axis is "Packet Delivery Ratio (%)" from 85 to 100. The plot shows a blue line with square markers.
- Command Window:** Shows the output of the script, displaying the SNR values and the corresponding packet delivery ratios for NB-IoT and LTE-M.

The figure displays two subplots comparing the latency of NB-IoT and LTE-M technologies across a range of Signal-to-Noise Ratios (SNR) from 0 to 30 dB. The y-axis for both plots represents Latency in milliseconds (ms).

Top Plot: NB-IoT Latency vs SNR

SNR (dB)	Latency (ms)
0	180
5	160
10	145
15	130
20	120
25	110
30	100

Bottom Plot: LTE-M Latency vs SNR

SNR (dB)	Latency (ms)
0	90
5	80
10	70
15	60
20	50
25	45
30	40