

```
mysql> DESC DBMS_Stud;
```

Field	Type	Null	Key	Default	Extra
Reg_No	int	NO	PRI	NULL	
Name	varchar(50)	YES		NULL	
Department	varchar(30)	YES		NULL	

```
mysql> SELECT * FROM DBMS_Stud;
```

Reg_No	Name	Department
1	Rahul	CSE
2	Priya	ECE
3	Arun	IT
4	Meena	CSE
5	Kumar	CSE
6	Anitha	ECE

6 rows in set (0.013 sec)

Register_No	Name	Department	Mark
1	Arun	CSE	85
2	Priya	IT	90
3	Rahul	ECE	78
4	Divya	CSE	88
5	Karthik	MECH	75
101	Vijay	CSE	82
102	Anu	IT	91
103	Ravi	ECE	76

```
mysql> SELECT * FROM DBMS_Stud;
```

Register_No	Name	Department	Mark
1	Arun	CSE	85
2	Priya	IT	90
3	Rahul	ECE	78
4	Divya	CSE	88
5	Karthik	MECH	75
101	Vijay	CSE	82
102	Anu	IT	91
103	Ravi	ECE	76
104	Sneha	CSE	89

```
mysql> DESC DBMS_Stud;
```

Field	Type	Null	Key	Default	Extra
Register_No	int	NO	PRI	NULL	
Name	varchar(50)	YES		NULL	
Department	varchar(50)	YES		NULL	
Mark	int	YES		NULL	

4 rows in set (0.231 sec)

```
mysql> CREATE PROCEDURE test_mysql_while_loop()
-> BEGIN
-> DECLARE x INT;
-> DECLARE str VARCHAR(255);
->
-> SET x = 1;
-> SET str = '';
->
-> WHILE x <= 5 DO
->     SET str = CONCAT(str,x,',');
->     SET x = x + 1;
-> END WHILE;
->
-> SELECT str;
-> END
-> //
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> CALL test_mysql_while_loop(); //
```

```
+-----+
| str   |
+-----+
| 1,2,3,4,5, |
+-----+
1 row in set (0.00 sec)
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> CREATE PROCEDURE dorepeat(p1 INT) BEGIN SET @x=0; REPEAT SET @x=@x+1; UNTIL @x>p1 END REPEAT; END //
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> CALL dorepeat(4001) //
```

Query OK, 0 rows affected (0.03 sec)

```
mysql> SELECT @x;
```

```
-> //
+-----+
| @x   |
+-----+
| 4002 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> CREATE FUNCTION IncomeLevel ( monthly_value INT )
-> RETURNS varchar(20)
->
-> BEGIN
-> DECLARE income_level varchar(20);
->
-> CASE monthly_value
-> WHEN 4000 THEN
-> SET income_level = 'Low Income';
->
-> WHEN 5000 THEN
-> SET income_level = 'Avg Income';
->
-> ELSE
-> SET income_level = 'High Income';
-> END CASE;
->
-> RETURN income_level;
-> END; //
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> SELECT INCOMELEVEL(5300); //
```

INCOMELEVEL(5300)
High Income

1 row in set (0.00 sec)

```
mysql> CREATE FUNCTION CALCINCOME2 ( starting_value INT )
-> RETURNS INT
->
-> BEGIN
-> DECLARE income INT;
->
-> SET income = 0;
->
-> label1: LOOP
-> SET income = income + starting_value;
-> IF income < 4000 THEN
-> ITERATE label1;
-> END IF;
-> LEAVE label1;
-> END LOOP label1;
->
-> RETURN income;
-> END; //
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> SELECT CALCINCOME2(2100); //
```

CALCINCOME2(2100)
4200

1 row in set (0.00 sec)

```
mysql> create table clss(name varchar(10),id int(5));
Query OK, 0 rows affected (0.19 sec)

mysql> insert into clss values('dj',5);
Query OK, 1 row affected (0.00 sec)

mysql> commit;
Query OK, 0 rows affected (0.04 sec)

mysql> update class set name='bravo' where id='5';
Query OK, 0 rows affected (0.00 sec)
Rows matched: 0 Changed: 0 Warnings: 0

mysql> savepoint A;
Query OK, 0 rows affected (0.00 sec)

mysql> insert into clss values('uppal',6);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> savepoint B;
Query OK, 0 rows affected (0.00 sec)

mysql> insert into clss values('balu',7);
Query OK, 1 row affected (0.00 sec)

mysql> savepoint C;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from class;
+-----+-----+
| name | id |
+-----+-----+
| dj   | 5 |
| uppal | 6 |
| balu | 7 |
+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> ROLLBACK TO B;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from class;
+-----+-----+
| name | id |
+-----+-----+
| dj   | 5 |
| uppal | 6 |
+-----+-----+
2 rows in set (0.00 sec)

mysql> ROLLBACK TO A;
Query OK, 0 rows affected (0.00 sec)

mysql> select * from class;
+-----+-----+
| name | id |
+-----+-----+
| dj   | 5 |
+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> CREATE PROCEDURE student_info()
-> select * from student_info;
->
Query OK, 0 rows affected (0.00 sec)

mysql> call student_info();
```

stuid	name	area	subject
201	raj	chennai	dbms
202	rahul	hyderabad	ooad
203	rahul	numbat	java
204	vikas	kochi	python

4 rows in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

```
mysql> DELIMITER $$
mysql> CREATE PROCEDURE GetCustomerLevel(
-> IN p_customerNumber int(11),
-> OUT p_customerLevel varchar(10))
-> BEGIN
-> DECLARE creditlim double;
->
-> SELECT creditlimit INTO creditlim
-> FROM customer
-> WHERE customerNumber = p_customerNumber;
->
-> IF creditlim > 50000 THEN
-> SET p_customerLevel = 'PLATINUM';
-> ELSEIF creditlim >= 10000 AND creditlim <= 50000 THEN
-> SET p_customerLevel = 'GOLD';
-> ELSE
-> SET p_customerLevel = 'SILVER';
-> END IF;
->
-> END$$
Query OK, 0 rows affected (0.00 sec)
```