

```
mysql> DELIMITER $$
mysql> CREATE PROCEDURE GetCustomerLevel(
->     IN p_customerNumber INT(11),
->     OUT p_customerLevel VARCHAR(10)
-> BEGIN
->     DECLARE creditLimit DOUBLE;
->     SELECT creditLimit INTO creditLimit
->     FROM customers
->     WHERE customerNumber = p_customerNumber;
->
->     IF creditLimit > 50000 THEN
->         SET p_customerLevel = 'PLATINUM';
->     ELSEIF (creditLimit >= 50000 AND creditLimit <= 18000) THEN
->         SET p_customerLevel = 'GOLD';
->     ELSEIF creditLimit < 18000 THEN
->         SET p_customerLevel = 'SILVER';
->     END IF;
-> END$$
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> CREATE PROCEDURE student_info()
-> select * from student_info;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql> call student_info();
```

| stuid | name  | area      | subject |
|-------|-------|-----------|---------|
| 201   | raj   | chennai   | dbms    |
| 202   | rahul | hyderabad | osad    |
| 203   | rahim | mumbai    | java    |
| 204   | vikas | kochi     | python  |

4 rows in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

```

mysql> DELIMITER //
mysql> CREATE FUNCTION CustomerLevel(p_CREDITLIMIT INT) RETURNS VARCHAR(10)
-> DETERMINISTIC
-> BEGIN
-> DECLARE lvl VARCHAR(10);
-> IF p_CREDITLIMIT > 50000 THEN
-> SET lvl = 'PLATINUM';
-> ELSEIF (p_CREDITLIMIT <= 50000 AND p_CREDITLIMIT >= 10000) THEN
-> SET lvl = 'GOLD';
-> ELSEIF p_CREDITLIMIT < 10000 THEN
-> SET lvl = 'SILVER';
-> END IF;
-> RETURN (lvl);
-> END
-> //
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT CNAME, CustomerLevel(CREDITLIMIT) FROM CUSTOMER ORDER BY CNAME;
+-----+-----+
| CNAME      | CustomerLevel(CREDITLIMIT) |
+-----+-----+
| DINESH     | GOLD                       |
| NAGENDRA   | PLATINUM                   |
| RAJA       | GOLD                       |
| RAMU       | SILVER                     |
+-----+-----+
4 rows in set (0.00 sec)

```

---

```

mysql> DELIMITER $$
mysql> CREATE PROCEDURE factorial(IN n INT, OUT fact INT)
-> BEGIN
-> IF n=1 THEN
-> SET fact:=1;
-> ELSE
-> CALL factorial(n-1,fact);
-> SET fact:=n*fact;
-> END IF;
-> END
-> $$
Query OK, 0 rows affected (0.01 sec)

mysql> CALL find_fact(5);
-> $$
+-----+
| @fact |
+-----+
| 120   |
+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

```

---

```

mysql> DELIMITER $$
mysql> CREATE PROCEDURE GetCustomerLevel(
-> IN p_customerNumber INT(11),
-> OUT p_customerLevel VARCHAR(10)
-> BEGIN
-> DECLARE creditLimit DOUBLE;
-> SELECT creditLimit INTO creditLimit
-> FROM customers
-> WHERE customerNumber = p_customerNumber;
->
-> IF creditLimit > 50000 THEN
-> SET p_customerLevel = 'PLATINUM';
-> ELSEIF (creditLimit >= 50000 AND creditLimit <= 18000) THEN
-> SET p_customerLevel = 'GOLD';
-> ELSEIF creditLimit < 18000 THEN
-> SET p_customerLevel = 'SILVER';
-> END IF;
-> END;
-> END$$
Query OK, 0 rows affected (0.00 sec)

```

```
mysql> DELIMITER $$
mysql> CREATE PROCEDURE factorial(IN n INT,OUT fact INT)
-> BEGIN
->   IF n=1 THEN
->     SET fact:=1;
->   ELSE
->     CALL factorial(n-1,fact);
->     SET fact:=n*fact;
->   END IF;
-> END
-> $$
```

Query OK, 0 rows affected (0.01 sec)

```
mysql> CALL find_fact(5);
-> $$
```

```
+-----+
| @fact |
+-----+
|  120  |
+-----+
```

1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)



## 1. REPEAT() Function

```
mysql> SELECT REPEAT('DBMS',10);
```

| REPEAT('DBMS',10)                        |
|------------------------------------------|
| DBMSDBMSDBMSDBMSDBMSDBMSDBMSDBMSDBMSDBMS |

```
1 row in set (0.00 sec)
```

```
mysql> SELECT REPEAT(' DBMS ',10);
```

| REPEAT(' DBMS ',10)                               |
|---------------------------------------------------|
| DBMS DBMS DBMS DBMS DBMS DBMS DBMS DBMS DBMS DBMS |

```
1 row in set (0.00 sec)
```

## 2. REVERSE() Function

```
mysql> SELECT REVERSE('Database');
+-----+
| REVERSE('Database') |
+-----+
| esabataD             |
+-----+
1 row in set (0.00 sec)
```

### 3. RIGHT() Function

```
mysql> SELECT RIGHT('Database',4);
+-----+
| RIGHT('Database',4) |
+-----+
| base                 |
+-----+
1 row in set (0.00 sec)
```

### 1. LEFT() Function

```
mysql> SELECT LEFT('Database', 5);
+-----+
| LEFT('Database', 5) |
+-----+
| Datab                |
+-----+
1 row in set (0.00 sec)
```

### 2. RPAD() Function

```
mysql> SELECT RPAD('Database',14,'#');
+-----+
| RPAD('Database',14,'#') |
+-----+
| Database#####         |
+-----+
1 row in set (0.00 sec)
```

### 3. LPAD() Function

```
mysql> SELECT LPAD('Database',20,'$');
+-----+
| LPAD('Database',20,'$') |
+-----+
| $$$$$$$$$$$$$Database  |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT LPAD('Database',4,'$');
+-----+
| LPAD('Database',4,'$') |
+-----+
| Data                    |
+-----+
1 row in set (0.00 sec)
```

### 4. ASCII() Function

```
mysql> SELECT ASCII(12);
+-----+
| ASCII(12) |
+-----+
|         49 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT ASCII('12');
+-----+
| ASCII('12') |
+-----+
|         49 |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT ASCII('a');
+-----+
| ASCII('a') |
+-----+
|         97 |
+-----+
1 row in set (0.00 sec)
```

## 1. BIN() Function

```
mysql> SELECT BIN(02);
```

```
+-----+
```

```
| BIN(02) |
```

```
+-----+
```

```
| 10      |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> SELECT BIN(11);
```

```
+-----+
```

```
| BIN(11) |
```

```
+-----+
```

```
| 1011     |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```

## 2. OCT() Function

```
mysql> SELECT OCT(8);
```

```
+-----+
```

```
| OCT(8) |
```

```
+-----+
```

```
| 10      |
```

```
+-----+
```

```
1 row in set (0.00 sec)
```