

```
r <- as.integer(
  readline("Enter number of rows: ")
)

c <- as.integer(
  readline("Enter number of columns: ")
)

total <- r * c

cat("Enter", total, "values for Array 1:\n")
v1 <- as.numeric(strsplit(readline(), " ")[[1]])

cat("Enter", total, "values for Array 2:\n")
v2 <- as.numeric(strsplit(readline(), " ")[[1]])

array1 <- matrix(v1, nrow = r, ncol = c)
array2 <- matrix(v2, nrow = r, ncol = c)

cat("\nArray 1:\n")
print(array1)

cat("\nArray 2:\n")
print(array2)

combined <- rbind(array1, array2)
```

```
cat("\nCombined Array Row-wise:\n")
```

```
print(combined)
```

The screenshot shows the RStudio interface with a script editor, environment pane, and console.

Script Editor:

```
8 total <- r * c
9
10
11 cat("Enter", total, "values for Array 1:\n")
12 v1 <- as.numeric(strsplit(readline(), " ")[[1]])
13
14 cat("Enter", total, "values for Array 2:\n")
15 v2 <- as.numeric(strsplit(readline(), " ")[[1]])
16
17 array1 <- matrix(v1, nrow = r, ncol = c)
18 array2 <- matrix(v2, nrow = r, ncol = c)
19
20 cat("\nArray 1:\n")
21 print(array1)
22
23 cat("\nArray 2:\n")
24 print(array2)
25
26 combined <- rbind(array1, array2)
27
28 cat("\nCombined Array Row-wise:\n")
29 print(combined)
```

Environment Pane:

Object	Class	Attributes
array1	num	[1:3, 1:2] 1 2 3 4 5 6
array2	num	[1:3, 1:2] 1 2 3 4 5 6
combined	num	[1:6, 1:2] 1 2 3 1 2 3 4 5 6 4 ...
c	2L	
r	3L	
total	6L	
v1	num	[1:6] 1 2 3 4 5 6
v2	num	[1:6] 1 2 3 4 5 6

Console:

```
> source("C:/Users/2021e/Desktop/EX 1.R")
Enter number of rows: 3
Enter number of columns: 2
Enter 6 values for Array 1:
1 2 3 4 5 6
Enter 6 values for Array 2:
1 2 3 4 5 6

Array 1:
     [,1] [,2]
[1,] 1    4
[2,] 2    5
[3,] 3    6

Array 2:
     [,1] [,2]
[1,] 1    4
[2,] 2    5
[3,] 3    6

Combined Array Row-wise:
     [,1] [,2]
[1,] 1    4
[2,] 2    5
[3,] 3    6
[4,] 1    4
[5,] 2    5
[6,] 3    6
> |
```