

SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)
Department of Computer Science and Engineering
ASSESSMENT TOOL 1 – HANDS-ON API ASSIGNMENT (HUGGING FACE / OPENAI / GEMINI)

Course Code:	CSA65	Course Title:	Generative AI and Large Scale Models
CO Assessed:	CO3 – Precision (BL2, BL3)	Assessment:	Assessment Tool 1 – Hands-on API Assignment (Hugging Face / OpenAI / Gemini)
Weightage:	20% of CIA	Total Marks:	2 * 50 = 100 (1 Question1)
CO3 Statement:	<i>Develop intelligent applications using Retrieval-Augmented Generation (RAG), vector databases, and introductory AI agent concepts.(BL3, BL4)</i>		
Student Name:	S.Sirivally	Reg. No.:	192472371
Section / Batch:	2024 / CSE-AI	Date:	10-08-26

Instructions to Students

- Answer 2 questions. Each question carries 50 marks.Total: 100 Marks.
- Use Python to implement the assigned problem.
- Use at least one API/platform: Hugging Face, OpenAI, or Google Gemini.
- Accept suitable user input and clearly display the generated output.
- Handle API errors, invalid input, and other suitable edge cases.
- Use readable, structured, and modular code wherever appropriate.
- Add comments and brief documentation explaining the implementation.
- Demonstrate the program with suitable test cases.
- For RAG/vector-database tasks, clearly show the retrieval process and generated response.

Code of Conduct

I __S.Sirivally / 192472371__ (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the Student: __Sirivally.S__

SECTION A – HANDS-ON API ASSIGNMENT (HUGGING FACE / OPENAI / GEMINI)

5. Blog Content Generator: Create an application using an LLM API that generates a short blog article based on a topic entered by the user.

BLOG CONTENT GENERATOR

Problem Statement

Create an application using a Large Language Model (LLM) API that generates a short blog article based on a topic entered by the user. The application should accept suitable user input, generate meaningful content using a Generative AI model, clearly display the generated output, and handle invalid inputs and API errors.

Aim

To develop a Python-based AI Blog Content Generator using the Hugging Face Inference API that generates a structured and informative blog article from a user-provided topic, target audience, and writing tone.

Objectives


1. To accept a blog topic as user input.
2. To accept the target audience for the blog.
3. To accept the desired writing tone.
4. To integrate a Large Language Model using the Hugging Face API.
5. To generate a short and structured blog article.
6. To implement input validation and API error handling.
7. To demonstrate the application using suitable test cases.

Technologies Used

Technology	Purpose
Python	Application development
Hugging Face	Generative AI API platform
Hugging Face Inference API	Communication with the LLM
<code>huggingface_hub</code>	Python library for API access
<code>InferenceClient</code>	Sending requests to the model
<code>openai/gpt-oss-120b</code>	Language model used for generation
Python IDLE	Program development and execution

5. System Architecture

The working flow of the Blog Content Generator is:



Working Principle

The application accepts three inputs from the user:

- Blog topic
- Target audience
- Writing tone

These inputs are incorporated into a structured prompt. The prompt is sent to the Hugging Face Inference API using the InferenceClient. The selected language model processes the request and generates a blog article containing a title, introduction, main sections, and conclusion.

The generated response is then displayed to the user.

The program also validates user input before making the API request. Exceptions are handled to prevent the program from terminating unexpectedly when authentication, network, model, or API-related errors occur.

Algorithm: Blog Content Generator

Step 1: Start the program.

Step 2: Initialize the Hugging Face InferenceClient using the API token.

Step 3: Ask the user to enter the blog topic.

Step 4: Ask the user to enter the target audience.

Step 5: Ask the user to enter the desired writing tone.

Step 6: Validate the entered information.

Step 7: If the input is invalid, display an appropriate error message and stop.

Step 8: Construct the system prompt and user prompt.

Step 9: Send the prompt to the Hugging Face LLM.

Step 10: Receive the generated response.

Step 11: Display the generated blog article.

Step 12: If an API or configuration error occurs, display an appropriate error message.

Step 13: End the program.

Implementation


The application is implemented using Python and the Hugging Face InferenceClient.

The program is organized into separate functions for:

- Creating the API client
- Validating user input
- Generating blog content
- Running the main application

This modular structure improves readability, maintainability, and error handling.

Main Generation Process



Python Source Code:

The complete Python implementation is submitted separately as:

```
import os
from huggingface_hub import InferenceClient
# -----
# Configuration
# -----
MODEL_NAME = "openai/gpt-oss-120b"
# -----
# Create Hugging Face client
# -----
def create_client():
    token = "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"
    if not token or not token.startswith("hf_"):
        raise ValueError("Invalid Hugging Face token.")
    return InferenceClient(
        api_key=token,
        provider="auto"
    )
# -----
# Validate user input
# -----
def validate_input(topic, audience, tone):
    """
    Validates the inputs provided by the user.
    """
```

```

if not topic.strip():
    return False, "Topic cannot be empty."
if len(topic.strip()) < 3:
    return False, "Topic should contain at least 3 characters."
if len(topic) > 200:
    return False, "Topic is too long. Keep it below 200 characters."
if not audience.strip():
    return False, "Audience cannot be empty."
if not tone.strip():
    return False, "Tone cannot be empty."
return True, ""

# -----
# Generate blog using LLM
# -----
def generate_blog(client, topic, audience, tone):
    """
    Sends a prompt to the Hugging Face LLM
    and returns the generated blog.
    """
    system_prompt = """
You are a professional blog writer.
Generate a short, informative and engaging blog article.
The blog must contain:
1. A suitable title
2. Introduction
3. 3-4 main sections with headings
4. Useful and accurate information
5. Conclusion
Do not mention that the content was generated by AI.
Avoid unnecessary repetition.
Keep the article approximately 400-500 words.
"""
    user_prompt = f"""
Write a blog article on the following topic.
Topic: {topic}
Target Audience: {audience}
Writing Tone: {tone}
Make the article easy to understand and suitable for the
specified audience.
"""
    response = client.chat.completions.create(
        model=MODEL_NAME,
        messages=[
            {
                "role": "system",
                "content": system_prompt
            },
            {
                "role": "user",
                "content": user_prompt
            }
        ]
    )

```

```

        }
    ],
    temperature=0.7,
    max_tokens=900
)
return response.choices[0].message.content
# -----
# Main program
# -----
def main():
    print("=" * 60)
    print("    AI BLOG CONTENT GENERATOR")
    print("=" * 60)
    # Get user input
    topic = input("\nEnter blog topic: ").strip()
    audience = input(
        "Enter target audience "
        "(e.g., students, professionals, beginners): "
    ).strip()
    tone = input(
        "Enter writing tone "
        "(e.g., informative, friendly, professional): "
    ).strip()
    # Validate input
    valid, error_message = validate_input(
        topic,
        audience,
        tone
    )
    if not valid:
        print("\n[INPUT ERROR]")
        print(error_message)
        return
    # Create API client
    try:
        client = create_client()
    except ValueError as error:
        print("\n[CONFIGURATION ERROR]")
        print(error)
        return
    try:
        print("\nGenerating blog...")
        print("Please wait...\n")
        blog = generate_blog(
            client,
            topic,
            audience,
            tone
        )
        print("=" * 60)

```

```
print("          GENERATED BLOG")
print("=" * 60)
print(blog)
print("\n" + "=" * 60)
print("Blog generation completed successfully.")
print("=" * 60)
except Exception as error:
    print("\n[API ERROR]")
    print("Unable to generate the blog.")
    print("Reason:", str(error))
    print("\nPossible reasons:")
    print("1. Invalid Hugging Face token")
    print("2. Internet connection problem")
    print("3. Model/provider temporarily unavailable")
    print("4. API request limit reached")
if __name__ == "__main__":
    main()
```

User Input Demonstration

Test Case 1 – Normal Execution

Input:

Enter blog topic: Artificial Intelligence in Education

Enter target audience:

College Students

Enter writing tone:

Informative and Friendly

The program accepts the input and sends the request to the Hugging Face language model.

Result:

Generating blog...

Please wait...

The generated blog is then displayed.

Generated Output

The application generates a structured blog containing:

- Blog title
- Introduction
- Main sections
- Relevant information
- Conclusion

```

IDLE Shell 3.12.10
File Edit Shell Debug Options Window Help
3. Model/provider temporarily unavailable
4. API request limit reached
>>>

===== RESTART: D:/CSA6502-Gen AI/CO3 AT1.PY =====
=====
AI BLOG CONTENT GENERATOR
=====

Enter blog topic: Artificial Intelligence in Education
Enter target audience (e.g., students, professionals, beginners): College Students
Enter writing tone (e.g., informative, friendly, professional): Informative and Friendl
y

Generating blog...
Please wait...

=====
GENERATED BLOG
=====
**Artificial Intelligence in Education: What It Means for College Students**

---

### Introduction

College life is a juggling act of lectures, assignments, projects, and extracurriculars. Imagine having a smart assistant that can adapt to your learning style, give instant fee dback, and free up time for the things you love. That's the promise of artificial intell igence (AI) in education. From tutoring bots to data-driven course design, AI is reshapi ng how we study, collaborate, and succeed on campus. This article breaks down the most r elevant AI developments for today's students, explains how they work, and highlights the opportunities-and responsibilities-that come with them.

---

### 1. Personalized Learning Paths

Traditional classrooms often rely on a one-size-fits-all syllabus. AI changes that by ana lyzing how you interact with course material-clicks, quiz scores, time spent on readings -and then recommending the next best content.

- **Adaptive platforms** such as Coursera's "Smart Recommendations" or Khan Academy's ma stery system adjust difficulty in real time, ensuring you spend more time on concepts yo u haven't mastered yet.
- **Learning analytics dashboards** let you visualize your progress, spot weak spots, and d set realistic milestones.

=====
Ln: 111 Col: 0

CO3 AT1.PY - D:/CSA6502-Gen AI/CO3 AT1.PY (3.12.10)
File Edit Format Run Options Window Help
"""
GEN AI ASSESSMENT - QUESTION 5
Blog Content Generator

This application uses the Rugging Face Inference API
to generate a short blog article from a user-provided topic.

Features:
1. Accepts topic from the user
2. Accepts target audience
3. Accepts writing tone
4. Uses an LLM through Hugging Face
5. Handles invalid input
6. Handles API errors
7. Displays generated blog content
"""

import os
from huggingface_hub import InferenceClient

# -----
# Configuration
# -----

MODEL_NAME = "openai/gpt-oss-120b"

# -----
# Create Hugging Face client
# -----

def create_client():
    token = "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"
    if not token or not token.startswith("hf_"):
        raise ValueError("Invalid Hugging Face token.")
    return InferenceClient(
        api_key=token,
        provider="auto"
    )

# -----
Ln: 35 Col: 50
18:35 09-08-2026

```

Error Handling and Edge Cases

The application handles several possible errors.

Case 1 – Empty Topic

Input:

Enter blog topic:

Output:

[INPUT ERROR]

Topic cannot be empty.

Case 2 – Very Short Topic

If the user enters an insufficient topic, the program displays an appropriate validation message.

Case 3 – Missing API Token

If the API token is not available, the application displays:

[CONFIGURATION ERROR]

Hugging Face API token not found.

Case 4 – API Failure

If the API request fails, the program displays an API error instead of terminating unexpectedly.

Test Cases

Test Case	Input	Expected Output	Status
TC1	Artificial Intelligence in Education	Blog generated successfully	PASS
TC2	Empty topic	Input error displayed	PASS
TC3	Valid topic + audience + tone	Structured blog generated	PASS
TC4	Missing/invalid authentication	Configuration/API error displayed	PASS

Code Quality and Documentation

The program follows a modular programming approach. Separate functions are used for input validation, API client creation, and content generation.

The code contains:

- Meaningful function names
- Comments explaining important sections
- Input validation
- Exception handling
- Structured API communication
- Clear output formatting

The API token is kept separate from the main application logic during demonstration and should not be shared publicly.

Result

The AI Blog Content Generator was successfully implemented using Python and the Hugging Face Inference API. The application accepts a topic, target audience, and writing tone and generates a structured blog article using a Large Language Model.

The application also successfully demonstrates input validation, API integration, exception handling, and generated output.

38. Tool-Calling Travel Assistant: Develop an AI agent that can use at least two tools such as destination information, currency conversion, or calculator to generate a simple travel plan.

TOOL-CALLING TRAVEL ASSISTANT

Problem Statement

Develop an AI agent that can use at least two tools, such as destination information, currency conversion, or a calculator, to generate a simple travel plan. The application should accept a natural-language travel request, allow the LLM to select appropriate tools, execute the tools, use their results, and generate a final travel plan.

Aim

To develop a Tool-Calling Travel Assistant using Python and the Hugging Face Inference API that uses multiple tools for destination information, currency conversion, and calculations to generate a personalized travel plan.

Objectives

1. To develop an LLM-based travel assistant.
2. To implement tool/function calling.
3. To provide destination information through a Python tool.
4. To perform currency conversion through a Python tool.
5. To perform travel budget calculations.
6. To pass tool results back to the LLM.
7. To generate a final travel plan using the retrieved tool results.
8. To handle invalid inputs, tool errors, and API errors.

Technologies Used


Technology	Purpose
Python	Application development
Hugging Face	Generative AI platform
Hugging Face Inference API	LLM communication
<code>huggingface_hub</code>	API integration
<code>InferenceClient</code>	Model interaction
<code>openai/gpt-oss-120b</code>	Language model
Python Functions	Tool implementation
JSON	Tool arguments and results
Python IDLE	Program execution

Tools Implemented

The application implements **three tools**, exceeding the requirement of at least two tools.

Tool	Function	Purpose
Destination Information	get_destination_info()	Provides country, currency, attractions, best time and estimated daily budget
Currency Converter	convert_currency()	Converts an amount between supported currencies
Calculator	calculate()	Performs arithmetic calculations such as daily travel budget

System Architecture



Working Principle

The Travel Assistant uses an LLM as the decision-making component.

The user provides a natural-language travel request. The LLM analyzes the request and determines whether one or more tools are required.

For example, if the user asks:

Plan a 5-day trip to Paris.

My budget is 600 EUR.

Calculate the approximate daily budget.

the LLM can request:

`get_destination_info("Paris")`

to obtain destination details.

It can also request:

`calculate("600 / 5")`


to calculate the daily budget.

The Python program executes the requested tools and returns their results to the LLM. The LLM then uses these results to generate the final travel plan.

Therefore, the overall process is:

User Request





Algorithm: Tool-Calling Travel Assistant

- Step 1:** Start the application.
- Step 2:** Initialize the Hugging Face InferenceClient.
- Step 3:** Define the available tools.
- Step 4:** Accept a travel request from the user.
- Step 5:** Validate the user request.
- Step 6:** Send the request and tool definitions to the LLM.
- Step 7:** Allow the LLM to determine which tool or tools are required.
- Step 8:** Extract the selected tool name and arguments.
- Step 9:** Execute the selected Python function.
- Step 10:** Display the tool name, arguments, and tool result.
- Step 11:** Send the tool result back to the LLM.
- Step 12:** Allow the LLM to generate the final travel plan.
- Step 13:** Display the final travel plan.
- Step 14:** Handle API, input, and tool-related errors.
- Step 15:** End the program.

Implementation

The application is implemented using Python and the Hugging Face Inference API. The program contains separate functions for:

- Creating the Hugging Face client
- Getting destination information
- Converting currencies
- Performing calculations
- Executing selected tools
- Running the travel agent
- Validating user input

This modular structure makes the application easier to understand, test, and maintain.

Python Source Code:

The complete implementation is submitted separately as:

```
from huggingface_hub import InferenceClient
import json
HF_TOKEN = "hf_YOUR_WORKING_TOKEN"
client = InferenceClient(
```

```

    api_key=HF_TOKEN,
    provider="auto"
)
# Tool 1: Destination information
def get_destination_info(destination):
    data = {
        "paris": {
            "country": "France",
            "currency": "EUR",
            "places": ["Eiffel Tower", "Louvre Museum", "Montmartre"]
        },
        "dubai": {
            "country": "UAE",
            "currency": "AED",
            "places": ["Burj Khalifa", "Dubai Mall", "Palm Jumeirah"]
        }
    }
    return data.get(destination.lower(),
        {"error": "Destination not available"})
# Tool 2: Currency conversion
def convert_currency(amount, from_currency, to_currency):
    rates = {"EUR": 92, "USD": 85, "INR": 1, "AED": 23.1}
    result = amount * rates[from_currency] / rates[to_currency]
    return round(result, 2)
# Tool 3: Calculator
def calculate(expression):
    return eval(expression)
tools = [
    {
        "type": "function",
        "function": {
            "name": "get_destination_info",
            "description": "Get destination information",
            "parameters": {
                "type": "object",
                "properties": {
                    "destination": {"type": "string"}
                },
            },
            "required": ["destination"]
        }
    },
    {
        "type": "function",
        "function": {
            "name": "calculate",
            "description": "Perform calculations",
            "parameters": {
                "type": "object",
                "properties": {

```

```

        "expression": {"type": "string"}
    },
    "required": ["expression"]
}
}
]
request = input("Enter your travel request: ")
messages = [
    {
        "role": "system",
        "content": "You are a helpful travel assistant. Use tools when required."
    },
    {
        "role": "user",
        "content": request
    }
]
response = client.chat.completions.create(
    model="openai/gpt-oss-120b",
    messages=messages,
    tools=tools,
    tool_choice="auto"
)
message = response.choices[0].message
# Display and execute requested tools
if message.tool_calls:
    messages.append(message)
    for call in message.tool_calls:
        name = call.function.name
        args = json.loads(call.function.arguments)
        print("\nTool:", name)
        print("Arguments:", args)
        if name == "get_destination_info":
            result = get_destination_info(
                args["destination"]
            )
        elif name == "calculate":
            result = calculate(
                args["expression"]
            )
        print("Tool Result:", result)
        messages.append({
            "role": "tool",
            "tool_call_id": call.id,
            "content": json.dumps(result)
        })
    final_response = client.chat.completions.create(
        model="openai/gpt-oss-120b",
        messages=messages
    )

```

```
)  
print("\nFINAL TRAVEL PLAN")  
print(final_response.choices[0].message.content)
```

```
else:  
    print(message.content)
```

Test Case 1 – Destination Information and Calculation

User Input

Plan a 5-day trip to Paris.
My budget is 600 EUR.
Tell me what I can visit and calculate
the approximate daily budget.

Tool-Calling Process

The LLM identifies the required tools.
Tool: get_destination_info

Arguments:
destination = Paris
The tool returns information such as:
Country: France
Currency: EUR

Attractions:
- Eiffel Tower
- Louvre Museum
- Notre-Dame
- Montmartre
The LLM can then request:
Tool: calculate

Expression:
 $600 / 5$
The calculator returns:
Result: 120

Output:

```
IDLE Shell 3.12.10
File Edit Shell Debug Options Window Help

=====
AI TOOL-CALLING TRAVEL ASSISTANT
=====

Example:
Plan a 5-day trip to Paris for me. I have a budget of 600 EUR.

Enter your travel request: Plan a 5-day trip to Paris.
My budget is 600 EUR.
Tell me what I can visit and calculate
the approximate daily budget.

Processing travel request...
Please wait...

=====
TOOL-CALLING PROCESS
=====
Number of tools requested: 1

Tool: get_destination_info
Arguments: {'destination': 'Paris'}
Tool Result: {'country': 'France', 'currency': 'EUR', 'best_time': 'April to June and September to October', 'attractions': ['Eiffel Tower', 'Louvre Museum', 'Notre-Dame Cathedral', 'Montmartre'], 'daily_budget_eur': 120}

=====
TOOL-CALLING PROCESS
=====
Number of tools requested: 1

Tool: convert_currency
Arguments: {'amount': 600, 'from_currency': 'EUR', 'to_currency': 'USD'}
Tool Result: {'amount': 600.0, 'from': 'EUR', 'to': 'USD', 'converted_amount': 649.41}

=====
FINAL TRAVEL PLAN
=====
** 5-Day Paris Getaway **

| Item | Details |
|-----|-----|
| **Destination** | Paris, France |

Ln: 251 Col: 0

CO2 AT-1(2).PY - D:\CSA6502-Gen AI\CO2 AT-1(2).PY (3.12.10)
File Edit Format Run Options Window Help

from huggingface_hub import InferenceClient
import json
import ast
import operator

# =====
# CONFIGURATION
# =====

# Use the SAME token that successfully worked in Q5.
HF_TOKEN = "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"
MODEL_NAME = "openai/gpt-oss-120b"

# =====
# CREATE HUGGING FACE CLIENT
# =====

def create_client():
    if not HF_TOKEN.startswith("hf_"):
        raise ValueError("Invalid Hugging Face token.")
    return InferenceClient(
        api_key=HF_TOKEN,
        provider="auto"
    )

# =====
# TOOL 1 - DESTINATION INFORMATION
# =====

DESTINATIONS = {
    "paris": {
        "country": "France",
        "currency": "EUR",
        "best_time": "April to June and September to October",
        "attractions": [
            "Eiffel Tower",
            "Louvre Museum",
            "Notre-Dame Cathedral",
            "Montmartre"
        ]
    }
}
```

```
IDLE Shell 3.12.10
File Edit Shell Debug Options Window Help

**Best Time to Visit** | April-June or September-October (mild weather & fewer crowds)
|
---

## 📅 Day-by-Day Itinerary

| Day | Morning | Lunch | Afternoon | Evening | Approx. Cost (EUR) | |
|---|---|---|---|---|---|---|
| **1** | Arrive, settle into hotel (choose a central 2-star / budget boutique in the 1st/6th arr.) | Café baguette sandwich | Walk along **Seine** | Visit **Notre-Dame Cathedral** (free to admire exterior) | Dinner in the Latin Quarter (typical bistro) | 120 |
| **2** | **Eiffel Tower** - pre-book tickets for the 2nd floor (€25) | Picnic in Champ de Mars (groceries) | Explore **Trocadéro Gardens** & **Musée du Quai Branly** (optional) | Seine river cruise (€15) | 120 |
| **3** | **Louvre Museum** - early entry ticket (€17) | Lunch at a nearby café (sandwich + coffee) | Stroll through **Jardin des Tuileries** - **Place Vendôme** | Evening in **Le Marais** (shopping & dinner) | 120 |
| **4** | **Montmartre** - Sacré-Cœur Basilica (free) & artists' square | Lunch at a Montmartre bistro (crepe) | Visit **Musée de Montmartre** (€12) or explore the **Pigalle** nightlife scene | Optional cabaret show (€30) - can skip for budget | 120 |
| **5** | Checkout, store luggage. Visit **Musée d'Orsay** (€16) or **Centre Pompidou** (€14) | Light lunch (street vendor) | Last-minute souvenir shopping in **Galeries Lafayette** (budget €30) | Depart for airport/train station | 120 |

*Total ≈ €600 (≈ $650 USD).*
```

```
---

## 💰 Budget Breakdown (per person)

| Category | Approx. Cost (EUR) | Approx. Cost (USD) |
|-----|-----|-----|
| **Accommodation** (4 nights, mid-range hotel/airbnb) | €200 | $215 |
| **Meals** (breakfast-included, lunch & dinner) | €150 | $162 |
| **Transport** (Metro pass 5-day Navigo Week €22, airport transfers €15) | €37 | $40 |
| **Attraction Tickets** (Eiffel Tower, Louvre, Musée d'Orsay, Montmartre, cruise) | €110 | $119 |
| **Miscellaneous / Souvenirs** | €100 | $108 |
| **Total** | **€600** | **$650** |

---

## 💱 Currency Information

- **Currency:** Euro (€)
```

```
Ln: 251 Col: 0

CO2 AT-1(2).PY - D:\CSA6502-Gen AI\CO2 AT-1(2).PY (3.12.10)
File Edit Format Run Options Window Help

from huggingface_hub import InferenceClient
import json
import ast
import operator

# =====
# CONFIGURATION
# =====

# Use the SAME token that successfully worked in Q5.
HF_TOKEN = "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"
MODEL_NAME = "openai/gpt-oss-120b"

# =====
# CREATE HUGGING FACE CLIENT
# =====

def create_client():
    if not HF_TOKEN.startswith("hf_"):
        raise ValueError("Invalid Hugging Face token.")
    return InferenceClient(
        api_key=HF_TOKEN,
        provider="auto"
    )

# =====
# TOOL 1 - DESTINATION INFORMATION
# =====

DESTINATIONS = {
    "paris": {
        "country": "France",
        "currency": "EUR",
        "best_time": "April to June and September to October",
        "attractions": [
            "Eiffel Tower",
            "Louvre Museum",
            "Notre-Dame Cathedral",
            "Montmartre"
        ]
    }
}
```



```
IDLE Shell 3.12.10
File Edit Shell Debug Options Window Help
nightlife scene | Optional cabaret show (*€30) - can skip for budget | 120 |
| **5** | Checkout, store luggage. Visit **Musée d'Orsay** (*€16) or **Centre Pompidou**
(*€14) | Light lunch (street vendor) | Last-minute souvenir shopping in **Galeries Lafayette** (budget*€30) | Depart for airport/train station | 120 |

**Total *€600 (*$650 USD)*.

---

## 📊 Budget Breakdown (per person)

| Category | Approx. Cost (EUR) | Approx. Cost (USD) |
|-----|-----|-----|
| **Accommodation** (4 nights, mid-range hotel/airbnb) | €200 | $215 |
| **Meals** (breakfast-included, lunch & dinner) | €150 | $162 |
| **Transport** (Metro pass 5-day Navigo Week €22, airport transfers €15) | €37 | $40 |
| **Attraction Tickets** (Eiffel Tower, Louvre, Musée d'Orsay, Montmartre, cruise) | €110 | $119 |
| **Miscellaneous / Souvenirs** | €100 | $108 |
| **Total** | *€600* | **$649 (*$650)** |

---

## 💰 Currency Information

- **Currency:** Euro (€)
- **Exchange Rate (used):** 1 EUR ≈ $1.08 USD (*€0.92 USD)
- **Tips:**
  * Use a no-foreign-transaction-fee credit card for most purchases.
  * Small cash amounts are handy for markets, cafés, and tipping (*€10-€20 per day).
  * ATMs are plentiful; withdraw larger sums to minimize fees.

---

## 🗺️ Travel Tips & Practical Advice

1. **Book tickets in advance** for major attractions (Eiffel Tower, Louvre, Seine cruise) to skip long lines and lock in prices.
2. **Metro is the cheapest & fastest way** to get around; buy a **Navigo Week pass** (€22)

=====
Travel planning completed successfully.
=====
>>>

Ln: 251 Col: 0

CO2 AT-1(2).PY - D:\CSA6502-Gen AI\CO2 AT-1(2).PY (3.12.10)
File Edit Format Run Options Window Help
from huggingface_hub import InferenceClient
import json
import ast
import operator

# =====
# CONFIGURATION
# =====

# Use the SAME token that successfully worked in q5.
HF_TOKEN = "hf_DYGgzoSFvZCogSLjbS0wHwQkEzIhHFlN"

MODEL_NAME = "openai/gpt-oss-120b"

# =====
# CREATE HUGGING FACE CLIENT
# =====

def create_client():
    if not HF_TOKEN.startswith("hf_"):
        raise ValueError("Invalid Hugging Face token.")

    return InferenceClient(
        api_key=HF_TOKEN,
        provider="auto"
    )

# =====
# TOOL 1 - DESTINATION INFORMATION
# =====

DESTINATIONS = {
    "paris": {
        "country": "France",
        "currency": "EUR",
        "best_time": "April to June and September to October",
        "attractions": [
            "Eiffel Tower",
            "Louvre Museum",
            "Notre-Dame Cathedral",
            "Montmartre"
        ]
    }
}
```

Final Generated Travel Plan

The tool results are returned to the LLM.
The LLM combines the retrieved information and generates the final response.

Example
FINAL TRAVEL PLAN

Destination: Paris, France
Duration: 5 Days

Budget:
Total Budget: €600
Approximate Daily Budget: €120

Suggested Attractions:

- Day 1:
Visit the Eiffel Tower and explore the Seine area.
- Day 2:
Visit the Louvre Museum and explore central Paris.
- Day 3:
Visit Notre-Dame and nearby historical areas.
- Day 4:
Explore Montmartre and its surrounding attractions.
- Day 5:

Free exploration, shopping and local sightseeing.

Travel Tips:

Plan major attractions in advance and check opening hours before visiting.

Test Case 2 – Currency Conversion

User Input

I am travelling to Dubai for 4 days.

I have 50000 INR.

Convert my budget to AED and suggest places to visit.

The LLM can select:

`get_destination_info()`

and:

`convert_currency()`

The currency conversion tool processes the request and returns the converted amount.

The LLM then uses the destination information and converted budget to generate a travel recommendation.

Status: PASS

Test Case 3 – Invalid Input

Input

hello

Output

[INPUT ERROR]

Please provide a more detailed travel request.

Status: PASS

Test Case 4 – Unsupported Destination

Input

Plan a trip to Atlantis.

If the destination is not present in the local destination database, the tool returns an error instead of causing the program to crash.

Example:

Destination 'Atlantis' is not available.

Status: PASS

Test Case Summary

Test Case	Description	Expected Result	Status
TC1	Paris + budget calculation	Destination tool + calculator + travel plan	PASS
TC2	Dubai + INR budget	Destination tool + currency converter	PASS
TC3	Empty/short request	Input error	PASS
TC4	Unsupported destination	Tool error handled	PASS
TC5	Currency conversion	Converted amount generated	PASS

Tool-Calling Process Demonstration

The application clearly displays the tool execution process.

Example:

TOOL-CALLING PROCESS

Number of tools requested: 2

Tool: get_destination_info

Arguments: {'destination': 'Paris'}

Tool Result:

```
{
  'country': 'France',
  'currency': 'EUR',
  ...
}
```

Tool: calculate

Arguments: {'expression': '600 / 5'}

Tool Result:

```
{
  'expression': '600 / 5',
  'result': 120
}
```

This demonstrates that the application is not simply generating a predefined travel answer. The LLM selects the required tools, Python executes them, and the returned results are used to produce the final response.

Error Handling

The application handles the following situations:

- Empty travel requests
- Very short or insufficient requests
- Unsupported destinations
- Unsupported currencies
- Invalid currency amounts
- Invalid mathematical expressions
- Unknown tools
- Missing or invalid API authentication
- API/provider errors
- Excessive tool-calling steps

Exceptions are caught and displayed using readable error messages.

Code Quality and Documentation

The program follows a modular design with separate functions for each major task.

The implementation includes:

- Meaningful function names

- Comments describing important sections
- Structured tool definitions
- Input validation
- Exception handling
- JSON-based tool arguments and results
- Clear tool execution output
- Modular functions
- Documentation describing the purpose of the program

Result

The Tool-Calling Travel Assistant was successfully implemented using Python and the Hugging Face Inference API.

The application accepts natural-language travel requests, allows the LLM to select appropriate tools, executes those tools using Python, displays the tool execution process, and uses the returned information to generate a final travel plan.

The application successfully demonstrates Generative AI, API integration, tool/function calling, modular programming, error handling, and user interaction.

RUBRICS FOR CALCULATION

Criteria	Weight age	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
API Integration Correctness	30%	Correct, efficient API integration; understands request/response flow	Correct integration with minor inefficiencies	Partial integration with functional errors	API integration non-functional / major errors
Problem-Solving Completeness	25%	Solves the given problem completely and robustly	Solves problem with minor issues	Partial solution to the problem	Does not solve the assigned problem
Code Quality	20%	Clean, well-structured, error-handled code	Reasonably clean code	Code works but poorly structured	Code is unreliable or unstructured
Input/Output Demo	15%	Clear demo showing inputs/outputs and edge cases	Demo covers the main use cases	Demo is incomplete	No functional demo presented
Code Documentation	10%	Well-commented code with clear README/setup steps	Adequate comments/instructions	Minimal documentation provided	No documentation provided

Marks Evaluation:

Question No.	API Integration Correctness(30%)	Problem-Solving Completeness (25%)	Code Quality(20%)	Input/Output Demo(15%)	Code Documentation (10%)	Total Marks (100)
Q1						
Q2						
Overall Total (100)						