

```
mysql> CREATE TABLE students (  
->     id INT AUTO_INCREMENT PRIMARY KEY,  
->     name VARCHAR(50)  
-> );  
Query OK, 0 rows affected (0.14 sec)  
  
mysql>  
mysql> INSERT INTO students (name) VALUES ('Alice'), ('Bob'), ('Charlie');  
Query OK, 3 rows affected (0.02 sec)  
Records: 3  Duplicates: 0  Warnings: 0  
  
mysql>  
mysql> DELIMITER $$  
mysql>  
mysql> CREATE PROCEDURE CursorExample()  
-> BEGIN  
->     DECLARE done INT DEFAULT FALSE;  
->     DECLARE s_name VARCHAR(50);  
->     DECLARE cur CURSOR FOR SELECT name FROM students;  
->     DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = TRUE;  
->  
->     OPEN cur;  
->  
->     read_loop: LOOP  
->         FETCH cur INTO s_name;  
->         IF done THEN  
->             LEAVE read_loop;  
->         END IF;  
->         SELECT s_name AS StudentName;  
->     END LOOP;  
->  
->     CLOSE cur;  
-> END$$  
Query OK, 0 rows affected (0.01 sec)
```

```
-> END$$
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL CursorExample();
```

```
+-----+
| StudentName |
+-----+
| Alice       |
+-----+
1 row in set (0.01 sec)
```

```
+-----+
| StudentName |
+-----+
| Bob         |
+-----+
1 row in set (0.01 sec)
```

```
+-----+
| StudentName |
+-----+
| Charlie     |
+-----+
1 row in set (0.02 sec)
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
mysql>
```