```
mysql> SELECT REPLACE('hello world', 'world', 'MySQL') AS ReplaceResult;
+---------------+
| ReplaceResult |
+---------------+
| hello MySQL   |
+---------------+
1 row in set (0.01 sec)

mysql> SELECT REPEAT('Hi ', 3) AS RepeatResult;
+--------------+
| RepeatResult |
+--------------+
| Hi Hi Hi     |
+--------------+
1 row in set (0.00 sec)

mysql> SELECT REVERSE('MySQL') AS ReverseResult;
+---------------+
| ReverseResult |
+---------------+
| LQSyM         |
+---------------+
1 row in set (0.00 sec)

mysql> SELECT RIGHT('Database', 4) AS RightResult;
+-------------+
| RightResult |
+-------------+
| base        |
+-------------+
1 row in set (0.00 sec)
```

```
mysql> SELECT LEFT('Database', 4) AS LeftResult;
+------------+
| LeftResult |
+------------+
| Data       |
+------------+
1 row in set (0.00 sec)

mysql> SELECT RPAD('SQL', 8, '*') AS RPADResult;
+------------+
| RPADResult |
+------------+
| SQL*****    |
+------------+
1 row in set (0.00 sec)

mysql> SELECT LPAD('SQL', 8, '#') AS LPADResult;
+------------+
| LPADResult |
+------------+
| #####SQL    |
+------------+
1 row in set (0.01 sec)

mysql>
```