

Q1
Reverse a list
1 mark

Q2
Reverse a string
1 mark

Q3
Searching
1 mark

3/3 answered

Write a C program that takes an array as input and returns it reversed.

Your Code

```
1 #include <stdio.h>
2
3 int main() {
4     int arr[50], n;
5     scanf("%d", &n);
6     for (int i = 0; i < n; i++) {
7         scanf("%d", &arr[i]);
8     }
9     for (int i = (n-1); i >= 0; i--) {
10         printf("%d\t", arr[i]);
11     }
12     return 0;
13 }
```

▶ Run

☁ Save

🚀 Submit

Input

5
1
2
3

Output

5 4 3 2 1



1 mark

Q2

Reverse a string

1 mark



Q3

Searching

1 mark



3/3 answered

Write a program for palindrom

Your Code

```
1 #include<stdio.h>
2 int main()
3 {
4     int temp,num,rev=0,rem;
5
6     printf("enter the number:");
7     scanf("%d",&num);
8
9     temp=num;
10
11    while(n!=0)
12    {
13        rem=n%10;
14        rev=rev*10+rem;
15        num=num/10;
16
17    }
18
19    if(temp==rev)
```

Input

stdin input

Output



1 mark

Q3

Searching

1 mark



3/3 answered

```
1 #include <stdio.h>
2
3 int main(){
4     int n, x, arr[50];
5     scanf("%d", &n);
6     for (int i=0; i<n; i++){
7         scanf("%d", &arr[i]);
8     }
9     scanf("%d", &x);
10    printf("Given Array:\n");
11    for (int i=0; i<n; i++){
12        printf("%d\t", arr[i]);
13    }
14    printf("\nElement to be searched:%d\n", x);
15    for (int i = 0; i < n; i++){
16        if(arr[i] == x){
17            printf("Element found at position: %d", i+1);
18            break;
19        }
20    }
21    return 0;
22 }
```

3
4
5
2

Output

```
Given Array:
1      2      3      4      5
Element to be searched:2
Element found at position: 2
```