

```
1 #include <stdio.h>
2
3 #define MAX 5
4
5 int queue[MAX];
6 int front = 0, rear = 0;
7
8 void enqueue(int x)
9 {
10     if (rear == MAX)
11     {
12         printf("Overflow\n");
13         return;
14     }
15     else
16     {
17         queue[rear++] = x;
18         printf("Value is %d\n", queue[rear - 1]);
19     }
20 }
21
22 int main()
23 {
24     int x;
25
26     printf("Enter the value: ");
27     scanf("%d", &x);
```

10

Output

Enter the value: Value is 10

 Pending manual review

```
2 #include <stdlib.h>
3
4 struct Node {
5     int data;
6     struct Node *next;
7 };
8
9 int main() {
10     struct Node *newNode;
11
12     // Allocate memory for the node
13     newNode = (struct Node *)malloc(sizeof(struct Node));
14
15     if (newNode == NULL) {
16         printf("Memory allocation failed\n");
17         return 1;
18     }
19
20     newNode->data = 10;
21     newNode->next = NULL;
22
23     printf("%d\n", newNode->data);
24
25     free(newNode);
26
27     return 0;
28 }
```

Output

10

 Pending manual review

3/3 answered

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 struct Node {
5     int data;
6     struct Node *next;
7 };
8
9 void display(struct Node *head)
10 {
11     while (head != NULL)
12     {
13         printf("%d ", head->data);
14         head = head->next;
15     }
16 }
17
18 int main()
19 {
20     struct Node *head = (struct Node *)malloc(sizeof(struct Node));
21     struct Node *second = (struct Node *)malloc(sizeof(struct Node));
22     struct Node *third = (struct Node *)malloc(sizeof(struct Node));
23
24     head->data = 10;
25     head->next = second;
26 }
```

10
20
30

Output

10 20 30

 Pending manual review