

Cisco Packet Tracer

FileEditOptionsViewToolsExtensionsWindowHelp

LogicalPhysical

x: 421, y: 152

Root

12:37:00

Data Link Layer Simulation using CSMA (No Collision)

Server
192.168.1.10

PC-PT
PC0
192.168.1.1

PC-PT
PC1
192.168.1.2

PC-PT
PC2
192.168.1.3

CSMA (Carrier Sense Multiple Access) – No Collision

PC0 senses the medium.
It is idle, so it sends data.

PC1 senses the medium after PC0.
It is idle, so it sends data.

Time

PC0 TransmissionPC1 Transmission

Simulation Panel - CSMA

Event List

Vis.	Time(sec)	Last Device	At Device	Type	Info
●	0.000	PC0	--	DATA	PC0 starts transmission
●	0.002	PC0	Server	DATA	Data frame delivered to Server
●	0.010	PC1	--	DATA	PC1 starts transmission
●	0.012	PC1	Server	DATA	Data frame delivered to Server

▶

Reset Simulation

☒ Constant Delay

Captured to: 4

Cisco Packet Tracer
File Edit Options View Tools Extensions Window Help
Logical Physical x: 612, y: 214
Root 14:52:30

Data Link Layer Traffic Simulation using CSMA (No Collision)

CSMA (Carrier Sense Multiple Access) – No Collision

1. PC0 senses the medium. It is idle, so it sends data.
2. PC1 senses the medium after PC0. It is idle, so it sends data.
3. PC2 senses the medium after PC1. It is idle.

Time → PC0 Transmission → PC1 Transmission → PC2 Transmission →

Vis.	Time(sec)	Last Device	At Device	Type	Info
●	0.000	PC0	--	DATA	PC0 starts transmission
●	0.002	PC0	Server	DATA	Data frame delivered to Server
●	0.010	PC1	--	DATA	PC1 starts transmission
●	0.012	PC1	Server	DATA	Data frame delivered to Server
●	0.020	PC2	--	DATA	PC2 starts transmission
●	0.022	PC2	Server	DATA	Data frame delivered to Server

Reset Simulation
☒ Constant Delay
Captured to: 6

▶
⏮
⏭

Event List Filters - Visible Events
DATA, ARP, ICMP, HTTP

Edit Filters
Show All

PDU Information

At Device: Server

OSI Model Inbound PDU Details

7. Application	
6. Presentation	
5. Session	
4. Transport	
3. Network	
2. Data Link	Type: Ethernet II Src: PC0 / PC1 / PC2 Dst: Server Status: Success
1. Physical	