

DDL Commands with Constraints – PRIMARY, FOREIGN KEY, UNIQUE, CHECK

1. Alter the table STUDENT2 with following structure.

```
mysql> DESC STUDENT2;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| RegNo | int           | NO   | PRI | NULL    |       |
| S1Name | varchar(50)   | YES  |     | NULL    |       |
| Age   | int           | YES  |     | NULL    |       |
| MobileNo | varchar(15) | YES  |     | NULL    |       |
| Address | varchar(100) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>
```

2. Alter the table name FACULTY with following structure

```
mysql> DESC FACULTY;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| FacNo | int           | NO   | PRI | NULL    |       |
| FacName | varchar(50) | YES  |     | NULL    |       |
| Gender | char(1)      | YES  |     | NULL    |       |
| DOB   | date         | YES  |     | NULL    |       |
| MobileNo | varchar(15) | YES  |     | NULL    |       |
| DOJ   | date         | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)

mysql>
```

3. Alter the table name DEPARTMENT with following structure.

```
mysql> DESC DEPARTMENT;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| DeptNo | int           | NO   | PRI | NULL    |       |
| DeptName | varchar(50) | YES  |     | NULL    |       |
| DeptHead | varchar(50) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.01 sec)

mysql>
```

4. Alter the table name COURSE with following structure

```
mysql> DESC COURSE;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| CourseNo | int           | NO   | PRI | NULL    |       |
| CourseDesc | varchar(100) | YES  |     | NULL    |       |
| CourseType | varchar(50) | YES  |     | NULL    |       |
| SemNo   | int           | YES  |     | NULL    |       |
| HallNo  | int           | YES  |     | NULL    |       |
| FacNo   | int           | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql>
```

5. Alter the table name STUDENT2 with following structure.

```
4 rows in set (0.04 sec)
mysql> DESC STUDENT2;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| RegNo | int           | NO   | PRI | NULL    |       |
| S1Name | varchar(50)   | YES  | UNI | NULL    |       |
| Age   | int           | YES  |     | NULL    |       |
| MobileNo | varchar(15) | YES  |     | NULL    |       |
| Address | varchar(100) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

6. After the STUDENT2 & STUDENT3 tables are successfully created, test if you can add a constraint

```
mysql> DESC STUDENT2;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| RegNo | int           | NO   | PRI | NULL    |       |
| S1Name | varchar(50)   | YES  | UNI | NULL    |       |
| Age   | int           | YES  |     | NULL    |       |
| Address | varchar(100) | YES  |     | NULL    |       |
| DOB   | date          | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>
```