

DDL Commands – CREATE,ALTER,DROP

1. Create a table name STUDENT with following structure

```
mysql> DESC STUDENT;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| RegNo | int  | YES  |     | NULL    |       |
| Name  | varchar(15) | YES  |     | NULL    |       |
| Gender | char(1) | YES  |     | NULL    |       |
| DOB   | date  | YES  |     | NULL    |       |
| MobileNo | bigint | YES  |     | NULL    |       |
| City  | varchar(15) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.06 sec)

mysql> |
```

2. Create a table name FACULTY with following structure.

```
ERROR 1050 (42501): Table 'faculty' already exists
mysql> DESC FACULTY;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| FacNo | int  | NO   | PRI | NULL    |       |
| FacName | varchar(50) | YES  |     | NULL    |       |
| Gender | char(1) | YES  |     | NULL    |       |
| DOB   | date  | YES  |     | NULL    |       |
| MobileNo | varchar(15) | YES  |     | NULL    |       |
| DOJ   | date  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.02 sec)

mysql> |
```

3. Create a table name DEPARTMENT with following structure

```
mysql> DESC DEPARTMENT;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| DeptNo | int  | NO   | PRI | NULL    |       |
| DeptName | varchar(50) | YES  |     | NULL    |       |
| DeptHead | varchar(50) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> |
```

4. Create a table name COURSE with following structure.

```
ERROR 1050 (42501): Table 'course' already exists
mysql> DESC COURSE;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| CourseNo | int  | NO   | PRI | NULL    |       |
| CourseDesc | varchar(100) | YES  |     | NULL    |       |
| CourseType | varchar(50) | YES  |     | NULL    |       |
| SemNo | int  | YES  |     | NULL    |       |
| HallNo | int  | YES  |     | NULL    |       |
| FacNo | int  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.04 sec)

mysql> |
```

5. Modify the table FACULTY by adding a column name Dept of datatype VARCHAR(10)

```
mysql> DESC FACULTY;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| FacNo | int  | NO   | PRI | NULL    |       |
| FacName | varchar(50) | YES  |     | NULL    |       |
| Gender | char(1) | YES  |     | NULL    |       |
| DOB   | date  | YES  |     | NULL    |       |
| MobileNo | varchar(15) | YES  |     | NULL    |       |
| DOJ   | date  | YES  |     | NULL    |       |
| Dept  | varchar(10) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
7 rows in set (0.04 sec)

mysql> |
```