

```
mysql> CREATE FUNCTION income_level(monthly_value INT)
-> RETURNS VARCHAR(20)
-> DETERMINISTIC
-> BEGIN
->     DECLARE income_level VARCHAR(20);
->
->     CASE
->         WHEN monthly_value <= 4000 THEN
->             SET income_level = 'Low Income';
->
->         WHEN monthly_value <= 5000 THEN
->             SET income_level = 'Avg Income';
->
->         ELSE
->             SET income_level = 'High Income';
->     END CASE;
->     RETURN income_level;
-> END //
```

Query OK, 0 rows affected (0.05 sec)

```
mysql>
mysql> DELIMITER ;
mysql> SELECT income_level(4000);
```

```
+-----+
| income_level(4000) |
+-----+
| Low Income        |
+-----+
1 row in set (0.04 sec)
```

```
mysql> SELECT income_level(4500);
```

```
+-----+
| income_level(4500) |
+-----+
| Avg Income         |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT income_level(6000);
```

```
+-----+
| income_level(6000) |
+-----+
| High Income        |
+-----+
```

```

mysql> DELIMITER //
mysql>
mysql> CREATE FUNCTION increase_income_loop()
-> RETURNS INT
-> DETERMINISTIC
-> BEGIN
->     DECLARE income INT DEFAULT 1000;
->
->     my_loop: LOOP
->
->         SET income = income + 500;
->
->         IF income >= 4000 THEN
->             LEAVE my_loop;
->         END IF;
->
->         ITERATE my_loop;
->
->     END LOOP my_loop;
->
->     RETURN income;
-> END //

```

Query OK, 0 rows affected (0.01 sec)

```

mysql>
mysql> DELIMITER ;
mysql> SELECT increase_income_loop();

```

```

+-----+
| increase_income_loop() |
+-----+
|                4000 |
+-----+

```

1 row in set (0.00 sec)

```
mysql> |
```