

Lab Exercise 15

DCL COMMANDS – GRANT, REVOKE

AIM

To learn and implement **GRANT** and **REVOKE** commands in MySQL to provide and remove privileges for users.

PROCEDURE

1. Create the `VegetableDB` database and `Vegetable` table.
2. Create a new database user.
3. Grant privileges to the user.
4. Check the granted privileges.
5. Revoke a privilege from the user.
6. Verify the revoked privilege.

1. Create a User

```
CREATE USER 'veguser'@'localhost'  
IDENTIFIED BY 'veg123';
```

2. GRANT Permission

Give the user permission to **SELECT** and **INSERT** data:

```
GRANT SELECT, INSERT  
ON VegetableDB.Vegetable  
TO 'veguser'@'localhost';
```

3. Display Granted Privileges

```
SHOW GRANTS FOR 'veguser'@'localhost';
```

```
mysql> SHOW GRANTS FOR 'veguser'@'localhost';  
+-----+  
| Grants for veguser@localhost |  
+-----+  
| GRANT USAGE ON *.* TO `veguser`@`localhost` |  
| GRANT SELECT, INSERT ON `vegetabledb`.`vegetable` TO `veguser`@`localhost` |  
+-----+  
2 rows in set (0.00 sec)
```

4. REVOKE Permission

Remove the `INSERT` permission:

5. Check Permissions Again

```
SHOW GRANTS FOR 'veguser'@'localhost';
```

```
mysql> SHOW GRANTS FOR 'veguser'@'localhost';
+-----+
| Grants for veguser@localhost |
+-----+
| GRANT USAGE ON *.* TO `veguser`@`localhost` |
| GRANT SELECT ON `vegetabledb`.`vegetable` TO `veguser`@`localhost` |
+-----+
2 rows in set (0.00 sec)
```

GRANT ALL PRIVILEGES

If you want to give the user all privileges on the `VegetableDB` database:

```
GRANT ALL PRIVILEGES
ON VegetableDB.*
TO 'veguser'@'localhost';
```

REVOKE ALL PRIVILEGES

```
REVOKE ALL PRIVILEGES
ON VegetableDB.*
FROM 'veguser'@'localhost';
```