

QUESTION:5 SINGLE LINKEDLIST-INSERT BEGIN

main.c	Output
<pre>1 #include <stdio.h> 2 #include <stdlib.h> 3 struct Node { 4 int data; 5 struct Node *next; 6 }; 7 struct Node* insertAtBeginning(struct Node *head, int value) { 8 struct Node *newNode; 9 newNode = (struct Node*)malloc(sizeof(struct Node)); 10 newNode->data = value; 11 newNode->next = head; 12 head = newNode; 13 return head; 14 } 15 void display(struct Node *head) { 16 struct Node *temp = head; 17 18 while (temp != NULL) { 19 printf("%d -> ", temp->data); 20 temp = temp->next;</pre>	<pre>Linked List before insertion: 10 -> 20 -> 30 -> NULL Linked List after insertion at beginning: 5 -> 10 -> 20 -> 30 -> NULL === Code Execution Successful ===</pre>
<pre>21 } 22 printf("NULL\n"); 23 } 24 int main() { 25 struct Node *head = NULL; 26 head = insertAtBeginning(head, 30); 27 head = insertAtBeginning(head, 20); 28 head = insertAtBeginning(head, 10); 29 printf("Linked List before insertion:\n"); 30 display(head); 31 head = insertAtBeginning(head, 5); 32 printf("Linked List after insertion at beginning:\n"); 33 display(head); 34 35 return 0; 36 }</pre>	