

Student 2

Akshaya T

192520019RD

Level 2 — 25 marks/question

4 / 4 submitted

8/29/26, 9:23 AM

SIMATS Engineering

• Department of Computer Science and Engineering

• CSA0209 — C Programming

• 29-08-2026

• Category: CO4_AT1_LEVEL2

• Student Submissions Report

Student Submissions — CO4_AT1_LEVEL2

L2-Q1. unique (M)

C

CODE

```
#include <stdio.h>

int main()
{
    int arr[50], target, i, j, k, l, n, a;
    scanf("%d", &n);
    for(i=0; i<n; i++)
    {
        scanf("%d", &target);
    }
    for(i=0; i<n-3; i++)
    {
        for(j=i+1; j<n-2; j++)
        {
            for(k=j+1; k<n-1; k++)
            {
                for(l=k+1; l<n; l++)
                {
                    if(a[i]+a[j]+a[k]+a[l] == target){
                        printf("[%d,%d,%d,%d]", a[i], a[j], a[k], a[l]);
                    }
                }
            }
        }
    }
    return 0;
}
```

INPUT

8
1 0 -1 0 -2 2 2 -1
0

OUTPUT

Compilation Error:
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c: In function 'main':
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:18:22: error: subscripted value is neither array nor pointer nor vector
18 | if(a[i]+a[j]+a[k]+a[l] == target){
 | ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:18:27: error: subscripted value is neither array nor pointer nor vector
18 | if(a[i]+a[j]+a[k]+a[l] == target){
 | ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:18:32: error: subscripted value is neither array nor pointer nor vector
18 | if(a[i]+a[j]+a[k]+a[l] == target){
 | ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:18:37: error: subscripted value is neither array nor pointer nor vector
18 | if(a[i]+a[j]+a[k]+a[l] == target){
 | ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:19:46: error: subscripted value is neither array nor pointer nor vector
19 | printf("[%d,%d,%d,%d]", a[i], a[j], a[k], a[l]);
 | ^

simatslab.saveetha.com/practice_app/classactivity/ajax/download_submissions.php

6/144

SIMATS Engineering • Department of Computer Science and Engineering • CSA0209 — C Programming • 29-08-2026 • Category: CO4_AT1_LEVEL2 • Student Submissions Report

C: \Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:19:51: error: subscripted value is neither array nor pointer nor vector
19 | printf("[%d,%d,%d,%d]", a[i],a[j],a[k],a[l]);
| ^

C: \Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:19:56: error: subscripted value is neither array nor pointer nor vector
19 | printf("[%d,%d,%d,%d]", a[i],a[j],a[k],a[l]);
| ^

C: \Windows\TEMP\sandbox_192520019RD_6a7d8a67006120_30336786\main.c:19:61: error: subscripted value is neither array nor pointer nor vector
19 | printf("[%d,%d,%d,%d]", a[i],a[j],a[k],a[l]);
| ^

C

CODE

```
#include <stdio.h>
struct flight{
    char number[20];
    char from[20];
    char to[20];
    char date[20];
};
struct passenger{
    char name[20];
    struct flight;
};
int main()
{
    struct passenger p;
    int choice;
    while(1)
    {
        printf("\n1.book the flight\n");
        printf("2.manage reservation\n");
        printf("3.display flight information\n");
        printf("4.exit\n");
        ptintf("enter your choice:");
        scanf("%d",&choice);
        if(choice==1)
        {
            printf("enter passenger name:");
            scanf("%s",p.f.number);
            printf("enter the departure:");
            scanf("%[^\\n]",p.f.from);
            printf("enter the desination:");
            scanf("%[^\\n]",p.f.to);
            printf("enter the date:");
            scanf("%S",p.f.date);
            printf("flight booking successfull!\n");
        }
    }
}
```

OUTPUT

Security Error: Disallowed code pattern detected.

C

CODE

```
#include <stdio.h>
int main()
{
    int arr[100][100], r, c, i, j, sum=0;
    scanf("%d", &r);
    scanf("%d", &c);
    for(i=0; i<r; i++)
    {
        for(j=0; j<c; j++)
        {
            scanf("%d", &arr[i][j]);
        }
    }
    for(i=0; i<r; i++)
    {
        for(j=0; j<c; j++)
        {
            if(i==0 || i==r-1 || j==0 || j==c-1)
            {
                sum=sum+arr[i][j];
            }
        }
    }
    printf("sum of boundary elements:%d", sum);
    return 0;
}
```

INPUT

```
4
4
1 2 3 4
5 6 7 8
9 10 11 12
13 14 15 16
```

OUTPUT

```
sum of boundary elements:102
```