

Student 2 **Akshaya T** [192520019RD](#)

4 / 4 submitted

Level 2 — 25 marks/question

C

CODE

```
#include <stdio.h>
int main()
{
    int arr[50],target,i,j,k,l,n,a;
    scanf("%d",&n);
    for(i=0;i<n;i++)
    {
        scanf("%d",&target);
    }
    for(i=0;i<n-3;i++)
    {
        for(j=i+1;j<n-2;j++)
        {
            for(k=j+1;k<n-1;k++)
            {
                for(l=k+1;l<n;i++)
                {
                    if(a[i]+a[j]+a[k]+a[l] == target){
                        printf("[%d,%d,%d,%d]",a[i],a[j],a[k],a[l]);
                    }
                }
            }
        }
    }
    return 0;
}
```

INPUT

```
8
1 0 -1 0 -2 2 2 -1
0
```

OUTPUT

```
Compilation Error:
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c: In function 'main':
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:18:22: error: subscripted value is neither array nor pointer nor vector
18 |         if(a[i]+a[j]+a[k]+a[l] == target){
   |             ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:18:27: error: subscripted value is neither array nor pointer nor vector
18 |         if(a[i]+a[j]+a[k]+a[l] == target){
   |             ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:18:32: error: subscripted value is neither array nor pointer nor vector
18 |         if(a[i]+a[j]+a[k]+a[l] == target){
   |             ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:18:37: error: subscripted value is neither array nor pointer nor vector
18 |         if(a[i]+a[j]+a[k]+a[l] == target){
   |             ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:19:46: error: subscripted value is neither array nor pointer nor vector
19 |         printf("[%d,%d,%d,%d]",a[i],a[j],a[k],a[l]);
   |                                ^
```

SIMATS Engineering • Department of Computer Science and Engineering • CSA0209 — C Programming • 29-08-2026 • Category: CO4_AT1_LEVEL2 • Student Submissions Report

```
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:19:51: error: subscripted value is neither array nor pointer nor vector
19 |         printf("[%d,%d,%d,%d]", a[i], a[j], a[k], a[l]);
   |                                         ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:19:56: error: subscripted value is neither array nor pointer nor vector
19 |         printf("[%d,%d,%d,%d]", a[i], a[j], a[k], a[l]);
   |                                         ^
C:\Windows\TEMP\sandbox_192520019RD_6a7d8a67006120.30336786\main.c:19:61: error: subscripted value is neither array nor pointer nor vector
19 |         printf("[%d,%d,%d,%d]", a[i], a[j], a[k], a[l]);
   |                                         ^
```

L2-Q2. Reservation (M)

C

CODE

```
#include <stdio.h>
struct flight{
    char number[20];
    char from[20];
    char to[20];
    char date[20];
};
struct passenger{
    char name[20];
    struct flight;
};
int main()
{
    struct passenger p;
    int choice;
    while(1)
    {
        printf("\n1.book the flight\n");
        printf("2.manage reservation\n");
        printf("3.display flight information\n");
        printf("4.exit\n");
        printf("enter your choice:");
        scanf("%d",&choice);
        if(choice==1)
        {
            printf("enter passenger name:");
            scanf("%s",p.f.number);
            printf("enter the departure:");
            scanf("%[^\\n\\n]",p.f.from);
            printf("enter the desination:");
            scanf("%[^\\n\\n]",p.f.to);
            printf("enter the date:");
            scanf("%S",p.f.date);
            printf("flight booking successfull!\\n");
        }
    }
}
```

OUTPUT

Security Error: Disallowed code pattern detected.

[C](#)

CODE

```
#include <stdio.h>
int main()
{
    char a[50],b[50];
    int i,j;;
    char temp;
    scanf("%s",a);
    scanf("%s",b);

    if(strlen(a) != strlen(b))
    {
        printf("the strings are not anagrams");
        return 0;
    }
    for(i=0;a[i] !='\0';i++)
    {
        for(j=0;b[j] !='\0';j++)
        {
            if(a[i]==b[j] && used[j]==0){
                count[i]=1;
                found=0;
                break;
            }
        }
        if(found==0){
            printf("the string not anagram.");
            return 0;
        }
    }
    printf("the string are anagram.");
    return 0;
}
```

INPUT

```
listen
silent
```

OUTPUT

```
Security Error: Disallowed code pattern detected.
```

L2-Q4. boundary elements (M)**C****CODE**

```
#include <stdio.h>
int main()
{
    int arr[100][100],r,c,i,j,sum=0;
    scanf("%d",&r);
    scanf("%d",&c);
    for(i=0;i<r;i++)
    {
        for(j=0;j<c;j++)
        {
            scanf("%d",&arr[i][j]);
        }
    }
    for(i=0;i<r;i++)
    {
        for(j=0;j<c;j++)
        {
            if(i==0 || i==r-1 || j==0 || j==c-1)
            {
                sum=sum+arr[i][j];
            }
        }
    }
    printf("sum of boundary elements:%d",sum);
    return 0;
}
```

INPUT

```
4
4
1 2 3 4
5 6 7 8
9 10 11 12
13 14 15 16
```

OUTPUT

```
sum of boundary elements:102
```