



OnlineGDB

online compiler and debugger for c/c++

[code](#) [compile](#) [run](#) [debug](#) [share](#)

IDE

My Projects

Classroom new

Learn Programming

Programming Questions

Sign Up

Login

Google Cloud

Serverless or containers?
Get the best of both with
Cloud Run.

ADS VIA BUYSELLADS

[About](#) • [FAQ](#) • [Docs](#) • [Blog](#) • [Terms of Use](#) • [Contact Us](#)
• [GDB Tutorial](#) • [Credits](#) • [Privacy](#)
© 2016 - 2026 GDB Online

main.py

```
1
2 def largeGroupPositions(s):
3     res = []
4     i = 0
5
6     while i < len(s):
7         j = i
8         while j < len(s) and s[j] == s[i]:
9             j += 1
10
11         if j - i >= 3:
12             res.append([i, j - 1])
13
14         i = j
15
16     return res
17
18 s = input()
19 print(largeGroupPositions(s))
```

input

```
abbxxxxxy
[[3, 6]]
```

```
...Program finished with exit code 0
Press ENTER to exit console.
```



OnlineGDB

online compiler and debugger for c/c++

code. compile. run. debug. share.

IDE

My Projects

Classroom new

Learn Programming

Programming Questions

Sign Up

Login

BugHerd.

Deliver website design projects faster with BugHerd. Get 20% off your first 3 months.

ADS VIA BUYSSELLADS

About • FAQ • Docs • Blog • Terms of Use • Contact Us
• GDB Tutorial • Credits • Privacy
© 2016 - 2026 GDB Online.

Run

Debug

Stop

Share

Save

Beautify

Language Python 3

main.py

```
1
2 def gameOfLife(board):
3     m, n = len(board), len(board[0])
4     copy = [row[:] for row in board]
5
6     for i in range(m):
7         for j in range(n):
8             live = 0
9             for x in range(max(0, i-1), min(m, i+2)):
10                 for y in range(max(0, j-1), min(n, j+2)):
11                     live += copy[x][y]
12             live -= copy[i][j]
13
14             if copy[i][j] == 1:
15                 board[i][j] = 1 if live in (2, 3) else 0
16             else:
17                 board[i][j] = 1 if live == 3 else 0
18
19     return board
20
21 board = [[0,1,0],[0,0,1],[1,1,1],[0,0,0]]
22 print(gameOfLife(board))
```

close ad [x]

Advertisement

input

```
[[0, 0, 0], [1, 0, 1], [0, 1, 1], [0, 1, 0]]

...Program finished with exit code 0
Press ENTER to exit console.
```



OnlineGDB

online compiler and debugger for c/c++

code. compile. run. debug. share.

IDE

My Projects

Classroom new

Learn Programming

Programming Questions

Sign Up

Login

BugHerd.

Deliver website design projects faster with BugHerd. Get 20% off your first 3 months.

ADS VIA BUYSSELLADS

[About](#) • [FAQ](#) • [Docs](#) • [Blog](#) • [Terms of Use](#) • [Contact Us](#)

• [GDB Tutorial](#) • [Credits](#) • [Privacy](#)

© 2016 - 2026 GDB Online

Run Debug Stop Share Save Beautify

main.py

```
1
2 def champagneTower(poured, query_row, query_glass):
3     dp = [[0.0] * 101 for _ in range(101)]
4     dp[0][0] = poured
5
6     for i in range(100):
7         for j in range(i + 1):
8             if dp[i][j] > 1:
9                 excess = (dp[i][j] - 1) / 2
10                dp[i+1][j] += excess
11                dp[i+1][j+1] += excess
12
13     return min(1.0, dp[query_row][query_glass])
14
15 poured = int(input())
16 query_row = int(input())
17 query_glass = int(input())
18
19 print(champagneTower(poured, query_row, query_glass))
20
```

input

```
2
1
1
0.5
```

...Program finished with exit code 0
Press ENTER to exit console.