SIMATS ENGINEERING
ASSESSMENT TOOL 1

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA07

COURSE OUTCOME COVERED

CO2: Configure IP addressing schemes, subnetting, and basic routing techniques using simulation tool, for efficient network design and topology. *(BL3)*

Assessment Tool Weightage: 40%

QUESTIONS: 5 **Total Marks:50**

Annexure A

ANALYTICAL PROBLEM SOLVING

Code of Conduct:

I _____ (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.
I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

Annexure A

ANALYTICAL PROBLEM SOLVING

1. A university network is assigned the IP address block 192.168.20.0/24 for its internal communication. The network administrator has decided to divide this network into subnets for three different labs using fixed subnet masks. Lab A is assigned a /26 subnet, Lab B is assigned a /27 subnet, and Lab C is assigned a /28 subnet. Based on the given subnet masks, apply subnetting concepts to determine the network address of each lab. Further, identify the valid range of host IP addresses and the broadcast address for each subnet. Finally, calculate the total number of usable host IP addresses available in each lab's subnet.

2. A network administrator has configured two systems with the following details: System 1 has IP address 192.168.1.130 with subnet mask 255.255.255.192, and System 2 has IP address 192.168.1.190 with subnet mask 255.255.255.192. Using the given configuration, apply subnetting techniques to determine the subnet range, network address, and broadcast address for each system. Identify the valid host IP range for both subnets based on the given subnet mask. Calculate whether each IP address falls within its respective subnet range. Also, determine the number of usable host addresses available in each subnet.

3. An organization has been allocated the IP block **172.16.0.0/16** for its internal network. The network administrator has already decided the subnet masks for each department as follows: HR → /25, Sales → /26, IT → /27, and Admin → /28. Using the given subnet masks, apply subnetting techniques to assign suitable subnet addresses for each department. Determine the network address, valid host IP range, and broadcast address for each subnet. Based on the allocation, calculate the number of usable host addresses in each department.

Finally, identify the remaining unused IP address range within the given network block.

4. A company uses the IP address **172.16.10.0/24** and has implemented subnetting using a **/27 subnet mask** for its internal departments. Using the given subnet mask, apply subnetting techniques to calculate the total number of subnets created and the number of usable hosts per subnet. Determine the subnet to which the IP address **172.16.10.78** belongs. Identify the network address and broadcast address for that subnet. Also, determine whether the IP address **172.16.10.95** falls within the same subnet range based on the given configuration.

5. A network uses the Internet Protocol version 6 address **2001:0db8:0000:0000:0000:ff00:0042:8329**. Apply IPv6 addressing rules to compress the given address into its shortest form and then expand the compressed address back to its full notation. Using a prefix length of **/64**, determine the network prefix of the given address. Also, calculate the total number of possible host addresses available within this network based on the given prefix length.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Problem Understanding	20%	Clearly interprets problem, identifies all parameters and requirements accurately	Understands problem with minor gaps	Partial understanding; misses key elements	Misinterprets or unable to understand problem
Method Selection	20%	Selects most appropriate method/formula with strong justification	Selects correct method with minor errors	Inappropriate or partially correct method	Unable to select method
Solution Process	25%	Logical, systematic steps with correct approach throughout	Mostly correct steps with minor mistakes	Disorganized steps; multiple errors	No clear process
Accuracy of Calculation	20%	All calculations accurate; correct final answer	Minor calculation errors	Frequent errors; incorrect final answer	No valid calculations
Interpretation of Results	15%	Clearly interprets results with units and engineering relevance	Basic interpretation with minor omissions	Limited or unclear interpretation	No interpretation

1. Subnetting 192.168.20.0/24 for Three Labs

Given:

Network address = 192.168.20.0/24

LAB A = /26, Lab B = /27, Lab C = /28.

Formula 1: Number of IP addresses and usable hosts

Total IPs = $2^{32-prefix}$

usable hosts = $2^{32-prefix} - 2$

Lab A (/26):

Total IPs = $2^{32-26} = 2^6 = 64$

Usable hosts = 64 - 2 = 62

* Network address: 192.168.20.0
* Valid host range: 192.168.20.1 – 192.168.20.62
* Broadcast address: 192.168.20.63.

Lab B(/27): Total IPs = $2^{32-27} = 2^5 = 32$

Usable hosts = 32 - 2 = 30

* Network address = 192.168.20.64
* Valid host range: 192.168.20.65 - 192.168.20.94
* Broadcast address: 192.168.20.95

Lab C (/28): Total IPs = $2^{32-28} = 2^4 = 16$

Usable hosts = 16 - 2 = 14

* Network address = 192.168.20.96
* Valid host range: 192.168.20.97 – 192.168.20.110
* Broadcast address = 192.168.20.111

Remaining unused address: 256 – (64+32+16) = 144

Subnet Analysis of Two Systems Using /26

Given:

* System 1 : 192.168.1.130
* System 2 : 192.168.1.190
* ~~System~~ Subnet mask : 255.255.255.192 (/26)

Formula 1 : Block size

$$\text{Block size} = 256 - \text{mask octet}$$

$$= 256 - 192 = 64$$

The subnet ranges are : .0 - .63, .64 - .127, .128 - .191 and .192 - .255

Both IP addresses belong to .128 - .191 subnet

Formula 2 : Usable hosts

$$\text{Usable hosts} = 2^{32-26} = 2$$

$$= 2^6 - 2 = 64 - 2 = 62$$

System 1 :

* Network address : 192.168.1.128
* Valid host range : 192.168.1.129 — 192.168.1.190
* Broadcast address : 192.168.1.191
* Usable hosts : 62

System 2 :

* Network address : 192.168.1.128
* Valid host range 192.168.1.129 — 192.168.1.190
* Broadcast address : 192.168.1.191
* Usable hosts : 62

Subnet Allocation for HR, Sales, IT and Admin

Given:

192.16.0.0 /16

* HR = /25
* Sales = /26
* IT = /27
* Admin = /28

Formula 1: Usable hosts per department

$$\text{Usable hosts} = 2^{32-\text{prefix}} - 2$$

HR (/25):

$$2^{32-25} - 2 = 2^7 - 2 = 126$$

* Network address: 172.16.0.128
* Valid host range: 172.16.0.129 – 172.16.0.190
* Broadcast address: 172.16.0.191

IT (/27):

$$2^{32-27} - 2 = 2^5 - 2 = 30$$

* Network address: 172.16.0.192
* Valid host range: 172.16.0.193 – 172.16.0.222
* Broadcast address: 172.16.0.223

Admin (/28):

$$2^{32-28} - 2 = 2^4 - 2 = 14$$

* Network address = 172.16.0.224
* Valid host range = 172.16.0.255 – 172.16.0.238
* Broadcast address = 172.16.0.239

Formula 2: Remaining unused IP addresses

Total addresses = $2^{32-16} = 65,536$

Allocated = 128+64+32+16 = 240

Remaining = 65,536 – 240 = 65,296

Unused range: 172.16.0.240 – 172.16.255.255

4. Subnetting 172.16.10.0/24 using /27.

Given:

* Original network: 172.16.10.0/24
* New prefix: /27
* IP addresses to check: 172.16.10.78 and 172.16.10.95

Formula 1 : Number of subnets

Borrowed bits = 27 - 24 = 3

Number of subnets = $2^3 = 8$

Formula 2: Usable hosts per subnet

Host bits = 32 - 27 = 5

Usable hosts = $2^5 - 2 = 32 - 2 = 30$

Formula 3: Block size:

Block size = 256 - 224 = 32

Subnet ranges are .0 - .31, .32 - .63, .64 - .95, .96 - .127, .128 - .159, .160 - .191, .192 - .233, and .224 - .255

* IP address 172.16.10.78 belongs to third subnet.

* Network address : 172.16.10.64
* Valid host range = 172.16.10.65 — 172.16.10.94
* Broadcast address : 172.16.10.95
* Usable hosts : 30

Verification of 172.16.10.95:

Since .95 is last address of .64 - .95 subnet, it's a broadcast address.

Therefore, 172.16.10.95 belongs to same subnets' address range, but it is not valid host address.

5. IPV6 Address Compression and /64 Prefix:

Given IPV6 address:-

2001:0db8:0000:0000:0000:ff00:0042:8329

Formula/Rule 1: IPV6 compression

* Remove leading zeros from each group
* Replace one consecutive sequence of zero groups with ::

Compressed address:

2001:db8::ff00:42:8329

Formula/Rule 2: IPV6 expansion:

An IPV6 address contains 8 groups of 16 bits each.

Total bits = $8 \times 16 = 128$

Expanding :: to restore the missing zero groups gives:

2001:0db8:0000:0000:0000:ff00:0042:8329

Formula 3: Network prefix and host bits

Host bits = 128 − prefix length

= 128 − 64 = 64 bits

Network prefix: 2001:0db8:0000:0000::/64

Formula 4: Total possible addresses

Total addresses = $2^{\text{Host bits}} = 2^{64}$

= 18,446,744,073,709,551,616

IPV6/64 network contains 2^{64} possible outcomes.

Unlike IPV4, IPV6 does not reserve a conventional broadcast address.