SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)

Department of Computer Science and Engineering

CO1 ASSESSMENT TOOL 1 – Case Study Analysis

Course Code:	CSA10 / CSA1021	**Course Title:**	Software Engineering
CO Assessed:	CO1	**Assessment:**	Assessment Tool 1 – Case Study Analysis
Weightage:	20%	**Total Marks:**	25
CO1 Statement:	*Apply advanced methodologies and agile project management techniques to manage software projects effectively*		
Student Name:	R SARVESH	**Reg. No.:**	192521143
Date:	12/10/2026	**Duration:**	60 minutes

Code of Conduct

I R SARVESH / 192521143 (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the Student: R SARVESH

Annexure A – Case Study Analysis

Instructions to Students:

Each student will be allotted **one problem statement**. Analyze the assigned problem systematically by following the steps given below. Your report should demonstrate your understanding of software engineering concepts and your ability to design an appropriate software solution.

Based on your allotted problem statement, prepare a report by answering the following questions:

1. **Understand the Problem Statement**
   - Explain the problem in your own words.
   - Identify the objectives of the proposed system.
   - State the scope of the problem.
2. **Identify Key Stakeholders and Challenges**
   - Identify all the stakeholders involved in the system.
   - Explain the roles and responsibilities of each stakeholder.
   - Discuss the major challenges and issues faced by the stakeholders.
3. **Analyze the Current Approach**
   - Describe the existing system or current process.
   - Identify its strengths and limitations.
   - Analyze the problems or gaps that need to be addressed.
4. **Propose a Suitable Solution Using Software Engineering Principles**
   - Design a software-based solution for the given problem.
   - Describe the major functional modules of the proposed system.
   - Identify the functional and non-functional requirements.
   - Explain how software engineering principles such as modularity, scalability, maintainability, reliability, usability, and security are incorporated into your solution.

5. **Justify the Chosen Methodology/Framework**
    - Select an appropriate Software Development Life Cycle (SDLC) model or software development framework (e.g., Agile, Scrum, Waterfall, Spiral, DevOps).
    - Justify why the selected methodology/framework is suitable for the proposed system.
    - Explain how it supports successful project development and maintenance.
6. **Discuss Expected Outcomes and Limitations**
    - Describe the expected benefits of the proposed solution.
    - Explain how the solution addresses the identified challenges.
    - Discuss potential risks, implementation challenges, and limitations.
    - Suggest possible future enhancements.

Rubrics for Calculation

Criteria	Excellent (5 Marks)	Good (3 Marks)	Satisfactory (2 Marks)	Needs Improvement (1 Mark)
Problem Understanding (30%)	Clearly explains the problem, objectives, and scope with complete understanding.	Explains the problem with minor omissions.	Basic understanding with limited explanation.	Poor understanding; objectives and scope are unclear or missing.
Stakeholder & Challenge Analysis (25%)	Identifies all stakeholders, their roles, and challenges with clear analysis.	Identifies most stakeholders and challenges with adequate analysis.	Identifies only a few stakeholders or challenges.	Stakeholders and system analysis are incomplete or inaccurate.
Current System Analysis (20%)	Thoroughly analyzes the existing system, strengths, weaknesses, and identifies all gaps.	Good analysis with most strengths and weaknesses identified.	Limited analysis with partial identification of issues.	Proposed solution is unclear or inappropriate; requirements are largely missing.
Proposed Software Solution & Software Engineering Principles (15%)	Proposes an innovative, feasible solution applying appropriate software engineering principles (modularity, scalability, maintainability, security, etc.).	Suitable solution with good application of software engineering principles.	Basic solution with limited application of software engineering principles.	Methodology is inappropriate, poorly justified, or not discussed.
Methodology/ Framework Justification	Selects the most suitable SDLC/model/fram	Suitable methodology selected with	Methodology selected but justification is	Outcomes, limitations, or future enhancements

(10%)	ework and provides strong technical justification.	adequate justification.	weak.	are missing; report lacks organization and clarity.

Criteria	**Mark**
Problem Understanding (30%)	/5
Stakeholder & Challenge Analysis (25%)	/5
Current System Analysis (20%)	/5
Proposed Software Solution & Software Engineering Principles (15%)	/5
Methodology/ Framework Justification (10%)	/5
TOTAL	/25

1. Autonomous Drone-Carrier Mesh Network for Hyper-Local Medical Logistics

Industry Context

Modern municipal emergency response infrastructures are heavily bottlenecked by urban traffic congestion, grid design limits, and unpredictable weather anomalies. During critical medical crises—such as sudden cardiac arrests, acute anaphylaxis, or postpartum hemorrhages—the delivery time of life-saving medical supplies (e.g., Automated External Defibrillators (AEDs), EpiPens, rare blood types, or anti-venoms) determines patient survival. Traditional ambulance response times in dense metropolises often stretch beyond the critical 4-to-6-minute survival window.

While commercial drone delivery networks are emerging, individual drone units suffer from limited operational ranges, rapid battery depletion, and high vulnerability to sudden micro-climate shifts. Centralized cloud-based dispatch systems introduce single points of failure and high network latency penalties, which are unacceptable in life-or-death scenarios. There is an immediate structural demand for a decentralized, edge-computed logistics platform that treats automated delivery vehicles, municipal rooftops, and public transit nodes as a cohesive, self-healing transit mesh network.

Problem Statement

Design and develop a highly concurrent, fault-tolerant Autonomous Drone-Carrier Mesh Network that dynamically routes, schedules, and dispatches automated medical delivery drones across dynamic smart city topographies.

The platform must ingest high-velocity streaming telemetry—including real-time 3D drone coordinates, localized wind velocity vectors, active airspace geofences, battery health diagnostics, and regional cellular signal strengths—from hundreds of airborne units and municipal charging hubs concurrently.

Using decentralized routing engines, the platform must coordinate drone handovers between automated charging platforms mounted on moving public transit buses and static municipal smart buildings. The solution must run autonomous collision avoidance, handle sudden edge computing node dropouts, and guarantee zero-latency emergency rerouting without relying on continuous, active cloud infrastructure connectivity.

Objectives

The platform should:

1. **Ingest and Process Sub-Second Telemetry:** Capture high-frequency 3D spatial positions and hardware diagnostic data from hundreds of active airborne drone arrays without packet loss.

2. **Orchestrate Dynamic 4D Routing:** Compute optimal, collision-free 4D flight corridors (latitude, longitude, altitude, time) that adapt dynamically to shifting wind patterns and temporary no-fly zones.

3. **Manage Moving Node Handovers:** Coordinate micro-second landing and deployment schedules onto mobile public transit carrier platforms using localized edge mesh communication loops.

4. **Enforce Edge Autonomy & Self-Healing:** Implement decentralized routing protocols that allow the local swarm to self-heal and re-allocate tasks autonomously if the central cloud goes offline.

5. **Ensure Mission-Critical Prioritization:** Design a strict traffic prioritization engine that automatically clears airspace and throttles commercial data streams when a high-priority medical alert is triggered.

6. **Generate Cryptographic Provenance Audits:** Maintain unalterable, cryptographically signed operational logs to satisfy civil aviation authorities and medical privacy compliance boards.

Expected Outcomes

The proposed platform will:

1. **Minimize Life-Saving Delivery Windows:** Reduce the average municipal transit window for critical medical payloads to under 4 minutes.

2. **Extend Fleet Operational Reach:** Increase effective drone flight ranges by up to 300% through optimized, multi-stage mobile carrier handovers.

3. **Guarantee High System Availability:** Achieve 99.999% network uptime for emergency dispatch tracking via fully decentralized edge computing worker networks.

4. **Lower Operational Asset Losses:** Eliminate mid-air drone collisions and forced emergency landings via highly responsive, predictive collision avoidance networks.

5. **Provide Regulatory Transparency:** Enable seamless compliance tracking for aviation authorities through instantly generated, immutable flight performance audit trails.

1. Understanding the Problem Statement

1.1 Problem Definition

Urban emergency medical logistics requires the rapid transportation of essential medical supplies, including Automated External Defibrillators (AEDs), epinephrine auto-injectors, blood products, and anti-venoms. In densely populated cities, road congestion, distance, and unpredictable traffic conditions can delay delivery during time-sensitive medical emergencies.

Traditional road-based delivery systems depend on accessible roads and available transport resources. Drone delivery provides an alternative for selected medical supplies, but a single drone has a limited flight range and battery capacity. Its performance may also be affected by wind, communication failures, temporary no-fly zones, and the availability of safe landing and charging facilities.

A further challenge arises when several drones must operate simultaneously. The system must prevent conflicting flight routes, allocate available drones efficiently, monitor battery health, coordinate charging, and respond to emergency requests with different priorities.

A centralized dispatch system may provide a unified view of the fleet, but continuous dependence on a central cloud creates a potential point of failure. If the central service or network connection becomes unavailable, local devices may lose access to current mission information or coordinated dispatch decisions.

The proposed Autonomous Drone-Carrier Mesh Network addresses these limitations by treating drones, stationary charging hubs, mobile public transport carriers, and local computing nodes as interconnected participants in a distributed logistics network.

The software platform will collect and process real-time telemetry, identify suitable resources, calculate feasible routes, coordinate carrier handovers, prioritize emergency missions, detect infrastructure failures, and maintain cryptographically verifiable operational records.

The main purpose is to create a fault-tolerant and responsive medical logistics coordination system that can continue performing defined safe operations even when central cloud connectivity is interrupted.

1.2 Objectives of the Proposed System

Objective 1: High-frequency telemetry ingestion

The system must receive and process continuous telemetry from hundreds of drones and infrastructure nodes.

Telemetry includes:

- Three-dimensional geographical position and altitude.
- Drone movement and operational status.
- Battery level and battery health.
- Local wind velocity and environmental conditions.
- Cellular signal strength and communication quality.
- Active airspace restrictions and geofence information.

- Charging hub and mobile carrier availability.

The objective is to maintain an accurate operational view of the fleet while detecting invalid, duplicated, delayed, or outdated information.

Objective 2: Dynamic four-dimensional routing

The system must calculate feasible flight routes using latitude, longitude, altitude, and time.

Route planning must consider weather conditions, battery reserve, payload capacity, airspace restrictions, other drone trajectories, and the availability of intermediate charging or transfer locations.

When environmental conditions change or a route becomes unavailable, the system should calculate an alternative route where safe and permitted.

Objective 3: Moving-node handover coordination

The system must coordinate drone handovers between stationary municipal charging hubs and mobile carrier platforms installed on public transport vehicles.

This requires the software to evaluate carrier location, predicted arrival time, platform readiness, drone battery condition, and the timing of the transfer.

If a carrier becomes unavailable or the handover cannot be completed safely, the system must use an approved alternative or initiate the defined safe fallback procedure.

Objective 4: Edge autonomy and self-healing

The system must continue performing designated local coordination functions when central cloud connectivity is interrupted.

Local edge nodes should be able to monitor nearby drones, use valid cached operational information, detect unavailable nodes, and reassign eligible tasks according to predefined rules.

Recovery mechanisms must reconcile operational events after connectivity is restored and prevent conflicting mission assignments.

Objective 5: Mission-critical prioritization

The system must distinguish emergency medical missions from lower-priority commercial or routine activities.

When a verified high-priority medical request is received, the scheduler should prioritize suitable resources and adjust eligible lower-priority tasks.

However, emergency prioritization must never override mandatory airspace restrictions, aircraft operating limits, collision-avoidance requirements, or other safety constraints.

Objective 6: Cryptographic provenance and auditability

The system must maintain reliable records of mission requests, resource assignments, route changes, handovers, operator overrides, and delivery confirmation.

Cryptographic signatures and tamper-evident record structures should allow authorized auditors to verify the integrity and origin of recorded events.

Access controls must protect sensitive medical information and prevent unauthorized modification or disclosure of operational records.

1.3 Scope of the Proposed System

The scope defines the functions and responsibilities included in the proposed software solution.

In-scope functions

1. Medical delivery request registration and validation.
2. Emergency priority classification and dispatch.
3. Real-time drone and infrastructure telemetry processing.
4. Fleet status and battery-health monitoring.
5. Dynamic route planning and geofence validation.
6. Drone-to-carrier and carrier-to-hub handover coordination.
7. Local edge processing and fault recovery.
8. Emergency mission prioritization and resource allocation.
9. Operational dashboards, alerts, and mission tracking.
10. Secure device authentication and communication.
11. Cryptographically verifiable audit records.
12. Simulation, performance testing, and operational monitoring.

Out-of-scope functions

1. Manufacturing or physically designing drones and transit carrier platforms.
2. Replacing certified drone flight controllers or their independent safety mechanisms.
3. Making medical diagnoses or independently deciding which treatment a patient requires.
4. Claiming aviation approval or clinical effectiveness without appropriate validation.
5. Guaranteeing absolute zero latency, zero collisions, or zero packet loss.
6. Guaranteeing the stated performance targets before testing and evaluation.

1.4 Assumptions and Constraints

The proposed design assumes that each drone, carrier, and charging hub has an authenticated identity and a defined communication interface.

Reliable operation also depends on receiving sufficiently current weather information, geofence data, location measurements, battery diagnostics, and carrier availability information.

The system must operate under practical constraints, including:

- Limited battery energy and payload capacity.
- Variable wireless connectivity and communication latency.
- Weather-related restrictions.
- Physical limitations of landing and charging platforms.
- Changing public transport schedules and routes.
- Applicable aviation regulations and permissions.
- Medical payload handling and custody requirements.
- Privacy, security, and data-retention obligations.

These constraints mean that the system must optimize delivery efficiency only within the permitted safety and operational boundaries.

2. Identify Key Stakeholders and Challenges

2.1 Stakeholder Identification

Stakeholders are individuals, organizations, or groups that influence the system, use its services, maintain its infrastructure, or are affected by its operation.

Stakeholder	Roles and responsibilities	Major challenges
Patients and caregivers	Request or receive emergency medical supplies and provide necessary delivery information.	Delivery delays, inaccurate locations, accessibility, and privacy concerns.
Emergency medical dispatchers	Validate requests, assign priorities, monitor missions, and coordinate emergency responses.	Time pressure, incomplete information, resource shortages, and alert overload.
Hospitals and medical facilities	Prepare, package, release, and verify medical payloads.	Inventory availability, safe packaging, temperature control, and custody tracking.
Drone fleet operators	Maintain drones, batteries, payload systems, and flight readiness.	Battery degradation, hardware failure, weather, and maintenance requirements.

Public transport operators	Provide moving carrier platforms and publish location, timing, and availability information.	Schedule changes, passenger safety, platform readiness, and missed handovers.
Municipal building and charging hub operators	Maintain charging stations, edge-computing infrastructure, and physical facilities.	Power outages, network failures, charging capacity, and physical security.
Aviation authorities	Define flight permissions, airspace restrictions, safety requirements, and reporting obligations.	Safety assurance, traceability, current geofence data, and incident investigation.
Software development team	Design, implement, test, deploy, and maintain the platform.	Distributed-system complexity, integration difficulties, and reliability testing.
Cybersecurity and privacy officers	Protect systems and data, define access controls, and coordinate security incidents.	Spoofed telemetry, device compromise, data leakage, and key management.
Telecommunications providers	Provide cellular and network connectivity.	Coverage gaps, congestion, variable latency, and connection loss.
Medical and privacy oversight bodies	Review medical handling and personal-data processing where applicable.	Compliance evidence, privacy protection, retention policies, and auditability.
General public and nearby airspace users	Share the urban environment affected by drone operations.	Public safety, noise, privacy, and potential flight incidents.

2.2 Major Challenges Faced by Stakeholders

Emergency dispatchers

Dispatchers must identify the urgency of each request and determine which drone or delivery resource can fulfil it within the required time.

A large number of simultaneous requests can increase decision-making complexity. The proposed system addresses this through automated request validation, documented priority rules, resource availability checks, and clear operator alerts.

Drone fleet operators

Fleet operators must ensure that each drone has sufficient battery capacity, appropriate payload capability, and acceptable hardware health before assignment.

The system will monitor operational telemetry and exclude resources that do not satisfy the configured mission requirements.

Medical facilities

Medical facilities must ensure that supplies are available, correctly packaged, and transferred to authorized recipients.

The proposed system will support delivery confirmation and custody records, but clinical suitability, preparation, and handling procedures must remain under the responsibility of authorized medical personnel.

Transit and hub operators

Mobile carriers introduce scheduling uncertainty because their locations and arrival times can change. Stationary hubs may also become unavailable because of maintenance, power failures, or network interruptions.

The system will monitor carrier and hub status and support alternative handover planning when a location becomes unavailable.

Software and cybersecurity teams

Distributed coordination creates technical challenges involving inconsistent state, concurrent task assignments, stale telemetry, network partitions, and compromised devices.

The system therefore requires authenticated communications, versioned message formats, fault detection, safe recovery procedures, automated testing, and detailed operational logs.

2.3 Stakeholder Conflicts and Resolution

Conflicting priorities	**Proposed resolution**
Delivery speed versus flight safety	Optimise speed only among routes that satisfy mandatory safety constraints.
Medical missions versus commercial traffic	Apply an explicit and auditable priority policy without bypassing safety rules.
Detailed tracking versus patient privacy	Minimise patient-identifying data and separate medical identity from general telemetry where possible.
High fleet utilisation versus maintenance	Give battery, maintenance, and aircraft operating limits precedence over utilisation.
Central control versus edge	Define the functions that local nodes may perform independently and the

autonomy	conditions requiring a safe hold or escalation.
Rapid releases versus system reliability	Use incremental development with automated testing and mandatory safety, security, and release reviews.

3. Analyze the Current Approach

3.1 Existing System and Current Process

The conventional medical logistics process begins when a patient, caregiver, or medical facility requests an emergency medical supply. The request is received by an emergency dispatch centre or a healthcare organization, where the urgency and availability of resources are assessed.


An ambulance, courier, or other suitable transport resource is then assigned. The resource travels to the destination using available transport infrastructure. Delivery completion is recorded through the relevant operational process.

Although this approach benefits from established procedures and human oversight, road transportation can be delayed by congestion, distance, road closures, and limited accessibility.

Drone-based delivery can avoid some road-related delays, but individual drones have limited battery capacity and range. They may also be unable to complete a mission because of weather conditions, restricted airspace, communication failure, or unavailable charging infrastructure.

A centralized drone dispatch system can simplify fleet management, but dependence on a central service creates a potential single point of failure unless local autonomy and recovery mechanisms are provided.

Existing process flow diagram



3.2 Comparison of Existing and Proposed Approaches

Aspect	Conventional road logistics	Individual drone delivery	Proposed drone-carrier mesh
Transportation	Roads and ground vehicles	Direct flight along an approved route	Flight routes coordinated with fixed and moving infrastructure
Traffic dependency	High in congested areas	Lower dependence on road traffic	Lower dependence on road traffic for eligible missions
Operational range	Depends on road network and vehicle availability	Limited by battery, payload, and operating conditions	Potentially extended through coordinated charging and handovers
Fleet coordination	Dispatch-based	May use centralized fleet management	Distributed coordination with local edge processing
Network dependency	Depends on dispatch and communication systems	Depends on aircraft and dispatch communication	Designed for bounded local operation during central disconnection
Dynamic routing	Road routes and traffic information	Flight routes and airspace restrictions	Four-dimensional routing with environmental and resource constraints
Emergency prioritization	Human and organizational dispatch rules	Depends on the implemented dispatch system	Explicit, auditable priority policy
Failure handling	Alternative vehicles and manual procedures	Return, land, or abort according to aircraft capabilities	Edge failure detection, task reassignment, and predefined safe fallback
Auditability	Existing operational records	Depends on implementation	Cryptographically verifiable mission events
Complexity	Established operational processes	Moderate to high	High because of distributed coordination and mobile handovers

3.3 Strengths of the Existing Approach

Conventional emergency logistics has several important strengths.

- Established emergency-response procedures and trained personnel.
- Ability to transport patients and supplies that drones cannot carry.
- Existing road infrastructure and vehicle maintenance systems.
- Human judgement for unusual or uncertain situations.
- Established methods for medical custody and delivery confirmation.

Drone delivery also offers benefits for eligible lightweight payloads because aircraft can bypass some road congestion and reach locations that may be difficult to access by ground vehicles.

3.4 Limitations of the Existing Approach

The main limitations are:

1. Travel-time variability: Road congestion, distance, and road accessibility may delay medical deliveries.
2. Limited drone range: Individual drones have finite battery energy and payload capacity.

3. Environmental uncertainty: Wind and weather changes may make planned routes unsuitable.
4. Centralized coordination dependency: Loss of the central service or network connection can reduce coordination capability.
5. Limited multi-stage coordination: Without specialized scheduling, drones may not efficiently coordinate with mobile charging or carrier platforms.
6. Resource allocation difficulties: Simultaneous emergency requests may compete for drones, charging hubs, and flight corridors.
7. Operational traceability: Separate systems may make it difficult to reconstruct the full sequence of assignments, route changes, handovers, and delivery events.

3.5 Identified Gaps

The proposed system is intended to address the following gaps:

- Lack of integrated fleet-wide and local operational information.
- Insufficient coordination of drones, moving carriers, and fixed charging stations.
- Dependence on continuous central connectivity.
- Need for consistent emergency mission prioritization.
- Need for reliable detection and recovery from edge-node failures.
- Need for tamper-evident operational records and secure data handling.
- Need for systematic simulation and verification before real-world deployment.

4. Propose a Suitable Solution Using Software Engineering Principles

4.1 Proposed System Overview

The proposed solution is a distributed software platform that coordinates medical delivery missions across drones, municipal hubs, mobile public transport carriers, and local edge-computing nodes.

The platform contains two complementary coordination layers.

Central operations layer: Responsible for fleet-wide monitoring, authorized mission management, policy distribution, long-term analytics, configuration, and consolidated audit management.


Local edge layer: Responsible for bounded local coordination, nearby drone monitoring, local resource availability, permitted task reassignment, and defined fallback operations when central connectivity is lost.

Drones transmit authenticated telemetry to the coordination network. The system processes this information to determine whether a drone is eligible for a mission. The route planner then evaluates feasible routes based on battery condition, weather, geofences, payload limits, and other known constraints.

The scheduler assigns resources and reserves the necessary route and handover windows. During the mission, telemetry is monitored continuously. If conditions change, the system requests a revised plan or initiates an approved fallback procedure.

When a mission is completed, the system records the final status and generates verifiable operational records.

4.2 Proposed System Architecture



The architecture separates request processing, route planning, task scheduling, telemetry, and audit management into distinct components. This reduces unnecessary coupling and allows individual components to be developed and tested independently.

The local edge mesh complements central coordination rather than replacing all central services. Some functions, such as global analytics and consolidated reporting, may require connectivity. Local nodes must therefore have clearly defined operating permissions and safe behavior when information is incomplete.


4.3 Major Functional Modules

Module	Description	Main output
Emergency request management	Accepts medical delivery requests and validates required information.	Validated mission request
Identity and access management	Authenticates users, drones, hubs, carriers, and software services.	Verified identity and access decision

Telemetry ingestion	Processes location, battery, health, weather, and connectivity information.	Normalized operational state
Fleet and asset management	Maintains drone capability, battery status, payload capacity, maintenance restrictions, and availability.	Eligible resource list
Geofence and environment management	Maintains authorized airspace boundaries, weather information, and restriction validity.	Current environmental constraints
Four-dimensional route planner	Generates route candidates across latitude, longitude, altitude, and time.	Candidate routes and constraint checks
Mission scheduler	Assigns resources, reserves route windows, and coordinates task ownership.	Mission plan and assignment
Emergency prioritization engine	Applies approved rules to distinguish critical medical missions from lower-priority work.	Priority decision and justification
Collision-risk monitoring	Detects potential conflicts and requests safe re-planning through approved interfaces.	Conflict alert and response recommendation
Carrier handover coordinator	Checks platform readiness, arrival windows, and custody acknowledgements.	Handover status
Edge autonomy and recovery	Detects failures and coordinates permitted local operations and recovery.	Degraded-mode state and recovery events
Audit and provenance service	Creates signed, tamper-evident records of mission events.	Verifiable audit trail
Operator dashboard	Displays missions, fleet status, alerts, and degraded operating conditions.	Operational view and alerts
Monitoring and simulation	Measures performance, failure recovery, route feasibility, and handover outcomes.	Test reports and operational metrics

4.4 Detailed Operational Flow

The proposed operational workflow is as follows.



Step 1: Receive and validate the request

The request interface receives the destination, medical supply category, required delivery timing, and other authorized information.

Invalid or incomplete requests are rejected or referred to an authorized dispatcher.

Step 2: Determine priority

The prioritization engine applies a documented policy to classify the mission. The system records the reason for the priority assignment so that it can be reviewed later.

Step 3: Evaluate resources

The fleet management module identifies drones that meet the mission's requirements, including battery reserve, payload capacity, maintenance status, and location.

Step 4: Generate route candidates

The route planner evaluates possible routes using available environmental information, time constraints, airspace restrictions, and resource availability.

Step 5: Validate and reserve the plan

The scheduler checks resource conflicts, carrier availability, and route reservations. A plan that fails mandatory safety checks cannot be dispatched.

Step 6: Dispatch and monitor

The approved mission is sent through the authorized interfaces. The system tracks progress and detects deviations, stale telemetry, or changing environmental conditions.

Step 7: Coordinate handovers

If the mission uses an intermediate carrier or charging hub, the handover coordinator checks readiness and required acknowledgements.

Step 8: Confirm delivery and record events

The system records the completion status, custody transition, and relevant operational events. The audit service generates the corresponding signed records.

4.5 Edge Failure and Recovery Process

A major requirement is that the system must not rely on continuous cloud connectivity for every local decision.

When an edge node becomes unavailable, nearby nodes should detect the failure through health checks or missed heartbeats. They should then evaluate which tasks can safely continue using valid local information.

Tasks that remain within approved local operating conditions may continue. If safety cannot be confirmed, the system must enter the appropriate hold, abort, return, or escalation procedure.

4.6 Functional Requirements

Functional requirements describe what the system must do.

ID	Functional requirement
FR-01	The system shall accept emergency delivery requests after validating required information and requester authority.
FR-02	The system shall assign mission priority using an approved, documented policy.
FR-03	The system shall ingest authenticated telemetry from multiple drones and infrastructure nodes concurrently.
FR-04	The system shall detect or reject malformed, duplicated, replayed, and stale telemetry.
FR-05	The route planner shall consider airspace restrictions, weather, battery reserve, payload capability, timing, and route conflicts.
FR-06	The scheduler shall prevent conflicting resource assignments and manage route reservations.
FR-07	The handover coordinator shall verify carrier readiness and required acknowledgements before recording a successful handover.
FR-08	The system shall detect edge-node failures and enter a defined degraded operating mode.
FR-09	The system shall apply an approved safe fallback when route safety cannot be established.

FR-10	The system shall prioritize eligible emergency missions without bypassing mandatory safety constraints.
FR-11	The system shall create signed records for dispatch, assignment, route changes, handovers, overrides, and delivery completion.
FR-12	The dashboard shall provide role-appropriate mission status, fleet health, and alerts.
FR-13	The system shall reconcile local operational events after connectivity is restored.
FR-14	The system shall support repeatable simulations and export performance-test results.

4.7 Non-Functional Requirements

Non-functional requirements describe the quality attributes and operational conditions under which the system must function.

Attribute	Requirement	Verification approach
Performance	Telemetry processing and dispatch decisions must meet defined latency budgets under a specified workload.	Measure throughput and P50, P95, and P99 latency.
Availability	Redundant services and tested local fallback must reduce service interruption.	Availability measurement, failure injection, and recovery tests.
Reliability	The system must detect failures and enter a defined safe state when necessary.	Scenario-based testing and fault injection.
Scalability	The architecture must support increasing numbers of drones and telemetry events.	Load, stress, and soak testing.
Security	Communication, device identity, access, and software updates must be protected against unauthorized actions.	Security testing, access-control tests, and key-revocation exercises.
Privacy	Medical data collection and access must be limited to legitimate operational needs.	Privacy impact assessment and access-log review.
Maintainability	Components must have documented interfaces, automated tests, and controlled releases.	Code review, defect analysis, and maintenance exercises.
Usability	Operators must be able to understand mission state, alerts, and degraded-mode conditions.	Usability tests with representative users.
Interoperability	Services and devices must exchange data using documented, versioned interfaces.	API contract and integration tests.
Auditability	Mission events must be verifiable and unauthorized changes detectable.	Signature verification and tamper-detection tests.

4.8 Application of Software Engineering Principles

Modularity

The system is divided into independent modules for telemetry, fleet management, route planning, scheduling, handovers, security, audit, and user interfaces.

This enables each module to be developed, tested, and updated without unnecessarily changing the entire platform.

Scalability

The system can use regional or local processing, asynchronous event handling, and bounded message queues to manage increasing telemetry volume.

Scaling decisions must be based on measured performance rather than assumptions about the number of devices the system can support.

Maintainability

Documented interfaces, automated testing, version-controlled changes, code reviews, configuration management, and operational runbooks help developers identify defects and introduce updates safely.

Reliability

Redundancy, health monitoring, controlled retries, durable event records, timeouts, and tested recovery procedures reduce the impact of component failures.

Usability

The operator interface should present mission status, emergency priority, battery condition, handover state, route changes, and connectivity warnings clearly.

Alerts should communicate both the issue and the action required. The interface must not hide uncertainty or imply that a mission is safe when the underlying information is incomplete.

Security

The system should use authenticated devices, least-privilege access, encryption, signed messages, secure key management, and controlled software updates.

Security mechanisms must protect against spoofed telemetry, compromised nodes, unauthorized dispatch, and exposure of sensitive medical information.

Separation of concerns

Medical request processing, route optimization, flight-control interfaces, audit storage, and user interface logic should have clearly defined responsibilities. This reduces complexity and makes the system easier to test and maintain.

Testability

A simulation environment should support repeatable tests for weather changes, battery decline, concurrent emergencies, network partitions, carrier failures, and invalid telemetry before the system is used in live operations.

5. The Chosen Methodology or Framework

5.1 Selected Methodology: Agile with XP and Lean/Kanban Practices

The recommended approach is an iterative Agile development model supported by Extreme Programming (XP), Lean/Kanban practices, and formal safety and security review gates.

This approach is appropriate because the proposed system combines several complex and interdependent components. Requirements may change after testing telemetry ingestion, dynamic routing, mobile handovers, and edge recovery.

Developing the entire system as one large release would delay feedback and make it harder to identify architectural defects. An iterative approach allows each major capability to be developed, evaluated, and improved before the next level of complexity is introduced.

The methodology combines three complementary practices.

Agile development

Agile development supports iterative and incremental delivery, collaboration with stakeholders, and responsiveness to changing requirements.

For this system, Agile allows the team to develop a basic telemetry service first, followed by mission management, routing, handovers, and fault recovery.

Extreme Programming

XP emphasizes technical practices such as test-driven development, pair programming, short iterations, continuous testing, and close stakeholder collaboration.

These practices are particularly useful for the system's critical functions. For example, the team can write tests for conflicting resource assignments, stale telemetry, invalid routes, and network failure before implementing the corresponding logic.

Lean Development and Kanban

Lean Development focuses on reducing waste, delivering customer value, and continuously improving the development process. Kanban helps visualise work, limit work in progress, and identify bottlenecks.

The development team can use a Kanban board to track tasks such as telemetry integration, routing tests, security review, simulation, and documentation. Limiting work in progress reduces the risk of starting too many features before existing components are properly integrated and tested.


5.4 Application of Agile Project Management

The lecture notes identify Scrum roles, sprint planning, backlog prioritization, retrospectives, and cross-functional team management as important Agile project management concepts.

These can be applied to the proposed project as follows.

Agile practice or role	**Application**
Product Owner	Represents stakeholder needs, prioritizes medical logistics features, and clarifies acceptance criteria.
Scrum Master or iteration facilitator	Helps the team follow the development process, resolve workflow impediments, and conduct improvement meetings.
Cross-functional development team	Includes software developers, testers, system designers, security specialists, and domain experts as available.
Product backlog	Contains functional requirements, safety requirements, security tasks, technical improvements, and documentation.
Sprint planning	Selects a manageable set of features and defines measurable acceptance criteria.
Daily coordination	Reviews progress, dependencies, blockers, failed tests, and emerging risks.
Sprint review	Demonstrates working features to relevant stakeholders using simulations or controlled test environments.
Retrospective	Identifies process weaknesses and defines improvements for subsequent iterations.
Backlog prioritization	Gives early attention to foundational, high-risk capabilities such as device identity, telemetry validation, and safe failure handling.

5.5 Proposed SDLC Process



5.6 Proposed Incremental Development Plan

Increment	Development activities	Expected deliverables
Increment 0: Discovery	Stakeholder research, requirements, feasibility, initial risk assessment, and architecture.	Scope definition, stakeholder analysis, risk register, and initial design.
Increment 1: Telemetry foundation	Device identity, telemetry schemas, ingestion services, and simulated drone data.	Working telemetry pipeline and performance baseline.
Increment 2: Mission management	Request validation, mission states, resource registry, and priority rules.	Working request-to-assignment workflow.
Increment 3:	Route generation, battery constraints, geofence	Simulated route-planning

Routing	checks, and route conflict detection.	capability with test evidence.
Increment 4: Carrier handovers	Fixed hub and moving carrier availability, scheduling, and handover acknowledgements.	Handover workflow and failure-handling tests.
Increment 5: Edge resilience	Failure detection, local coordination, task ownership, and reconnection recovery.	Demonstrable degraded-mode and recovery behavior.
Increment 6: Security and audit	Signed records, key management, privacy controls, monitoring, and security testing.	Verifiable audit records and security test results.
Increment 7: Controlled pilot	Restricted operational testing, operator training, incident procedures, and performance evaluation.	Pilot evidence and a documented go/no-go decision.

5.7 Support for Maintenance and Long-Term Development

The selected methodology supports maintenance because development and testing continue after the initial release.

New weather sources, drone hardware, charging facilities, and regulatory requirements may require changes to the software. An iterative process allows these changes to be introduced in controlled increments.

Automated regression tests help ensure that new features do not break existing functionality. Versioned interfaces allow hardware integrations to evolve without forcing every module to change simultaneously.

Formal release gates remain necessary. Agile delivery does not remove the need for safety assessment, security review, operational approval, and rollback planning.

6. Feasibility Analysis

Feasibility analysis determines whether a proposed software system is technically achievable, operationally appropriate, and financially viable.

The supplied lecture notes identify three core dimensions: technical feasibility, operational feasibility, and financial feasibility.

6.1 Technical Feasibility

Technical feasibility evaluates whether the required hardware, software, network architecture, and technical expertise are available to develop the system.

Technical component	**Feasibility assessment**	**Requirements and concerns**
Telemetry processing	Technically plausible using concurrent, event-driven processing.	Must be benchmarked against the intended device count, message frequency, and

		network conditions.
Distributed communication	Possible with authenticated messaging and local networking.	Network partitions, message duplication, delay, and conflicting state must be handled.
Dynamic routing	Feasible as a constrained planning problem.	Requires reliable maps, current geofences, energy models, environmental data, and independent safety checks.
Moving carrier coordination	Possible where carriers expose reliable position, timing, and readiness information.	Landing tolerances, vehicle motion, physical platform safety, and missed handovers require validation.
Edge autonomy	Feasible for clearly bounded local functions.	Local nodes need valid cached policies, defined permissions, and safe degraded-mode behavior.
Cryptographic audit	Standard cryptographic mechanisms can make unauthorized record modification detectable.	Secure key storage, rotation, revocation, event ordering, and trusted timestamps must be addressed.
Collision-risk monitoring	Software can contribute to detecting and reducing collision risk.	Absolute collision elimination cannot be established through software testing alone.
Integration	Achievable if participating systems provide documented interfaces.	Hardware compatibility, device protocols, and external system access may create integration work.

Technical feasibility conclusion: The proposed software architecture is technically plausible, but real-world deployment depends on hardware integration, reliable environmental data, safety validation, and approved operational procedures.

6.2 Operational Feasibility

Operational feasibility evaluates whether the system can fit into existing workflows and be used effectively by its intended users.

The proposed platform must integrate with medical facilities, emergency dispatchers, fleet operators, transit operators, and municipal infrastructure teams.

Important operational requirements include:

- Training dispatchers to use mission management and alerting features.
- Defining responsibilities for approving requests, assigning missions, and handling exceptions.
- Establishing procedures for medical payload preparation, custody, and delivery confirmation.
- Training operators to respond to connectivity loss, route changes, and failed handovers.

- Establishing drone maintenance, battery replacement, charging, and hardware inspection procedures.
- Defining manual escalation and alternative delivery arrangements when drone operations are unsafe or unavailable.
- Providing monitoring, support, incident reporting, and software maintenance after deployment.

Operational feasibility conclusion: The system can be operationally suitable if it complements existing emergency procedures, clearly defines human responsibilities, and provides appropriate fallback arrangements.

6.3 Financial Feasibility

Financial feasibility determines whether the benefits of the proposed system justify its development and operating costs.

A reliable numerical assessment cannot be made until actual fleet size, hardware costs, staffing, infrastructure requirements, insurance, maintenance, and operational demand are known.

Estimated cost categories

Cost category	**Components to be considered**
Initial capital expenditure	Drones, payload containers, charging hubs, mobile carrier modifications, edge-computing hardware, and networking equipment.
Software development	System design, implementation, testing, simulation, security engineering, integrations, and documentation.
Operating expenditure	Staff salaries, electricity, network services, monitoring, hosting, maintenance, and battery replacement.
Safety and compliance	Training, independent reviews, operational approvals, insurance, and required safety assessments.
Maintenance	Hardware inspection, software updates, replacement components, incident response, and technical support.

Potential financial benefits

- Reduced transport time for suitable medical deliveries.
- Improved utilisation of available drones and charging infrastructure.
- Reduced dependence on road transportation for selected missions.
- Better operational visibility and resource allocation.
- Reduced manual coordination effort where automation is effective.
- More efficient generation and retrieval of audit records.

Financial evaluation metrics:

Total Cost of Ownership (TCO): The combined cost of acquiring, developing, operating, maintaining, and eventually retiring the system.

Return on Investment (ROI): A measure comparing net benefits with investment cost.

ROI = [[(Total Benefits)-(Total Costs)]/Total Costs] *100%

Payback period: The time required for cumulative net benefits to recover the initial investment.

These metrics should be calculated using measured pilot data, realistic assumptions, and clearly defined cost categories.

6.4 Overall Feasibility Assessment

Feasibility dimension	**Assessment**	**Main condition for success**
Technical	Plausible, with significant integration and safety challenges.	Validated routing, secure communication, reliable hardware interfaces, and fault testing.
Operational	Potentially suitable for selected emergency medical logistics workflows.	Staff training, clear responsibilities, approved procedures, and fallback arrangements.
Financial	Undetermined without cost and demand data.	Pilot measurements, cost-benefit analysis, and a credible long-term operating model.

The project should proceed incrementally, beginning with feasibility validation and simulation rather than immediately assuming that the full operational system can be deployed.

7. Product Management and Design Thinking

7.1 Product Management

Product management connects business objectives, technical development, and user experience.

For this project, product management involves identifying the needs of emergency dispatchers, medical facilities, drone operators, transit operators, and other stakeholders. These needs must be translated into prioritized requirements and measurable product outcomes.

The product should be evaluated not merely by the number of implemented features but by its ability to support reliable, safe, and timely medical logistics.

Product management responsibilities include:

- Defining the product vision and scope.
- Prioritizing stakeholder requirements.
- Maintaining the product backlog.
- Establishing measurable success criteria.
- Coordinating development and testing.
- Collecting feedback from representative users.
- Evaluating operational performance after deployment.

7.2 Design Thinking

The supplied lecture notes describe Design Thinking as a non-linear, iterative, user-centered process consisting of five phases: Empathize, Define, Ideate, Prototype, and Test.

Phase	Application to the proposed system	Expected output
Empathize	Study the workflows and difficulties of dispatchers, medical personnel, drone operators, and transit staff.	Stakeholder needs, pain points, and workflow observations.
Define	Convert observations into clear problem statements and measurable objectives.	Prioritized requirements and user personas.
Ideate	Explore alternatives for routing, handovers, emergency prioritization, and failure recovery.	Alternative solutions and design concepts.
Prototype	Develop dashboard wireframes, simulated telemetry, and virtual mission workflows.	Interface prototypes and simulation scenarios.
Test	Evaluate usability, workflow correctness, and system behavior with representative users.	Feedback, defects, and improved requirements.

7.3 Application Example

Consider an emergency dispatcher who needs to deliver an AED to a location affected by road congestion.

During the **Empathize phase**, the development team examines how the dispatcher receives requests and identifies available delivery resources.

During the **Define phase**, the team specifies the need for rapid resource identification, location validation, and clear emergency priority handling.

During the **Ideate phase**, the team considers direct drone delivery, a route using an intermediate charging hub, and alternative approved delivery methods.

During the **Prototype phase**, the team creates a simulated dispatcher dashboard and models different drone and carrier states.

During the **Test phase**, dispatchers evaluate whether the interface clearly identifies the best feasible option and explains why other options are unavailable.

Feedback from testing is then used to refine the product backlog.

7.4 Product Success Metrics

Product objective	Measurement	Purpose
Improve delivery speed	Median and 95th-percentile request-to-delivery time	Measures end-to-end performance.
Improve mission completion	Percentage of missions completed successfully	Measures operational effectiveness.
Improve resilience	Failure detection and recovery time	Measures the ability to handle component failures.
Improve handover coordination	Successful and failed handover rates	Identifies scheduling and infrastructure problems.
Improve fleet utilisation	Mission utilisation and empty repositioning distance	Evaluates resource efficiency without compromising safety.
Improve audit readiness	Completeness and verification time for audit records	Measures traceability.
Improve usability	Task completion time, operator errors, and user feedback	Evaluates whether users can operate the system effectively.

8. Ethics in Software Development

8.1 Data Ethics

Data ethics concerns the responsible collection, processing, storage, and sharing of information.

The proposed system may process patient locations, medical delivery requests, contact details, drone telemetry, and operational records. These data must be handled according to legitimate purposes and applicable privacy obligations.

The system should follow data minimization by collecting only the information necessary to fulfil a mission. Patient-identifying data should not be included in general telemetry broadcasts or unnecessary operational records.

Access to sensitive data must be restricted to authorized users and services.

8.2 Privacy by Design

Privacy by design means incorporating privacy controls into the system architecture from the beginning rather than adding them after development.

The proposed system should implement:

1. Data minimization: Collect only necessary patient and operational information.
2. Encryption: Protect sensitive information during transmission and storage.
3. Access control: Restrict information according to user roles and responsibilities.
4. Data separation: Separate patient identity from general fleet telemetry where practical.
5. Retention policies: Define how long each category of information must be retained.
6. Access auditing: Record and review access to sensitive information.
7. Secure deletion: Remove data when retention requirements no longer justify keeping it.
8. Incident handling: Establish procedures for investigating and reporting data breaches where required.

Consent should be obtained when applicable. Emergency processing must follow the relevant legal basis and must not depend on a misleading consent interface.

8.3 Security and Ethical Challenges

Threat or ethical issue	**Potential consequence**	**Proposed mitigation**
Spoofed telemetry	Incorrect drone location or battery information may lead to unsafe decisions.	Device authentication, signed messages, replay protection, and plausibility checks.
Compromised edge node	Unauthorized task assignments or altered operational state.	Least privilege, secure updates, node monitoring, and isolation procedures.
Denial-of-service attack	Delayed telemetry and reduced dispatch availability.	Rate limiting, bounded queues, priority traffic handling, and local fallback.
Stolen cryptographic key	Forged messages or audit records.	Protected key storage, rotation, revocation, and incident response.
Medical-data leakage	Privacy harm and possible legal consequences.	Data minimization, encryption, access controls, and retention limits.
Incorrect geofence information	The planner may consider an unauthorized route feasible.	Trusted data sources, freshness checks, versioning, and fail-safe handling.
Biased resource allocation	Some neighborhoods or populations may receive systematically poorer service.	Evaluate geographic service coverage and fairness using appropriate, privacy-conscious metrics.

Misleading user interface	Operators may misunderstand the system's confidence or operational state.	Transparent status indicators, clear alerts, usability testing, and human escalation.

8.4 Ethical Decision-Making

The system must not present automated decisions as infallible.

An operator should be able to understand why a mission received a particular priority, why a route was rejected, and whether the system is operating with stale information or reduced connectivity.

Human overrides must be authenticated and recorded. However, they must not silently bypass mandatory safety restrictions.

The development team should also ensure that patient data are not reused for unrelated purposes without appropriate authorization and that service allocation does not systematically disadvantage underserved communities.

The fundamental ethical principle is that operational efficiency must not take precedence over human safety, privacy, fairness, and accountability.

9. Expected Outcomes and Limitations

9.1 Expected Outcomes

The proposed system is expected to improve the coordination of emergency medical deliveries by integrating drone telemetry, dynamic routing, charging infrastructure, mobile carriers, and distributed computing.

1. Reduction in medical delivery time

The system aims to reduce delivery time for eligible medical supplies by selecting suitable drones, calculating feasible routes, and coordinating available infrastructure.

The expected improvement depends on the delivery location, weather, payload preparation, airspace permissions, drone availability, and recipient handover.

2. Extension of effective operational range

Multi-stage routes using stationary charging hubs and mobile carrier platforms may extend the geographical area that a drone network can serve.

The actual improvement depends on battery capacity, carrier schedules, charging time, route geometry, and the additional time introduced by handovers.

3. Improved service availability

Distributed edge coordination can reduce dependence on continuous central cloud connectivity. Local nodes can continue permitted functions when the central service becomes unavailable.

The extent of service continuity depends on the availability of local infrastructure, current operational data, communication links, and safe fallback policies.

4. Reduced collision risk

The route planner and collision-risk monitoring module can identify potential conflicts and request safe re-planning through approved flight-control interfaces.

These mechanisms aim to reduce risk, but cannot guarantee that every possible collision will be prevented.

5. Improved resource utilisation

The scheduler can allocate drones and charging resources according to availability, battery condition, mission priority, and route feasibility.

This may reduce unnecessary repositioning and improve the use of available infrastructure.

6. Improved regulatory transparency

Cryptographically signed, tamper-evident records can provide a verifiable history of mission assignments, route changes, handovers, overrides, and delivery confirmation.

This supports audit preparation and incident investigation, although the authenticity of a digital record does not independently prove that every physical event occurred exactly as recorded.

9.2 Comparison of Expected Outcomes with the Problem Statement

Stated target	Proposed system capability	Evidence required
Medical delivery within four minutes	Emergency prioritization, resource selection, dynamic routing, and coordinated handovers.	End-to-end delivery measurements across representative scenarios.
Up to 300% improvement in effective range	Multi-stage routes involving charging hubs and mobile carriers.	Comparison against a defined baseline using realistic energy models and operational trials.
99.999% availability	Distributed processing, redundancy, fault detection, and local fallback.	Long-duration availability measurements and reliability testing.
Elimination of mid-air collisions	Route conflict detection, safety constraints, and approved collision-avoidance interfaces.	Safety analysis and extensive validation; absolute elimination cannot be guaranteed.
Zero-latency emergency rerouting	Local decision-making intended to reduce rerouting delays.	Measured latency under defined hardware and network conditions. Literal zero latency is not achievable.
Immutable operational records	Cryptographic signatures and tamper-evident event records.	Signature verification, tamper-detection tests, and key-management validation.

The performance figures above originate from the assigned problem statement. They are proposed targets rather than measured results.

9.3 Potential Risks and Mitigation Strategies

Risk	Potential impact	Mitigation
Adverse weather	Routes may become unsafe or unavailable.	Weather monitoring, configured operating limits, alternative routes, and safe fallback procedures.
Battery or hardware failure	A mission may be interrupted.	Battery-health monitoring, maintenance checks, reserve thresholds, and independent aircraft fail-safes.
Mobile carrier delay	A planned handover may be missed.	Real-time carrier monitoring, scheduling updates, alternative hubs, and handover-abort procedures.
Network partition	Different nodes may hold inconsistent mission information.	Explicit task ownership, stale-state detection, conservative local policies, and reconciliation.
Cyberattack	Telemetry, mission assignments, or availability may be compromised.	Authentication, encryption, monitoring, key revocation, and incident response.
Incorrect environmental data	A route may be incorrectly considered feasible.	Trusted sources, freshness checks, independent constraint validation, and safe failure handling.
Regulatory approval delays	Live deployment may be postponed.	Early engagement with authorities and a staged development and approval plan.
High implementation cost	The project may not deliver sufficient economic benefit.	Pilot evaluation, cost-benefit analysis, and clear continuation criteria.
Operator overload	Critical alerts may be missed.	Clear alert prioritization, escalation procedures, training, and usability testing.
Audit key compromise	The trustworthiness of recorded events may be reduced.	Key rotation, revocation, protected key storage, and independent verification.

9.4 Limitations of the Proposed System

The system has several limitations that must be considered during development and deployment.

Physical limitations: Software cannot eliminate the battery, payload, weather, landing, and charging limitations of physical aircraft.

Network limitations: Decentralized operation can improve resilience, but communication failures may prevent nodes from sharing current information. Some missions may need to stop when safe coordination cannot be established.

Environmental uncertainty: Route planning depends on the accuracy and freshness of location, weather, geofence, and battery information.

Coordination complexity: Mobile carrier handovers create additional scheduling dependencies and may introduce delays when carriers are late or unavailable.

Security limitations: Cryptographic mechanisms can help establish message origin and detect record modification, but cannot guarantee that a compromised device reports truthful physical measurements.

Regulatory limitations: Real-world deployment depends on the applicable aviation rules, operating permissions, medical handling requirements, and privacy obligations.

Validation limitations: Simulation results alone cannot establish that the platform is safe under every real-world condition.

Financial uncertainty: The total investment and long-term economic benefit cannot be determined without actual hardware costs, staffing estimates, mission demand, maintenance costs, and pilot results.

9.5 Future Enhancements

Possible future enhancements include:

1. Digital-twin simulation: Simulate urban routes, weather changes, drone movement, carrier schedules, and charging availability.
2. Predictive maintenance: Estimate battery degradation and hardware maintenance needs using validated operational data.
3. Demand forecasting: Improve the placement of medical supplies and charging infrastructure while protecting patient privacy.
4. Advanced interoperability: Integrate with authorized hospital inventory, emergency dispatch, weather, and municipal transport systems.
5. Formal safety verification: Apply formal methods to selected safety-critical state machines and operating constraints.
6. Improved security: Introduce stronger device attestation, protected key storage, and more advanced anomaly detection where appropriate.
7. Fairness monitoring: Evaluate whether service availability differs systematically across neighborhoods.
8. Expanded deployment coordination: Consider SAFe or other scaled approaches if multiple development teams and partner organizations must coordinate.
9. Improved accessibility: Introduce multilingual interfaces, accessible request processes, and clearer notifications for different user groups.
10. Continuous operational learning: Use verified incident records and performance metrics to refine scheduling policies and system reliability.

10. Verification, Validation, and Acceptance Strategy

Testing is essential because the proposed platform supports time-critical medical logistics and safety-sensitive autonomous operations.

Verification determines whether the system has been built according to its specified requirements. Validation determines whether the resulting system meets the needs of its intended users and operational environment.

10.1 Testing Strategy

Testing level	Purpose	Example tests
Unit testing	Verify individual functions and rules.	Priority calculations, battery reserve checks, and stale telemetry detection.
API and contract testing	Verify communication between components.	Telemetry schemas, mission APIs, and carrier acknowledgements.
Integration testing	Verify that connected modules work together.	Request validation, scheduling, route planning, dispatch, and audit recording.
Simulation testing	Evaluate system behavior without exposing real aircraft or people to unnecessary risk.	Wind changes, concurrent emergencies, carrier delays, and battery decline.
Fault-injection testing	Verify behavior when components fail.	Cloud disconnection, edge-node crashes, packet loss, duplicate messages, and clock drift.
Security testing	Identify weaknesses in identity, authorization, communication, and data protection.	Replay attempts, forged telemetry, privilege escalation, and key revocation.
Performance testing	Measure response times and system capacity.	Concurrent telemetry ingestion, dispatch latency, and message queue behavior.
Usability testing	Evaluate whether operators understand the interface and can complete tasks correctly.	Emergency request handling, alert acknowledgement, and degraded-mode interpretation.
Pilot acceptance testing	Evaluate readiness under a controlled operational environment.	Restricted routes, limited payloads, trained operators, and incident-response drills.

10.2 Acceptance Criteria

Acceptance criteria must be established before testing begins.

The following table identifies the evidence required for the major system capabilities.

System capability	Acceptance evidence
Telemetry ingestion	Measured throughput, latency, and handling of invalid or stale messages under the agreed workload.
Mission prioritization	Demonstrated compliance with approved priority rules and an auditable record of decisions.
Dynamic routing	Successful tests of permitted routes, rejected routes, route changes, and conflicting trajectories.
Carrier handovers	Successful handover simulations and verified safe behavior when a carrier becomes unavailable.
Edge resilience	Demonstrated local operation within defined limits, safe handling of uncertain states, and successful recovery.
Security	Passed authentication, authorization, message-integrity, and relevant security tests.
Auditability	Successful verification of signatures and detection of deliberately modified records.
Usability	Representative users complete critical workflows and correctly interpret alerts and degraded states.
Operational readiness	Approved procedures, trained personnel, monitoring, rollback arrangements, and appropriate operational authorization.

Test reports should record the environment, assumptions, test data, sample sizes, results, defects, and unresolved risks.

Passing simulation tests is necessary but does not independently establish that the system is ready for unrestricted live deployment.

11. Conclusion

The Autonomous Drone-Carrier Mesh Network for Hyper-Local Medical Logistics proposes a distributed software solution to improve the coordination of time-critical medical deliveries in urban environments.

The system integrates real-time telemetry processing, dynamic four-dimensional routing, emergency mission prioritization, mobile carrier handovers, charging infrastructure, local edge autonomy, failure recovery, and cryptographically verifiable operational records.

The analysis identifies the limitations of conventional road-based logistics, individual drone delivery, and systems that depend excessively on centralized coordination. The proposed architecture addresses these

limitations through modular services, distributed processing, explicit safety constraints, secure communication, and auditable mission management.

The recommended development methodology is iterative Agile development supported by XP engineering practices and Lean/Kanban workflow management. This approach enables incremental implementation, early feedback, continuous testing, and systematic improvement. Formal safety, security, privacy, and release reviews remain necessary throughout the SDLC.

The feasibility analysis indicates that the architecture is technically plausible, provided that hardware integration, environmental data quality, communication resilience, and safety requirements are properly validated. Operational feasibility depends on effective integration with medical facilities, dispatchers, fleet operators, transit services, and municipal infrastructure. Financial feasibility must be established using realistic cost estimates and measured pilot outcomes.

Product management and Design Thinking help ensure that the platform meets the needs of its users. Data minimization, privacy by design, least-privilege access, and transparent decision-making address the ethical responsibilities associated with sensitive medical information and safety-critical automated decisions.

Ultimately, the project should progress through feasibility assessment, simulation, incremental development, controlled testing, and appropriately authorized pilot deployment. Its performance targets must be demonstrated through evidence rather than assumed from the proposed architecture.

The governing principle is that medical delivery speed and operational efficiency must always be optimized within verified safety, security, privacy, legal, and operational constraints.