

EX. No. 15 – Simple Programming using CASE and LOOP

```
MySQL 8.0 Command Line Cli x + -
mysql> CREATE DATABASE IF NOT EXISTS CaseLoopDB;
Query OK, 1 row affected (0.04 sec)

mysql> USE CaseLoopDB;
Database changed
mysql> DELIMITER $$
mysql> CREATE PROCEDURE CheckNumber(IN num INT)
-> BEGIN
-> CASE
-> WHEN num > 0 THEN
-> SELECT 'Positive' AS Result;
-> WHEN num < 0 THEN
-> SELECT 'Negative' AS Result;
-> ELSE
-> SELECT 'Zero' AS Result;
-> END CASE;
-> END$$
Query OK, 0 rows affected (0.04 sec)

mysql> DELIMITER ;
mysql> CALL CheckNumber(10);
+-----+
| Result |
+-----+
| Positive |
+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> CALL CheckNumber(-5);
+-----+
| Result |
+-----+
| Negative |
+-----+
1 row in set (0.00 sec)
```

```
MySQL 8.0 Command Line Cli x + -
mysql> CALL CheckNumber(0);
+-----+
| Result |
+-----+
| Zero |
+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> DELIMITER $$
mysql> CREATE PROCEDURE SumNaturalNumbers(IN N INT)
-> BEGIN
-> DECLARE i INT DEFAULT 1;
-> DECLARE total INT DEFAULT 0;
->
-> myLoop: LOOP
-> SET total = total + i;
-> SET i = i + 1;
-> IF i > N THEN
-> LEAVE myLoop; -- Exit the loop
-> END IF;
-> END LOOP;
-> SELECT total AS SumResult;
-> END$$
Query OK, 0 rows affected (0.04 sec)

mysql> DELIMITER ;
mysql> CALL SumNaturalNumbers(5);
+-----+
| SumResult |
+-----+
| 15 |
+-----+
1 row in set (0.00 sec)
```