

EX. No. 20 – MySQL String Functions – REPLACE, REPEAT, REVERSE, RIGHT, LEFT, RPAD, LPAD

```
MySQL 8.0 Command Line Cli x + v

mysql> CREATE DATABASE IF NOT EXISTS StringDB;
Query OK, 1 row affected (0.04 sec)

mysql> USE StringDB;
Database changed
mysql> DROP TABLE IF EXISTS SampleStrings;
Query OK, 0 rows affected, 1 warning (0.04 sec)

mysql>
mysql> CREATE TABLE SampleStrings (
  -> ID INT AUTO INCREMENT PRIMARY KEY,
  -> TextValue VARCHAR(50)
  -> );
Query OK, 0 rows affected (0.05 sec)

mysql>
mysql> INSERT INTO SampleStrings (TextValue) VALUES
  -> ('Hello World'),
  -> ('MySQL String Functions'),
  -> ('Data Science'),
  -> ('OpenAI GPT');
Query OK, 4 rows affected (0.01 sec)
Records: 4 Duplicates: 0 Warnings: 0

mysql> SELECT TextValue, REPLACE(TextValue, ' ', '_') AS ReplacedText
  -> FROM SampleStrings;
+-----+-----+
| TextValue | ReplacedText |
+-----+-----+
| Hello World | Hello_World |
| MySQL String Functions | MySQL_String_Functions |
| Data Science | Data_Science |
| OpenAI GPT | OpenAI_GPT |
+-----+-----+
4 rows in set (0.00 sec)

mysql> SELECT TextValue, REPEAT('Hi! ', 3) AS RepeatedText
  -> FROM SampleStrings
  -> LIMIT 1;
+-----+-----+
| TextValue | RepeatedText |
+-----+-----+
| Hello World | Hi! Hi! Hi! |
+-----+-----+
1 row in set (0.00 sec)
```

```
MySQL 8.0 Command Line Cli x + v

+-----+-----+
| TextValue | RepeatedText |
+-----+-----+
| Hello World | Hi! Hi! Hi! |
+-----+-----+
1 row in set (0.00 sec)

mysql> SELECT TextValue, REVERSE(TextValue) AS ReversedText
  -> FROM SampleStrings;
+-----+-----+
| TextValue | ReversedText |
+-----+-----+
| Hello World | dlrow olleH |
| MySQL String Functions | snoitcnuF gnirtS LQSyM |
| Data Science | ecneicS ataD |
| OpenAI GPT | TPG IAnepO |
+-----+-----+
4 rows in set (0.00 sec)

mysql> SELECT TextValue, RIGHT(TextValue, 5) AS Right5
  -> FROM SampleStrings;
+-----+-----+
| TextValue | Right5 |
+-----+-----+
| Hello World | World |
| MySQL String Functions | tions |
| Data Science | ience |
| OpenAI GPT | I GPT |
+-----+-----+
4 rows in set (0.00 sec)

mysql> SELECT TextValue, LEFT(TextValue, 5) AS Left5
  -> FROM SampleStrings;
+-----+-----+
| TextValue | Left5 |
+-----+-----+
| Hello World | Hello |
| MySQL String Functions | MySQL |
| Data Science | Data |
| OpenAI GPT | OpenA |
+-----+-----+

29°C
Partly cloudy
Search
ENG IN
21:37
08-10-2025
```

```
MySQL 8.0 Command Line Cli x + -
+-----+
4 rows in set (0.00 sec)

mysql> SELECT TextValue, LEFT(TextValue, 5) AS Left5
-> FROM SampleStrings;
+-----+-----+
| TextValue | Left5 |
+-----+-----+
| Hello World | Hello |
| MySQL String Functions | MySQL |
| Data Science | Data |
| OpenAI GPT | OpenA |
+-----+-----+
4 rows in set (0.00 sec)

mysql> ^C
mysql> SELECT TextValue, RPAD(TextValue, 25, '*') AS RightPadded
-> FROM SampleStrings;
+-----+-----+
| TextValue | RightPadded |
+-----+-----+
| Hello World | Hello World***** |
| MySQL String Functions | MySQL String Functions*** |
| Data Science | Data Science***** |
| OpenAI GPT | OpenAI GPT***** |
+-----+-----+
4 rows in set (0.00 sec)

mysql> SELECT TextValue, LPAD(TextValue, 25, '-') AS LeftPadded
-> FROM SampleStrings;
+-----+-----+
| TextValue | LeftPadded |
+-----+-----+
| Hello World | -----Hello World |
| MySQL String Functions | ---MySQL String Functions |
| Data Science | -----Data Science |
| OpenAI GPT | -----OpenAI GPT |
+-----+-----+
4 rows in set (0.00 sec)

mysql>
```