8. Execute and display the results for the following Nmap service version and OS detection commands in Kali Linux operating systems:

i) detect the version of services running

ii) aggressive scan

iii) detect operating system of the target

```
┌──(root㉿DESKTOP-H18E37R)-[/mnt/c/Users/Sudha V]
└─# nmap -A 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-20 21:50 +053
0
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00014s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored s
tates.
Not shown: 1000 closed tcp ports (reset)
Too many fingerprints match this host to give specific OS detail
s
Network Distance: 0 hops

OS and Service detection performed. Please report any incorrect
results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 2.99 seconds

┌──(root㉿DESKTOP-H18E37R)-[/mnt/c/Users/Sudha V]
└─# nmap -O 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-20 21:51 +053
0
Nmap scan report for localhost (127.0.0.1)
Host is up (0.00023s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored s
tates.
Not shown: 1000 closed tcp ports (reset)
Too many fingerprints match this host to give specific OS detail
s
Network Distance: 0 hops

OS detection performed. Please report any incorrect results at h
ttps://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 1.72 seconds
```